



Features

- ◆ Single-in-Line (SIL) Package
- ◆ Single and Dual Output Models
- ◆ I/O-Isolation 1'000 VDC
- ◆ High Efficiency up to 81%
- ◆ Operating Temperature -40°C to $+85^{\circ}\text{C}$
- ◆ Industry Standard Pinout
- ◆ 100% Burn-in (8 h)
- ◆ Lead free Design, RoHS compliant
- ◆ 3 Year Product Warranty



The TMA series are miniature, isolated 1 W DC/DC-converters in a Single-in-Line package (SIP). Requiring only 1.2 cm² board space they offer the ideal solution in many space critical applications for board level power distribution. The use of SMD-technology makes it possible to offer a product with high performance at low cost.

Models

Ordercode	Input voltage	Output voltage	Output current max.	Efficiency typ.
TMA 0505S	5 VDC $\pm$ 10%	5 VDC	200 mA	71 %
TMA 0512S		12 VDC	80 mA	78 %
TMA 0515S		15 VDC	65 mA	78 %
TMA 0505D		$\pm$ 5 VDC	$\pm$ 100 mA	72 %
TMA 0512D		$\pm$ 12 VDC	$\pm$ 40 mA	78 %
TMA 0515D		$\pm$ 15 VDC	$\pm$ 35 mA	79 %
TMA 1205S	12 VDC $\pm$ 10%	5 VDC	200 mA	73 %
TMA 1212S		12 VDC	80 mA	80 %
TMA 1215S		15 VDC	65 mA	80 %
TMA 1205D		$\pm$ 5 VDC	$\pm$ 100 mA	74 %
TMA 1212D		$\pm$ 12 VDC	$\pm$ 40 mA	81 %
TMA 1215D		$\pm$ 15 VDC	$\pm$ 35 mA	81 %
TMA 1505S	15 VDC $\pm$ 10%	5 VDC	200 mA	73 %
TMA 1512S		12 VDC	80 mA	80 %
TMA 1515S		15 VDC	65 mA	80 %
TMA 1505D		$\pm$ 5 VDC	$\pm$ 100 mA	74 %
TMA 1512D		$\pm$ 12 VDC	$\pm$ 40 mA	81 %
TMA 1515D		$\pm$ 15 VDC	$\pm$ 35 mA	81 %
TMA 2405S	24 VDC $\pm$ 10%	5 VDC	200 mA	71 %
TMA 2412S		12 VDC	80 mA	78 %
TMA 2415S		15 VDC	65 mA	79 %
TMA 2405D		$\pm$ 5 VDC	$\pm$ 100 mA	72 %
TMA 2412D		$\pm$ 12 VDC	$\pm$ 40 mA	79 %
TMA 2415D		$\pm$ 15 VDC	$\pm$ 35 mA	80 %

Input Specifications

Input current no load /full load	5 Vin models: 30 mA / 260 mA typ. 12 Vin models: 12 mA / 110 mA typ. 15 Vin models: 12 mA / 100 mA typ. 24 Vin models: 7 mA / 55 mA typ.
Surge voltage (1 sec. max.)	5 Vin models: 9 V max. 12 Vin models: 18 V max. 15 Vin models: 21 V max. 24 Vin models: 30 V max.
Reverse voltage protection	0.3 A max.
Reflected input ripple current	can be reduced by ext. 1–3.3 µF polyester film capacitor
Input filter	internal capacitors

Output Specifications

Voltage set accuracy	± 3 %
Voltage balance (dual output models)	± 1 % max.
Regulation	– Input variation – Load variation 20 – 100 % ± 1.2 % / 1 % change Vin ± 10 % max.
Ripple and noise (20 MHz Bandwidth)	75 mV pk-pk max.
Temperature coefficient	± 0.02 % / K
Short circuit protection	limited 1 sec. max.
Capacitive load	– Single output models – Dual output models 220 µF max. 100 µF max.

General Specifications

Temperature ranges	– Operating – Case temperature – Storage –40 °C ... +85 °C +95 °C max. –40 °C ... +105 °C
Humidity (non condensing)	95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217E)	>2'000'000 h @ 25 °C
Isolation voltage (input/output)	1'000 VDC
Isolation capacity (input/output)	60 pF typ.
Isolation resistance (input/output)	>1'000 Mohm
Switching frequency	100 kHz typ. (frequency modulation)
Frequency change over line and load	± 30 % max.

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Case material	non conductive black plastic (UL 94V-0 rated)	
Package weight	Single output models:	2.1 g (0.07 oz)
	Dual output models:	2.6 g (0.09 oz)
Soldering temperature	max. 265°C / 10 sec	

Figure 1 shows two mechanical drawings of the 15/24 V in Models. The top drawing is a front view, and the bottom drawing is a bottom view.

Front View Dimensions:

- Total width: 19.5 (0.77)
- Total height: 10.2 (0.4)
- Left circular feature diameter: 0.5 (0.02)
- Slot widths and spacings (from left to right):
 - Slot 1: 2.3 ±0.4 (0.09 ±0.02)
 - Space 1: 0.1 (0.1)
 - Slot 2: 2.54 (0.1)
 - Space 2: 5.08 (0.2)
 - Slot 3: 2.54 (0.1)
 - Space 3: 0.1 (0.1)
 - Slot 4: 2.54 (0.1)
 - Space 4: 0.1 (0.1)
 - Slot 5: 2.54 (0.1)
 - Space 5: 0.1 (0.1)
 - Slot 6: 2.54 (0.1)
 - Space 6: 0.1 (0.1)
 - Slot 7: 2.54 (0.1)
 - Space 7: 0.1 (0.1)
 - Slot 8: 2.54 (0.1)
 - Space 8: 0.1 (0.1)
 - Slot 9: 2.54 (0.1)
 - Space 9: 0.1 (0.1)
 - Slot 10: 2.54 (0.1)
 - Space 10: 0.1 (0.1)
 - Slot 11: 2.54 (0.1)
 - Space 11: 0.1 (0.1)
 - Slot 12: 2.54 (0.1)
 - Space 12: 0.1 (0.1)
 - Slot 13: 2.54 (0.1)
 - Space 13: 0.1 (0.1)
 - Slot 14: 2.54 (0.1)
 - Space 14: 0.1 (0.1)
 - Slot 15: 2.54 (0.1)
 - Space 15: 0.1 (0.1)
 - Slot 16: 2.54 (0.1)
 - Space 16: 0.1 (0.1)
 - Slot 17: 2.54 (0.1)
 - Space 17: 0.1 (0.1)
 - Slot 18: 2.54 (0.1)
 - Space 18: 0.1 (0.1)
 - Slot 19: 2.54 (0.1)
 - Space 19: 0.1 (0.1)
 - Slot 20: 2.54 (0.1)
 - Space 20: 0.1 (0.1)
 - Slot 21: 2.54 (0.1)
 - Space 21: 0.1 (0.1)
 - Slot 22: 2.54 (0.1)
 - Space 22: 0.1 (0.1)
 - Slot 23: 2.54 (0.1)
 - Space 23: 0.1 (0.1)
 - Slot 24: 2.54 (0.1)
 - Space 24: 0.1 (0.1)
 - Slot 25: 2.54 (0.1)
 - Space 25: 0.1 (0.1)
 - Slot 26: 2.54 (0.1)
 - Space 26: 0.1 (0.1)
 - Slot 27: 2.54 (0.1)
 - Space 27: 0.1 (0.1)
 - Slot 28: 2.54 (0.1)
 - Space 28: 0.1 (0.1)
 - Slot 29: 2.54 (0.1)
 - Space 29: 0.1 (0.1)
 - Slot 30: 2.54 (0.1)
 - Space 30: 0.1 (0.1)
 - Slot 31: 2.54 (0.1)
 - Space 31: 0.1 (0.1)
 - Slot 32: 2.54 (0.1)
 - Space 32: 0.1 (0.1)
 - Slot 33: 2.54 (0.1)
 - Space 33: 0.1 (0.1)
 - Slot 34: 2.54 (0.1)
 - Space 34: 0.1 (0.1)
 - Slot 35: 2.54 (0.1)
 - Space 35: 0.1 (0.1)
 - Slot 36: 2.54 (0.1)
 - Space 36: 0.1 (0.1)
 - Slot 37: 2.54 (0.1)
 - Space 37: 0.1 (0.1)
 - Slot 38: 2.54 (0.1)
 - Space 38: 0.1 (0.1)
 - Slot 39: 2.54 (0.1)
 - Space 39: 0.1 (0.1)
 - Slot 40: 2.54 (0.1)
 - Space 40: 0.1 (0.1)
 - Slot 41: 2.54 (0.1)
 - Space 41: 0.1 (0.1)
 - Slot 42: 2.54 (0.1)
 - Space 42: 0.1 (0.1)
 - Slot 43: 2.54 (0.1)
 - Space 43: 0.1 (0.1)
 - Slot 44: 2.54 (0.1)
 - Space 44: 0.1 (0.1)
 - Slot 45: 2.54 (0.1)
 - Space 45: 0.1 (0.1)
 - Slot 46: 2.54 (0.1)
 - Space 46: 0.1 (0.1)
 - Slot 47: 2.54 (0.1)
 - Space 47: 0.1 (0.1)
 - Slot 48: 2.54 (0.1)
 - Space 48: 0.1 (0.1)
 - Slot 49: 2.54 (0.1)
 - Space 49: 0.1 (0.1)
 - Slot 50: 2.54 (0.1)
 - Space 50: 0.1 (0.1)
 - Slot 51: 2.54 (0.1)
 - Space 51: 0.1 (0.1)
 - Slot 52: 2.54 (0.1)
 - Space 52: 0.1 (0.1)
 - Slot 53: 2.54 (0.1)
 - Space 53: 0.1 (0.1)
 - Slot 54: 2.54 (0.1)
 - Space 54: 0.1 (0.1)
 - Slot 55: 2.54 (0.1)
 - Space 55: 0.1 (0.1)
 - Slot 56: 2.54 (0.1)
 - Space 56: 0.1 (0.1)
 - Slot 57: 2.54 (0.1)
 - Space 57: 0.1 (0.1)
 - Slot 58: 2.54 (0.1)
 - Space 58: 0.1 (0.1)
 - Slot 59: 2.54 (0.1)
 - Space 59: 0.1 (0.1)
 - Slot 60: 2.54 (0.1)
 - Space 60: 0.1 (0.1)
 - Slot 61: 2.54 (0.1)
 - Space 61: 0.1 (0.1)
 - Slot 62: 2.54 (0.1)
 - Space 62: 0.1 (0.1)
 - Slot 63: 2.54 (0.1)
 - Space 63: 0.1 (0.1)
 - Slot 64: 2.54 (0.1)
 - Space 64: 0.1 (0.1)
 - Slot 65: 2.54 (0.1)
 - Space 65: 0.1 (0.1)
 - Slot 66: 2.54 (0.1)
 - Space 66: 0.1 (0.1)
 - Slot 67: 2.54 (0.1)
 - Space 67: 0.1 (0.1)
 - Slot 68: 2.54 (0.1)
 - Space 68: 0.1 (0.1)
 - Slot 69: 2.54 (0.1)
 - Space 69: 0.1 (0.1)
 - Slot 70: 2.54 (0.1)
 - Space 70: 0.1 (0.1)
 - Slot 71: 2.54 (0.1)
 - Space 71: 0.1 (0.1)
 - Slot 72: 2.54 (0.1)
 - Space 72: 0.1 (0.1)
 - Slot 73: 2.54 (0.1)
 - Space 73: 0.1 (0.1)
 - Slot 74: 2.54 (0.1)
 - Space 74: 0.1 (0.1)
 - Slot 75: 2.54 (0.1)
 - Space 75: 0.1 (0.1)
 - Slot 76: 2.54 (0.1)
 - Space 76: 0.1 (0.1)
 - Slot 77: 2.54 (0.1)
 - Space 77: 0.1 (0.1)
 - Slot 78: 2.54 (0.1)
 - Space 78: 0.1 (0.1)
 - Slot 79: 2.54 (0.1)
 - Space 79: 0.1 (0.1)
 - Slot 80: 2.54 (0.1)
 - Space 80: 0.1 (0.1)
 - Slot 81: 2.54 (0.1)
 - Space 81: 0.1 (0.1)
 - Slot 82: 2.54 (0.1)
 - Space 82: 0.1 (0.1)
 - Slot 83: 2.54 (0.1)
 - Space 83: 0.1 (0.1)
 - Slot 84: 2.54 (0.1)
 - Space 84: 0.1 (0.1)
 - Slot 85: 2.54 (0.1)
 - Space 85: 0.1 (0.1)
 - Slot 86: 2.54 (0.1)
 - Space 86: 0.1 (0.1)
 - Slot 87: 2.54 (0.1)
 - Space 87: 0.1 (0.1)
 - Slot 88: 2.54 (0.1)
 - Space 88: 0.1 (0.1)
 - Slot 89: 2.54 (0.1)
 - Space 89: 0.1 (0.1)
 - Slot 90: 2.54 (0.1)
 - Space 90: 0.1 (0.1)
 - Slot 91: 2.54 (0.1)
 - Space 91: 0.1 (0.1)
 - Slot 92: 2.54 (0.1)
 - Space 92: 0.1 (0.1)
 - Slot 93: 2.54 (0.1)
 - Space 93: 0.1 (0.1)
 - Slot 94: 2.54 (0.1)
 - Space 94: 0.1 (0.1)
 - Slot 95: 2.54 (0.1)
 - Space 95: 0.1 (0.1)
 - Slot 96: 2.54 (0.1)
 - Space 96: 0.1 (0.1)
 - Slot 97: 2.54 (0.1)
 - Space 97: 0.1 (0.1)
 - Slot 98: 2.54 (0.1)
 - Space 98: 0.1 (0.1)
 - Slot 99: 2.54 (0.1)

Tolerances ± 0.25 (0.01)
pins ± 0.05 (0.002)

Pin-Out		
Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
2	-Vin (GND)	-Vin (GND)
4	-Vout	-Vout
5	No pin	Common
6	+Vout	+Vout

Specifications can be changed without notice



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.