

## 1164B Coax - Bundled RGB Coaxial Cable



For more Information  
please call

1-800-Belden1



### General Description:

26 AWG stranded (7x34) .019" bare copper conductors, foam HDPE insulation, Duofoil® + tinned copper braid shield (95% coverage), overall PVC jacket, inner PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
3	26	7x34	BC - Bare Copper	.019

Total Number of Conductors: 3

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FHDPE - Foam High Density Polyethylene	.089

#### Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	TC - Tinned Copper	95.000

#### Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.146

Inner Jacket Color Code Chart:

Number	Color
1	Red
2	Green
3	Blue

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Cabling Separator Material: Polyester Tape

Overall Nominal Diameter: 0.388 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +60°C

UL Temperature Rating: 60°C (UL AWM Style 1354)

Bulk Cable Weight: 70 lbs/1000 ft.

Max. Recommended Pulling Tension: 103 lbs.

Min. Bend Radius/Minor Axis: 4 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

AWM Specification: UL Style 1354 (30 V 60°C) (each coax); UL Style 2668 (overall)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Other Specification:	SMPTE

### Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

75

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

17.3

### Nominal Velocity of Propagation:

VP (%)

78

### Nominal Delay:

Delay (ns/ft)

1.30

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

41.5

### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

8.6

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.6
5	1.3
10	1.8
30	3.1
50	3.9
100	5.4
200	7.5
400	10.4
700	13.5
900	15.2
1000	15.9

### Max. Operating Voltage - UL:

Voltage

30 V RMS (UL AWM Style 1354)

300 V RMS (CM)

### Minimum Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
		10	40	25

### Sweep Test

Sweep Testing: 100% sweep tested 10 MHz to 40 MHz.

## Misc. Information (Overall)

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1164B 0101000	1,000 FT	78.000 LB	BLACK	C	3 #26 FPE SH PVC PVC

## ENGLISH MEASUREMENT VERSION

### 1164B Coax - Bundled RGB Coaxial Cable

1164B 010500	500 FT	38.000 LB	BLACK	C	3 #26 FPE SH PVC PVC
--------------	--------	-----------	-------	---	----------------------

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 10-15-2012

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.