

## Interactive Catalog Replaces Catalog Pages

Honeywell Sensing and Control has replaced the PDF product catalog with the new **Interactive Catalog**. The **Interactive Catalog** is a power search tool that makes it easier to find product information. It includes more installation, application, and technical information than ever before.



**Click this icon to try the new  
Interactive Catalog.**

---

### **Sensing and Control**

Honeywell Inc.

11 West Spring Street

Freeport, Illinois 61032

# Temperature Sensors

## Platinum RTDs

HEL-776/HEL-777



### FEATURES

- Linear resistance vs temperature
- Accurate and interchangeable
- Excellent stability
- Small size
- Printed circuit mountable
- Ceramic SIP package

HEL-776 and HEL-777 platinum RTDs are designed to measure temperatures from  $-55^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$  ( $-67^{\circ}$  to  $302^{\circ}\text{F}$ ) in printed circuit boards, temperature probes, or other lower temperature applications. Solderable leads in 0.050" or 0.100" spacing provide strong connections for wires or printed circuits.

### TYPICAL APPLICATIONS

- HVAC – room, duct and refrigerant equipment
- Instrument and probe assemblies
- Electronic assemblies – temperature compensation
- Process control – temperature regulation


The 1000 $\Omega$ , 375 alpha version, provides 10x greater sensitivity and signal-to-noise. Both are ideal for air temperature sensing.

### ORDER GUIDE

|           |                                                          |
|-----------|----------------------------------------------------------|
| HEL-776-A | Molded SIP pkg. 0.100" lead spacing                      |
| HEL-777-A | Molded SIP pkg. 0.100" lead spacing                      |
| -U        | 1000 $\Omega$ , 0.00375 $\Omega/\Omega/^{\circ}\text{C}$ |
| -T        | 100 $\Omega$ , 0.00385 $\Omega/\Omega/^{\circ}\text{C}$  |
| -0        | $\pm 0.2\%$ Resistance Trim (Standard)                   |
| -1        | $\pm 0.1\%$ Resistance Trim (Optional)                   |

### MOUNTING DIMENSIONS (for reference only) mm/in.

#### HEL-776-A



#### HEL-777-A



Fig. 1: Wheatstone Bridge 2-Wire Interface



Fig. 2: Linear Output Voltage



Fig. 3: Adjustable Point (Comparator) Interface



### CAUTION PRODUCT DAMAGE

The inherent design of this component causes it to be sensitive to electrostatic discharge (ESD). To prevent ESD-induced damage and/or degradation, take normal ESD precautions when handling this product.

Temperature

# Temperature Sensors

HEL-776/HEL-777

## Platinum RTDs

### FUNCTIONAL BEHAVIOR

$$R_T = R_0(1 + AT + BT^2 - 100CT^3 + CT^4)$$

RT = Resistance ( $\Omega$ ) at temperature T ( $^{\circ}\text{C}$ )

R<sub>0</sub> = Resistance ( $\Omega$ ) at 0 $^{\circ}\text{C}$

T = Temperature in  $^{\circ}\text{C}$

$$A = \alpha + \frac{\alpha \delta}{100} \quad B = \frac{-\alpha \delta}{100^2} \quad C_{T < 0} = \frac{-\alpha \beta}{100^4}$$

### CONSTANTS

|                                                                        |                           |                            |
|------------------------------------------------------------------------|---------------------------|----------------------------|
| <b>Alpha, <math>\alpha</math> (<math>^{\circ}\text{C}^{-1}</math>)</b> | 0.00375<br>$\pm 0.000029$ | 0.003850<br>$\pm 0.000010$ |
| <b>Delta, <math>\delta</math> (<math>^{\circ}\text{C}</math>)</b>      | $1.605 \pm 0.009$         | $1.4999 \pm 0.007$         |
| <b>Beta, <math>\beta</math> (<math>^{\circ}\text{C}</math>)</b>        | 0.16                      | 0.10863                    |
| <b>A (<math>^{\circ}\text{C}^{-1}</math>)</b>                          | $3.81 \times 10^{-3}$     | $3.908 \times 10^{-3}$     |
| <b>B (<math>^{\circ}\text{C}^{-2}</math>)</b>                          | $-6.02 \times 10^{-7}$    | $-5.775 \times 10^{-7}$    |
| <b>C (<math>^{\circ}\text{C}^{-4}</math>)</b>                          | $-6.0 \times 10^{-12}$    | $-4.183 \times 10^{-12}$   |

Both  $\beta = 0$  and  $C = 0$  for  $T > 0^{\circ}\text{C}$

### ACCURACY VS TEMPERATURE

| Temperature ( $^{\circ}\text{C}$ ) | Standard $\pm 0.2\%$          |                                       | Optional $\pm 0.1\%$          |                                       |
|------------------------------------|-------------------------------|---------------------------------------|-------------------------------|---------------------------------------|
|                                    | $\pm \Delta R^*$ ( $\Omega$ ) | $\pm \Delta T$ ( $^{\circ}\text{C}$ ) | $\pm \Delta R^*$ ( $\Omega$ ) | $\pm \Delta T$ ( $^{\circ}\text{C}$ ) |
| -200                               | 6.8                           | 1.6                                   | 5.1                           | 1.2                                   |
| -100                               | 2.9                           | 0.8                                   | 2.4                           | 0.6                                   |
| 0                                  | 2.0                           | 0.5                                   | 1.0                           | 0.3                                   |
| 100                                | 2.9                           | 0.8                                   | 2.2                           | 0.6                                   |
| 200                                | 5.6                           | 1.6                                   | 4.3                           | 1.2                                   |
| 300                                | 8.2                           | 2.4                                   | 6.2                           | 1.8                                   |
| 400                                | 11.0                          | 3.2                                   | 8.3                           | 2.5                                   |
| 500                                | 12.5                          | 4.0                                   | 9.6                           | 3.0                                   |
| 600                                | 15.1                          | 4.8                                   | 10.4                          | 3.3                                   |

\* 1000 $\Omega$  RTD. Divide  $\Delta R$  by 10 for 100 $\Omega$  RTD.

### RESISTANCE VS TEMPERATURE CURVE



### SPECIFICATIONS

|                                                                         |                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sensor Type                                                             | Thin film platinum RTD: R <sub>0</sub> = 1000 $\Omega$ @ 0 $^{\circ}\text{C}$ ; alpha = 0.00375 $\Omega/\Omega/^{\circ}\text{C}$<br>R <sub>0</sub> = 100 $\Omega$ @ 0 $^{\circ}\text{C}$ ; alpha = 0.00385 $\Omega/\Omega/^{\circ}\text{C}$                           |
| Temperature Range                                                       | TFE Teflon: -200 $^{\circ}$ to +260 $^{\circ}\text{C}$ (-320 $^{\circ}$ to +500 $^{\circ}\text{F}$ )<br>Fiberglass: -75 $^{\circ}$ to +540 $^{\circ}\text{C}$ (-100 $^{\circ}$ to +1000 $^{\circ}\text{F}$ )                                                          |
| Temperature Accuracy                                                    | $\pm 0.5^{\circ}\text{C}$ or 0.8% of temperature $^{\circ}\text{C}$ (R <sub>0</sub> $\pm 0.2\%$ trim), whichever is greater<br>$\pm 0.3^{\circ}\text{C}$ or 0.6% of temperature $^{\circ}\text{C}$ (R <sub>0</sub> $\pm 0.1\%$ trim), whichever is greater (optional) |
| Base Resistance and Interchangeability, R <sub>0</sub> $\pm \Delta R_0$ | 1000 $\pm 2 \Omega$ ( $\pm 0.2\%$ ) @ 0 $^{\circ}\text{C}$ or 100 $\pm 0.2 \Omega$ ( $\pm 0.2\%$ ) @ 0 $^{\circ}\text{C}$<br>1000 $\pm 1 \Omega$ ( $\pm 0.1\%$ ) @ 0 $^{\circ}\text{C}$ or 100 $\pm 0.2 \Omega$ ( $\pm 0.2\%$ ) @ 0 $^{\circ}\text{C}$ (optional)     |
| Linearity                                                               | $\pm 0.1\%$ of full scale for temperatures spanning -40 $^{\circ}$ to 125 $^{\circ}\text{C}$<br>$\pm 2.0\%$ of full scale for temperatures spanning -75 $^{\circ}$ to 540 $^{\circ}\text{C}$                                                                          |
| Time Constant                                                           | <0.5 sec, 0.85 inch O.D. in water at 3 ft/sec; <1.0 sec, 0.85 inch O.D. in still water                                                                                                                                                                                |
| Operating Current                                                       | 2 mA maximum for self heating errors of <1 $^{\circ}\text{C}$ ; 1 mA recommended                                                                                                                                                                                      |
| Stability                                                               | <0.25 $^{\circ}\text{C}/\text{year}$ ; 0.05 $^{\circ}\text{C}$ per 5 years in occupied environments                                                                                                                                                                   |
| Self Heating                                                            | <15mW/ $^{\circ}\text{C}$ for 0.85 O.D. typical                                                                                                                                                                                                                       |
| Insulation Resistance                                                   | >50 M $\Omega$ @ 50 VDC @ 25 $^{\circ}\text{C}$                                                                                                                                                                                                                       |
| Construction                                                            | Alumina case; Epoxy potting (Teflon leads); Ceramic potting (fiberglass leads)                                                                                                                                                                                        |
| Lead Material                                                           | Nickel coated stranded copper, Teflon or Fiberglass insulated                                                                                                                                                                                                         |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.