

Silicon Carbide Power Schottky Diode



V_{RRM}	=	3300 V
I_F ($T_C \leq 125^\circ\text{C}$)	=	0.3 A
Q_C	=	20 nC

Features

- Industry's leading low leakage currents
- 175 °C maximum operating temperature
- Electrically isolated base-plate
- Positive temperature coefficient of V_F
- Fast switching speeds
- Superior figure of merit Q_C/I_F

Package

- RoHS Compliant



TO – 220FP (Isolated Base-plate Package)

Advantages

- Low standby power losses
- Improved circuit efficiency (Lower overall cost)
- Significantly reduced switching losses compare to Si PiN diodes
- Ease of paralleling devices without thermal runaway
- Smaller heat sink requirements
- Low reverse recovery current
- Low device capacitance

Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- High Voltage Multipliers
- Military Power Supplies

Maximum Ratings at $T_j = 175^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Repetitive peak reverse voltage	V_{RRM}			3300		V
Continuous forward current	I_F	$T_C \leq 125^\circ\text{C}$		0.3		A
RMS forward current	$I_{F(RMS)}$	$T_C \leq 125^\circ\text{C}$		0.35		A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ ms}$		2		A
		$T_C = 125^\circ\text{C}$, $t_p = 10\text{ ms}$		1		A
Non-repetitive peak forward current	$I_{F,max}$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ }\mu\text{s}$		10		A
i^2t value	$\int i^2 dt$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ ms}$		0.1		A ² S
Power dissipation	P_{tot}	$T_C = 25^\circ\text{C}$		89		W
Operating and storage temperature	T_j, T_{stg}			-55 to 175		°C

Electrical Characteristics at $T_j = 175^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Diode forward voltage	V_F	$I_F = 0.3\text{ A}$, $T_j = 25^\circ\text{C}$		1.7	2.2	V
		$I_F = 0.3\text{ A}$, $T_j = 175^\circ\text{C}$		4.0	5.0	
Reverse current	I_R	$V_R = 3300\text{ V}$, $T_j = 25^\circ\text{C}$		1	10	μA
		$V_R = 3300\text{ V}$, $T_j = 175^\circ\text{C}$		10	100	
Total capacitive charge	Q_C	$I_F \leq I_{F,MAX}$ $di_F/dt = 35\text{ A}/\mu\text{s}$ $T_j = 175^\circ\text{C}$	$V_R = 1500\text{ V}$		20	nC
Switching time	t_s			$V_R = 1500\text{ V}$		< 60
Total capacitance	C	$V_R = 1\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$		42		pF
		$V_R = 400\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$		8		
		$V_R = 1000\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$		7		

Thermal Characteristics

Thermal resistance, junction – Cu lead frame	R_{thJC}	1.69	°C/W
--	------------	------	------

Mechanical Properties

Mounting torque, M3 screw	M	0.6	Nm
---------------------------	---	-----	----




Figure 1: Typical Forward Characteristics




Figure 2: Typical Reverse Characteristics





Figure 3: Power Derating Curve



**Figure 4: Current Derating Curves ($D = t_p/T$, $t_p = 400 \mu s$)
(Considering worst case Z_{th} conditions)**




Figure 5: Typical Junction Capacitance vs Reverse Voltage Characteristics




Figure 6: Typical Capacitive Energy vs Reverse Voltage Characteristics




Figure 7: Current vs Pulse Duration Curves at $T_C = 150\text{ }^\circ\text{C}$





Figure 8: Transient Thermal Impedance

Package Dimensions:

TO-220FP

PACKAGE OUTLINE



NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS
3. CONTROLLED LEAD COPLANARITY <D> 0.004 INCH MAXIMUM

Revision History

Date	Revision	Comments	Supersedes
2014/12/19	3	Updated Electrical Characteristics	
2014/08/26	2	Updated Electrical Characteristics	
2013/03/22	1	Added Thermal Characteristics	
2013/01/23	0	Initial Release	

Published by
GeneSiC Semiconductor, Inc.
43670 Trade Center Place Suite 155
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

SPICE Model Parameters

This is a secure document. Please copy this code from the SPICE model PDF file on our website (http://www.genesicsemi.com/images/products_sic/rectifiers/GAP3SLT33-220FP_SPICE.pdf) into LTSPICE (version 4) software for simulation of the GAP3SLT33-220FP.

```

*      MODEL OF GeneSiC Semiconductor Inc.
*
*      $Revision:   1.0           $
*      $Date:      04-SEP-2013   $
*
*      GeneSiC Semiconductor Inc.
*      43670 Trade Center Place Ste. 155
*      Dulles, VA 20166
*
*      COPYRIGHT (C) 2013 GeneSiC Semiconductor Inc.
*      ALL RIGHTS RESERVED
*
* These models are provided "AS IS, WHERE IS, AND WITH NO WARRANTY
* OF ANY KIND EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED
* TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE."
* Models accurate up to 2 times rated drain current.
*
* Start of GAP3SLT33-220FP SPICE Model
*
.SUBCKT GAP3SLT33 ANODE KATHODE
R1 ANODE INT R=((TEMP-24)*0.0535); Temperature Dependant Resistor
D1 INT KATHODE GAP3SLT33_25C; Call the 25C Diode Model
D2 ANODE KATHODE GAP3SLT33_PIN; Call the PiN Diode Model
.MODEL GAP3SLT33_25C D
+ IS      1.39E-14      RS      2.88
+ N       1.0120127    IKF     36.05007504
+ EG      1.2          XTI     -3
+ CJO     6.01E-11     VJ     0.924257443
+ M       0.3084545    FC     0.5
+ TT      1.00E-10     BV     3300
+ IBV     1.00E-03     VPK    3300
+ IAVE    3.00E-01     TYPE   SiC_Schottky
+ MFG     GeneSiC_Semiconductor
.MODEL GAP3SLT33_PIN D
+ IS      178.99E-18   RS      15
+ N       5            EG     3.23
+ XTI     50          FC     0.5
+ TT      0           BV     3300
+ IBV     1.00E-03     VPK    3300
+ IAVE    3.00E-01     TYPE   SiC_PiN
.ENDS
* End of GAP3SLT33-220FP SPICE Model

```



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.