

## 9116 Coax - CATV Cable

For more Information  
please call

1-800-Belden1

**Description:**

Series 6, 18 AWG solid .040" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II + aluminum braid shield (60% coverage), PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Coax | AWG | Stranding | Conductor Material               | Dia. (in.) |
|--------|-----|-----------|----------------------------------|------------|
| 1      | 18  | Solid     | BCCS - Bare Copper Covered Steel | .040       |

Total Number of Conductors: 1

**Insulation****Insulation Material:**

| Insulation Material                  | Dia. (in.) |
|--------------------------------------|------------|
| Gas-injected FPE - Foam Polyethylene | .180       |

**Outer Shield****Outer Shield Material:**

| Layer # | Outer Shield Trade Name | Type  | Outer Shield Material                             | Coverage (%) |
|---------|-------------------------|-------|---------------------------------------------------|--------------|
| 1       | Bonded Duofoil®         | Tape  | Bonded Aluminum Foil-Polyester Tape-Aluminum Foil | 100          |
| 2       |                         | Braid | AL - Aluminum                                     | 60           |

**Outer Jacket****Outer Jacket Material:**

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

**Overall Cable**

Overall Nominal Diameter: 0.270 in.

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -40°C To +80°C

Bulk Cable Weight: 27 lbs/1000 ft.

Max. Recommended Pulling Tension: 126 lbs.

Min. Bend Radius/Minor Axis: 2.750 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CATV, CM

CEC/C(UL) Specification: CM

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire &amp; Cable): Yes

MII Order #39 (China RoHS): Yes

Series Type: Series 6

**Flame Test**

UL Flame Test: UL1581 Vertical Flame and FT-1 Flame Test

**Plenum/Non-Plenum**

Plenum (Y/N): No

Plenum Number: 9116P

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

| Impedance (Ohm) | Tolerance (Ohms) |
|-----------------|------------------|
| 75              | ± 3              |

**Nom. Inductance:**

| Inductance (µH/ft) |
|--------------------|
| .097               |

**Nom. Capacitance Conductor to Shield:**

| Capacitance (pF/ft) |
|---------------------|
| 16.2                |

**Nominal Velocity of Propagation:**

| VP (%) |
|--------|
| 83     |

**Nominal Delay:**

| Delay (ns/ft) |
|---------------|
| 1.2           |

**Nom. Conductor DC Resistance:**

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 28                       |

**Nominal Outer Shield DC Resistance:**

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 9                        |

**Max. Attenuation:**

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 5           | 0.67                     |
| 55          | 1.60                     |
| 211         | 2.87                     |
| 270         | 3.24                     |
| 300         | 3.43                     |
| 350         | 3.72                     |
| 400         | 4.00                     |
| 450         | 4.26                     |
| 550         | 4.71                     |
| 750         | 5.59                     |
| 870         | 6.00                     |
| 1000        | 6.54                     |

**Max. Operating Voltage - UL:**

| Voltage   |
|-----------|
| 350 V RMS |

**Minimum Structural Return Loss:**

| Description | Freq. (MHz) | Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------|-------------|-------------------|------------------|---------------|
|             |             | 5                 | 1000             | 20            |

**Sweep Test****Sweep Testing:**

5 MHz - 1 GHz

**Put Ups and Colors:**

| Item #        | Putup    | Ship Weight | Color          | Notes | Item Desc           |
|---------------|----------|-------------|----------------|-------|---------------------|
| 9116 Q5HU1000 | 1,000 FT | 29.000 LB   | WHITE, NEUTRAL |       | #18 GIFHDLDP SH PVC |
| 9116 Q5H1000  | 1,000 FT | 30.000 LB   | WHITE, NEUTRAL |       | #18 GIFHDLDP SH PVC |
| 9116 009U1000 | 1,000 FT | 29.000 LB   | WHITE          |       | #18 GIFHDLDP SH PVC |
| 9116 0091000  | 1,000 FT | 30.000 LB   | WHITE          |       | #18 GIFHDLDP SH PVC |
| 9116 009500   | 500 FT   | 15.500 LB   | WHITE          |       | #18 GIFHDLDP SH PVC |
| 9116 010S700  | 700 FT   | 18.900 LB   | BLACK          |       | #18 GIFHDLDP SH PVC |
| 9116 010U1000 | 1,000 FT | 29.000 LB   | BLACK          |       | #18 GIFHDLDP SH PVC |
| 9116 010U500  | 500 FT   | 15.000 LB   | BLACK          |       | #18 GIFHDLDP SH PVC |
| 9116 0101000  | 1,000 FT | 30.000 LB   | BLACK          | C     | #18 GIFHDLDP SH PVC |
| 9116 010500   | 500 FT   | 15.500 LB   | BLACK          |       | #18 GIFHDLDP SH PVC |
| 9116 290U1000 | 1,000 FT | 29.000 LB   | BEIGE, LIGHT   |       | #18 GIFHDLDP SH PVC |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 08-08-2012

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.