

Type HES 105 °C High Energy Screw Terminal Aluminum Electrolytic High Power Input Filtering, Screw Terminal Capacitors



Type HES screw terminal, aluminum electrolytic capacitors have excellent reliability and are ideal for high power input and charge-discharge applications for welders and strobe lights. The HES can be operated at 105 °C at full rated voltage

Highlights

- High reliability - 1000 hours at 105 °C
- Great for charge-discharge applications
- Ideal for high power input filter applications
- Operates at 105 °C at full rated voltage

Specifications

Capacitance Range: 300 to 5,600 μF

Voltage Range: 350 to 450 WVdc

Capacitance Tolerance: -0% +50%

Operating Temperature: -40 °C to +105 °C

Ripple Current Multipliers: Ambient Temperature

+25 °C	+35 °C	+45 °C	+55 °C	+65 °C	+85 °C
2.00	1.88	1.72	1.58	1.42	1.00

Rated Voltage	Frequency / Ripple Multiplier				
	120 Hz	400 Hz	1000 Hz	2500 Hz	10 kHz
350 to 450	1.000	1.080	1.113	1.175	1.230

DC Leakage Current: $I \leq 3 \sqrt{CV}$ after 5 minutes

Not to exceed 4.0 mA

C = Capacitance in μF

V = Rated Voltage

I = Leakage current in mA

QA Stability Test: Life test:

1000 h @ +105 °C

Ripple Test:

2000 h, full load @ +85 °C

Shelf test:

500 h @ +105 °C

[Click here to see: Hardware & Mounting Options](#)

[Click here to see: Mechanical Details](#)

Type HES 105 °C High Energy Screw Terminal Aluminum Electrolytic Ratings

		Typical	Max Ripple		
	Catalog	Max ESR	120 Hz		
Cap	Part Number	120 Hz	+85 °C	Dia.	Length
(μF)		(Ω)	(A) RMS	(Inches)	(Inches)
350 WVdc (400 Vdc Surge)					
600	HES601G350V2C	0.173	2.6	2.00	2.125
900	HES901G350V5C	0.110	4.6	2.00	5.125
1,100	HES112G350V3C	0.099	4.0	2.00	3.125
1,400	HES142G350W5C	0.080	6.2	2.50	5.125
1,600	HES162G350V4C	0.062	5.6	2.00	4.125
1,900	HES192G350V4L	0.053	6.4	2.00	4.625
2,500	HES252G350W4C	0.045	7.4	2.50	4.125
3,100	HES312G350X3L	0.040	8.6	3.00	3.625
3,400	HES342G350W5C	0.034	9.4	2.50	5.125
3,700	HES372G350X4C	0.034	9.8	3.00	4.125
4,400	HES442G350X4L	0.029	11.0	3.00	4.625
5,000	HES502G350X5C	0.026	12.1	3.00	5.125
5,600	HES562G350X5L	0.024	13.2	3.00	5.625
400 WVdc (450 Vdc Surge)					
300	HES301G400U3C	0.275	2.2	1.75	3.125
500	HES501G400V2C	0.180	2.6	2.00	2.125
1,300	HES132G400V4C	0.066	5.4	2.00	4.125
2,000	HES202G400V5L	0.044	7.3	2.00	5.625
2,000	HES202G400W4C	0.048	7.3	2.50	4.125
2,100	HES212G400X5L	0.045	9.5	3.00	5.625
3,000	HES302G400W5L	0.033	9.9	2.50	5.625
3,500	HES352G400X4L	0.031	10.7	3.00	4.625
4,100	HES412G400X5C	0.027	11.9	3.00	5.125
4,600	HES462G400X5L	0.025	13.0	3.00	5.625

		Typical	Max Ripple		
	Catalog	ESR	120 Hz		
Cap	Part Number	120 Hz	+85 °C	Dia.	Length
(µF)		(Ω)	(A) RMS	(Inches)	(Inches)
450 WVdc (525 Vdc Surge)					
300	HES301G450V3C	0.268	2.4	2.00	3.125
400	HES401G450V3L	0.203	2.9	2.00	3.625
550	HES551G450V4C	0.150	3.6	2.00	4.125
700	HES701G450V3C	0.125	3.5	2.00	3.125
1,200	HES122G450X4L	0.069	7.1	3.00	4.625
1,500	HES152G450X5L	0.056	8.5	3.00	5.625
1,600	HES162G450V5L	0.053	6.9	2.00	5.625
1,700	HES172G450W4C	0.051	7.1	2.50	4.125
2,000	HES202G450X5L	0.041	9.7	3.00	5.625
2,200	HES222G450X5L	0.040	10.1	3.00	5.625
2,400	HES242G450W5C	0.038	9.0	2.50	5.125
2,700	HES272G450W5L	0.034	9.9	2.50	5.625
3,600	HES362G450X5C	0.028	11.7	3.00	5.125
4,000	HES402G450X5L	0.025	12.7	3.00	5.625



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.