

**TO-92S**

**Pin Definition:**

1. V<sub>CC</sub>
2. GND
3. Output

**SOT-23**

**Pin Definition:**

1. V<sub>CC</sub>
2. Output
3. GND

## Description

TSH282 is an unipolar Hall effect sensor IC. It incorporates advanced chopper stabilization technology to provide accurate and stable magnetic switch points. The design, specifications and performance have been optimized for applications of solid state switches. The output transistor will be switched on ( $B_{OP}$ ) in the presence of a sufficiently strong South pole magnetic field facing the marked side of the package. Similarly, the output will be switched off ( $B_{RP}$ ) in the presence of a weaker South field and remain off with "0" field.

## Features

- CMOS Hall IC Technology
- Solid-State Reliability
- Chopper stabilized amplifier stage
- Unipolar, output switches with absolute value of South pole from magnet
- Operation down to 3.0V
- High Sensitivity for direct reed switch replacement applications

## Application

- Solid state switch
- Limit switch, Current limit
- Interrupter
- Current sensing
- Magnet proximity sensor for reed switch replacement

## Ordering Information

Part No.	Package	Packing
TSH282CT B0G	TO-92S	1Kpcs / Bulk Bag
TSH282CX RFG	SOT-23	3Kpcs / 7" Reel


Note: "G" denote for Halogen Free Product

## Absolute Maximum Rating (Ta = 25°C unless otherwise noted)

Characteristics		Limit	Value	Unit
Supply voltage		V <sub>CC</sub>	27	V
Output Voltage		V <sub>OUT</sub>	27	V
Reverse voltage		V <sub>CC/OUT</sub>	-0.3	V
Magnetic flux density			Unlimited	Gauss
Output current		I <sub>OUT</sub>	50	mA
Operating Temperature Range		T <sub>OPR</sub>	-40 to +85	°C
Storage temperature range		T <sub>STG</sub>	-55 to +150	°C
Maximum Junction Temp		T <sub>J</sub>	150	°C
Thermal Resistance - Junction to Ambient	TO-92S	$\theta_{JA}$	206	°C/W
	SOT-23		543	
Thermal Resistance - Junction to Case	TO-92S	$\theta_{JC}$	148	°C/W
	SOT-23		410	
Package Power Dissipation	TO-92S	P <sub>D</sub>	606	mW
	SOT-23		230	


**Note:** Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum-rated conditions for extended periods may affect device reliability.

### Block Diagram



**Note:** Static sensitive device; please observe ESD precautions. Reverse VDD protection is not included. For reverse voltage protection, a 100Ω resistor in series with VDD is recommended.

### Typical Application Circuit



### Electrical Specifications (DC Operating Parameters : $T_A=+25^\circ\text{C}$ , $V_{CC}=12\text{V}$ )

Parameters	Test Conditions	Min	Typ	Max	Units
Supply Voltage	Operating	3.0	--	24	V
Supply Current	$B < B_{OP}$	--	2.5	5.0	mA
Output Low Voltage	$I_{OUT} = 20\text{mA}$ , $B > B_{OP}$	--	--	500	mV
Output Leakage Current	$I_{OFF}$ $B < B_{RP}$ , $V_{OUT} = 20\text{V}$	--	--	10	uA
Output Rise Time	$R_L=1\text{k}\Omega$ , $C_L=20\text{pF}$	--	0.04	--	uS
Output Fall Time	$R_L=1\text{k}\Omega$ ; $C_L = 20\text{pF}$	--	0.18	--	uS

### Magnetic Specifications

DC Operating Parameters : TA=+25°C, V<sub>DD</sub>=12V


Parameter	Symbol	Test condition	Min	Typ	Max	Unit
Operate Point	B <sub>OP</sub>		45	--	100	Gauss
Release Point	B <sub>RP</sub>		25	--	70	Gauss
Hysteresis	B <sub>HYS</sub>		--	20	--	Gauss

Note: 1G (Gauss) = 0.1mT (millitesla)

### Output Behavior versus Magnetic Pole

DC Operating Parameters Ta = -40 to 125°C, V<sub>DD</sub> = 3.0 ~ 24V

Parameter	Test condition	OUT(TO-92S)	OUT(SOT-23)
South pole	B>B <sub>Op</sub> [(100)~(45)]	Low	Open(Pull-up Voltage)
Null or weak magnetic field	-Brp ~ +Brp	Open(Pull-up Voltage)	Open(Pull-up Voltage)
North pole	B< -B <sub>Op</sub> (-25~-70)	Open(Pull-up Voltage)	Low



### Characteristic Performance




Figure 1. Supply Voltage vs. Flux Density




Figure 2. Temperature vs. Flux Density




Figure 3. Supply Current vs. Temperature




Figure 4. Supply Current vs. Supply Voltage




Figure 5. Output Saturation Voltage vs. Supply Voltage






Figure 6. Output Saturation Voltage vs. Temperature

### Characteristic Performance




**Figure 7. Output Leakage Current vs.  
Supply Voltage**




**Figure 8. Power Dissipation vs. Temperature**

## TO-92S Mechanical Drawing







## Marking Diagram




**282** = Device Code  
**Y** = Year Code (3=2013, 4=2014....)  
**WW** = Week Code (01~52)

## SOT-23 Mechanical Drawing



Unit: Millimeters

## Marking Diagram



**282** = Device Code

**WW** = Week Code Table

week	1	2	3	4	5	6	7	8	9	10	11	12	13
code	OA	OB	OC	OD	OE	OF	OG	OH	OI	OJ	OK	OL	OM
week	14	15	16	17	18	19	20	21	22	23	24	25	26
code	ON	OO	OP	OQ	OR	OS	OT	OU	OV	OW	OX	OY	OZ
week	27	28	29	30	31	32	33	34	35	36	37	38	39
code	PA	PB	PC	PD	PE	PF	PG	PH	PI	PJ	PK	PL	PM
week	40	41	42	43	44	45	46	47	48	49	50	51	52
code	PN	PO	PP	PQ	PR	PS	PT	PU	PV	PW	PX	PY	PZ

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.