
THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.


LOC	DIST
ES	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H7	REVISED PER ECR-13-003827	4MAR2013	R.M	C.W



RETENTION BARB TYPE SHOWN ON ALL SHEET UNLESS OTHERWISE NOTED



1. MATERIALS:
   - HOUSING: HIGH TEMPERATURE NYLON, UL94 V-0
   - EXTRACTOR: HIGH TEMPERATURE NYLON, UL94 V-0
   - CONTACTS: COPPER ALLOY
   - RETENTION BARB: BRASS, TIN PLATED
2. INTERFACE FINISH:
   - (1) 0.00038 MIN THK GOLD OVER 0.00127 MIN THK NICKEL.
   - (2) 0.00008 MIN THK GOLD OVER 0.00127 MIN THK NICKEL.
   - (3) 0.00076 MIN THK GOLD OVER 0.00127 MIN THK NICKEL.
3. FINISHED HOLE SIZE. 0.15 MAXIMUM ANNULAR RING.
4. KEEP OUT ZONE.
5. KEEP OUT AREA RESERVED FOR SOCKET EXTRACTORS, BOTH ENDS.
6. SOLDERTAIL FINISH:
   - 0.00300 MIN THK MATTE TIN OVER 0.00127 MIN THK NICKEL.
7. LED LOCATION AS APPLICABLE PER CUSTOMER.
8. DATUM -G- IS CONNECTOR SIDE SURFACE OF PCB.


THIS DRAWING IS A CONTROLLED DOCUMENT.	DWN LEO ZHOU 28FEB2007	TE Connectivity	
DIMENSIONS: mm	CHK STEVEN YAO 28FEB2007	NAME	SOCKET ASSEMBLY, VERTICAL DDR3 DIMM, SOLDER TAIL, 240 POSITION
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± -, 1 PLC ± 0.5, 2 PLC ± 0.13, 3 PLC ± 0.013, 4 PLC ± 0.0001, ANGLES ± -	APVD STEVEN YAO 28FEB2007	PRODUCT SPEC 108-2256	
		APPLICATION SPEC 114-13154	SIZE A1 / CAGE CODE 00779 / DRAWING NO C-1932000 / RESTRICTED TO —
MATERIAL 1	FINISH 2 6	WEIGHT —	SCALE 4:1 / SHEET 1 OF 4 / REV H7
		CUSTOMER DRAWING	

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- -
© COPYRIGHT - By - ALL RIGHTS RESERVED.


LOC	DIST
ES	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



PARTIAL BOTTOM VIEW
SCALE 12:1
7



SECTION N-N
SCALE 10:1

HOUSING STYLE	EXTRACTOR COLOR	HOUSING COLOR	CONTACT GOLD INTERFACE	TAIL LENGTH	PART NUMBER
RETENTION BARB	BLACK	BLACK	0.00076 MIN (30u'')	2.54	7-1932000-6
	NATURAL			2.54	7-1932000-5
	NATURAL	BLUE(2935U)	0.00038 MIN(15u'')	2.67	7-1932000-2
	NATURAL	PINK(701C)	0.00008 MIN (3u'', FLASH)	2.54	6-1932000-5
		BLUE(284C)		2.54	6-1932000-4
	BLACK	BLACK	0.00076 MIN (30u'')	4.00	5-1932000-2
				3.18	5-1932000-1
	NATURAL	BLACK		4.00	4-1932000-8
				3.18	4-1932000-7
				2.67	4-1932000-6
	NATURAL	GREEN(368C)	0.00038 MIN (15u'')	2.67	3-1932000-3
		BLUE(284C)		2.67	2-1932000-5
		ORANGE(021C)		2.67	2-1932000-1
	BLACK	BLACK	0.00038 MIN (15u'')	3.18	1-1932000-7
				2.67	1-1932000-6
			0.00008 MIN(3u'')	4.00	1-1932000-5
	NATURAL	BLACK	0.00038 MIN (15u'')	3.18	1-1932000-1
				2.67	1-1932000-0
			0.00008 MIN(3u'')	2.67	1932000-7
	NATURAL	NATURAL	0.00038 MIN (15u'')	4.00	1932000-6
				3.18	1932000-5
				2.67	1932000-4
			0.00008 MIN (3u'', FLASH)	4.00	1932000-3
				3.18	1932000-2
				2.67	1932000-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± 0.5
2 PLC ± 0.13
3 PLC ± 0.013
4 PLC ± 0.0001
ANGLES ± -

MATERIAL -
FINISH -

DWN LEO ZHOU 28FEB2007
CHK STEVEN YAO 28FEB2007
APVD STEVEN YAO 28FEB2007
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME
SOCKET ASSEMBLY,
VERTICAL DDR3 DIMM,
SOLDER TAIL, 240 POSITION

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-1932000	-


CUSTOMER DRAWING | SCALE 4:1 | SHEET 2 OF 4 | REV H7

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By, - ALL RIGHTS RESERVED.


LOC	DIST
ES	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



RECOMMENDED PCB LAYOUT
VIEWED FROM CONNECTOR SIDE



RECOMMENDED MODULE LAYOUT
SCALE 3:1
REFER TO JEDEC MO-269 FOR COMPLETE MODULE DETAILS

DETAIL E
SCALE 8:1


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN LEO ZHOU 28FEB2007	TE Connectivity
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - ; 1 PLC ± 0.50 ; 2 PLC ± 0.13 ; 3 PLC ± 0.013 ; 4 PLC ± 0.0001 ; ANGLES ± -	CHK STEVEN 28FEB2007	NAME SOCKET ASSEMBLY, VERTICAL DDR3 DIMM, SOLDER TAIL, 240 POSITION
		APVD STEVEN YAO 28FEB2007	PRODUCT SPEC -
			APPLICATION SPEC -
MATERIAL -	FINISH -	WEIGHT -	SIZE A1 · CAGE CODE 00779 · DRAWING NO C-1932000 · RESTRICTED TO -
		CUSTOMER DRAWING	SCALE 4:1 · SHEET 3 OF 4 · REV H7

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By, - ALL RIGHTS RESERVED.


LOC	DIST
ES	00

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



BOTTOM TRAY



TRAY



CARTON

NOTES:

1. MATERIAL:
   1.1 TRAY: PVC
   1.2 SHIPPING CARTON : CORRUGATED FIBERBOARD

2. DIMENSION :
   2.1 TRAY : L=363, W=255, H=33
   2.2 SHIPPING CARTON : L=375, W=265, H=280

3. QUANTITY :
   3.1 PRIMARY PACKING : 50 PCS/TRAY
   3.2 SECONDARY PACKING : 8 TRAY/CARTON(400PCS)

4. WEIGHT :
   4.1 NET WEIGHT : 3.76 KG
   4.2 GROSS WEIGHT: 6.00 KG

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± 0.50
2 PLC ± 0.13
3 PLC ± 0.013
4 PLC ± 0.0001
ANGLES ± -

MATERIAL -
FINISH -

DWN 28FEB2007 LEO ZHOU
CHK 28FEB2007 STEVEN
APVD 28FEB2007 STEVEN YAO
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME
SOCKET ASSEMBLY,
VERTICAL DDR3 DIMM,
SOLDER TAIL, 240 POSITION

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-1932000	-

CUSTOMER DRAWING | SCALE - - | SHEET 4 OF 4 | REV H7


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.