



For more Information
please call

1-800-Belden1



General Description:

CAT5E Patch Cord, Bonded-Pair, 4 Pair, 24 AWG Solid, CMR, T568A/B-T568A/B, Blue, 25 ft. (7.6 m).

Usage (Overall)

Suitable Applications: IBDN System 1200, TIA Category 5E, ISO Class D, 1000BASE-T, 100BASE-T
Related Parts: CAT5E Modular Jacks, CAT5E Patch Panels

Multi Conductor

Physical Characteristics

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | Solid | BC - Bare Copper |

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Color Code Chart:

| Color |
|-------|
| Blue |

Overall Diameter

Overall Nominal Diameter: 0.208 in.

Physical Characteristics (Connectivity)

Materials

Materials:

| Description | Type | Material |
|------------------|--------|--|
| Plug | RJ45 | Polycarbonate |
| Boot | | Elastomer |
| Front Connection | Blades | Phosphor Bronze with 50u inch Gold over Nickel Plating |

Color

Boot Color: Translucent

Wiring Scheme

Wiring Scheme: T568A/B

Weight

Weight: 0.535 lbs.

Packaging

Packaging: Individually packaged in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Plug / Jack Compatibility: RJ45

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|------------------|--------------|
| RJ45 | Mated Connection | 750 Cycles |

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

C501106025 Cable Assemblies - CAT5E Modular Cord

| | |
|-----------------------------------|-------------|
| Max. Recommended Pull Tension: | 11.250 lbs. |
| Min. Bend Radius (Overall Cable): | 1.040 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-------------------------------------|
| UL Rating: | Riser |
| Other Standards: | FCC Part 68, Subpart F, IEC 60603-7 |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2006 |
| MII Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | Category 5e - TIA 568.C.2 |
| Safety Listing: | Bi-national Standard Listed |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Transmission Characteristics (Connectivity)

Performance Table 1:

| Frequency (MHz) | Max. Insertion Loss TIA* (dB) | Max. Insertion Loss Belden (dB) | Min. PSNEXT TIA* (dB) | Min PSNEXT Belden (dB) | Min. PSACRF TIA* (dB) | Min. PSACRF Belden (dB) |
|-----------------|-------------------------------|---------------------------------|-----------------------|------------------------|-----------------------|-------------------------|
| 1.000 | 2.400 | 2.000 | 62.300 | 65.300 | 60.800 | 60.800 |
| 4.000 | 4.900 | 4.000 | 53.300 | 56.300 | 48.800 | 48.800 |
| 8.000 | 6.900 | 5.700 | 48.800 | 51.800 | 42.700 | 42.700 |
| 10.000 | 7.800 | 6.400 | 47.300 | 50.300 | 40.800 | 40.800 |
| 16.000 | 9.900 | 8.100 | 44.200 | 47.300 | 36.700 | 36.700 |
| 20.000 | 11.100 | 9.200 | 42.800 | 45.800 | 34.800 | 34.800 |
| 25.000 | 12.500 | 10.300 | 41.300 | 44.300 | 32.800 | 32.800 |
| 31.250 | 14.100 | 11.600 | 39.900 | 42.900 | 30.900 | 30.900 |
| 62.500 | 20.400 | 16.800 | 35.400 | 38.400 | 24.900 | 24.900 |
| 100.000 | 26.400 | 21.700 | 32.300 | 35.300 | 20.800 | 20.800 |
| 160.000 | | 28.200 | | 32.300 | | 16.700 |

Performance Table - Footnote:

100 Meter Cable Specifications - * TIA-EIA-568-C.2 Category 5e Standard ----- PSACRF is formally PSELFEXT

Performance Table 2:

| Frequency (MHz) | Min. Return Loss TIA* (dB) | Min. Return Loss Belden (dB) |
|-----------------|----------------------------|------------------------------|
| 1.000 | 20.000 | 20.000 |
| 4.000 | 23.000 | 23.000 |
| 8.000 | 24.500 | 24.500 |
| 10.000 | 25.000 | 25.000 |
| 16.000 | 25.000 | 25.000 |
| 20.000 | 25.000 | 25.000 |
| 25.000 | 24.200 | 25.000 |
| 31.250 | 23.300 | 25.000 |
| 62.500 | 20.700 | 25.000 |
| 100.000 | 19.000 | 20.000 |
| 160.000 | | 19.000 |

| | |
|--------------------------|----------------------------------|
| Dielectric Strength: | 1,000 V RMS @ 60 Hz for 1 minute |
| Current Rating: | 1.500 A |
| Insulation Resistance: | 500 M-Ohm Minimum |
| Max. Contact Resistance: | 20 m-Ohm |

Electrical Characteristics (Overall)

Labeling

| | |
|-----------|---|
| Labeling: | Labeling: Belden Part Number, Performance Acronym, Wiring Scheme and Cord Length. |
|-----------|---|

Notes (Overall)

Notes: C501106025 is subdivided as following C5-01-1-06-025 C5 stands for performance, 01 stands for cable type, 1 stands for termination type, 06 stands for color, 025 stands for length Use last 3 digits of the code to specify length in feet - 001-015 ft in increments of 1 ft than 20 ft or 25 ft. xxx stands for special required length.

Product Family

Product List:

C501106025 Cable Assemblies - CAT5E Modular Cord

| Length | Yellow | Green | Blue | Gray | White | Black |
|----------------|------------|------------|------------|------------|------------|------------|
| 2 ft. (0.6 m) | C501104002 | C501105002 | C501106002 | C501108002 | C501109002 | C501100002 |
| 4 ft. (1.2 m) | C501104004 | C501105004 | C501106004 | C501108004 | C501109004 | C501100004 |
| 7 ft. (2.1 m) | C501104007 | C501105007 | C501106007 | C501108007 | C501109007 | C501100007 |
| 10 ft. (3.0 m) | C501104010 | C501105010 | C501106010 | C501108010 | C501109010 | C501100010 |
| 15 ft. (4.6 m) | C501104015 | C501105015 | C501106015 | C501108015 | C501109015 | C501100015 |
| 25 ft. (7.6 m) | C501104025 | C501105025 | C501106025 | C501108025 | C501109025 | C501100025 |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|------------|-------|-------------|-------------|-------|-------------------------------|
| C501106025 | 1 EA | 0.580 LB | BLUE, LIGHT | | PATCHCORD BCAT5E CMR BLU 25FT |

Revision Number: 0 Revision Date: 05-03-2016

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.