

100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

General Description

The AS78LXX series are three terminal positive regulators designed for a wide variety of applications including local, on-card regulation.

This series of regulators are complete with internal current limiting, thermal shutdown protection, and safe-area compensation which make them virtually immune from output overload. If adequate heat sinking are provided, these regulators can deliver output currents up to 100mA.

The AS78LXX series are available in TO-92 (bulk or ammo packing), SOT-89 and SOIC-8 packages.

Features

- Output Current up to 100mA
- Fixed Output Voltages of 5V, 12V and 15V
- Output Voltage Accuracy of $\pm 5\%$ over the Full Temperature Range
- Internal Short Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components
- Output Transistor Safe-area Protection

Applications

- Consumer Electronics
- Microprocessor Power Supply
- Mother Board




Figure 1. Package Types of AS78LXX

Pin Configuration





Figure 2. Pin Configuration of AS78LXX (Top View)

100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Functional Block Diagram



A (B)

A for 3-pin B for 8-pin


Figure 3. Functional Block Diagram of AS78LXX



100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Ordering Information



| Package | Temperature Range | Part Number | | Marking ID | | Packing Type |
|---------|-------------------|----------------|----------------|-------------|-------------|--------------|
| | | Lead Free | Green | Lead Free | Green | |
| TO-92 | -40 to 125°C | AS78L05Z-E1 | AS78L05Z-G1 | AS78L05Z-E1 | AS78L05Z-G1 | Bulk |
| | | AS78L05ZTR-E1 | AS78L05ZTR-G1 | AS78L05Z-E1 | AS78L05Z-G1 | Ammo |
| | | AS78L05CZTR-E1 | AS78L05CZTR-G1 | AS78L05Z-E1 | AS78L05Z-G1 | Ammo |
| | | AS78L12Z-E1 | AS78L12Z-G1 | AS78L12Z-E1 | AS78L12Z-G1 | Bulk |
| | | AS78L12ZTR-E1 | AS78L12ZTR-G1 | AS78L12Z-E1 | AS78L12Z-G1 | Ammo |
| | | AS78L15Z-E1 | AS78L15Z-G1 | AS78L15Z-E1 | AS78L15Z-G1 | Bulk |
| | | AS78L15ZTR-E1 | AS78L15ZTR-G1 | AS78L15Z-E1 | AS78L15Z-G1 | Ammo |
| SOT-89 | -40 to 125°C | AS78L05RTR-E1 | AS78L05RTR-G1 | E78E | G78E | Tape & Reel |
| | | AS78L12RTR-E1 | AS78L12RTR-G1 | E78F | G78F | Tape & Reel |
| | | AS78L15RTR-E1 | AS78L15RTR-G1 | E78G | G78G | Tape & Reel |
| SOIC-8 | -40 to 125°C | AS78L05M-E1 | AS78L05M-G1 | AS78L05M-E1 | AS78L05M-G1 | Tube |
| | | AS78L05MTR-E1 | AS78L05MTR-G1 | AS78L05M-E1 | AS78L05M-G1 | Tape & Reel |
| | | AS78L12M-E1 | AS78L12M-G1 | AS78L12M-E1 | AS78L12M-G1 | Tube |
| | | AS78L12MTR-E1 | AS78L12MTR-G1 | AS78L12M-E1 | AS78L12M-G1 | Tape & Reel |
| | | AS78L15M-E1 | AS78L15M-G1 | AS78L15M-E1 | AS78L15M-G1 | Tube |
| | | AS78L15MTR-E1 | AS78L15MTR-G1 | AS78L15M-E1 | AS78L15M-G1 | Tape & Reel |

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant. Products with "G1" suffix are available in green packages.

**100mA POSITIVE VOLTAGE REGULATOR****AS78LXX****Absolute Maximum Ratings (Note 1)**

| Parameter | Symbol | Value | | Unit |
|-------------------------------------|---------------|------------|-----|------|
| Input Voltage | V_{IN} | 36 | | V |
| Operating Junction Temperature | T_J | 150 | | °C |
| Lead Temperature (Soldering, 10sec) | T_{LEAD} | 260 | | °C |
| Power Dissipation | P_D | 750 | | mW |
| Storage Temperature Range | T_{STG} | -65 to 150 | | °C |
| Thermal Resistance | θ_{JA} | TO-92 | 180 | °C/W |
| ESD (Human Body Model) | ESD | 2000 | | V |
| ESD (Machine Model) | ESD | 200 | | V |

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

Recommended Operating Conditions

| Parameter | | Symbol | Min | Max | Unit |
|--------------------------------------|---------|----------|-----|-----|------|
| Input Voltage | AS78L05 | V_{IN} | | 30 | V |
| | AS78L12 | | | 36 | |
| | AS78L15 | | | 36 | |
| Operating Junction Temperature Range | | T_J | -40 | 125 | °C |

**100mA POSITIVE VOLTAGE REGULATOR****AS78LXX****Electrical Characteristics**

AS78L05 ($V_{IN}=10V$, $I_{OUT}=40mA$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, $T_J=25^\circ C$, **Bold** typeface applies over $-40^\circ C \leq T_J \leq 125^\circ C$, unless otherwise specified.)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--|---|---|-------------|------|-------------|-----------------|
| Output Voltage | V_{OUT} | | 4.8 | 5.0 | 5.2 | V |
| | | $7V \leq V_{IN} \leq 20V$, $1mA \leq I_{OUT} \leq 100mA$, $P_D \leq 0.75W$ | 4.75 | | 5.25 | |
| Line Regulation | V_{RLINE} | $7V \leq V_{IN} \leq 20V$ | | 8 | 150 | mV |
| Load Regulation | V_{RLOAD} | $1mA \leq I_{OUT} \leq 100mA$ | | 10 | 60 | mV |
| Quiescent Current | I_Q | | | 3 | 5.5 | mA |
| Quiescent Current Change | ΔI_Q | $8V \leq V_{IN} \leq 20V$ | | | 1.5 | mA |
| | | $1mA \leq I_{OUT} \leq 40mA$ | | | 0.1 | |
| Ripple Rejection | PSRR | $f=120Hz$, $8V \leq V_{IN} \leq 18V$ | 47 | 62 | | dB |
| Dropout Voltage | V_{DROP} | $I_{OUT}=40mA$ | | 1.7 | | V |
| | | $I_{OUT}=100mA$ | | 1.8 | | |
| Output Noise Voltage | N_O | $10Hz \leq f \leq 100kHz$ (Note 2) | | 40 | | μV |
| Output Voltage Temperature Coefficient | $\frac{\Delta V_{OUT}}{\Delta T}$ | $I_{OUT}=5mA$ | | 0.42 | | mV/ $^\circ C$ |
| | $\frac{(\Delta V_{OUT}/V_{OUT})}{\Delta T}$ | | | 84 | | ppm/ $^\circ C$ |
| Thermal Resistance | θ_{JC} | TO-92 | | 40 | | $^\circ C/W$ |
| | | SOT-89 | | 28.3 | | |
| | | SOIC-8 | | 62 | | |

Note 2: 0.01 μF minimum load capacitance is recommended to limit high frequency noise.

**100mA POSITIVE VOLTAGE REGULATOR****AS78LXX****Electrical Characteristics (Continued)**

AS78L05C ($V_{IN}=10V$, $I_{OUT}=40mA$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, $T_J=25^\circ C$, **Bold** typeface applies over $-40^\circ C \leq T_J \leq 125^\circ C$, unless otherwise specified.)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--|-------------------------------------|---------------------------------------|-----|------|------------|-----------------|
| Output Voltage | V_{OUT} | | 5.0 | | 5.1 | V |
| Line Regulation | V_{RLINE} | $7V \leq V_{IN} \leq 20V$ | | 8 | 150 | mV |
| Load Regulation | V_{RLOAD} | $1mA \leq I_{OUT} \leq 100mA$ | | 10 | 60 | mV |
| Quiescent Current | I_Q | | | 3 | 5.5 | mA |
| Quiescent Current Change | ΔI_Q | $8V \leq V_{IN} \leq 20V$ | | | 1.5 | mA |
| | | $1mA \leq I_{OUT} \leq 40mA$ | | | 0.1 | |
| Ripple Rejection | PSRR | $f=120Hz$, $8V \leq V_{IN} \leq 18V$ | 47 | 62 | | dB |
| Dropout Voltage | V_{DROP} | $I_{OUT}=40mA$ | | 1.7 | | V |
| | | $I_{OUT}=100mA$ | | 1.8 | | |
| Output Noise Voltage | N_O | $10Hz \leq f \leq 100kHz$ (Note 2) | | 40 | | μV |
| Output Voltage Temperature Coefficient | $\Delta V_{OUT}/\Delta T$ | $I_{OUT}=5mA$ | | 0.42 | | $mV/^\circ C$ |
| | $(\Delta V_{OUT}/V_{OUT})/\Delta T$ | | | 84 | | ppm/ $^\circ C$ |
| Thermal Resistance | θ_{JC} | TO-92 | | 40 | | $^\circ C/W$ |
| | | SOT-89 | | 28.3 | | |
| | | SOIC-8 | | 62 | | |

Note 2: 0.01 μF minimum load capacitance is recommended to limit high frequency noise.



100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Electrical Characteristics (Continued)

AS78L12 ($V_{IN}=19V$, $I_{OUT}=40mA$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, $T_J=25^\circ C$, **Bold** typeface applies over $-40^\circ C \leq T_J \leq 125^\circ C$, unless otherwise specified.)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--|-------------------------------------|--|-------------|------|-------------|-----------------|
| Output Voltage | V_{OUT} | | 11.5 | 12.0 | 12.5 | V |
| | | $14.5V \leq V_{IN} \leq 27V$, $1mA \leq I_{OUT} \leq 100mA$, $P_D \leq 0.75W$ | 11.4 | | 12.6 | |
| Line Regulation | V_{RLINE} | $14.5V \leq V_{IN} \leq 27V$ | | 20 | 250 | mV |
| Load Regulation | V_{RLOAD} | $1mA \leq I_{OUT} \leq 100mA$ | | 20 | 100 | mV |
| Quiescent Current | I_Q | | | 3 | 6 | mA |
| Quiescent Current Change | ΔI_Q | $16V \leq V_{IN} \leq 27V$ | | | 1.5 | mA |
| | | $1mA \leq I_{OUT} \leq 40mA$ | | | 0.1 | |
| Ripple Rejection | PSRR | $f=120Hz$, $15V \leq V_{IN} \leq 25V$ | 37 | 42 | | dB |
| Dropout Voltage | V_{DROP} | $I_{OUT}=40mA$ | | 1.7 | | V |
| | | $I_{OUT}=100mA$ | | 1.8 | | |
| Output Noise Voltage | N_O | $10Hz \leq f \leq 100kHz$ (Note 2) | | 80 | | μV |
| Output Voltage Temperature Coefficient | $\Delta V_{OUT}/\Delta T$ | $I_{OUT}=5mA$ | | 1 | | $mV/^\circ C$ |
| | $(\Delta V_{OUT}/V_{OUT})/\Delta T$ | | | 84 | | ppm/ $^\circ C$ |
| Thermal Resistance | θ_{JC} | TO-92 | | 40 | | $^\circ C/W$ |
| | | SOT-89 | | 28.3 | | |
| | | SOIC-8 | | 62 | | |

Note 2: 0.01 μF minimum load capacitance is recommended to limit high frequency noise.

**100mA POSITIVE VOLTAGE REGULATOR****AS78LXX****Electrical Characteristics (Continued)**

AS78L15 ($V_{IN}=23V$, $I_{OUT}=40mA$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, $T_J=25^\circ C$, **Bold** typeface applies over $-40^\circ C \leq T_J \leq 125^\circ C$, unless otherwise specified.)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--|-------------------------------------|--|--------------|------|--------------|-----------------|
| Output Voltage | V_{OUT} | | 14.4 | 15.0 | 15.6 | V |
| | | $17.5V \leq V_{IN} \leq 30V$, $1mA \leq I_{OUT} \leq 100mA$, $P_D \leq 0.75W$ | 14.25 | | 15.75 | |
| Line Regulation | V_{RLINE} | $17.5V \leq V_{IN} \leq 30V$ | | 25 | 250 | mV |
| Load Regulation | V_{RLOAD} | $1mA \leq I_{OUT} \leq 100mA$ | | 25 | 150 | mV |
| Quiescent Current | I_Q | | | 3 | 6 | mA |
| Quiescent Current Change | ΔI_Q | $20V \leq V_{IN} \leq 30V$ | | | 1.5 | mA |
| | | $1mA \leq I_{OUT} \leq 40mA$ | | | 0.1 | |
| Ripple Rejection | PSRR | $f=120Hz$, $18.5V \leq V_{IN} \leq 28.5V$ | 34 | 39 | | dB |
| Dropout Voltage | V_{DROP} | $I_{OUT}=40mA$ | | 1.7 | | V |
| | | $I_{OUT}=100mA$ | | 1.8 | | |
| Output Noise Voltage | N_O | $10Hz \leq f \leq 100kHz$ (Note 2) | | 90 | | μV |
| Output Voltage Temperature Coefficient | $\Delta V_{OUT}/\Delta T$ | $I_{OUT}=5mA$ | | 1.25 | | $mV/^\circ C$ |
| | $(\Delta V_{OUT}/V_{OUT})/\Delta T$ | | | 84 | | ppm/ $^\circ C$ |
| Thermal Resistance | θ_{JC} | TO-92 | | 40 | | $^\circ C/W$ |
| | | SOT-89 | | 28.3 | | |
| | | SOIC-8 | | 62 | | |

Note 2: 0.01 μF minimum load capacitance is recommended to limit high frequency noise.



100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Typical Performance Characteristics




Figure 4. Output Voltage vs. Input Voltage




Figure 5. Output Voltage vs. Case Temperature




Figure 6. Over Temperature Protection




Figure 7. Dropout Voltage vs. Case Temperature



100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Typical Performance Characteristics (Continued)




Figure 8. Output Voltage vs. Output Current




Figure 9. Quiescent Current vs. Case Temperature




Figure 10. Power Dissipation vs. Case Temperature




Figure 11. PSRR vs. Frequency

Typical Performance Characteristics (Continued)




Figure 12. Line Transient
 (Conditions: $I_{OUT}=40mA$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$)




Figure 13. Load Transient
 (Conditions: $V_{IN}=10V$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$)


100mA POSITIVE VOLTAGE REGULATOR**AS78LXX****Typical Application**

Figure 14. Typical Application of AS78LXX




100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Mechanical Dimensions

TO-92(Bulk Packing)

Unit: mm(inch)






100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Mechanical Dimensions (Continued)

TO-92(Ammo Packing)

Unit: mm(inch)






100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Mechanical Dimensions (Continued)

SOT-89

Unit: mm(inch)






100mA POSITIVE VOLTAGE REGULATOR

AS78LXX

Mechanical Dimensions (Continued)

SOIC-8

Unit: mm(inch)



Note: Eject hole, oriented hole and mold mark is optional.



BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

MAIN SITE

- Headquarters

BCD (Shanghai) Micro-electronics Limited

No. 1600, Zi Xing Road, Shanghai ZiZhu Science-based Industrial Park, 200241, P. R. C.
Tel: +86-021-2416-2266, Fax: +86-021-2416-2277

- Wafer Fab

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.

800 Yishan Road, Shanghai 200233, China
Tel: +021-6485-1491, Fax: +86-021-5450-0008

REGIONAL SALES OFFICE

Shenzhen Office

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office

Unit A Room 1203, Skyworth Bldg., Gaoxin Ave.1.S., Nanshan District
Shenzhen 518057, China

Tel: +86-0755-8660-4900, Fax: +86-0755-8660-4958

Taiwan Office (Taipei)

BCD Semiconductor (Taiwan) Company Limited

3F, No.17, Lane 171, Sec. 2, Jiu-Zong Rd., Nei-Hu Dist., Taipei(114), Taiwan, R.O.C
Tel: +886-2-2656-2808

Fax: +886-2-2656-2806/26562950

Taiwan Office (Hsinchu)

BCD Semiconductor (Taiwan) Company Limited

8F, No.176, Sec. 2, Gong-Dao 5th Road, East District
HsinChu City 300, Taiwan, R.O.C

Tel: +886-3-5160181, Fax: +886-3-5160181

USA Office

BCD Semiconductor Corp.

48460 Kato Road, Fremont, CA 94538, USA
Tel: +1-510-668-1950

Fax: +1-510-668-1990

Korea Office

BCD Semiconductor Limited Korea office.

Room 101-1112, Digital-Empire II, 486 Sin-dong,
Yeongtong-Gu, Suwon-city, Gyeonggi-do, Korea

Tel: +82-31-695-8430



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.