




**Miniature SOP6-pin type of  
60 to 600V load voltage**

**PhotoMOS®  
GU SOP 1 Form A  
(AQV21OS)**

### FEATURES



**RoHS compliant**


**1. Controls low-level analog signals**  
PhotoMOS feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.

**2. Small SOP6-Pin package**  
The device comes in a miniature SOP measuring (W) 4.4 × (L) 6.3 ×(H) 2.1 mm (W) .173× (L) .248×(H) .083 inch approx. 25% of the volume and 50% of the footprint size of DIP type

**3. Low-level off state leakage current of max. 1 µA**  
**4. Wide variation of load voltage 60V to 600V**

### TYPICAL APPLICATIONS

- Telephones
- Measuring instruments
- Computers
- Industrial robots



### TYPES

	Output rating*		Package	Part No.			Packing quantity	
	Load voltage	Load current		Tape and reel packing style		Tube	Tape and reel	
				Tube packing style	Picked from the 1/2/3-pin side			
AC/DC dual use	60V	500mA	SOP6-pin	AQV212S	AQV212SX	AQV212SZ	1 tube contains: 75 pcs. 1 batch contains: 1,500 pcs.	1,000 pcs.
	100V	300mA		AQV215S	AQV215SX	AQV215SZ		
	200V	160mA		AQV217S	AQV217SX	AQV217SZ		
	350V	120mA		AQV210S	AQV210SX	AQV210SZ		
	400V	100mA		AQV214S	AQV214SX	AQV214SZ		
	600V	40mA		AQV216S	AQV216SX	AQV216SZ		

\* Indicate the peak AC and DC values.

Note: For space reasons, the two initial letters of the part number "AQ" and the packing style indicator "X" or "Z" are not marked on the device.  
(Ex. the label for product number AQV212SX is V212S.)

# GU SOP 1 Form A (AQV21OS)

## RATING


### 1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item	Symbol	Type of connection	AQV212S	AQV215S	AQV217S	AQV210S	AQV214S	AQV216S	Remarks
Input	LED forward current	$I_F$	50 mA						
LED reverse voltage	$V_R$		5 V						
Peak forward current	$I_{FP}$		1 A						$f = 100 \text{ Hz}$ , Duty factor = 0.1%
Power dissipation	$P_{in}$		75 mW						
Output	Load voltage (peak AC)	$V_L$	60 V	100 V	200 V	350 V	400 V	600 V	
	Continuous load current	$I_L$	A	0.50 A	0.30 A	0.16 A	0.12 A	0.10 A	A connection: Peak AC, DC B, C connection: DC
			B	0.65 A	0.40 A	0.20 A	0.13 A	0.11 A	
			C	0.80 A	0.56 A	0.28 A	0.15 A	0.12 A	0.06 A
	Peak load current	$I_{peak}$		1.5A	0.90A	0.48A	0.3 A	0.3 A	0.12 A
	Power dissipation	$P_{out}$		450 mW					
Total power dissipation		$P_T$	500 mW						
I/O isolation voltage		$V_{iso}$	1,500 Vrms						
Ambient temperature	Operating	$T_{opr}$	−40 to +85°C −40 to +185°F						(Non-icing at low temperatures)
	Storage	$T_{stg}$	−40 to +100°C −40 to +212°F						

### 2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item	Symbol	Type of connection	AQV212S	AQV215S	AQV217S	AQV210S	AQV214S	AQV216S	Condition			
Input	LED operate current	$I_{Fon}$	—	0.7 mA								
	Maximum			3 mA								
	LED turn off current	$I_{Foff}$	—	0.4 mA								
	Typical			0.65 mA								
Output	LED dropout voltage	$V_F$	—	1.25 V (1.14 V at $I_F = 5 \text{ mA}$ )								
	Maximum			1.5 V								
	On resistance	$R_{on}$	A	0.83 Ω	2.3 Ω	11 Ω	23 Ω	30 Ω	70 Ω			
				2.5 Ω	4.0 Ω	15 Ω	35 Ω	50 Ω	120 Ω			
		$R_{on}$	B	0.44 Ω	1.15 Ω	5.5 Ω	11.5 Ω	22.5 Ω	55 Ω			
				1.25 Ω	2.0 Ω	7.5 Ω	17.5 Ω	25 Ω	100 Ω			
		$R_{on}$	C	0.25 Ω	0.6 Ω	2.8 Ω	6.0 Ω	11.3 Ω	28 Ω			
				0.63 Ω	1.0 Ω	3.8 Ω	8.8 Ω	12.5 Ω	50 Ω			
Transfer characteristics	Off state leakage current	$I_{leak}$	—	1 μA								
	Turn on time*	$T_{on}$	—	0.65 ms	0.60 ms	0.25 ms		0.28 ms	$I_F = 5 \text{ mA}$ $V_L = \text{Max.}$			
				2.0 ms		1.0 ms	0.5 ms					
	Turn off time	$T_{off}$	—	0.08 ms	0.06 ms	0.05 ms		0.04 ms	$I_F = 5 \text{ mA}$ $V_L = \text{Max.}$			
				0.2 ms								
	I/O capacitance	$C_{iso}$	—	0.8 pF								
				1.5 pF								
	Initial I/C isolation resistance	$R_{iso}$	—	1,000 MΩ								
	500 V DC											

\*Turn on/Turn off time



### 3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.

Item	Symbol	Min.	Max.	Unit
LED current	$I_F$	5	30	mA
AQV212S	Load voltage (Peak AC)	$V_L$	—	48 V
	Continuous load current (A connection)	$I_L$	—	0.5 A
AQV215S	Load voltage (Peak AC)	$V_L$	—	80 V
	Continuous load current (A connection)	$I_L$	—	0.3 A
AQV217S	Load voltage (Peak AC)	$V_L$	—	160 V
	Continuous load current (A connection)	$I_L$	—	0.16 A
AQV210S	Load voltage (Peak AC)	$V_L$	—	280 V
	Continuous load current (A connection)	$I_L$	—	0.12 A
AQV214S	Load voltage (Peak AC)	$V_L$	—	320 V
	Continuous load current (A connection)	$I_L$	—	0.1 A
AQV216S	Load voltage (Peak AC)	$V_L$	—	480 V
	Continuous load current (A connection)	$I_L$	—	0.04 A

■ These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

## REFERENCE DATA

### 1. Load current vs. ambient temperature characteristics


Allowable ambient temperature: -40 to +85°C  
-40 to +185°F

Type of connection: A




### 2.-1) On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
LED current: 5 mA; Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 2.-2) On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
LED current: 5 mA; Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 2.-3) On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
LED current: 5 mA; Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 3. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 4. Turn off time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 5. LED operate current vs. ambient temperature characteristics

Sample: All types;  
Load voltage: Max. (DC);  
Continuous load current: Max. (DC)




### 6. LED turn off current vs. ambient temperature characteristics

Sample: All types;  
Load voltage: Max. (DC);  
Continuous load current: Max. (DC)



### 7. LED dropout voltage vs. ambient temperature characteristics


Sample: All types;  
LED current: 5 to 50 mA



# GU SOP 1 Form A (AQV21OS)


## 8.-(1). Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 4 and 6;  
Ambient temperature: 25°C 77°F




## 8.-(2). Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 4 and 6;  
Ambient temperature: 25°C 77°F




## 9. Off state leakage current vs. load voltage characteristics

Measured portion: between terminals 4 and 6;  
Ambient temperature: 25°C 77°F




## 10. Turn on time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6;  
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




## 11. Turn off time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6;  
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F



## 12. Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 4 and 6;  
Frequency: 1 MHz;  
Ambient temperature: 25°C 77°F



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

\*Recognized in Japan, the United States, all member states of European Union and other countries.

---

Please contact .....

**Panasonic Corporation**

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadomashi, Osaka 571-8506, Japan  
[industrial.panasonic.com/ac/e/](http://industrial.panasonic.com/ac/e/)

**Panasonic®**

©Panasonic Corporation 2017

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[AQV212SZ](#) [AQV214SZ](#) [AQV215SZ](#) [AQV217SZ](#) [AQV210SZ](#) [AQV216SZ](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.