



PNP POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/535

Qualified Levels:
JAN, JANTX, and JANTXV

DESCRIPTION

This high speed transistor is rated at 5 amps and is military qualified up to a JANTXV level. This TO-59 isolated package is available with a 180 degree lead orientation. Microsemi also offers numerous other products to meet higher and lower power voltage regulation applications.

Important: For the latest information, visit our website <http://www.microsemi.com>.

FEATURES

- JEDEC registered 2N5003 and 2N5005.
- Internal metallurgical bond option available.
- JAN, JANTX, and JANTXV, qualification per MIL-PRF-19500/535 available.
- RoHS compliant versions available (commercial grade only).



Marking may vary.

**TO-59 (TO-210AA)
Isolated Package**

APPLICATIONS / BENEFITS

- Fast switching capable - 0.5 μ s rise time.
- High frequency response.
- TO-59 case with Isolated terminals.
- Class 3B to ESD per MIL-STD-750 Method 1020.

MAXIMUM RATINGS

Parameters/Test Conditions	Symbol	Value	Unit
Junction and Storage Temperature	T_J and T_{STG}	-65 to +200	$^{\circ}C$
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	88	$^{\circ}C/W$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	3.0	$^{\circ}C/W$
Collector Current	I_C	5.0	A
	$I_C^{(3)}$	10	
Collector-Emitter Voltage	V_{CEO}	80	V
Collector-Base Voltage	V_{CBO}	100	V
Emitter-Base Voltage	V_{EBO}	5.5	V
Steady-State Power Dissipation	@ $T_A = +25^{\circ}C^{(1)}$	2.0	W
	@ $T_C = +25^{\circ}C^{(2)}$	58	

- Notes:**
1. Derate linearly 11.4 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$.
 2. Derate linearly 331 mW/ $^{\circ}C$ for $T_C > +25^{\circ}C$.
 3. This value applies for $PW \leq 8.3$ ms, duty cycle $\leq 1\%$.

MSC – Lawrence

6 Lake Street,
Lawrence, MA 01841
1-800-446-1158
(978) 620-2600
Fax: (978) 689-0803

MSC – Ireland


Gort Road Business Park,
Ennis, Co. Clare, Ireland
Tel: +353 (0) 65 6840044
Fax: +353 (0) 65 6822298

Website:

www.microsemi.com

MECHANICAL and PACKAGING

- CASE: Nickel Plated.
- TERMINALS: Solder Dip over Nickel Plating. RoHS compliant Matte/Tin available on commercial grade only.
- MARKING: Manufacturer's ID, Date Code, Part Number, BeO.
- POLARITY: See Package Outline Drawing on last page.
- See [Package Dimensions](#) on last page.

PART NOMENCLATURE

SYMBOLS & DEFINITIONS

Symbol	Definition
C_{obo}	Common-base open-circuit output capacitance.
I_{CEO}	Collector cutoff current, base open.
I_{CES}	Collector emitter cutoff current, circuit between base and emitter.
I_{EBO}	Emitter cutoff current, collector open.
h_{FE}	Common-emitter static forward current transfer ratio.
V_{CEO}	Collector-emitter voltage, base open.
V_{CBO}	Collector-emitter voltage, emitter open.
V_{EBO}	Emitter-base voltage, collector open.

ELECTRICAL CHARACTERISTICS @ $T_C = 25^\circ\text{C}$ unless otherwise noted.

Characteristic	Symbol	Min.	Max.	Unit
----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 100\text{ mA}$	$V_{(BR)CEO}$	80		V
Collector-Emitter Cutoff Current $V_{CE} = 40\text{ V}, I_B = 0$	I_{CEO}		50	μA
Collector-Emitter Cutoff Current $V_{CE} = 60\text{ V}, V_{BE} = 0$ $V_{CE} = 100\text{ V}, V_{BE} = 0$	I_{CES}		1.0 1.0	μA mA
Emitter-Base Cutoff Current $V_{BE} = 4.0\text{ V}, I_C = 0$ $V_{BE} = 5.5\text{ V}, I_C = 0$	I_{EBO}		1.0 1.0	μA mA

ON CHARACTERISTICS

Forward-Current Transfer Ratio $I_C = 50\text{ mA}, V_{CE} = 5.0\text{ V}$ $I_C = 2.5\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 5.0\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 50\text{ mA}, V_{CE} = 5.0\text{ V}$ $I_C = 2.5\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 5.0\text{ A}, V_{CE} = 5.0\text{ V}$	2N5003 2N5005	h_{FE}	20 30 20 50 70 40	90 200	
Base-Emitter Voltage Non-saturated $V_{CE} = 5.0\text{ V}, I_C = 2.5\text{ A}$		V_{BE}		1.45	V
Collector-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$		$V_{CE(sat)}$		0.75 1.5	V
Base-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$		$V_{BE(sat)}$		1.45 2.2	V

DYNAMIC CHARACTERISTICS

Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 100\text{ mA}, V_{CE} = 5.0\text{ V}, f = 1\text{ kHz}$	2N5003 2N5005	h_{fe}	20 50		
Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 500\text{ mA}, V_{CE} = 5.0\text{ V}, f = 10\text{ MHz}$	2N5003 2N5005	$ h_{fe} $	6.0 7.0		
Output Capacitance $V_{CB} = 10\text{ V}, I_E = 0, f = 1\text{ MHz}$		C_{obo}		250	pF


SWITCHING CHARACTERISTICS

Turn-On Time $I_C = 5\text{ A}; I_{B1} = 500\text{ mA}$		t_{on}		0.5	μs
Storage Time $I_{B2} = -500\text{ mA}$		t_s		1.4	μs
Fall Time $V_{BE(OFF)} = 3.7\text{ V}$		t_f		0.5	μs
Turn-Off Time $R_L = 6\text{ Ohms}$		t_{off}		1.5	μs

ELECTRICAL CHARACTERISTICS @ $T_C = 25^\circ\text{C}$ unless otherwise noted. (continued)
SAFE OPERATING AREA (See Figure below and [MIL-STD-750, Test Method 3053](#))
DC Tests
 $T_C = +25^\circ\text{C}$, $V_{CE} = 0$, $t_P = 1$ second 1 Cycle

Test 1
 $V_{CE} = 12$ V, $I_C = 5$ A

Test 2
 $V_{CE} = 32$ V, $I_C = 1.7$ A

Test 3
 $V_{CE} = 80$ V, $I_C = 100$ mA

Maximum safe operating area


GRAPHS


FIGURE 1
Temperature-Power Derating






FIGURE 2
Thermal Impedance

PACKAGE DIMENSIONS

NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. See NSB Handbook H28, "Screw-Thread Standards for Federal Services".
4. The orientation of the terminals in relation to the hex flats is not controlled.
5. All three terminals.
6. The case temperature may be measured anywhere on the seating plane within .125 inch (3.18 mm) of the stud.
7. Terminal spacing measured at the base seat only.
8. This dimension applies to the location of the center line of the terminals.
9. Terminal - 1, emitter; terminal - 2, base; terminal - 3, collector. Collector lead is isolated from the case.
10. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

Symbol	Dimension				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A1		.250		6.35	
CD	.330	.360	8.38	9.14	
CD1	.370	.437	9.40	11.10	
CH	.320	.468	8.13	11.89	
HF	.424	.437	10.77	11.10	
HT	.090	.150	2.29	3.81	
OAH	.575	.763	14.61	19.38	5
PS	.185	.215	4.70	5.46	4, 8
PS1	.090	.110	2.29	2.79	4, 8
SL	.400	.455	10.16	11.56	
SU		.078		1.98	7
T	.040	.065	1.02	1.65	
UD	.155	.189	3.94	4.80	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[2N5005](#) [2N5003](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.