




SECTION A-A
TPA SHOWN IN AS-SHIPPED
PRE-LOCKED POSITION
SEE NOTE 3




SECTION A-A
TPA SHOWN IN FINAL
LOCKED POSITION




BOTTOM VIEW




FRONT VIEW



RIGHT SIDE VIEW



BACK VIEW




ITEM	DESCRIPTION	COLOR
1	CONNECTOR HOUSING	SEE CHART
2	TERMINAL HOUSING	BLACK
3	TPA	NATURAL
4	MATTE SEAL	SEE CHART
5	PERIPHERAL SEAL	SEE CHART
6	CPA - OPTIONAL	RED


CONNECTOR ASSEMBLY
WITHOUT CLIPSLOT

NOTES:


1. DESIGNED TO MATE WITH DEVICE CONNECTION AS SPECIFIED IN USCAR DRAWINGS AVAILIBLE AT <http://ewcap.uscarteams.org/>.
   1X2 064-S-002-1-Z02
   1X3 064-S-003-1-Z01
   1X4 064-S-004-1-Z02
   1X5 064-S-005-1-Z02
   1X6 064-S-006-1-Z02
   1X8 064-S-008-1-Z02
2. ASSEMBLY SHIPPED WITH TPA IN PRE-LOCKED POSITION (SEE SECTION A-A). UPON FULL TERMINAL ASSEMBLY, TPA MUST BE SEATED TO THE FINAL LOCKED POSITION.
3. TPA'S MAY BECOME SEATED DURING TRANSIT. IF THIS OCCURS, TPA'S SHOULD BE MOVED TO THE PRE-LOCKED POSITION PRIOR TO FEMALE TERMINAL INSTALLATION. REFERENCE PRODUCT SPECIFICATION: PS-34646-001
4. SYSTEM TO BE USED WITH OUTSIDE WIRE DIAMETERS RANGING FROM 1,20MM TO 2,06MM WITHIN RANGE OF:
   - SAE 22 AWG TO 18 AWG PER ESB-M1L123-A2
   - ISO 0,35MM² TO 0,75MM² PER GMW15626 AND ES-AU5T-1A348-AA
5. POLARIZATION FEATURE EFFECTIVENESS PER USCAR-2 PARAGRAPH 5.4.4 IS REDUCED WHEN TESTING ALL POLARIZATION OPTIONS: 100N MIN.
6. DATE CODE: FIRST TWO DIGITS ARE THE CALENDAR YEAR (EXAMPLE: 04 = 2004). THIRD THROUGH 5TH DIGIT DAY # OF THE CALENDAR YEAR (EXAMPLE: FEB. 3RD = '034').
7. SEE SHEET #2 FOR CONNECTOR ASSEMBLY WITH CLIP SLOT.
8. FOR CLIPSSLOT CONNECTOR: CLIP OVERHANGS CONNECTOR, PLEASE CHECK APPLICATION (COULD CAUSE WIRE CHAFING)-SHORTER CLIP IS A RECOMMENDATION.



POLARIZATION B



POLARIZATION C



POLARIZATION D

PART NUMBER LEGEND
CONNECTOR ASSEMBLY

3140X-XXXX

- SEAL PLUG CONFIGURATION (AS MOLDED)
  0 - ALL CIRCUITS OPEN
  1-9 SEE CHART
- CPA OPTION
  0 OR 2 - WITHOUT CPA
  1 OR 3 - WITH CPA
  4 - WITHOUT CPA, WITH CLIPSLOT
  5 - WITH CPA, WITH CLIPSLOT
- USCAR POLARIZATION OPTION
  1 - POLARIZATION OPTION A
  2 - POLARIZATION OPTION B
  3 - POLARIZATION OPTION C
  4 - POLARIZATION OPTION D
  5 - POLARIZATION OPTION B, BLACK
  6 - POLARIZATION OPTION C, BLACK
  7 - POLARIZATION OPTION D, BLACK
  8 - POLARIZATION OPTION C, NATURAL
  9 - POLARIZATION OPTION D, GRAY
- CIRCUIT SIZE 2, 3, 4, 5, 6 & 8
- TERMINAL OPTION
  2 - TYCO/MOLEX GET 0,64
  3 - MOLEX 0,64
  4 - YAZAKI KAIZEN 0,64

ADD NEW P/N
EC NO: UAU2015-0819 2014/11/20
DRWN: DENG02 2014/11/21
CHKD:
APPR: WKOSHY
DESCRIPTION
REV
K1

QUALITY SYMBOLS
=0
=0
=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.13	± ---
1 PLACE	± 0,3	± ---
0 PLACE	±	±

ANGULAR ± 3 °
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 4:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


		DATE
DRAWN BY	RCARLSON	2003/09/25
CHECKED BY	RCARLSON	2004/09/28
APPROVED BY	VKOSHY	2010/11/22

TITLE: 0.64 USCAR CONNECTOR SEALED SINGLE ROW ASSEMBLY

molex


MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-31402-211
SHEET NO.: 1 OF 5
SIZE: D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION




SECTION C-C

TPA SHOWN IN AS-SHIPPED
PRE-LOCKED POSITION
SEE NOTE 3





SECTION C-C

TPA SHOWN IN FINAL
LOCKED POSITION




BOTTOM VIEW






FRONT VIEW

POLARIZATION A



RIGHT SIDE VIEW



BACK VIEW

CONNECTOR ASSEMBLY WITH CLIPSLOT

ADD NEW P/N
EC NO: UAU2015-0819 2014/11/20
DRWN: JDENG02 2014/11/21
CHKD:
APPR: VKOSHY
DESCRIPTION
REV K1

QUALITY SYMBOLS
▽=0
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.13	± ---
1 PLACE	± 0.3	± ---
0 PLACE	±	±

ANGULAR ± 3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 4:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

		DATE
DRAWN BY	RCARLSON	2003/09/25
CHECKED BY	RCARLSON	2004/09/28
APPROVED BY	VKOSHY	2010/11/22
MATERIAL NO.	SEE CHART	

TITLE: 0.64 USCAR CONNECTOR SEALED SINGLE ROW ASSEMBLY

molex

DOCUMENT NO. SD-31402-211
SHEET NO. 2 OF 5

SIZE D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

PART NUMBER WITHOUT CPA	PART NUMBER WITH CPA	CLIPSLOT OPTION	ROW/ CIRCUITS	KEY*	MATTE SEAL COLOR	PERIMETER SEAL COLOR	CONNECTOR COLOR	WIDTH DIM (A)	MIN. PASS THRU DIA.	FEMALE TERMINAL SUPPLIER	USCAR FOOTPRINT DRAWING NO.	STATUS
31402-2100	31402-2110	NO	1 X 2	A	ROYAL BLUE	BLUE	BLACK	16.88	(20,80)	TYCO OR MOLEX GET 0.64	064-S-002-1-Z02	TOOLED
31402-2200	31402-2210			B			GRAY					TOOLED
31402-2300	31402-2310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31402-2400	31402-2410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31402-2500	31402-2510			B			BLACK					TOOLED
31402-2600	31402-2610			C			BLACK					TOOLED
31402-2700	31402-2710			D			BLACK					TOOLED
31403-2100	31403-2110			A			BLACK			MOLEX 0.64		TOOLED
31403-2200	31403-2210			B			GRAY					TOOLED
31403-2300	31403-2310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31403-2400	31403-2410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31403-2500	31403-2510			B			BLACK					TOOLED BUT NOT VALIDATED
31403-2600	31403-2610			C			BLACK					TOOLED
31403-2700	31403-2710			D			BLACK					TOOLED
31403-2800	31403-2810			C			NATURAL					OK TO TOOL
31403-2900	31403-2910			D			GRAY					TOOLED
31404-2100	31404-2110			A			BLACK			YAZAKI KAIZEN 0.64		NOT TOOLED
31404-2200	31404-2210			B			GRAY					NOT TOOLED
31404-2300	31404-2310			C			BROWN					NOT TOOLED
31404-2400	31404-2410			D			GREEN					NOT TOOLED
31404-2500	31404-2510			B			BLACK					NOT TOOLED
31404-2600	31404-2610			C			BLACK					NOT TOOLED
31404-2700	31404-2710			D			BLACK					NOT TOOLED
31402-3100	31402-3110	NO	1 X 3	A	LIGHT BLUE	RUST RED	BLACK	18.70	(22,00)	TYCO OR MOLEX GET 0.64	064-S-003-1-Z01	TOOLED
31402-3200	31402-3210			B			GRAY					TOOLED
31402-3300	31402-3310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31402-3400	31402-3410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31402-3500	31402-3510			B			BLACK					TOOLED
31402-3600	31402-3610			C			BLACK					TOOLED
31402-3700	31402-3710			D			BLACK					TOOLED
31403-3100	31403-3110			A			BLACK			MOLEX 0.64		TOOLED
31403-3200	31403-3210			B			GRAY					TOOLED
31403-3300	31403-3310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31403-3400	31403-3410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31403-3500	31403-3510			B			BLACK					TOOLED
31403-3600	31403-3610			C			BLACK					TOOLED
31403-3700	31403-3710			D			BLACK					TOOLED
31404-3100	31404-3110			A			BLACK			YAZAKI KAIZEN 0.64		TOOLED
31404-3200	31404-3210			B			GRAY					TOOLED
31404-3300	31404-3310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31404-3400	31404-3410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31404-3500	31404-3510			B			BLACK					TOOLED
31404-3600	31404-3610			C			BLACK					TOOLED
31404-3700	31404-3710			D			BLACK					TOOLED
31402-4100	31402-4110	NO	1 X 4	A	TBD	TBD	BLACK	21.25	(22,34)	TYCO OR MOLEX GET 0.64	064-S-004-1-Z02	NOT TOOLED
31402-4200	31402-4210			B			GRAY					NOT TOOLED
31402-4300	31402-4310			C			BROWN					NOT TOOLED
31402-4400	31402-4410			D			GREEN					NOT TOOLED
31402-4500	31402-4510			B			BLACK					NOT TOOLED
31402-4600	31402-4610			C			BLACK					NOT TOOLED
31402-4700	31402-4710			D			BLACK					NOT TOOLED
31403-4100	31403-4110			A			BLACK			MOLEX 0.64		NOT TOOLED
31403-4200	31403-4210			B			GRAY					NOT TOOLED
31403-4300	31403-4310			C			BROWN					NOT TOOLED
31403-4400	31403-4410			D			GREEN					NOT TOOLED
31403-4500	31403-4510			B			BLACK					NOT TOOLED
31403-4600	31403-4610			C			BLACK					NOT TOOLED
31403-4700	31403-4710			D			BLACK					NOT TOOLED
31404-4100	31404-4110			A			BLACK			YAZAKI KAIZEN 0.64		NOT TOOLED
31404-4200	31404-4210			B			GRAY					NOT TOOLED
31404-4300	31404-4310			C			BROWN					NOT TOOLED
31404-4400	31404-4410			D			GREEN					NOT TOOLED
31404-4500	31404-4510			B			BLACK					NOT TOOLED
31404-4600	31404-4610			C			BLACK					NOT TOOLED
31404-4700	31404-4710			D			BLACK					NOT TOOLED

ADD NEW P/N
EC NO: UAU2015-0819 2014/11/20
DRWN: JDENG02 2014/11/21
CHKD:
APPR: VKOSHY
DESCRIPTION
REV
K1

QUALITY SYMBOLS
▽=0
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.13	± ---
1 PLACE	± 0.3	± ---
0 PLACE	±	±

ANGULAR ± 3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 4:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: RCARLSON DATE: 2003/09/25
CHECKED BY: RCARLSON DATE: 2004/09/28
APPROVED BY: VKOSHY DATE: 2010/11/22
MATERIAL NO.: SEE CHART

TITLE: 0.64 USCAR CONNECTOR SEALED SINGLE ROW ASSEMBLY

molex

DOCUMENT NO.: SD-31402-211
SHEET NO.: 3 OF 5
SIZE: D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

PART NUMBER WITHOUT CPA	PART NUMBER WITH CPA	CLIPSLOT OPTION	ROW/ CIRCUITS	KEY*	MATTE SEAL COLOR	PERIMETER SEAL COLOR	CONNECTOR COLOR	WIDTH DIM (A)	MIN. PASS THRU DIA.	FEMALE TERMINAL SUPPLIER	USCAR FOOTPRINT DRAWING NO.	STATUS
31402-5100	31402-5110	NO	1 X 5	A	TBD	TBD	BLACK	23.80	(24.28)	TYCO OR MOLEX GET 0.64	064-S-005-1-Z02	NOT TOOLED
31402-5200	31402-5210			B			GRAY					NOT TOOLED
31402-5300	31402-5310			C			BROWN					NOT TOOLED
31402-5400	31402-5410			D			GREEN					NOT TOOLED
31402-5500	31402-5510			B			BLACK					NOT TOOLED
31402-5600	31402-5610			C			BLACK					NOT TOOLED
31402-5700	31402-5710			D			BLACK					NOT TOOLED
31403-5100	31403-5110			A			BLACK			MOLEX 0.64		NOT TOOLED
31403-5200	31403-5210			B			GRAY					NOT TOOLED
31403-5300	31403-5310			C			BROWN					NOT TOOLED
31403-5400	31403-5410			D			GREEN					NOT TOOLED
31403-5500	31403-5510			B			BLACK					NOT TOOLED
31403-5600	31403-5610			C			BLACK					NOT TOOLED
31403-5700	31403-5710			D			BLACK					NOT TOOLED
31404-5100	31404-5110			A			BLACK			YAZAKI KAIZEN 0.64		NOT TOOLED
31404-5200	31404-5210			B			GRAY					NOT TOOLED
31404-5300	31404-5310			C			BROWN					NOT TOOLED
31404-5400	31404-5410			D			GREEN					NOT TOOLED
31404-5500	31404-5510			B			BLACK					NOT TOOLED
31404-5600	31404-5610			C			BLACK					NOT TOOLED
31404-5700	31404-5710			D			BLACK					NOT TOOLED
31402-6100	31402-6110	NO	1 X 6	A	ROYAL BLUE	LIGHT BLUE	BLACK	26.33	(26.82)	TYCO OR MOLEX GET 0.64	064-S-006-1-Z02	TOOLED
31402-6200	31402-6210			B			GRAY					TOOLED
31402-6300	31402-6310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31402-6400	31402-6410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31402-6500	31402-6510			B			BLACK					TOOLED
31402-6600	31402-6610			C			BLACK					TOOLED
31402-6700	31402-6710			D			BLACK					TOOLED
31403-6100	31403-6110			A			BLACK			MOLEX 0.64		TOOLED
31403-6200	31403-6210			B			GRAY					TOOLED
31403-6300	31403-6310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31403-6400	31403-6410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31403-6500	31403-6510			B			BLACK					TOOLED
31403-6600	31403-6610			C			BLACK					TOOLED
31403-6700	31403-6710			D			BLACK					TOOLED
31404-6100	31404-6110			A			BLACK			YAZAKI KAIZEN 0.64		TOOLED
31404-6200	31404-6210			B			GRAY					TOOLED
31404-6300	31404-6310			C			BROWN					TOOLED, COLOR UNAVAILABLE
31404-6400	31404-6410			D			GREEN					TOOLED, COLOR UNAVAILABLE
31404-6500	31404-6510			B			BLACK					TOOLED
31404-6600	31404-6610			C			BLACK					TOOLED
31404-6700	31404-6710			D			BLACK					TOOLED
31404-6800	31404-6810			C			NATURAL					OK TO TOOL

ADD NEW P/N
EC NO: UAU2015-0819 2014/11/20
DRWN: JDENG02 2014/11/21
CHKD:
APPR: VKOSHY
DESCRIPTION
REV K1

QUALITY SYMBOLS
▽=0
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.13	± ---
1 PLACE	± 0.3	± ---
0 PLACE	±	±

ANGULAR ± 3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 4:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

		DATE
DRAWN BY	RCARLSON	2003/09/25
CHECKED BY	RCARLSON	2004/09/28
APPROVED BY	VKOSHY	2010/11/22
MATERIAL NO.	SEE CHART	

TITLE: 0.64 USCAR CONNECTOR SEALED SINGLE ROW ASSEMBLY

molex

DOCUMENT NO.: SD-31402-211
SHEET NO.: 4 OF 5
SIZE: D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

PART NUMBER WITHOUT CPA	PART NUMBER WITH CPA	CLIPSLOT OPTION	ROW/ CIRCUITS	KEY*	MATTE SEAL COLOR	PERIMETER SEAL COLOR	CONNECTOR COLOR	WIDTH DIM (A)	MIN. PASS THRU DIA.	FEMALE TERMINAL SUPPLIER	USCAR FOOTPRINT DRAWING NO.	STATUS
31402-8100	31402-8110	NO	1 X 8	A	TBD	TBD	BLACK	31.25	(31.90)	TYCO OR MOLEX GET 0.64	064-S-008-1-Z02	NOT TOOLED
31402-8200	31402-8210			B			GRAY					NOT TOOLED
31402-8300	31402-8310			C			BROWN					NOT TOOLED
31402-8400	31402-8410			D			GREEN					NOT TOOLED
31402-8500	31402-8510			B			BLACK					NOT TOOLED
31402-8600	31402-8610			C			BLACK					NOT TOOLED
31402-8700	31402-8710			D			BLACK					NOT TOOLED
31403-8100	31403-8110			A			BLACK			MOLEX 0.64		NOT TOOLED
31403-8200	31403-8210			B			GRAY					NOT TOOLED
31403-8300	31403-8310			C			BROWN					NOT TOOLED
31403-8400	31403-8410			D			GREEN					NOT TOOLED
31403-8500	31403-8510			B			BLACK					NOT TOOLED
31403-8600	31403-8610			C			BLACK					NOT TOOLED
31403-8700	31403-8710			D			BLACK					NOT TOOLED
31404-8100	31404-8110			A			BLACK			YAZAKI KAIZEN 0.64		NOT TOOLED
31404-8200	31404-8210			B			GRAY					NOT TOOLED
31404-8300	31404-8310			C			BROWN					NOT TOOLED
31404-8400	31404-8410			D			GREEN					NOT TOOLED
31404-8500	31404-8510			B			BLACK					NOT TOOLED
31404-8600	31404-8610			C			BLACK					NOT TOOLED
31404-8700	31404-8710			D			BLACK					NOT TOOLED

ADDITIONAL CAVITY PLUG CONFIGURATIONS:

ROW/ CIRCUITS	FEMALE TERMINAL	MOLEX P/N WITH CPA	MOLEX P/N WITHOUT CPA	KEY OPTION	CLIPSLOT OPTION	COLOR	CIRCUIT NUMBER: "0" INDICATED PLUG LOCATION						TOTAL CIRCUITS PLUGGED	STATUS	
							1	2	3	4	5	6			
1X6	TYCO/MOLEX GET	31402-6110	31402-6100	A	NO	BLACK							0	TOOLED	
		31402-6111	31402-6101	A	NO	BLACK	0	0	0	0	0	0	6	TOOLED	
		31402-6112	31402-6102	A	NO	BLACK	0	0					2	TOOLED	
		31402-6113	31402-6103	A	NO	BLACK		0					1	TOOLED	
		31402-6114	31402-6104	A	NO	BLACK	0	0	0	0			4	TOOLED	
		31402-6115	31402-6105	A	NO	BLACK			0		0	0	3	TOOLED	
		31402-6150	31402-6140	A	YES	BLACK							0	TOOLED	
	MOLEX 0.64	31403-6110	31403-6100	A	NO	BLACK							0	TOOLED	
		31403-6111	31403-6101	A	NO	BLACK	0	0	0	0	0	0	6	TOOLED	
		31403-6112	31403-6102	A	NO	BLACK			0				1	TOOLED	
		31403-6113	31403-6103	A	NO	BLACK	0	0	0		0		4	TOOLED	(J9)
		31404-6110	31404-6100	A	NO	BLACK							0	TOOLED	
	YAZAKI KAIZEN	31404-6111	31404-6101	A	NO	BLACK	0	0	0	0	0	0	6	TOOLED	
		31404-6112	31404-6102	A	NO	BLACK	0		0				2	TOOLED	
		31404-6113	31404-6103	A	NO	BLACK	0					0	2	TOOLED	
		31404-6116	31404-6106	A	NO	BLACK						0	1	TOOLED	
		31404-6117	31404-6107	A	NO	BLACK	0		0			0	3	TOOLED	
		31404-6118	31404-6108	A	NO	BLACK	0						1	TOOLED	
		31404-6119	31404-6109	A	NO	BLACK			0		0	0	3	TOOLED	
		31404-6132	31404-6122	A	NO	BLACK			0				1	TOOLED	
		31404-6213	31404-6203	B	NO	GRAY	0					0	2	TOOLED	(J10)
		31404-6214	31404-6204	B	NO	GRAY						0	1	OK TO TOOL	(K1)
		31404-6812	31404-6802	C	NO	NATURAL				0	0	0	3	OK TO TOOL	
1X3	TYCO/MOLEX GET	31402-3113	31402-3103	A	NO	BLACK			0				1	OK TO TOOL	(K)

ADD NEW P/N
EC NO: UAU2015-0819 2014/11/20
DRWN: JDENG02
CHKD:
APPR: VKOSHY 2014/11/21
DESCRIPTION
REV
K1

QUALITY SYMBOLS
▽=0
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.13	± ---
1 PLACE	± 0.3	± ---
0 PLACE	±	±

ANGULAR ± 3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 4:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: RCARLSON DATE: 2003/09/25
CHECKED BY: RCARLSON DATE: 2004/09/28
APPROVED BY: VKOSHY DATE: 2010/11/22
MATERIAL NO.: SEE CHART

TITLE: 0.64 USCAR CONNECTOR SEALED SINGLE ROW ASSEMBLY

molex

DOCUMENT NO.: SD-31402-211
SHEET NO.: 5 OF 5

SIZE: D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.