

Surface Mount Multilayer Ceramic Chip Capacitors for TCC Critical Applications



FEATURES

- Designed for excellent T/VCC
- Temperature voltage coefficient (T/VCC) does not exceed - 25 % at rated voltage
- Excellent aging characteristics
- Surface mount, precious metal technology, wet build process

**RoHS**
COMPLIANT

GENERAL SPECIFICATIONS

Note: Electrical characteristics at + 25 °C unless otherwise specified

Capacitance Range: 120 pF to 2.7 μ F

Voltage Range: 25 Vdc to 100 Vdc

Temperature Coefficient of Capacitance (TCC):

+ 15 %, - 25 % from - 55 °C to + 125 °C, with rated voltage applied

\pm 15 % from - 55 °C to + 125 °C, with 0 Vdc applied

Dissipation Factor (DF):

2.5 % maximum at 1.0 V_{rms} and 1 kHz

Aging Rate: 1 % maximum per decade

Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 M Ω minimum or 1000 Ω F, whichever is less

At + 125 °C and rated voltage 10 000 M Ω minimum or 100 Ω F, whichever is less


Dielectric Withstanding Voltage (DWV):

This is the maximum voltage the capacitors are tested for a 1 to 5 second period and the charge/discharge current does not exceed 50 mA

\leq 100 V DC: DWV at 250 % of rated voltage

Vishay Vitramon Surface Mount Multilayer Ceramic Chip Capacitors for TCC Critical Applications

DIMENSIONS in inches [millimeters]



EIA STYLE	PART ORDERING NUMBER	LENGTH (L)	WIDTH (W)	MAXIMUM THICKNESS (T)	TERMINATION (P)	
					MINIMUM	MAXIMUM
0402	VJ0402	0.040 + 0.004/- 0.002 [1.00 + 0.10/- 0.05]	0.020 + 0.004/- 0.002 [0.50 + 0.10/- 0.05]	0.024 [0.60]	0.004 [0.10]	0.016 [0.41]
0603	VJ0603	0.063 ± 0.005 [1.60 ± 0.12]	0.031 ± 0.005 [0.80 ± 0.12]	0.036 [0.92]	0.012 [0.30]	0.018 [0.46]
0805	VJ0805	0.079 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.057 [1.45]	0.010 [0.25]	0.028 [0.71]
1206	VJ1206	0.126 ± 0.008 [3.20 ± 0.20]	0.063 ± 0.008 [1.60 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
1210	VJ1210	0.126 ± 0.008 [3.20 ± 0.20]	0.098 ± 0.008 [2.50 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
-	VJ1808	0.177 ± 0.010 [4.50 ± 0.25]	0.080 ± 0.010 [2.03 ± 0.25]	0.067 [1.70]	0.010 [0.25]	0.030 [0.76]
1812	VJ1812	0.177 ± 0.010 [4.50 ± 0.25]	0.126 ± 0.008 [3.20 ± 0.20]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
1825	VJ1825	0.177 ± 0.010 [4.50 ± 0.25]	0.252 ± 0.010 [6.40 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2220	0.220 ± 0.008 [5.59 ± 0.20]	0.200 ± 0.010 [5.08 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2225	0.220 ± 0.010 [5.59 ± 0.25]	0.250 ± 0.010 [6.35 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]

ORDERING INFORMATION

VJ0805	X	102	K	X	A	A	C	### ⁽²⁾
CASE SIZE	DIELECTRIC	CAPACITANCE NOMINAL CODE	CAPACITANCE TOLERANCE	TERMINATION	DC VOLTAGE RATING ⁽¹⁾	MARKING	PACKAGING	PROCESS CODE
0402 0603 0805 1206 1210 1808 1812 1825 2220 2225	X = BX	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. Example: 102 = 1000 pF	J = ± 5 % K = ± 10 % M = ± 20 %	X = Ni barrier 100 % tin plated F = AgPd	X = 25 V A = 50 V B = 100 V	A = Unmarked M = Marked Note: Marking is only available for 0805 and 1206 on request		
							T = 7" reel/plastic tape C = 7" reel/paper tape R = 11 1/4" reel/plastic tape P = 11 1/4" reel/paper tape O = 7" reel/flamed paper tape I = 11 1/4"/13" reel/flamed paper tape Note: "I" and "O" is used for "F" termination	

Notes:

(1) DC voltage rating should not be exceeded in application

(2) Process Code may be added with up to three digits, used to control non-standard products and/or special requirements



SELECTION CHART																												
STYLE		VJ0402		VJ0603		VJ0805			VJ1206			VJ1210 ⁽¹⁾			VJ1808 ⁽¹⁾			VJ1812 ⁽¹⁾			VJ1825 ⁽¹⁾			VJ2220 ⁽¹⁾		VJ2225 ⁽¹⁾		
EIA TYPE		0402		0603		0805			1206			1210			-			1812			1825			-		-		
VOLTAGE (Vdc)		25	50	25	50	25	50	100	25	50	100	25	50	100	25	50	100	25	50	100	25	50	100	50	100	25	50	
CAP. CODE	CAP.																											
101	100 pF		**																									
121	120 pF	**	**																									
151	150 pF	**	**																									
181	180 pF	**	**																									
221	220 pF	**	**																									
271	270 pF	**	**																									
331	330 pF	**	**																									
391	390 pF	**	**	**	**		**	**																				
471	470 pF	**	**	**	**	**	**	**	**																			
561	560 pF	**	**	**	**	**	**	**	**																			
681	680 pF	**	**	**	**	**	**	**	**																			
821	820 pF	**	**	**	**	**	**	**	**																			
102	1000 pF	**	**	**	**	**	**	**	*	*	*																	
122	1200 pF	**	**	**	**	**	**	**	*	*	*																	
152	1500 pF	**	**	**	**	**	**	**	*	*	*																	
182	1800 pF	**	**	**	**	**	**	**	*	*	*																	
222	2200 pF	**	**	**	**	**	**	**	*	*	*																	
272	2700 pF	**		**	**	**	**	**	*	*	*																	
332	3300 pF	**		**	**	**	**	**	*	*	*																	
392	3900 pF	**		**	**	**	**	**	*	*	*																	
472	4700 pF			**	**	**	**	**	*	*	*																	
562	5600 pF			**	**	**	**	**	*	*	*																	
682	6800 pF			**	**	**	**	**	*	*	*																	
822	8200 pF			**	**	**	**	**	*	*	*																	
103	0.010 μF			**	**	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
123	0.012 μF			**		*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
153	0.015 μF			**		*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
183	0.018 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
223	0.022 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
273	0.027 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
333	0.033 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
393	0.039 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
473	0.047 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
563	0.056 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
683	0.068 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
823	0.082 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
104	0.10 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
124	0.12 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
154	0.15 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
184	0.18 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
224	0.22 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
274	0.27 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
334	0.33 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
394	0.39 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
474	0.47 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
564	0.56 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
684	0.68 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
824	0.82 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
105	1.0 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
125	1.2 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
155	1.5 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
185	1.8 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
225	2.2 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
275	2.7 μF					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*


Notes:

⁽¹⁾ See soldering recommendations within this data book, or visit www.vishay.com/doc?45034


** Paper Tape • Plastic Tape

BX DIELECTRIC - TYPICAL PARAMETERS


TEMPERATURE COEFFICIENT OF CAPACITANCE




VOLTAGE COEFFICIENT OF CAPACITANCE - BX




MINIMUM INSULATION RESISTANCE VS. TEMPERATURE



DISSIPATION FACTOR VS. TEMPERATURE



AGING RATE - BX





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.