
## Adapter Plates (Z-Rail Type)


| Part No. | Description |
|---|---|
| AS1/2 (Pkg of 2) | Adapter plate for mounting DIN connectors directly onto subrack, 84 tapped holes (2.5mm x 4.5mm pitch) To be used without backplane |




## Insulation Strips

Mounted between backplane and rear extrusion


| Part No. | HP | Width |
|---|---|---|
| 5250998-84 | 84 | 17.00” (431.8mm) |




## Nut Strips

Threaded mounting holes spaced at 0.2” centers slide into extrusion grooves, can be used to anchor panels, cards or other components. Used on front & rear extrusions on all Vector DIN based metric subracks.


| Part No. | HP | Width |
|---|---|---|
| 5250268-84 | 84 | 17” (431.8mm) |
| 5250268-63 | 63 | 12.8” (325.1mm) |
| 5250268-42 | 42 | 8.6” (218.4mm) |
| 5250268-21 | 21 | 4.4” (111.8mm) |




# Extrusions

All extrusions available in any length


### Front




| Part No. | HP | A |
|---|---|---|
| 5250236-84 | 84 | 17.00” (431.8) |
| 5250236-63 | 63 | 12.80” (325.8) |
| 5250236-42 | 42 | 8.60” (218.4) |
| 5250236-21 | 21 | 4.40” (11.8) |

Pack of 12 8-32 screws, P/N HD94


### Rear




| Part No. | HP | A |
|---|---|---|
| 5250238-84 | 84 | 17.00” (431.8) |
| 5250238-63 | 63 | 12.80” (325.8) |
| 5250238-42 | 42 | 8.60” (218.4) |
| 5250238-21 | 21 | 4.40” (11.8) |


Pack of 12 8-32 screws, P/N HD94

### Rear Center




| Part No. | HP | A |
|---|---|---|
| 5250237-84 | 84 | 17.00” (431.8) |
| 5250237-63 | 63 | 12.80” (325.8) |
| 5250237-42 | 42 | 8.60” (218.4) |
| 5250237-21 | 21 | 4.40” (11.8) |


Pack of 12 8-32 screws, P/N HD94




| Part No. | HP | A |
|---|---|---|
| 5250229-84 | 84 | 17.00” (431.8) |
| 5250229-63 | 63 | 12.80” (325.8) |
| 5250229-42 | 42 | 8.60” (218.4) |
| 5250229-21 | 21 | 4.40” (11.8) |

Pack of 12 8-32 screws, P/N HD94

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | B | | | |
| | | | | |
| | | | | |




SOLD IN 17.000" LENGTH TO BE CUT TO SIZE
VECTOR P/N # AS1/2 (pkg of 2)

| PART NO. | DESCRIPTION |
|---|---|
| AS1/2 (Pkg of 2) | Adapter plate for mounting DIN connectors directly onto subrack, 84 tapped holes (2.5mm x 4.5mm pitch) to be used without backplane |

3. REMOVE ALL BURRS & SHARP EDGES
2. FINISH: ZINC PLATE PER ASTM-B-633, CLASS 3, TYPE I
1. MAT'L: STEEL, COLD ROLLED, 16 GA.

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: ±.5°
TWO PLACE DECIMAL ±.02
THREE PLACE DECIMAL ±.005
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL 1
FINISH 2
DO NOT SCALE DRAWING

| | NAME | DATE |
|---|---|---|
| DRAWN | TRUSHAR | 01/13/09 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |

THIRD ANGLE PROJECTION


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605

# DIN ADAPTER PLATE
## VME CARD CAGE

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5700201 | B |

SCALE: 2:3 | WEIGHT: | SHEET 1 OF 1

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | C | INC ECO 3213 & REDRAWN | 08/13/86 | |
| | C1 | INC ECO 3873 | 08/13/90 | |




SOLD IN 16.970" LENGTH TO BE CUT TO SIZE
VECTOR P/N # 5250998-84

| PART NO. | DESCRIPTION |
|---|---|
| 5250998-84 | Mounted between backplane and rear extrusion |

2. INSPECTION: ACCEPTABLE UP TO .040 THK.
1. MAT'L: PP VINYL SHEET, .026 TO .033 THK., (COLOR : BLACK), P/N 99400003

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: ±.5°
TWO PLACE DECIMAL ±.02
THREE PLACE DECIMAL ±.005
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL 1
FINISH
DO NOT SCALE DRAWING

| | NAME | DATE |
|---|---|---|
| DRAWN | TRUSHAR | 01/12/09 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |

THIRD ANGLE PROJECTION


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605

# INSULATION STRIP
## VME CARD CAGE

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5210208 | C1 |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | A | | | |
| | | | | |
| | | | | |




| TABULATION | | |
|---|---|---|
| PART NO. | "A" | "B" |
| 5250268-03 | 0.800 | 3 |
| 5250268-04 | 1.000 | 4 |
| 5250268-05 | 1.200 | 5 |
| 5250268-06 | 1.400 | 6 |
| 5250268-07 | 1.600 | 7 |
| 5250268-08 | 1.800 | 8 |
| 5250268-09 | 2.000 | 9 |
| 5250268-10 | 2.200 | 10 |
| 5250268-11 | 2.400 | 11 |
| 5250268-12 | 2.600 | 12 |
| 5250268-13 | 2.800 | 13 |
| 5250268-14 | 3.000 | 14 |
| 5250268-15 | 3.200 | 15 |
| 5250268-16 | 3.400 | 16 |
| 5250268-17 | 3.600 | 17 |
| 5250268-18 | 3.800 | 18 |
| 5250268-19 | 4.000 | 19 |
| 5250268-20 | 4.200 | 20 |
| 5250268-21 | 4.400 | 21 |

6

| TABULATION | | |
|---|---|---|
| PART NO. | "A" | "B" |
| 5250268-22 | 4.600 | 22 |
| 5250268-23 | 4.800 | 23 |
| 5250268-24 | 5.000 | 24 |
| 5250268-25 | 5.200 | 25 |
| 5250268-26 | 5.400 | 26 |
| 5250268-27 | 5.600 | 27 |
| 5250268-28 | 5.800 | 28 |
| 5250268-29 | 6.000 | 29 |
| 5250268-30 | 6.200 | 30 |
| 5250268-31 | 6.400 | 31 |
| 5250268-32 | 6.600 | 32 |
| 5250268-33 | 6.800 | 33 |
| 5250268-34 | 7.000 | 34 |
| 5250268-35 | 7.200 | 35 |
| 5250268-36 | 7.400 | 36 |
| 5250268-37 | 7.600 | 37 |
| 5250268-38 | 7.800 | 38 |
| 5250268-39 | 8.000 | 39 |
| 5250268-40 | 8.200 | 40 |
| 5250268-41 | 8.400 | 41 |
| 5250268-42 | 8.600 | 42 |

6

| TABULATION | | |
|---|---|---|
| PART NO. | "A" | "B" |
| 5250268-43 | 8.800 | 43 |
| 5250268-44 | 9.000 | 44 |
| 5250268-45 | 9.200 | 45 |
| 5250268-46 | 9.400 | 46 |
| 5250268-47 | 9.600 | 47 |
| 5250268-48 | 9.800 | 48 |
| 5250268-49 | 10.000 | 49 |
| 5250268-50 | 10.200 | 50 |
| 5250268-51 | 10.400 | 51 |
| 5250268-52 | 10.600 | 52 |
| 5250268-53 | 10.800 | 53 |
| 5250268-54 | 11.000 | 54 |
| 5250268-55 | 11.200 | 55 |
| 5250268-56 | 11.400 | 56 |
| 5250268-57 | 11.600 | 57 |
| 5250268-58 | 11.800 | 58 |
| 5250268-59 | 12.000 | 59 |
| 5250268-60 | 12.200 | 60 |
| 5250268-61 | 12.400 | 61 |
| 5250268-62 | 12.600 | 62 |
| 5250268-63 | 12.800 | 63 |

6

| TABULATION | | |
|---|---|---|
| PART NO. | "A" | "B" |
| 5250268-64 | 13.000 | 64 |
| 5250268-65 | 13.200 | 65 |
| 5250268-66 | 13.400 | 66 |
| 5250268-67 | 13.600 | 67 |
| 5250268-68 | 13.800 | 68 |
| 5250268-69 | 14.000 | 69 |
| 5250268-70 | 14.200 | 70 |
| 5250268-71 | 14.400 | 71 |
| 5250268-72 | 14.600 | 72 |
| 5250268-73 | 14.800 | 73 |
| 5250268-74 | 15.000 | 74 |
| 5250268-75 | 15.200 | 75 |
| 5250268-76 | 15.400 | 76 |
| 5250268-77 | 15.600 | 77 |
| 5250268-78 | 15.800 | 78 |
| 5250268-79 | 16.000 | 79 |
| 5250268-80 | 16.200 | 80 |
| 5250268-81 | 16.400 | 81 |
| 5250268-82 | 16.600 | 82 |
| 5250268-83 | 16.800 | 83 |
| 5250268-84 | 17.000 | 84 |

6

6. DASH NOS. INDICATE RACK SPACE IN "HP" UNITS (HOLE PITCH OF .200)
5. DEGREASE & SEAL CUT ENDS
4. MAKE FROM P/N # 5700202
3. REMOVE ALL BURRS & SHARP EDGES
2. FINISH: ZINC PLATE PER ASTM-B-633, CLASS 3, TYPE I
1. MAT'L: STEEL, COLD ROLLED, 16 GA.(.0598) (REF.)

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: ±.5°
TWO PLACE DECIMAL ±.03
THREE PLACE DECIMAL ±.010
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL 1
FINISH 2
DO NOT SCALE DRAWING

| | NAME | DATE |
|---|---|---|
| DRAWN | TRUSHAR | 01/09/09 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |


THIRD ANGLE PROJECTION


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605

# NUT STRIP CARD CAGES

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5250268 | A |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1




| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | D | INCORP ECO 4061 & 4040 | 02/02/93 | |
| | E | ECO 4282, ADD 5250236A | 06/21/95 | |

| TABULATION | | |
|---|---|---|
| PART NO. 7 | "A" | "B" |
| 5250236-03 | 0.800 | 3 |
| 5250236-04 | 1.000 | 4 |
| 5250236-05 | 1.200 | 5 |
| 5250236-06 | 1.400 | 6 |
| 5250236-07 | 1.600 | 7 |
| 5250236-08 | 1.800 | 8 |
| 5250236-09 | 2.000 | 9 |
| 5250236-10 | 2.200 | 10 |
| 5250236-11 | 2.400 | 11 |
| 5250236-12 | 2.600 | 12 |
| 5250236-13 | 2.800 | 13 |
| 5250236-14 | 3.000 | 14 |
| 5250236-15 | 3.200 | 15 |
| 5250236-16 | 3.400 | 16 |
| 5250236-17 | 3.600 | 17 |
| 5250236-18 | 3.800 | 18 |
| 5250236-19 | 4.000 | 19 |
| 5250236-20 | 4.200 | 20 |
| 5250236-21 | 4.400 | 21 |

| TABULATION | | |
|---|---|---|
| PART NO. 7 | "A" | "B" |
| 5250236-22 | 4.600 | 22 |
| 5250236-23 | 4.800 | 23 |
| 5250236-24 | 5.000 | 24 |
| 5250236-25 | 5.200 | 25 |
| 5250236-26 | 5.400 | 26 |
| 5250236-27 | 5.600 | 27 |
| 5250236-28 | 5.800 | 28 |
| 5250236-29 | 6.000 | 29 |
| 5250236-30 | 6.200 | 30 |
| 5250236-31 | 6.400 | 31 |
| 5250236-32 | 6.600 | 32 |
| 5250236-33 | 6.800 | 33 |
| 5250236-34 | 7.000 | 34 |
| 5250236-35 | 7.200 | 35 |
| 5250236-36 | 7.400 | 36 |
| 5250236-37 | 7.600 | 37 |
| 5250236-38 | 7.800 | 38 |
| 5250236-39 | 8.000 | 39 |
| 5250236-40 | 8.200 | 40 |
| 5250236-41 | 8.400 | 41 |
| 5250236-42 | 8.600 | 42 |

| TABULATION | | |
|---|---|---|
| PART NO. 7 | "A" | "B" |
| 5250236-43 | 8.800 | 43 |
| 5250236-44 | 9.000 | 44 |
| 5250236-45 | 9.200 | 45 |
| 5250236-46 | 9.400 | 46 |
| 5250236-47 | 9.600 | 47 |
| 5250236-48 | 9.800 | 48 |
| 5250236-49 | 10.000 | 49 |
| 5250236-50 | 10.200 | 50 |
| 5250236-51 | 10.400 | 51 |
| 5250236-52 | 10.600 | 52 |
| 5250236-53 | 10.800 | 53 |
| 5250236-54 | 11.000 | 54 |
| 5250236-55 | 11.200 | 55 |
| 5250236-56 | 11.400 | 56 |
| 5250236-57 | 11.600 | 57 |
| 5250236-58 | 11.800 | 58 |
| 5250236-59 | 12.000 | 59 |
| 5250236-60 | 12.200 | 60 |
| 5250236-61 | 12.400 | 61 |
| 5250236-62 | 12.600 | 62 |
| 5250236-63 | 12.800 | 63 |

| TABULATION | | |
|---|---|---|
| PART NO. 7 | "A" | "B" |
| 5250236-64 | 13.000 | 64 |
| 5250236-65 | 13.200 | 65 |
| 5250236-66 | 13.400 | 66 |
| 5250236-67 | 13.600 | 67 |
| 5250236-68 | 13.800 | 68 |
| 5250236-69 | 14.000 | 69 |
| 5250236-70 | 14.200 | 70 |
| 5250236-71 | 14.400 | 71 |
| 5250236-72 | 14.600 | 72 |
| 5250236-73 | 14.800 | 73 |
| 5250236-74 | 15.000 | 74 |
| 5250236-75 | 15.200 | 75 |
| 5250236-76 | 15.400 | 76 |
| 5250236-77 | 15.600 | 77 |
| 5250236-78 | 15.800 | 78 |
| 5250236-79 | 16.000 | 79 |
| 5250236-80 | 16.200 | 80 |
| 5250236-81 | 16.400 | 81 |
| 5250236-82 | 16.600 | 82 |
| 5250236-83 | 16.800 | 83 |
| 5250236-84 | 17.000 | 84 |

5250236A FINISH : GOLD IRRIDITE

7. DASH NO(S). INDICATE RACK SPACE IN "HP" UNITS (HOLE PITCH OF .200)
6. FINISH: SATIN ETCH, 7 MIN., CHEM FILM, CLEAR, CLASS 1A, IAW MIL-C-5541
5. DEGREASE
4. REMOVE ALL BURS & SHARP EDGES
3. FINE GRAIN FINISH ON SURFACES INDICATED (3 PL.)
2. ENDS TO BE SQUARE WITHIN: .0025 PER INCH OF WIDTH
1. MAT'L: MAKE FROM P/N # 5280233

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: ±.5°
TWO PLACE DECIMAL ±.XX
THREE PLACE DECIMAL ±.005
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL 1
FINISH 6
DO NOT SCALE DRAWING

| | NAME | DATE |
|---|---|---|
| DRAWN | TRUSHAR | 01/12/09 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |

THIRD ANGLE PROJECTION


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605

# EXTRUSION FRONT
## FULL SIZE CAGES & DIVIDER KITS

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5250236 | E |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | A | PROD. REL. | 05/01/86 | |
| | B | INCORP ECO 3157 | 05/20/86 | |
| | C | ECO 4283, ADD 5250238A | 06/21/95 | |




| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250238-03 | 0.800 | 3 |
| 5250238-04 | 1.000 | 4 |
| 5250238-05 | 1.200 | 5 |
| 5250238-06 | 1.400 | 6 |
| 5250238-07 | 1.600 | 7 |
| 5250238-08 | 1.800 | 8 |
| 5250238-09 | 2.000 | 9 |
| 5250238-10 | 2.200 | 10 |
| 5250238-11 | 2.400 | 11 |
| 5250238-12 | 2.600 | 12 |
| 5250238-13 | 2.800 | 13 |
| 5250238-14 | 3.000 | 14 |
| 5250238-15 | 3.200 | 15 |
| 5250238-16 | 3.400 | 16 |
| 5250238-17 | 3.600 | 17 |
| 5250238-18 | 3.800 | 18 |
| 5250238-19 | 4.000 | 19 |
| 5250238-20 | 4.200 | 20 |
| 5250238-21 | 4.400 | 21 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250238-22 | 4.600 | 22 |
| 5250238-23 | 4.800 | 23 |
| 5250238-24 | 5.000 | 24 |
| 5250238-25 | 5.200 | 25 |
| 5250238-26 | 5.400 | 26 |
| 5250238-27 | 5.600 | 27 |
| 5250238-28 | 5.800 | 28 |
| 5250238-29 | 6.000 | 29 |
| 5250238-30 | 6.200 | 30 |
| 5250238-31 | 6.400 | 31 |
| 5250238-31 | 6.600 | 32 |
| 5250238-33 | 6.800 | 33 |
| 5250238-34 | 7.000 | 34 |
| 5250238-35 | 7.200 | 35 |
| 5250238-36 | 7.400 | 36 |
| 5250238-37 | 7.600 | 37 |
| 5250238-38 | 7.800 | 38 |
| 5250238-39 | 8.000 | 39 |
| 5250238-40 | 8.200 | 40 |
| 5250238-41 | 8.400 | 41 |
| 5250238-42 | 8.600 | 42 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250238-43 | 8.800 | 43 |
| 5250238-44 | 9.000 | 44 |
| 5250238-45 | 9.200 | 45 |
| 5250238-46 | 9.400 | 46 |
| 5250238-47 | 9.600 | 47 |
| 5250238-48 | 9.800 | 48 |
| 5250238-49 | 10.000 | 49 |
| 5250238-50 | 10.200 | 50 |
| 5250238-51 | 10.400 | 51 |
| 5250238-52 | 10.600 | 52 |
| 5250238-53 | 10.800 | 53 |
| 5250238-54 | 11.000 | 54 |
| 5250238-55 | 11.200 | 55 |
| 5250238-56 | 11.400 | 56 |
| 5250238-57 | 11.600 | 57 |
| 5250238-58 | 11.800 | 58 |
| 5250238-59 | 12.000 | 59 |
| 5250238-60 | 12.200 | 60 |
| 5250238-61 | 12.400 | 61 |
| 5250238-62 | 12.600 | 62 |
| 5250238-63 | 12.800 | 63 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250238-64 | 13.000 | 64 |
| 5250238-65 | 13.200 | 65 |
| 5250238-66 | 13.400 | 66 |
| 5250238-67 | 13.600 | 67 |
| 5250238-68 | 13.800 | 68 |
| 5250238-69 | 14.000 | 69 |
| 5250238-70 | 14.200 | 70 |
| 5250238-71 | 14.400 | 71 |
| 5250238-72 | 14.600 | 72 |
| 5250238-73 | 14.800 | 73 |
| 5250238-74 | 15.000 | 74 |
| 5250238-75 | 15.200 | 75 |
| 5250238-76 | 15.400 | 76 |
| 5250238-77 | 15.600 | 77 |
| 5250238-78 | 15.800 | 78 |
| 5250238-79 | 16.000 | 79 |
| 5250238-80 | 16.200 | 80 |
| 5250238-81 | 16.400 | 81 |
| 5250238-82 | 16.600 | 82 |
| 5250238-83 | 16.800 | 83 |
| 5250238-84 | 17.000 | 84 |

5250238A FINISH: GOLD IRRIDITE

7. DASH NO(S). INDICATE RACK SPACE IN "HP" UNITS (HOLE PITCH OF .200)
6. FINISH: SATIN ETCH, 7 MIN., CHEM FILM, CLEAR, CLASS 1A, IAW MIL-C-5541
5. DEGREASE
4. REMOVE ALL BURS & SHARP EDGES
3. FINE GRAIN FINISH ON SURFACES INDICATED ONLY
2. ENDS TO BE SQUARE WITHIN: .0025 PER INCH OF WIDTH
1. MAT'L: MAKE FROM P/N # 5280234

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

| UNLESS OTHERWISE SPECIFIED: | | NAME | DATE |
|---|---|---|---|
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL ±<br>ANGULAR: ±.5°<br>TWO PLACE DECIMAL ±.XX<br>THREE PLACE DECIMAL ±.005<br>INTERPRET GEOMETRIC TOLERANCING PER: | DRAWN | TRUSHAR | 01/12/09 |
| | CHECKED | | |
| | ENG APPR. | | |
| | MFG APPR. | | |
| | Q.A. | | |
| MATERIAL [1]<br>FINISH [6]<br>DO NOT SCALE DRAWING | THIRD ANGLE PROJECTION | | |


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605

# EXTRUSION REAR
## VME CARD CAGE

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5250238 | C |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | B | REVISED & REDRAWN, ECO 3156 | 05/20/86 | |
| | | | | |
| | | | | |




| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250237-03 | 0.800 | 3 |
| 5250237-04 | 1.000 | 4 |
| 5250237-05 | 1.200 | 5 |
| 5250237-06 | 1.400 | 6 |
| 5250237-07 | 1.600 | 7 |
| 5250237-08 | 1.800 | 8 |
| 5250237-09 | 2.000 | 9 |
| 5250237-10 | 2.200 | 10 |
| 5250237-11 | 2.400 | 11 |
| 5250237-12 | 2.600 | 12 |
| 5250237-13 | 2.800 | 13 |
| 5250237-14 | 3.000 | 14 |
| 5250237-15 | 3.200 | 15 |
| 5250237-16 | 3.400 | 16 |
| 5250237-17 | 3.600 | 17 |
| 5250237-18 | 3.800 | 18 |
| 5250237-19 | 4.000 | 19 |
| 5250237-20 | 4.200 | 20 |
| 5250237-21 | 4.400 | 21 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250237-22 | 4.600 | 22 |
| 5250237-23 | 4.800 | 23 |
| 5250237-24 | 5.000 | 24 |
| 5250237-25 | 5.200 | 25 |
| 5250237-26 | 5.400 | 26 |
| 5250237-27 | 5.600 | 27 |
| 5250237-28 | 5.800 | 28 |
| 5250237-29 | 6.000 | 29 |
| 5250237-30 | 6.200 | 30 |
| 5250237-31 | 6.400 | 31 |
| 5250237-32 | 6.600 | 32 |
| 5250237-33 | 6.800 | 33 |
| 5250237-34 | 7.000 | 34 |
| 5250237-35 | 7.200 | 35 |
| 5250237-36 | 7.400 | 36 |
| 5250237-37 | 7.600 | 37 |
| 5250237-38 | 7.800 | 38 |
| 5250237-39 | 8.000 | 39 |
| 5250237-40 | 8.200 | 40 |
| 5250237-41 | 8.400 | 41 |
| 5250237-42 | 8.600 | 42 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250237-43 | 8.800 | 43 |
| 5250237-44 | 9.000 | 44 |
| 5250237-45 | 9.200 | 45 |
| 5250237-46 | 9.400 | 46 |
| 5250237-47 | 9.600 | 47 |
| 5250237-48 | 9.800 | 48 |
| 5250237-49 | 10.000 | 49 |
| 5250237-50 | 10.200 | 50 |
| 5250237-51 | 10.400 | 51 |
| 5250237-52 | 10.600 | 52 |
| 5250237-53 | 10.800 | 53 |
| 5250237-54 | 11.000 | 54 |
| 5250237-55 | 11.200 | 55 |
| 5250237-56 | 11.400 | 56 |
| 5250237-57 | 11.600 | 57 |
| 5250237-58 | 11.800 | 58 |
| 5250237-59 | 12.000 | 59 |
| 5250237-60 | 12.200 | 60 |
| 5250237-61 | 12.400 | 61 |
| 5250237-62 | 12.600 | 62 |
| 5250237-63 | 12.800 | 63 |

| TABULATION | | |
|---|---|---|
| PART NO. [7] | "A" | "B" |
| 5250237-64 | 13.000 | 64 |
| 5250237-65 | 13.200 | 65 |
| 5250237-66 | 13.400 | 66 |
| 5250237-67 | 13.600 | 67 |
| 5250237-68 | 13.800 | 68 |
| 5250237-69 | 14.000 | 69 |
| 5250237-70 | 14.200 | 70 |
| 5250237-71 | 14.400 | 71 |
| 5250237-72 | 14.600 | 72 |
| 5250237-73 | 14.800 | 73 |
| 5250237-74 | 15.000 | 74 |
| 5250237-75 | 15.200 | 75 |
| 5250237-76 | 15.400 | 76 |
| 5250237-77 | 15.600 | 77 |
| 5250237-78 | 15.800 | 78 |
| 5250237-79 | 16.000 | 79 |
| 5250237-80 | 16.200 | 80 |
| 5250237-81 | 16.400 | 81 |
| 5250237-82 | 16.600 | 82 |
| 5250237-83 | 16.800 | 83 |
| 5250237-84 | 17.000 | 84 |

7. DASH NO(S). INDICATE RACK SPACE IN "HP" UNITS (HOLE PITCH OF .200)
6. FINISH: SATIN ETCH, 7 MIN., CHEM FILM, CLEAR, CLASS 1A, IAW MIL-C-5541
5. DEGREASE
4. REMOVE ALL BURS & SHARP EDGES
3. FINE GRAIN FINISH ON SURFACES INDICATED (3 PL.)
2. ENDS TO BE SQUARE WITHIN: .0025 PER INCH OF WIDTH
1. MAT'L: MAKE FROM P/N # 5280220

NOTES: UNLESS OTHERWISE SPECIFIED.

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: ±.5°
TWO PLACE DECIMAL ±.XX
THREE PLACE DECIMAL ±.005
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL [1]
FINISH [6]
DO NOT SCALE DRAWING

| | NAME | DATE |
|---|---|---|
| DRAWN | TRUSHAR | 01/12/09 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |

THIRD ANGLE PROJECTION

VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605


# EXTRUSION CENTER
## VME CARD CAGE


| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5250237 | B |


SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1

| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| ALL | A | REVISED & REDRAWN | | |
| | | | | |
| | | | | |

#8-32 TAP x .600 DEEP
4 PL.
NOTE: TAP THRU FOR
P/N # -03, -04, -05




| TABULATION | |
|---|---|
| PART NO. [7] | "A" |
| 5250229-03 | 0.800 |
| 5250229-04 | 1.000 |
| 5250229-05 | 1.200 |
| 5250229-06 | 1.400 |
| 5250229-07 | 1.600 |
| 5250229-08 | 1.800 |
| 5250229-09 | 2.000 |
| 5250229-10 | 2.200 |
| 5250229-11 | 2.400 |
| 5250229-12 | 2.600 |
| 5250229-13 | 2.800 |
| 5250229-14 | 3.000 |
| 5250229-15 | 3.200 |
| 5250229-16 | 3.400 |
| 5250229-17 | 3.600 |
| 5250229-18 | 3.800 |
| 5250229-19 | 4.000 |
| 5250229-20 | 4.200 |
| 5250229-21 | 4.400 |

| TABULATION | |
|---|---|
| PART NO. [7] | "A" |
| 5250229-22 | 4.600 |
| 5250229-23 | 4.800 |
| 5250229-24 | 5.000 |
| 5250229-25 | 5.200 |
| 5250229-26 | 5.400 |
| 5250229-27 | 5.600 |
| 5250229-28 | 5.800 |
| 5250229-29 | 6.000 |
| 5250229-30 | 6.200 |
| 5250229-31 | 6.400 |
| 5250229-32 | 6.600 |
| 5250229-33 | 6.800 |
| 5250229-34 | 7.000 |
| 5250229-35 | 7.200 |
| 5250229-36 | 7.400 |
| 5250229-37 | 7.600 |
| 5250229-38 | 7.800 |
| 5250229-39 | 8.000 |
| 5250229-40 | 8.200 |
| 5250229-41 | 8.400 |
| 5250229-42 | 8.600 |

| TABULATION | |
|---|---|
| PART NO. [7] | "A" |
| 5250229-43 | 8.800 |
| 5250229-44 | 9.000 |
| 5250229-45 | 9.200 |
| 5250229-46 | 9.400 |
| 5250229-47 | 9.600 |
| 5250229-48 | 9.800 |
| 5250229-49 | 10.000 |
| 5250229-50 | 10.200 |
| 5250229-51 | 10.400 |
| 5250229-52 | 10.600 |
| 5250229-53 | 10.800 |
| 5250229-54 | 11.000 |
| 5250229-55 | 11.200 |
| 5250229-56 | 11.400 |
| 5250229-57 | 11.600 |
| 5250229-58 | 11.800 |
| 5250229-59 | 12.000 |
| 5250229-60 | 12.200 |
| 5250229-61 | 12.400 |
| 5250229-62 | 12.600 |
| 5250229-63 | 12.800 |

| TABULATION | |
|---|---|
| PART NO. [7] | "A" |
| 5250229-64 | 13.000 |
| 5250229-65 | 13.200 |
| 5250229-66 | 13.400 |
| 5250229-67 | 13.600 |
| 5250229-68 | 13.800 |
| 5250229-69 | 14.000 |
| 5250229-70 | 14.200 |
| 5250229-71 | 14.400 |
| 5250229-72 | 14.600 |
| 5250229-73 | 14.800 |
| 5250229-74 | 15.000 |
| 5250229-75 | 15.200 |
| 5250229-76 | 15.400 |
| 5250229-77 | 15.600 |
| 5250229-78 | 15.800 |
| 5250229-79 | 16.000 |
| 5250229-80 | 16.200 |
| 5250229-81 | 16.400 |
| 5250229-82 | 16.600 |
| 5250229-83 | 16.800 |
| 5250229-84 | 17.000 |

7. DASH NO(S). INDICATE RACK SPACE IN "HP" UNITS (HOLE PITCH OF .200)
6. FINISH: SATIN ETCH, 7 MIN., CHEM FILM, CLEAR, CLASS 1A, IAW MIL-C-5541
5. DEGREASE
4. REMOVE ALL BURS & SHARP EDGES
3. FINE GRAIN FINISH ON SURFACES INDICATED (3 PL.)
2. ENDS TO BE SQUARE WITHIN: .0025 PER INCH OF WIDTH
1. MAT'L: MAKE FROM P/N # 5280220

NOTES: UNLESS OTHERWISE SPECIFIED.


**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VECTOR ELECTRONICS & TECH., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VECTOR ELECTRONICS & TECH., INC. IS PROHIBITED.


| UNLESS OTHERWISE SPECIFIED: | | NAME | DATE |
|---|---|---|---|
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL ±<br>ANGULAR: ±.5°<br>TWO PLACE DECIMAL ±.XX<br>THREE PLACE DECIMAL ±.005<br>INTERPRET GEOMETRIC TOLERANCING PER:<br>MATERIAL [1]<br>FINISH [6]<br>DO NOT SCALE DRAWING | DRAWN | TRUSHAR | 01/12/09 |
| | CHECKED | | |
| | ENG APPR. | | |
| | MFG APPR. | | |
| | Q.A. | | |
| | THIRD ANGLE PROJECTION | | |


VECTOR ELECTRONICS & TECHNOLOGY, INC
11115 VANOWEN ST., NORTH HOLLYWOOD, CA 91605


# EXTRUSION CENTER NARROW
## VME CARD CAGE

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | 5250229 | A |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.