


## CPU-161-18

- HPEC and Microserver Ready
- Intel® Xeon® D-15xx
- Hybrid RAM Architecture
- Compact Size with PCIe x16 Port
- Rugged and Fanless
- Customizable
- Professional Services



## FEATURES

**HPeC and Microserver Ready** - Combines computational power with a rugged design to enable High Performance applications even in-the-field

**Powerful** - Supports the latest generation of embedded Intel Pentium® and Xeon D-15xx CPUs to deliver a server-class module

**Hybrid RAM Architecture** - Innovates by offering the reliability of soldered-down RAM and the expandability of SO-DIMMs

**Compact Size with PCIe x16 Port** - Complies with COM Express® Type 6 Rev 2.1, including support for a PCIe x16 port

**Rugged and Fanless** - Allows robust, fanless designs thanks to 100% soldered-down components and with a range of energy efficient CPUs

**Customizable** - Comes with optional personalization and full customization services, ranging from factory options to deep HW/SW configuration changes

**Professional Services** - Provides the foundation for Eurotech Professional Services that span from carrier board development to complete system design, certification and manufacturing

The CPU-161-18 combines a high performance and truly embedded CPU with an innovative hybrid RAM architecture that offers the ruggedness of soldered memory and the expandability of SO-DIMMs. The standard configuration provides 8GB of memory soldered directly on the PCB and supports up to 24GB DDR4 RAM with ECC error correction through a SO-DIMM slot, targeting use cases where extreme ruggedness is required, and those that need a large memory.

The CPU-161-18 can be configured with any member of the Xeon/Pentium D 15xx family; standard versions support extended temperature CPUs, such as the Pentium D-1519 and the Xeon D-1559, closing the gap between traditional embedded applications and servers.

Compatible with existing Type 6 carrier boards, the CPU-161-18 is a headless unit that provides a fast upgrade path to existing projects and that allows the creation of new high-performance ones: a notable feature of this Compact size module is the availability of a x16 PCIe Gen 3 port in addition to the x8 one, a characteristic that is more commonly found only on larger modules; other features include: Gigabit Ethernet, 4x SATA 3.0 ports, 4x USB 3.0 and 7x USB 2.0 interfaces.

Supported operating systems include Yocto Linux and CentOS; moreover, the CPU-161-18 supports Everyware Software Framework (ESF), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT gateways.

Professional Services are available for the CPU-161-18, starting from BIOS personalization and including carrier board design, system development and production. Deep module customization, such as feature changes are also available.

# CPU-161-18

## Specifications

## Rugged Intel Xeon D-15xx COM Express Compact Type 6

Ordering code: CPU-161-18-XX					
XX		- 05	- 06	- 07	- 08
PROCESSOR	<b>CPU</b>	Pentium D-1519 1.50GHz, 4 Cores	Xeon D-1529 1.30GHz, 4 Cores (IEC 61508 Safety Integrity Compliant)	Xeon D-1539 1.60GHz, 8 Cores	Xeon D-1559 1.50GHz, 12 Cores
MEMORY	<b>On-board</b>	8GB DDR4 ECC Memory Down (2133-2400MT/s)			
	<b>On-socket</b>	1x DDR4 ECC SODIMM up to 16GB			
STORAGE	<b>Embedded</b>	2x SPI-Flash (16MB + 32MB) 1x EEPROM (8kB)			
	<b>SATA</b>	4x SATA 3.0 (up to 6Gb/s)	2x SATA 3.0 (up to 6Gb/s)	4x SATA 3.0 (up to 6Gb/s)	
	<b>RAID</b>	Factory Option			
I/O INTERFACES	<b>Ethernet</b>	1x 10/100/1000Mbps			
	<b>USB</b>	4x USB 3.0 7x USB 2.0 (EHCI supported)	7x USB 2.0 (EHCI supported)	4x USB 3.0 7x USB 2.0 (EHCI supported)	
	<b>Serial</b>	2x UART (TX/RX)			
	<b>Digital I/O</b>	1x 8bit Digital I/O			
	<b>PCI Express</b>	1x PCIe x16 (Gen 3) 4x PCIe x1 (Gen 2) 1x PCIe x4 (Gen 2) Non-transparent bridge or Transparent bridge (Switchable)	1x PCIe x16 (Gen 2) Non-transparent bridge or Transparent bridge (Switchable)	1x PCIe x16 (Gen 3) 4x PCIe x1 (Gen 2) 1x PCIe x4 (Gen 2) Non-transparent bridge or Transparent bridge (Switchable)	
	<b>LPC</b>	Yes			
	<b>I2C</b>	Yes			
OTHER	<b>SMBus</b>	Yes			
	<b>RTC</b>	Yes			
	<b>Watchdog</b>	Yes			
	<b>Security</b>	Intel AES-NI Intel Secure Key			
POWER	<b>Sensors</b>	Temperature Sensor			
	<b>Input</b>	12V, 5VSBY, 3V_RTC			
	<b>Consumption</b>	25W (CPU TDP)	20W (CPU TDP)	35W (CPU TDP)	45W (CPU TDP)
ENVIRONMENT	<b>Operating Temp</b>	- 40 to +85°C			
	<b>Storage Temp</b>	- 40 to +85°C			
	<b>Humidity</b>	35% to 85%			
CERTIFICATIONS	<b>Environmental</b>	RoHS (2011/65/EU)			
	<b>Compliance</b>	PICMG COM Express R2.1, Type 6			
MECHANICAL	<b>Dimensions</b>	95x95mm (LxW) - COM Express Compact			

### SUPPORTED SOFTWARE

<b>OS</b>	Yocto Linux, CentOS 7 (Professional Services: Windows 10 IoT Enterprise, Fedora, Other Linux and RTOS)
<b>IoT Framework</b>	Everyware Software Framework (Java/OSGi)

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.