

TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified Uncompensated/Unamplified Millivolt Analog Output, 1 psi to 150 psi (60 mbar to 10 bar)



DESCRIPTION

The TruStability® NSC Series-Uncompensated/Unamplified is a piezoresistive silicon pressure sensor offering a ratiometric analog output for reading pressure over the specified full scale pressure span and temperature range.

The NSC Series is both unamplified and uncompensated. It offers infinite resolution on the pressure signal. Frequency response is limited only by the end user's system. The sensor will operate as specified from -40 °C to 85 °C [-40 °F to 185 °F].

These products are ideal for those customers who want to do their own compensation, calibration, and amplification in order to make use of the maximum resolution of the bare sensor output, leveraging a custom algorithm required for the application.

The NSC Series allows customers the flexibility of self-calibration while still benefiting from the industry-leading stability, accuracy, and repeatability that the Honeywell TruStability® Pressure Sensors provide.

Additionally, the NSC Series offers numerous package styles and mounting options, making it easier for the device manufacturer to integrate the product into their application.

These sensors measure absolute, differential, and gage pressures. The absolute versions have an internal vacuum reference and an output value proportional to absolute pressure. Differential versions allow application of pressure to either side of the sensing diaphragm. Gage versions are referenced to atmospheric pressure and provide an output proportional to pressure variations from atmosphere.

The NSC Series sensors are intended for use with non-corrosive, non-ionic gases, such as air and other dry gases and for non-corrosive, non-ionic liquids. All products are designed and manufactured according to ISO 9001.

FEATURES AND BENEFITS (★=competitive differentiator)

- ★ Industry-leading long-term stability: Even after long-term use and thermal extremes, these sensors perform substantially better relative to stability than any other pressure sensor available in the industry today:
 - Minimizes system calibration needs and maximizes system performance
 - Helps support system uptime by eliminating the need to service or replace the sensor during its application life
- ★ Industry-leading accuracy: Extremely tight accuracy of $\pm 0.25\%$ FSS BFSL:
 - Reduces software needed to correct system inaccuracies, minimizing system design time
 - Supports system accuracy and warranty requirements
 - Helps to optimize system uptime

TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified

FEATURES AND BENEFITS (★=competitive differentiator) (continued)

- ★ Industry-leading flexibility:
 - Modular, flexible design with numerous package styles, pressure ports, and options simplify integration into the device manufacturer's application
 - Single side wet media option allows the end customer to use one port of the sensor with condensing humidity or directly with non-corrosive liquid media
- ★ Small size: Miniature 10 mm x 10 mm [0.39 in x 0.39 in] package is very small when compared to most board mount pressure sensors
 - Occupies less area on the PCB
 - Typically allows for easy placement on crowded PCBs or in small devices
- ★ Repeatability: Provides excellent repeatability, high accuracy and reliability under many demanding conditions
- Extremely low power consumption (operating supply voltage as low as 1.8 Vdc):
 - Reduces power consumption
 - Provides extended battery life
 - Promotes energy efficiency
- Low operating voltage
- Sensitive: Meets specified pressure level requirements, providing enhanced sensitivity and accuracy over the range
- Virtually insensitive to mounting orientation, allowing for flexibility of use within the application
- Ratiometric analog output
- Infinite resolution
- Fast response time
- RoHS compliant
- Absolute, differential and gage types
- Pressure ranges from 1 psi to 150 psi (60 mbar to 10 bar)
- Also available in the HSC Series and the SSC Series which are fully compensated and calibrated with amplified analog or digital I²C or SPI outputs

POTENTIAL APPLICATIONS (★=focus applications)

Medical:

- Respiratory breathing circuits:
 - Nebulizers
 - Spirometers
 - Patient monitoring
- Flow/pressure control:
 - Therapeutic hospital beds
- Gas collection/delivery:
 - ★ Hospital gas supply
 - Oxygen concentrators
- Precise sampling/gas flow:
 - ★ Blood analysis
 - ★ Gas chromatography
 - ★ Analytical instrument sampling systems

Industrial:

- Pneumatic components:
 - ★ Valves
 - ★ Pumps
 - ★ Actuators
- Pneumatic systems:
 - ★ HVAC transmitters
 - ★ Automated pneumatic assembly equipment
 - ★ Pneumatic operator control systems
- Gas collection/delivery:
 - ★ Industrial gas supply
- Precise sampling/gas flow:
 - ★ Barometry
 - ★ Gas chromatography
 - ★ Analytical instrument sampling systems

Table 1. Absolute Maximum Ratings¹

| Parameter | Min. | Max. | Unit |
|---------------------------------------|-----------|------------------------------|---------|
| Supply voltage (V _{supply}) | -12.0 | 12.0 | Vdc |
| ESD susceptibility (human body model) | 3 | – | kV |
| Storage temperature | -40 [-40] | 85 [185] | °C [°F] |
| Soldering time and temperature: | | | |
| Lead solder temperature (SIP, DIP) | | 4 s max. at 250 °C [482 °F] | |
| Peak reflow temperature (SMT) | | 15 s max. at 250 °C [482 °F] | |

Uncompensated/Unamplified Millivolt Analog Output

Table 2. Operating Specifications

| Parameter | Min. | Typ. | Max. | Unit |
|-----------------------------------------------------|-----------|------------------|----------|------------------------|
| Supply voltage (V_{supply}) ² | 1.8 | 5.0 ³ | 12.0 | Vdc |
| Supply current (at 5.0 Vdc supply) | – | 1.5 | 2 | mA |
| Specified temperature range ⁴ | -40 [-40] | – | 85 [185] | °C [°F] |
| Startup time | – | – | 5 | ms |
| Accuracy ⁵ | – | – | ±0.25 | %FSS BFSL ⁶ |

Table 3. Environmental Specifications

| Parameter | Characteristic |
|-------------------|----------------------------------------|
| Humidity | 0% to 95% RH, non-condensing |
| Vibration | MIL-STD-202F, Curve AK (20.7 g random) |
| Shock | MIL-STD-202F, Method 213B, Condition F |
| Life ⁷ | 1 million pressure cycles minimum |
| Solder reflow | J-STD-020-C |

Table 4. Wetted Materials⁸

| Parameter | Port 1 (Pressure Port) | Port 2 (Reference Port) |
|-----------------------|----------------------------|------------------------------|
| Covers | high temperature polyamide | high temperature polyamide |
| Substrate | alumina ceramic | alumina ceramic |
| Adhesives | epoxy, RTV | epoxy, RTV |
| Electronic components | ceramic, silicon | silicon, glass, gold, solder |

Notes:

1. Absolute maximum ratings are the extreme limits the device will withstand without damage.
2. Ratiometricity of the sensor (the ability of the device output to scale to the supply voltage) is achieved within the specified operating voltage.
3. Incorrect application of supply voltage or ground to the wrong pin may cause electrical failure.
4. The specified temperature range is the temperature range over which the sensor will produce an output proportional to pressure within the specified performance limits.
5. Accuracy: The maximum deviation in output from a Best Fit Straight Line (BFSL) fitted to the output measured over the pressure range at 25 °C [77 °F]. Includes all errors due to pressure non-linearity, pressure hysteresis, and non-repeatability.
6. Full Scale Span (FSS) is the algebraic difference between the output signal measured at the maximum (P_{max}) and minimum (P_{min}) limits of the pressure range. (See Figure 1 for ranges.)
7. Life may vary depending on specific application in which sensor is utilized.
8. Contact Honeywell Customer Service for detailed material information.

CAUTION

PRODUCT DAMAGE

- Ensure liquid media is applied to Port 1 only; Port 2 is not compatible with liquids.
- Ensure liquid media contains no particulates. All TruStability® sensors are dead-ended devices. Particulates can accumulate inside the sensor, causing damage or affecting sensor output.
- Recommend that the sensor be positioned with Port 1 facing downwards; any particulates in the system are less likely to enter and settle within the pressure sensor if it is in this position.
- Ensure liquid media does not create a residue when dried; build-up inside the sensor may affect sensor output. Rinsing of a dead-ended sensor is difficult and has limited effectiveness for removing residue.
- Ensure liquid media are compatible with wetted materials. Non-compatible liquid media will degrade sensor performance and may lead to sensor failure.

Failure to comply with these instructions may result in product damage.

TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified

Figure 1. Nomenclature and Order Guide



Note:

9. See Table 5 for an explanation of sensor pressure types.

Uncompensated/Unamplified Millivolt Analog Output

Figure 2. Completed Catalog Listing Example



Table 5. Pressure Types

| Pressure Type | Description |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Absolute | Output is proportional to the difference between applied pressure and a built-in reference to vacuum. Reference pressure is absolute zero pressure (full vacuum). |
| Differential | Output is proportional to the difference between the pressures applied to each port. (Port 1 – Port 2) Reference pressure is Port 1 = Port 2. |
| Gage | Output is proportional to the difference between applied pressure and atmospheric (ambient) pressure. Reference pressure is atmospheric pressure. |

Table 6. Pressure Range Specifications for 1 psi to 150 psi

| Pressure Range (see Figure 1) | Pressure Range | | Unit | Over Pressure | Burst Pressure | Common Mode Pressure | Offset ¹⁰ (mV/V) | | Sensitivity (mV/V/Full Scale Span) | | | TCO ¹¹ (%FSS/25 °C) | | | TCS ¹² (%FSS/25 °C) | | | Bridge Resistance ¹³ (kOhm) | | | TCR ¹⁴ (-40 °C to 25 °C) (ppm/°C) | | TCR ¹⁵ (25 °C to 85 °C) (ppm/°C) | | Long-term Stability (1000 hr, 25 °C [77 °F]) (%FSS) |
|----------------------------------|----------------|-------|------|---------------|----------------|----------------------|--------------------------------|------|---------------------------------------|------|------|-----------------------------------|------|------|-----------------------------------|------|------|-------------------------------------------|------|------|----------------------------------------------------|------|---------------------------------------------------|------|-----------------------------------------------------------|
| | Pmin. | Pmax. | | | | | Min. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Max. | Min. | Max. | |
| Absolute | | | | | | | | | | | | | | | | | | | | | | | | | |
| 015PA | 0 | 15 | psi | 30 | 60 | N/A | -6.0 | 6.0 | 10.3 | 15.0 | 19.7 | -3.6 | 0.0 | 3.6 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 030PA | 0 | 30 | psi | 60 | 120 | N/A | -6.0 | 6.0 | 9.9 | 14.8 | 19.7 | -3.8 | 0.0 | 3.8 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 060PA | 0 | 60 | psi | 120 | 250 | N/A | -6.0 | 6.0 | 10.7 | 15.2 | 19.7 | -3.5 | 0.0 | 3.5 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 100PA | 0 | 100 | psi | 250 | 250 | N/A | -6.0 | 6.0 | 9.1 | 12.6 | 16.1 | -4.1 | 0.0 | 4.1 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 150PA | 0 | 150 | psi | 250 | 250 | N/A | -6.0 | 6.0 | 13.6 | 18.9 | 24.2 | -2.8 | 0.0 | 2.8 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| Differential | | | | | | | | | | | | | | | | | | | | | | | | | |
| 001PD | -1 | 1 | psi | 5 | 20 | 150 | -8.5 | 3.5 | 9.0 | 13.0 | 17.0 | -1.1 | 0.5 | 1.1 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2200 | 3200 | ±0.35% |
| 005PD | -5 | 5 | psi | 20 | 40 | 150 | -8.5 | 3.5 | 20.0 | 30.0 | 40.0 | -0.6 | 0.2 | 0.6 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2200 | 3200 | ±0.35% |
| 015PD | -15 | 15 | psi | 30 | 60 | 150 | -7.0 | 5.3 | 20.7 | 31.0 | 41.4 | -0.6 | 0.3 | 0.5 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 030PD | -30 | 30 | psi | 60 | 120 | 150 | -7.0 | 5.3 | 31.0 | 41.4 | 51.7 | -0.3 | 0.2 | 0.3 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 060PD | -60 | 60 | psi | 120 | 250 | 250 | -7.0 | 5.3 | 34.8 | 41.4 | 48.0 | -0.3 | 0.2 | 0.3 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 100PD | -100 | 100 | psi | 250 | 250 | 250 | -7.0 | 5.3 | 29.0 | 34.5 | 40.0 | -0.3 | 0.3 | 0.3 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 150PD | -150 | 150 | psi | 250 | 250 | 250 | -7.0 | 5.3 | 43.4 | 51.7 | 60.0 | -0.2 | 0.2 | 0.2 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| Gage | | | | | | | | | | | | | | | | | | | | | | | | | |
| 001PG | 0 | 1 | psi | 5 | 20 | 150 | -8.5 | 3.5 | 4.5 | 6.5 | 8.5 | -2.2 | 1.0 | 2.2 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2200 | 3200 | ±0.35% |
| 005PG | 0 | 5 | psi | 20 | 40 | 150 | -8.5 | 3.6 | 10.0 | 15.0 | 20.0 | -1.0 | 0.4 | 1.0 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2200 | 3200 | ±0.35% |
| 015PG | 0 | 15 | psi | 30 | 60 | 150 | -7.0 | 5.3 | 10.3 | 15.5 | 20.7 | -1.0 | 0.6 | 1.0 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 030PG | 0 | 30 | psi | 60 | 120 | 150 | -7.0 | 5.3 | 15.5 | 20.7 | 25.9 | -0.6 | 0.4 | 0.6 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 060PG | 0 | 60 | psi | 120 | 250 | 250 | -7.0 | 5.3 | 17.4 | 20.7 | 24.0 | -0.6 | 0.4 | 0.6 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 100PG | 0 | 100 | psi | 250 | 250 | 250 | -7.0 | 5.3 | 14.5 | 17.2 | 20.0 | -0.7 | 0.5 | 0.7 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |
| 150PG | 0 | 150 | psi | 250 | 250 | 250 | -7.0 | 5.3 | 21.7 | 25.9 | 30.0 | -0.6 | 0.3 | 0.6 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2200 | 3200 | ±0.25% |

TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified

Table 7. Pressure Range Specifications for 60 mbar to 10 bar

| Pressure Range (see Figure 1) | Pressure Range | | Unit | Over Pressure | Burst Pressure | Common Mode Pressure | Offset ¹⁰ (mV/V) | | Sensitivity (mV/V/Full Scale Span) | | | TCO ¹¹ (%FSS/25 °C) | | | TCS ¹² (%FSS/25 °C) | | | Bridge Resistance ¹³ (kOhm) | | | TCR ¹⁴ (-40 °C to 25 °C) (ppm/°C) | | TCR ¹⁵ (25 °C to 85 °C) (ppm/°C) | | Long-term Stability (1000 hr, 25 °C [77 °F]) (%FSS) |
|----------------------------------|----------------|-------|------|---------------|----------------|----------------------|--------------------------------|------|---------------------------------------|------|------|-----------------------------------|------|------|-----------------------------------|------|------|-------------------------------------------|------|------|----------------------------------------------------|------|---------------------------------------------------|------|-----------------------------------------------------------|
| | Pmin. | Pmax. | | | | | Min. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Nom. | Max. | Min. | Max. | Min. | Max. | |
| Absolute | | | | | | | | | | | | | | | | | | | | | | | | | |
| 001BA | 0 | 1 | bar | 2 | 4 | N/A | -6.0 | 6.0 | 10.0 | 14.5 | 19.0 | -3.8 | 0.0 | 3.8 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 1.6BA | 0 | 1.6 | bar | 4.1 | 8 | N/A | -6.0 | 6.0 | 7.7 | 11.4 | 15.2 | -4.9 | 0.0 | 4.9 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 2.5BA | 0 | 2.5 | bar | 4.1 | 8 | N/A | -6.0 | 6.0 | 12.0 | 17.9 | 23.8 | -3.1 | 0.0 | 3.1 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 004BA | 0 | 4 | bar | 8 | 17 | N/A | -6.0 | 6.0 | 10.3 | 14.7 | 19.0 | -3.6 | 0.0 | 3.6 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 006BA | 0 | 6 | bar | 17 | 17 | N/A | -6.0 | 6.0 | 7.9 | 11.0 | 14.0 | -4.8 | 0.0 | 4.8 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| 010BA | 0 | 10 | bar | 17 | 17 | N/A | -6.0 | 6.0 | 13.2 | 18.3 | 23.4 | -2.9 | 0.0 | 2.9 | -7.5 | -5.0 | -3.0 | 2.6 | 3.5 | 4.4 | 500 | 1500 | 1500 | 2500 | ±0.25% |
| Differential | | | | | | | | | | | | | | | | | | | | | | | | | |
| 060MD | -60 | 60 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 7.8 | 11.3 | 14.8 | -1.3 | 0.6 | 1.3 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 100MD | -100 | 100 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 13.1 | 18.9 | 24.7 | -0.8 | 0.3 | 0.8 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 160MD | -160 | 160 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 20.9 | 30.2 | 39.4 | -0.5 | 0.2 | 0.5 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 250MD | -250 | 250 | mbar | 1380 | 2760 | 10000 | -8.5 | 3.5 | 14.5 | 21.8 | 29.0 | -0.7 | 0.3 | 0.7 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 400MD | -400 | 400 | mbar | 1380 | 2760 | 10000 | -7.0 | 5.3 | 23.2 | 34.8 | 46.4 | -0.4 | 0.2 | 0.4 | -6.3 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 600MD | -600 | 600 | mbar | 2060 | 4100 | 10000 | -7.0 | 5.3 | 12.0 | 18.0 | 24.0 | -0.8 | 0.5 | 0.8 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 001BD | -1 | 1 | bar | 2 | 4 | 10 | -7.0 | 5.3 | 20.0 | 30.0 | 40.0 | -0.6 | 0.3 | 0.5 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 1.6BD | -1.6 | 1.6 | bar | 4.1 | 8 | 10 | -7.0 | 5.3 | 24.0 | 32.0 | 40.0 | -0.4 | 0.3 | 0.4 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 2.5BD | -2.5 | 2.5 | bar | 4.1 | 8 | 10 | -7.0 | 5.3 | 37.5 | 50.0 | 62.5 | -0.3 | 0.2 | 0.3 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 004BD | -4.0 | 4.0 | bar | 8 | 17 | 17 | -7.0 | 5.3 | 33.6 | 40.0 | 46.4 | -0.3 | 0.2 | 0.3 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 006BD | -6.0 | 6.0 | bar | 17 | 17 | 17 | -7.0 | 5.3 | 25.2 | 30.0 | 34.8 | -0.4 | 0.3 | 0.4 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 010BD | -10.0 | 10 | bar | 17 | 17 | 17 | -7.0 | 5.3 | 42.0 | 50.0 | 58.0 | -0.2 | 0.1 | 0.2 | -6.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| Gage | | | | | | | | | | | | | | | | | | | | | | | | | |
| 060MG | 0 | 60 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 3.9 | 5.7 | 7.4 | -2.6 | 1.1 | 2.6 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 100MG | 0 | 100 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 6.5 | 9.4 | 12.3 | -1.5 | 0.7 | 1.5 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 160MG | 0 | 160 | mbar | 340 | 1380 | 10000 | -8.5 | 3.5 | 10.4 | 15.1 | 19.7 | -1.0 | 0.4 | 1.0 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 250MG | 0 | 250 | mbar | 1380 | 2760 | 10000 | -8.5 | 3.5 | 7.3 | 10.9 | 14.5 | -1.4 | 0.6 | 1.4 | -6.3 | -5.0 | -3.8 | 4 | 5 | 6 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 400MG | 0 | 400 | mbar | 1380 | 2760 | 10000 | -7.0 | 5.3 | 11.6 | 17.4 | 23.2 | -0.9 | 0.4 | 0.9 | -6.3 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 600MG | 0 | 600 | mbar | 2060 | 4100 | 10000 | -7.0 | 5.3 | 6.0 | 9.0 | 12.0 | -1.7 | 1.0 | 1.7 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.35% |
| 001BG | 0 | 1 | bar | 2 | 4 | 10 | -7.0 | 5.3 | 10.0 | 15.0 | 20.0 | -1.0 | 0.6 | 1.0 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 1.6BG | 0 | 1.6 | bar | 4.1 | 8 | 10 | -7.0 | 5.3 | 12.0 | 16.0 | 20.0 | -0.8 | 0.5 | 0.8 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 2.5BG | 0 | 2.5 | bar | 4.1 | 8 | 10 | -7.0 | 5.3 | 18.8 | 25.0 | 31.3 | -0.6 | 0.4 | 0.5 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 004BG | 0 | 4 | bar | 8 | 17 | 17 | -7.0 | 5.3 | 16.8 | 20.0 | 23.2 | -0.6 | 0.4 | 0.6 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 006BG | 0 | 6 | bar | 17 | 17 | 17 | -7.0 | 5.3 | 12.6 | 15.0 | 17.4 | -0.8 | 0.6 | 0.8 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |
| 010BG | 0 | 10 | bar | 17 | 17 | 17 | -7.0 | 5.3 | 21.0 | 25.0 | 29.0 | -0.5 | 0.4 | 0.5 | -8.0 | -5.0 | -3.8 | 2.4 | 3 | 5.5 | 1200 | 2200 | 2220 | 3200 | ±0.25% |

Notes:

- Offset: The output signal obtained when the reference pressure is applied to all available pressure ports. Also known as “null” or “zero”.
- TCO (Thermal Effect on Offset): The deviation in offset due to changes in temperature over the specified temperature range, relative to offset measured at 25 °C.
- TCS (Thermal Effect on Span): The deviation in full scale span due to changes in temperature over the specified temperature range, relative to full scale span measured at 25 °C.
- Bridge Resistance: The resistance of the device measured across the power supply leads.
- TCR (Thermal Coefficient of Resistance): The deviation in bridge resistance due to changes in temperature over the specified temperature range, relative to bridge resistance measured at 25 °C.

Table 8. Pinout for DIP and SMT Packages

| Output Type | Pin 1 | Pin 2 | Pin 3 | Pin 4 | Pin 5 | Pin 6 | Pin 7 | Pin 8 |
|-------------|-------|---------|---------------------|---------|-------|-------|-------|-------|
| analog | GND | OUTPUT+ | V _{supply} | OUTPUT- | NC | NC | NC | NC |

Table 9. Pinout for SIP Packages

| Output Type | Pin 1 | Pin 2 | Pin 3 | Pin 4 |
|-------------|-------|---------|---------------------|---------|
| analog | GND | OUTPUT+ | V _{supply} | OUTPUT- |

Uncompensated/Unamplified Millivolt Analog Output

Figure 3. DIP Pressure Port Dimensional Drawings (For reference only: mm [in])



TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified

Figure 4. SMT Pressure Port Dimensional Drawings (For reference only: mm [in])



Uncompensated/Unamplified Millivolt Analog Output


Figure 5. SIP Package Dimensional Drawings (For reference only: mm [in])



TruStability® Board Mount Pressure Sensors: NSC Series— Uncompensated/Unamplified

Figure 5. SIP Package Dimensional Drawings (continued)


SIP GN: Ribbed fastener mount, single axial barbed port




SIP NB: Fastener mount, dual axial ports, same side



SIP RN: Single radial barbed port




SIP RR: Dual radial barbed ports, same side



Uncompensated/Unamplified Millivolt Analog Output

Figure 5. SIP Package Dimensional Drawings (continued)



WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet is for reference only. DO NOT USE this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

SALES AND SERVICE

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office or:

E-mail: info.sc@honeywell.com

Internet: www.honeywell.com/sensing

Phone and Fax:

| | |
|---------------|---------------------------------------------------------|
| Asia Pacific | +65 6355-2828; +65 6445-3033 Fax |
| Europe | +44 (0) 1698 481481; +44 (0) 1698 481676 Fax |
| Latin America | +1-305-805-8188; +1-305-883-8257 Fax |
| USA/Canada | +1-800-537-6945; +1-815-235-6847 +1-815-235-6545 Fax |

Sensing and Control
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422
www.honeywell.com/sensing

008221-1-EN IL50 GLO Printed in USA
July 2011
© 2011 Honeywell International Inc.

Honeywell



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.