NSBA114EDXV6T1, NSBA114EDXV6T5

Preferred Devices

Dual Bias Resistor Transistors

PNP Silicon Surface Mount Transistors with Monolithic Bias Resistor Network

The BRT (Bias Resistor Transistor) contains a single transistor with a monolithic bias network consisting of two resistors; a series base resistor and a base−emitter resistor. These digital transistors are designed to replace a single device and its external resistor bias network. The BRT eliminates these individual components by integrating them into a single device. In the NSBA114EDXV6T1 series, two BRT devices are housed in the SOT−563 package which is ideal for low−power surface mount applications where board space is at a premium.

- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- Available in 8 mm, 7 inch Tape and Reel
- Lead Free Solder Plating

ON Semiconductor®

http://onsemi.com





SOT−563
CASE 463A
PLASTIC

MAXIMUM RATINGS

(T_A = 25°C unless otherwise noted, common for Q_1 and Q_2)

Rating	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	−50	Vdc
Collector-Emitter Voltage	V_{CEO}	−50	Vdc
Collector Current	I_C	−100	mAdc

THERMAL CHARACTERISTICS

Characteristic (One Junction Heated)	Symbol	Max	Unit
Total Device Dissipation T_A = 25°C Derate above 25°C	P_D	357 (Note 1) 2.9 (Note 1)	mW mW/°C
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	350 (Note 1)	°C/W
Characteristic (Both Junctions Heated)	**Symbol**	**Max**	**Unit**
Total Device Dissipation T_A = 25°C Derate above 25°C	P_D	500 (Note 1) 4.0 (Note 1)	mW mW/°C
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	250 (Note 1)	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

1. FR−4 @ Minimum Pad

MARKING DIAGRAM

xx = Specific Device Code
(see table on page 2)
D = Date Code

ORDERING INFORMATION

Device	Package	Shipping
NSBA114EDXV6T1	SOT−563	4 mm pitch 4000/Tape & Reel
NSBA114EDXV6T5	SOT−563	2 mm pitch 8000/Tape & Reel

DEVICE MARKING INFORMATION

See specific marking information in the device marking table on page 2 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2004

DEVICE MARKING AND RESISTOR VALUES

Device	Package	Marking	R1 (kΩ)	R2 (kΩ)
NSBA114EDXV6T1	SOT−563	0A	10	10
NSBA124EDXV6T1	SOT−563	0B	22	22
NSBA144EDXV6T1	SOT−563	0C	47	47
NSBA114YDXV6T1	SOT−563	0D	10	47
NSBA114TDXV6T1 (Notes 2)	SOT−563	0E	10	∞
NSBA143TDXV6T1 (Notes 2)	SOT−563	0F	4.7	∞
NSBA113EDXV6T1 (Notes 2)	SOT−563	0G	1.0	1.0
NSBA123EDXV6T1 (Notes 2)	SOT−563	0H	2.2	2.2
NSBA143EDXV6T1 (Notes 2)	SOT−563	0J	4.7	4.7
NSBA143ZDXV6T1 (Notes 2)	SOT−563	0K	4.7	47
NSBA124XDXV6T1 (Notes 2)	SOT−563	0L	22	47
NSBA123JDXV6T1 (Notes 2)	SOT−563	0M	2.2	47
NSBA115EDXV6T1 (Notes 2)	SOT−563	0N	100	100
NSBA144WDXV6T1 (Notes 2)	SOT−563	0P	47	22

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted, common for Q_1 and Q_2)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector-Base Cutoff Current (V_{CB} = −50 V, I_E = 0)		I_{CBO}	−	−	−100	nAdc
Collector-Emitter Cutoff Current (V_{CE} = −50 V, I_B = 0)		I_{CEO}	−	−	−500	nAdc
Emitter-Base Cutoff Current (V_{EB} = −6.0 V, I_C = 0)	NSBA114EDXV6T1	I_{EBO}	−	−	−0.5	mAdc
	NSBA124EDXV6T1		−	−	−0.2	
	NSBA144EDXV6T1		−	−	−0.1	
	NSBA114YDXV6T1		−	−	−0.2	
	NSBA114TDXV6T1		−	−	−0.9	
	NSBA143TDXV6T1		−	−	−1.9	
	NSBA113EDXV6T1		−	−	−4.3	
	NSBA123EDXV6T1		−	−	−2.3	
	NSBA143EDXV6T1		−	−	−1.5	
	NSBA143ZDXV6T1		−	−	−0.18	
	NSBA124XDXV6T1		−	−	−0.13	
	NSBA123JDXV6T1		−	−	−0.2	
	NSBA115EDXV6T1		−	−	−0.05	
	NSBA144WDXV6T1		−	−	−0.13	
Collector-Base Breakdown Voltage (I_C = −10 μA, I_E = 0)		$V_{(BR)CBO}$	−50	−	−	Vdc
Collector-Emitter Breakdown Voltage (Note 3) (I_C = −2.0 mA, I_B = 0)		$V_{(BR)CEO}$	−50	−	−	Vdc
ON CHARACTERISTICS (Note 3)						
Collector-Emitter Saturation Voltage (I_C = −10 mA, I_E = −0.3 mA)		$V_{CE(sat)}$	−	−	−0.25	Vdc
(I_C = −10 mA, I_B = −5 mA)	NSBA113EDXV6T1/NSBA123EDXV6T1					
(I_C = −10 mA, I_B = −1 mA)	NSBA114TDXV6T1/NSBA143TDXV6T1					
	NSBA143EDXV6T1/NSBA143ZDXV6T1/NSBA124XDXV6T1					

2. New resistor combinations. Updated curves to follow in subsequent data sheets.
3. Pulse Test: Pulse Width < 300 μs, Duty Cycle < 2.0%

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted, common for Q_1 and Q_2) (continued)

Characteristic		Symbol	Min	Typ	Max	Unit
ON CHARACTERISTICS (Note 3) (continued)						
DC Current Gain (V_{CE} = −10 V, I_C = −5.0 mA)	NSBA114EDXV6T1	h_{FE}	35	60	−	
	NSBA124EDXV6T1		60	100	−	
	NSBA144EDXV6T1		80	140	−	
	NSBA114YDXV6T1		80	140	−	
	NSBA114TDXV6T1		160	250	−	
	NSBA143TDXV6T1		160	250	−	
	NSBA113EDXV6T1		3.0	5.0	−	
	NSBA123EDXV6T1		8.0	15	−	
	NSBA143EDXV6T1		15	27	−	
	NSBA143ZDXV6T1		80	140	−	
	NSBA124XDXV6T1		80	130	−	
	NSBA123JDXV6T1		80	140	−	
	NSBA115EDXV6T1		80	130	−	
	NSBA144WDXV6T1		80	140	−	
Output Voltage (on)		V_{OL}				Vdc
(V_{CC} = −5.0 V, V_B = −2.5 V, R_L = 1.0 kΩ)	NSBA114EDXV6T1		−	−	−0.2	
	NSBA124EDXV6T1		−	−	−0.2	
	NSBA114YDXV6T1		−	−	−0.2	
	NSBA114TDXV6T1		−	−	−0.2	
	NSBA143TDXV6T1		−	−	−0.2	
	NSBA113EDXV6T1		−	−	−0.2	
	NSBA123EDXV6T1		−	−	−0.2	
	NSBA143EDXV6T1		−	−	−0.2	
	NSBA143ZDXV6T1		−	−	−0.2	
	NSBA124XDXV6T1		−	−	−0.2	
	NSBA123JDXV6T1		−	−	−0.2	
(V_{CC} = −5.0 V, V_B = −3.5 V, R_L = 1.0 kΩ)	NSBA144EDXV6T1		−	−	−0.2	
(V_{CC} = −5.0 V, V_B = −5.5 V, R_L = 1.0 kΩ)	NSBA115EDXV6T1		−	−	−0.2	
(V_{CC} = −5.0 V, V_B = −4.0 V, R_L = 1.0 kΩ)	NSBA144WDXV6T1		−	−	−0.2	
Output Voltage (off) (V_{CC} = −5.0 V, V_B = −0.5 V, R_L = 1.0 kΩ)		V_{OH}	−4.9	−	−	Vdc
(V_{CC} = −5.0 V, V_B = −0.05 V, R_L = 1.0 kΩ)	NSBA113EDXV6T1					
(V_{CC} = −5.0 V, V_B = −0.25 V, R_L = 1.0 kΩ)	NSBA114TDXV6T1					
	NSBA143TDXV6T1					
	NSBA123EDXV6T1					
	NSBA143ZDXV6T1					
Input Resistor	NSBA114EDXV6T1	R_1	7.0	10	13	k Ω
	NSBA124EDXV6T1		15.4	22	28.6	
	NSBA144EDXV6T1		32.9	47	61.1	
	NSBA114YDXV6T1		7.0	10	13	
	NSBA114TDXV6T1		7.0	10	13	
	NSBA143TDXV6T1		3.3	4.7	6.1	
	NSBA113EDXV6T1		0.7	1.0	1.3	
	NSBA123EDXV6T1		1.5	2.2	2.9	
	NSBA143EDXV6T1		3.3	4.7	6.1	
	NSBA143ZDXV6T1		3.3	4.7	6.1	
	NSBA124XDXV6T1		15.4	22	28.6	
	NSBA123JDXV6T1		1.54	2.2	2.86	
	NSBA115EDXV6T1		70	100	130	
	NSBA144WDXV6T1		32.9	47	61.1	
Resistor Ratio	NSBA114EDXV6T1/NSBA124EDXV6T1/ NSBA144EDXV6T1/NSBA115EDXV6T1	R_1/R_2	0.8	1.0	1.2	
	NSBA114YDXV6T1		0.17	0.21	0.25	
	NSBA114TDXV6T1/NSBA143TDXV6T1		−	−	−	
	NSBA113EDXV6T1/NSBA123EDXV6T1/NSBA143EDXV6T1		0.8	1.0	1.2	
	NSBA143ZDXV6T1		0.055	0.1	0.185	
	NSBA124XDXV6T1		0.38	0.47	0.56	
	NSBA123JDXV6T1		0.038	0.047	0.056	
	NSBA144WDXV6T1		1.7	2.1	2.6	

2. New resistor combinations. Updated curves to follow in subsequent data sheets.
3. Pulse Test: Pulse Width < 300 μs, Duty Cycle < 2.0%

ALL NSBA114EDXV6T1 SERIES DEVICES



Figure 1. Derating Curve − ALL DEVICES

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA114EDXV6T1



Figure 2. $V_{CE(sat)}$ versus I_C

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA114EDXV6T1



Figure 3. DC Current Gain



Figure 4. Output Capacitance



Figure 5. Output Current versus Input Voltage



Figure 6. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA124EDXV6T1



Figure 7. $V_{CE(sat)}$ versus I_C



Figure 8. DC Current Gain



Figure 9. Output Capacitance



Figure 10. Output Current versus Input Voltage



Figure 11. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA144EDXV6T1



Figure 12. $V_{CE(sat)}$ versus I_C



Figure 13. DC Current Gain



Figure 14. Output Capacitance



Figure 15. Output Current versus Input Voltage



Figure 16. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA114YDXV6T1



Figure 17. $V_{CE(sat)}$ versus I_C



Figure 18. DC Current Gain



Figure 19. Output Capacitance



Figure 20. Output Current versus Input Voltage



Figure 21. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA114TDXV6T1



Figure 22. DC Current Gain

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA143TDXV6T1



Figure 23. DC Current Gain

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA115EDXV6T1



Figure 24. Maximum Collector Voltage versus Collector Current



Figure 25. DC Current Gain



Figure 26. Output Capacitance



Figure 27. Output Current versus Input Voltage



Figure 28. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — NSBA144WDXV6T1



Figure 29. Maximum Collector Voltage versus Collector Current



Figure 30. DC Current Gain



Figure 31. Output Capacitance



Figure 32. Output Current versus Input Voltage



Figure 33. Input Voltage versus Output Current

PACKAGE DIMENSIONS

SOT−563, 6 LEAD
CASE 463A−01
ISSUE O



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	1.50	1.70	0.059	0.067
B	1.10	1.30	0.043	0.051
C	0.50	0.60	0.020	0.024
D	0.17	0.27	0.007	0.011
G	0.50 BSC		0.020 BSC	
J	0.08	0.18	0.003	0.007
K	0.10	0.30	0.004	0.012
S	1.50	1.70	0.059	0.067

STYLE 1:
PIN 1. EMITTER 1
2. BASE 1
3. COLLECTOR 2
4. EMITTER 2
5. BASE 2
6. COLLECTOR 1

STYLE 2:
PIN 1. EMITTER 1
2. EMITTER2
3. BASE 2
4. COLLECTOR 2
5. BASE 1
6. COLLECTOR 1

STYLE 3:
PIN 1. CATHODE 1
2. CATHODE 1
3. ANODE/ANODE 2
4. CATHODE 2
5. CATHODE 2
6. ANODE/ANODE 1

STYLE 4:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

SOLDERING FOOTPRINT*



SCALE 20:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2−9−1 Kamimeguro, Meguro−ku, Tokyo, Japan 153−0051
Phone: 81−3−5773−3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.

NSBA114EDXV6/D

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.