

# NTR5103N

## Small Signal MOSFET

60 V, 310 mA, Single, N-Channel, SOT-23

### Features

- Low  $R_{DS(on)}$
- Small Footprint Surface Mount Package
- Trench Technology
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### Applications

- Low Side Load Switch
- Level Shift Circuits
- DC-DC Converter
- Portable Applications i.e. DSC, PDA, Cell Phone, etc.

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise stated)

| Rating                                                               | Symbol         | Value                           | Unit             |
|----------------------------------------------------------------------|----------------|---------------------------------|------------------|
| Drain-to-Source Voltage                                              | $V_{DS}$       | 60                              | V                |
| Gate-to-Source Voltage                                               | $V_{GS}$       | $\pm 30$                        | V                |
| Drain Current (Note 1)<br>Steady State                               | $I_D$          | $T_A = 25^\circ\text{C}$<br>260 | mA               |
|                                                                      |                | $T_A = 85^\circ\text{C}$<br>190 |                  |
| $t < 5$ s                                                            | $I_D$          | $T_A = 25^\circ\text{C}$<br>310 |                  |
|                                                                      |                | $T_A = 85^\circ\text{C}$<br>220 |                  |
| Power Dissipation (Note 1)<br>Steady State                           | $P_D$          | 300                             | mW               |
| $t < 5$ s                                                            |                | 420                             |                  |
| Pulsed Drain Current ( $t_p = 10$ $\mu\text{s}$ )                    | $I_{DM}$       | 1.2                             | A                |
| Operating Junction and Storage<br>Temperature Range                  | $T_J, T_{STG}$ | $-55$ to $+150$                 | $^\circ\text{C}$ |
| Source Current (Body Diode)                                          | $I_S$          | 300                             | mA               |
| Lead Temperature for Soldering Purposes<br>(1/8" from case for 10 s) | $T_L$          | 260                             | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### THERMAL CHARACTERISTICS

| Characteristic                                 | Symbol          | Max | Unit               |
|------------------------------------------------|-----------------|-----|--------------------|
| Junction-to-Ambient – Steady State<br>(Note 1) | $R_{\theta JA}$ | 417 | $^\circ\text{C/W}$ |
| Junction-to-Ambient – $t \leq 5$ s (Note 1)    | $R_{\theta JA}$ | 300 |                    |

1. Surface-mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)




ON Semiconductor®


<http://onsemi.com>

| $V_{(BR)DSS}$ | $R_{DS(on)}$ MAX     | $I_D$ MAX<br>(Note 1) |
|---------------|----------------------|-----------------------|
| 60 V          | $3.0 \Omega$ @ 4.5 V | 310 mA                |
|               | $2.5 \Omega$ @ 10 V  |                       |


### Simplified Schematic



### MARKING DIAGRAM & PIN ASSIGNMENT



SOT-23  
CASE 318  
STYLE 21



TJ4 = Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device      | Package             | Shipping†          |
|-------------|---------------------|--------------------|
| NTR5103NT1G | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# NTR5103N

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

| Parameter                                                 | Symbol            | Test Condition                                      | Min                       | Typ | Max | Units                |
|-----------------------------------------------------------|-------------------|-----------------------------------------------------|---------------------------|-----|-----|----------------------|
| <b>OFF CHARACTERISTICS</b>                                |                   |                                                     |                           |     |     |                      |
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$ | 60                        |     |     | V                    |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ |                                                     |                           | 75  |     | mV/ $^\circ\text{C}$ |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0\text{ V},$<br>$V_{DS} = 60\text{ V}$    | $T_J = 25^\circ\text{C}$  |     | 1   | $\mu\text{A}$        |
|                                                           |                   |                                                     | $T_J = 125^\circ\text{C}$ |     | 500 |                      |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0\text{ V}, V_{GS} = \pm 30\text{ V}$     |                           |     | 200 | nA                   |

## ON CHARACTERISTICS (Note 2)

|                                            |                  |                                                 |     |     |     |                      |
|--------------------------------------------|------------------|-------------------------------------------------|-----|-----|-----|----------------------|
| Gate Threshold Voltage                     | $V_{GS(TH)}$     | $V_{GS} = V_{DS}, I_D = 250\text{ }\mu\text{A}$ | 1.9 |     | 2.6 | V                    |
| Negative Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ |                                                 |     | 4.4 |     | mV/ $^\circ\text{C}$ |
| Drain-to-Source On Resistance              | $R_{DS(on)}$     | $V_{GS} = 10\text{ V}, I_D = 240\text{ mA}$     |     | 1.0 | 2.5 | $\Omega$             |
|                                            |                  | $V_{GS} = 4.5\text{ V}, I_D = 50\text{ mA}$     |     | 1.4 | 3.0 |                      |
| Forward Transconductance                   | $g_{FS}$         | $V_{DS} = 5\text{ V}, I_D = 200\text{ mA}$      |     | 530 |     | mS                   |

## CHARGES AND CAPACITANCES

|                              |              |                                                                       |  |      |    |    |
|------------------------------|--------------|-----------------------------------------------------------------------|--|------|----|----|
| Input Capacitance            | $C_{ISS}$    | $V_{GS} = 0\text{ V}, f = 1\text{ MHz},$<br>$V_{DS} = 25\text{ V}$    |  | 26.7 | 40 | pF |
| Output Capacitance           | $C_{OSS}$    |                                                                       |  | 4.6  |    |    |
| Reverse Transfer Capacitance | $C_{RSS}$    |                                                                       |  | 2.9  |    |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 5\text{ V}, V_{DS} = 10\text{ V};$<br>$I_D = 240\text{ mA}$ |  | 0.81 |    | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  |                                                                       |  | 0.31 |    |    |
| Gate-to-Source Charge        | $Q_{GS}$     |                                                                       |  | 0.48 |    |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |                                                                       |  | 0.08 |    |    |

## SWITCHING CHARACTERISTICS, $V_{GS} = V$ (Note 3)

|                     |              |                                                                                                |  |     |  |    |
|---------------------|--------------|------------------------------------------------------------------------------------------------|--|-----|--|----|
| Turn-On Delay Time  | $t_{d(ON)}$  | $V_{GS} = 10\text{ V}, V_{DD} = 30\text{ V},$<br>$I_D = 200\text{ mA}, R_G = 10\text{ }\Omega$ |  | 1.7 |  | ns |
| Rise Time           | $t_r$        |                                                                                                |  | 1.2 |  |    |
| Turn-Off Delay Time | $t_{d(OFF)}$ |                                                                                                |  | 4.8 |  |    |
| Fall Time           | $t_f$        |                                                                                                |  | 3.6 |  |    |

## DRAIN-SOURCE DIODE CHARACTERISTICS

|                       |          |                                                 |                          |  |      |     |   |
|-----------------------|----------|-------------------------------------------------|--------------------------|--|------|-----|---|
| Forward Diode Voltage | $V_{SD}$ | $V_{GS} = 0\text{ V},$<br>$I_S = 200\text{ mA}$ | $T_J = 25^\circ\text{C}$ |  | 0.79 | 1.2 | V |
|                       |          |                                                 | $T_J = 85^\circ\text{C}$ |  | 0.7  |     |   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse Test: pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$

3. Switching characteristics are independent of operating junction temperatures

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Temperature




Figure 4. On-Resistance vs. Drain Current and Temperature




Figure 5. On-Resistance vs. Gate-to-Source Voltage




Figure 6. On-Resistance Variation with Temperature

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge





Figure 9. Diode Forward Voltage vs. Current

# NTR5103N

## PACKAGE DIMENSIONS

### SOT-23 (TO-236) CASE 318-08 ISSUE AP



#### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.040 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.018 | 0.020 |
| c   | 0.09        | 0.13 | 0.18 | 0.003  | 0.005 | 0.007 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.081 |
| L   | 0.10        | 0.20 | 0.30 | 0.004  | 0.008 | 0.012 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.029 |
| HE  | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| θ   | 0°          |      | 10°  | 0°     |       | 10°   |

#### STYLE 21:

- PIN 1. GATE
- SOURCE
- DRAIN

## SOLDERING FOOTPRINT



**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.