

# HCV1707

## High current power inductors



### Product features

- Flat-wire construction
- Low DCR, high efficiency
- Secure 3 terminal mounting
- 17.8 mm x 14.35 mm footprint surface mount package in a 6.9 mm height
- Ferrite core material
- Moisture Sensitivity Level: 1

### Applications

- Compatible with Picor® Cool-Power® ZVS Buck and Buck-Boost Regulator Families

### Environmental data

- Storage temperature range (Component): -55 °C to +125 °C
- Operating temperature range: -55 °C to +125 °C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020 (latest revision) compliant
- Halogen free, lead free, RoHS compliant



Picor® and Cool-Power® are trademarks of Vicor Corporation.


**Product specifications**

Part Number <sup>7</sup>	OCL <sup>1</sup> ( $\mu$ H) $\pm 10\%$	FLL <sup>2</sup> ( $\mu$ H) minimum	I <sub>rms</sub> <sup>3</sup> (A)	I <sub>sat</sub> <sup>1</sup> <sup>4</sup> (A)	I <sub>sat</sub> <sup>2</sup> <sup>5</sup> (A)	I <sub>sat</sub> <sup>3</sup> <sup>6</sup> (A)	DCR (m $\Omega$ ) $\pm 10\%$ @ +20 °C
HCV1707R1-R48-R	0.48	0.42	32	55	68	47	1.7


1. Open Circuit Inductance (OCL) Test Parameters: 100 kHz, 0.1 Vrms, 0.0 Adc, +25 °C
2. Full Load Inductance (FLL) Test Parameters: 100 kHz, 0.1 Vrms, I<sub>sat</sub><sup>1</sup>, +25 °C
3. I<sub>rms</sub><sup>3</sup>: DC current for an approximate temperature rise of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed +125 °C under worst case operating conditions verified in the end application.

4. I<sub>sat</sub><sup>1</sup>: Peak current for approximately 2% rolloff @ +25 °C
5. I<sub>sat</sub><sup>2</sup>: Peak current for approximately 2% rolloff @ -55 °C
6. I<sub>sat</sub><sup>3</sup>: Peak current for approximately 2% rolloff @ +125 °C
7. Part Number Definition: HCV1707Rx-Rxxx-R  
HCV1707= Product code and size  
Rx= Version indicator  
Rxx= Inductance value in  $\mu$ H, R= decimal point,  
If no R is present last character equals number of zeros  
-R suffix = RoHS compliant


**Dimensions (mm)**



**Recommended Pad Layout**




**Schematic**




Part marking: HCV1707Rx-Rxx, Rxx= inductance value in  $\mu$ H, R= decimal point, if no R is present last character equals number of zeros  
xxxx=lot code  
All soldering surface to be coplanar within 0.1 millimeters  
Tolerances are  $\pm 0.15$  millimeters unless stated otherwise  
Pad layout tolerances are  $\pm 0.1$  millimeters unless stated otherwise  
Pin NC is for mounting stability. No connection.  
Do not route traces or vias underneath the inductor

**Packaging information (mm)**


Supplied in tape and reel packaging , 350 parts per 13" diameter reel




**Temperature rise vs. total loss**



**Inductance characteristics**



**Solder reflow profile**



**Table 1 - Standard SnPb Solder (T<sub>C</sub>)**

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> ≥350
<2.5mm)	235 °C	220 °C
≥2.5mm	220 °C	220 °C

**Table 2 - Lead (Pb) Free Solder (T<sub>C</sub>)**

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> 350 - 2000	Volume mm <sup>3</sup> >2000
<1.6mm	260 °C	260 °C	260 °C
1.6 – 2.5mm	260 °C	250 °C	245 °C
>2.5mm	250 °C	245 °C	245 °C

**Reference JDEC J-STD-020**

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T <sub>smin</sub> )	100 °C	150 °C
• Temperature max. (T <sub>smax</sub> )	150 °C	200 °C
• Time (T <sub>smin</sub> to T <sub>smax</sub> ) (t <sub>s</sub> )	60-120 Seconds	60-120 Seconds
Average ramp up rate T <sub>smax</sub> to T <sub>p</sub>	3°C/ Second Max.	3 °C/ Second Max.
Liquidous temperature (T <sub>L</sub> )	183 °C	217 °C
Time at liquidous (t <sub>L</sub> )	60-150 Seconds	60-150 Seconds
Peak package body temperature (T <sub>p</sub> )*	Table 1	Table 2
Time (t <sub>p</sub> )** within 5 °C of the specified classification temperature (T <sub>C</sub> )	20 Seconds**	30 Seconds**
Average ramp-down rate (T <sub>p</sub> to T <sub>smax</sub> )	6 °C/ Second Max.	6 °C/ Second Max.
Time 25 °C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

\* Tolerance for peak profile temperature (T<sub>p</sub>) is defined as a supplier minimum and a user maximum.  
\*\* Tolerance for time at peak profile temperature (t<sub>p</sub>) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
**Electronics Division**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
www.eaton.com/electronics

© 2017 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10712 BU-MC17044  
September 2017



Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.