

Non-Magnetic Connectors

RADIALL
The next conneXion

CONTENTS

Pages

Introduction ..... 17-4 to 17-7

NON-MAGNETIC MCX

MMCX Plugs 17-8
Plugs ..... 17-8 to 17-9
Jacks 17-9
Receptacles 17-9

NON-MAGNETIC SMP

Plugs 17-10
Receptacles 17-10

NON-MAGNETIC SMB

Plugs 17-11
Jacks 17-11
Receptacles ..... 17-11 to 17-12

NON-MAGNETIC CABLE TERMINALS

Right angle terminal 17-12
Straight terminal 17-12

NON-MAGNETIC CABLE ASSEMBLIES

Non-magnetic cable assemblies 17-13

Panel drilling 17-13

Radiall . . . The Best Choice for Non-Magnetic Connectivity Solutions

We Know Your Market

We offer a range of non-magnetic RF connectors and cable assemblies for medical and space applications.

Why Radiall Is Your Best Choice



- Collaboration: We work closely with your engineers to understand your business, your technical needs, and your budgetary issues.
- High Performance, Competitively Priced Products: Our connectivity solutions give you the best combination of performance and value.
- Wide Product Range: We manage our product lines through the entire lifecycle, in order to offer you a wide selection of standard products at an affordable price.
- Global Presence: We're everywhere you need us, with worldwide sales, engineering support, R&D in North America, Europe, and Asia, and manufacturing facilities strategically located in the United States, Mexico, France, India, and China to provide on-demand cable assemblies.
- Responsive Support and Service: From the design stage, planning to post-installation support, we're with you at every step, whether you need sales support or engineering expertise.
- Warranty: We stand behind our products.

Certifications and Environmental

Radiall is ISO 9001:2008 certified and dedicated to continuous improvement programs that have resulted in also being AS9100, TS16949, and ISO 14001 certified. In addition, Radiall is committed to investing in its people, future technologies, and the environment, such as being RoHS (Restriction of Hazardous Substances) and REACH (Registration, Evaluation, Authorization and Restriction of Chemical Substances) compliant.

The Best Manufacturing and Process Technologies

Our dedication to innovation and continuous improvement in leading-edge products means we excel in the techniques to create them:

- High precision machining: metal stamping, milling, turning, and cutting
- Molding, polishing
- Laser, ultrasonic, and vapor soldering
- Plating and plastic metallization
- Automatic assembly
- Characterization
- Test and measurement
- Cable and PTFE wrapping
- Thin- and thick-film processes

NON-MAGNETIC CONNECTOR FAMILIES

Radiall offers a growing range of non-magnetic connectors for medical, space, and other applications that includes MMCX, MCX, SMP, and SMB interfaces. To guarantee an exceptional non-magnetism level and repeatability, each non-magnetic connector is manufactured through a strictly controlled production process according to our quality assurance procedures.

For space applications, such as satellites used for scientific exploration, we offer an extensive range of SMA products, fully ESA qualified, meeting the residual magnetism required by the ESCC 3402 generic specification and the ESCC 3402/001, 002, and 003 detail specifications. Connectors are made of beryllium copper, with gold plating and copper underplating.

NEW NON-MAGNETIC MCX SERIES

Radiall has expanded our range of non-magnetic connectors with the non-magnetic MCX series. These connectors meet the need for smaller interconnections in space-limited MRI equipment, such as those for head, shoulder, or foot. With more reliable connections through superior performance, the reinforced connection system eliminates the risk of perturbation in image quality.

The non-magnetic MCX family also includes a new full-detent cable version, which has been tested in high-vibration conditions, that eliminates intermittent connections. It complies with MIL-STD-202, Method 204, Condition D for vibration testing.

Non-magnetic MCX connectors are available in a wide range of configurations for:

- Board-to-board connections
- Cable-to-board connections
- Cable-to-cable connections

NON-MAGNETIC CABLE ASSEMBLIES





Radiall offers non-magnetic cable assemblies that provide a totally non-magnetic solution to reduce the risk of perturbation while working inside the B_0 magnetic field. Non-magnetic cables are available in RG/316, RG/178 flexible or .085" and .141" semi-rigid styles.

INTRODUCTION







CUSTOM PRODUCTS

We are continually developing new non-magnetic products, including high-density, multiposition configurations.

Multi-port connectors: We offer a wide variety of solutions for high-density coaxial contacts based on the standard SMP, Coaxipack 2, SMB and SMA ranges with additional multiple DC contacts. Our expertise and extensive knowledge in RF coaxial connector and cable assembly technology allows us to offer superior technical project support including those projects that need new coaxial connections developed. Multi-port connectors offer the advantage of having only one connector instead of several separate connectors to mate and unmate.

NON-MAGNETIC RF CONNECTORS FOR MEDICAL

Non-magnetic coaxial connectors are used primarily inside MRI and other medical imaging equipment. Magnetic resonance imaging produces high-resolution cross-sectional images of the inside of the human body by exploiting radio frequency (RF) pulses. MRI technology has seen tremendous improvements in recent years with continued advances in technology, a small part of which is due to coaxial non-magnetic connectors.



MRI medical equipment consists of a large magnet or electromagnet to create an intense and homogenous magnetic field (0.3 to 7 T) that surrounds the patient, “gradient coils” to position the area under analysis, and two high-frequency coils. One coil transmits RF pulses of 20 to 300 MHz to excite the atomic nucleus in the area under analysis. The other coil receives a signal that constitutes the image after excitation. The output is sent to a computer for processing and display.

The quality of the picture depends mainly on the homogeneity of the magnetic field and on the signal-to-noise ratio. To avoid any interference in the field homogeneity, coaxial connectors and cables located in the magnetic field to connect the coils should be transparent relative to the field, which means their relative permittivity μ_r should be equal to 1.

High-quality non-magnetic connectors have extremely low magnetic susceptibility so that they are not magnetized by the fields created in the equipment.

RADIALL NON-MAGNETIC CONNECTORS

Radiall connectors are specified for coils because they are manufactured with materials especially adapted to non-magnetism (with relative permittivity μr close to 1). Each rod of raw material is selected based on a direct measurement with a vibrant magnetometer, with the highest quality of surface plating such as BBR (Bright Bronze Radiall), GBR (Golden Bronze Radiall) or NPGR (gold plated over a non-magnetic nickel phosphorous).

Our non-magnetic connectors have a susceptibility of around 10^{-5}, as opposed to 10^{-2} for standard connectors made of brass/nickel materials. As a result, our non-magnetic connectors are transparent to the magnetic field, which means no field distortion, a higher SNR, and higher quality images.

Performance of Radiall non-magnetic RF connectors

Table of distortion comparison

	Distortion at 10 mm $\Delta H/H_{ext}$ with B_0=1.5 Tesla	Magnetic susceptibility χ
Radiall non-magnetic connector	$\leq 5.10^{-7}$	$\approx 10^{-5}$
Standard non-magnetic connector	$\approx 10^{-5}$	$\approx 10^{-3}$
Brass/nickel connector	$\approx 10^{-4}$	$\approx 10^{-2}$

The relative distortion of a magnetic field of 1.5 T, generated by Radiall non-magnetic connectors is only 5.10^{-7} maximum, at a distance of 10 mm from the surface of the connector. Furthermore, they meet the electrical and mechanical characteristics required for any reliable coaxial connector. In addition, these connectors are extremely durable for medical applications.

Manufacturing

Manufacturing a Radiall non-magnetic connector involves a special “clean room” environment where all precautions are taken to avoid any contact with ferromagnetic materials during the machining and cleaning process. Radiall follows strict manufacturing guidelines through a quality assurance plan whose documented rules are enforced throughout the production line. This quality assurance procedure guarantees the highest level of non-magnetism and repeatability for all Radiall non-magnetic connectors.

MMCX PLUG AND PCB RECEPTACLE

RIGHT-ANGLE PLUG CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Captive center contact	Body material	Finish
RG-178 Non-magnetic cable	2/50/S	R110 170 147	Yes	Non-magnetic bronze	BBR

STRAIGHT PCB RECEPTACLE



Part number	Captive center contact	Panel drilling	Body material
R110 426 107	Yes	P01	Non-magnetic bronze

MCX PLUG

STRAIGHT PLUG CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Dimensions (mm)			Note	Finish
			A	B	C		
RG-178	2/50/S	R113 081 097	16.1	2.55	1.1	—	BBR
RG-316	2.6/50/S	R113 082 097	16.1	2.95	1.65	—	
RG-316	2.6/50/S	R299 122 097	16.1	2.95	1.65	Full detent	

PRODUCT SPECIFICATION: please refer to the standard range

To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

RIGHT-ANGLE PLUG CRIMP TYPE FOR FLEXIBLE CABLE





Cable type	Cable group dia.	Part number	Dimensions (mm)				Note	Finish
			A	B	C	D		
RG-178	2/50/S	R113 181 097	8.6	11.9	2.55	1.1	—	BBR
RG-316	2.6/50/S	R113 182 097	8.6	11.9	2.95	1.65	—	
RG-316	2.6/50/S	R299 122 087	8.6	11.9	2.95	1.65	Full detent	

STRAIGHT JACK CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Finish
RG-316	2.6/50/S	R113 240 097	BBR

STRAIGHT PCB RECEPTACLE





Fig. 1



Fig. 2



Fig. 3

Part number	Figure	Dimensions (mm)			Panel drilling	Termination	Finish	Type
		A	B	C				
R113 426 097	1	10	4.1	0.98	P01	Solder legs	GBR	Female
R113 424 097	2	5.9	4.7	0.96	--	SMT		Female
R113 425 097	3	9.65	4.1	0.98	P01	Solder legs		Male

RIGHT-ANGLE PCB RECEPTACLE





Part number	Panel drilling	Termination style	Finish	Type
R113 665 097	P01	Solder legs	GBR	Female

PRODUCT SPECIFICATION: please refer to the standard range

To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

RADIALL
The next conneXion

SMP PLUG AND RECEPTACLE

RIGHT-ANGLE PLUG CRIMP TYPE FOR FLEXIBLE CABLE





Cable type	Cable group dia.	Part number	Captive center contact	Body material	Finish
RG-179 non-magnetic cable	2.6/50/S	R222 900 357	Yes	Non-magnetic bronze	BBR

STRAIGHT SMT RECEPTACLE



Part number	Retention	Captive center contact	Body material	Finish
R222 941 324	Limited detent	Yes	Non-magnetic bronze	Gold over copper

PRODUCT SPECIFICATION: please refer to the standard range

To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

STRAIGHT PLUG FULL CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Captive center contact	Body material	Finish
RG-179, RG-316 non-magnetic cable	2.6/50+75/S	R114 082 107	Yes	Non-magnetic bronze	BBR

RIGHT-ANGLE PLUG CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Captive center contact	Body material	Finish
RG-179, RG-316 non-magnetic cable	2.6/50+75/S	R114 186 197	Yes	Non-magnetic bronze	BBR

STRAIGHT BULKHEAD JACK CRIMP TYPE FOR FLEXIBLE CABLE



Cable type	Cable group dia.	Part number	Captive center contact	Panel drilling	Body material	Finish
RG-316 non-magnetic cable	2.6/50+75/S	R114 313 197	Yes	P02	Non-magnetic bronze	BBR

STRAIGHT MALE RECEPTACLE FOR PCB



PRODUCT SPECIFICATION: please refer to the standard range
To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

SMB RECEPTACLE

RIGHT-ANGLE RECEPTACLE FOR PCB, SOLDER LEGS





Part number	Captive center contact	Body material	Finish
R114 665 107	Yes	Non-magnetic bronze	GBR

CABLE TERMINALS

RIGHT-ANGLE TERMINAL SOLDER TYPE FOR FLEXIBLE CABLES



Cable group	Cable group dia.	Part number	Panel drilling	Body material	Finish
RG-174, RG-316, RD-316, RG-179, RD-179	2.6/50+75	R280 220 027	P05	Non-magnetic bronze	GBR

STRAIGHT TERMINAL SOLDER TYPE FOR SEMI-RIGID CABLES





Cable group	Cable group dia.	Part number	Panel drilling	Body material	Finish
RG-174, RG-316, RD-316, RG-179, RD-179	.047	R280 287 107	P06	Non-magnetic bronze	GBR

PRODUCT SPECIFICATION: please refer to the standard range

To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

NON-MAGNETIC CABLE ASSEMBLIES

Radiall also offers a standard range of non-magnetic cable assemblies fit to work within the B_0 magnetic field. The cables are not sold separately.

In order to meet our customer's specific project requirements, Radiall provides worldwide technical support.







Cable type	Cable group dia.	Part number
RG-178 non-magnetic	2/50/S	C291 140 087
RG-316 non-magnetic	2.6/50/S	C291 170 079
RG-400 non-magnetic	5/50/S	C291 324 079
.085" semi-rigid	.085	C291 851 001
.141" semi-rigid	.141	C291 861 061

PANEL DRILLING

P01



	mm	
	Maxi	mini
A	1.29	1.25
B	0.85	0.75
C	2.56	2.52

P02



	mm	
	Maxi	mini
A	5	4.9
B	4.58	4.46

P03



	mm	
	Maxi	mini
A	2.59	2.49
B	1.40	1.30
C	5.16	5.00

P04



	mm		inch	
	Maxi	mini	Maxi	mini
A	1.4	1.3	.055	.051
B	5.16	5.00	.203	.197

P05



	mm	
	Maxi	mini
B	1.5	1.4
C	5.13	5.03

P06



	mm		inch	
	Maxi	mini	Maxi	mini
A	1.1	1.05	.043	.041
B	1.1	1.05	.043	.041
C	5.16	5.00	.203	.197

PRODUCT SPECIFICATION: please refer to the standard range

To download data sheets and assembly instructions, visit **www.radiall.com** & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
See page 8 and 9 for packaging information.

NOTES

AEROSPACE AUTOMOTIVE DEFENSE INDUSTRIAL INSTRUMENTATION MEDICAL SPACE TELECOM

EUROPE

France - RADIALL S.A.
101, Rue Ph. Hoffmann
93116 ROSNY sous BOIS (Paris)
Tel.: +33 1 49 35 35 35 - Fax: +33 1 48 54 63 63
E-Mail: info@radiall.com

Finland - RADIALL SF
P.O. Box 202 - 90101 OULU
Tel.: +358 407 522 412
E-Mail: infofi@radiall.com

Germany - RADIALL GmbH
Carl-Zeiss Str. 10 Postfach 200143
D63307 - RÖDERMARK (Frankfurt)
Tel.: +49 60 74 91 07 0 - Fax: +49 60 74 91 07 70
E-Mail: infode@radiall.com

Italy - RADIALL Elettronica S.R.L.
Via Concordia, 5 - 20090 ASSAGO MILANO
Tel.: +39 02 48 85 121 - Fax: +39 02 48 84 30 18
E-Mail: infoit@radiall.com
Regional office: Roma

Netherlands - RADIALL B.V.
Hogebrinkerweg 15b - 3871 KM HOEVELAKEN
Tel.: +31 33 253 40 09 - Fax: +31 33 253 45 12
E-Mail: infonl@radiall.com

Sweden - RADIALL A.B.
Sjöängsvägen 2 - SE-192 72 SOLLENTUNA (Stockholm)
Tel.: +46 844 434 10 - Fax: +46 875 449 16
E-Mail: infose@radiall.com

U.K. - RADIALL Ltd.
Ground Floor, 6 The Grand Union Office Park,
Packet Boat Lane
UXBRIDGE Middlesex UB8 2GH (London)
Tel.: +44 1895 425 000 - Fax: +44 1895 425 010
E-Mail: infouk@radiall.com

NORTH AMERICA

USA - RADIALL USA, Inc.
8950 South 52nd Street, Suite
401, Tempe, Arizona 85284
Tel.: +1 480 682 9400 - Fax: +1 480 682 9403
E-Mail: infousa@radiall.com

ALSO REPRESENTED IN

Australia	Hungary	Poland
Austria	Indonesia	Russia
Belgium	Israel	Singapore
Brazil	Korea	Spain
Czech	Latvia	Switzerland
Republic	Lithuania	Taïwan
Denmark	Malaysia	Thailand
Estonia	Norway	Vietnam
Greece	Philippines	South Africa

For the above countries, please contact the local agent or RADIALL at info@radiall.com

ASIA

China - SHANGHAI RADIALL Electronic Co., Ltd.
N° 390 Yong He Road 200072 - SHANGHAI
Tel.: +86 21 66 52 37 88 - Fax: +86 21 66 52 11 77
E-Mail: infosh@radiall.com

Japan - NIHON RADIALL
Shibuya-ku Ebisu 1-5-2, Kougetsu Bldg 405
TOKYO 150-0013
Tel.: +81 3 3440 6241 - Fax: +81 3 3440 6242
E-Mail: infojp@radiall.com

Hong Kong - RADIALL Electronics Ltd.
Flat D, 6/F, Ford Glory Plaza,
37-39 Wing Hong Street
Cheung Sha Wan
KOWLOON HONG KONG
Tel: +852-2959-3833 - Fax: +852-2959-2636
E-Mail: infohk@radiall.com

India - RADIALL India Pvt. Ltd.
25 D, II Phase, Peenya Industrial Area
BANGALORE 560058
Tel.: +91 80 83 95 271 - Fax: +91 80 83 97 228
E-Mail: infoin@radiall.com

This information is intended as a guide only. To ensure a continuing policy of product improvement, Radiall reserves the right to modify its specifications without prior notification.

D1C004XE - 2012 January Edition

www.radiall.com

RADIALL
The next conneXion

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.