


Power MOSFET

| PRODUCT SUMMARY | |
|----------------------------|----------------------------------|
| V _{DS} (V) | 500 |
| R _{D(on)} (Ω) | V _{GS} = 10 V 0.40 |
| Q _g (Max.) (nC) | 64 |
| Q _{gs} (nC) | 16 |
| Q _{gd} (nC) | 26 |
| Configuration | Single |



FEATURES

- Low Gate Charge Q_g Results in Simple Drive Requirement
- Improved Gate, Avalanche and Dynamic dV/dt Ruggedness
- Fully Characterized Capacitance and Avalanche Voltage and Current
- Effective C_{oss} Specified
- Lead (Pb)-free Available



APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptable Power Supply
- High Speed Power Switching

TYPICAL SMPS TOPOLOGIES

- Two Transistor Forward
- Half Bridge, Full Bridge
- PFC Boost

ORDERING INFORMATION

| | |
|----------------|-----------------------------|
| Package | TO-247 |
| Lead (Pb)-free | IRFP450APbF SiHFP450A-E3 |
| SnPb | IRFP450A SiHFP450A |

ABSOLUTE MAXIMUM RATINGS T_C = 25 °C, unless otherwise noted

| PARAMETER | SYMBOL | LIMIT | UNIT |
|--------------------------------------------------|-----------------------------------|------------------|----------|
| Drain-Source Voltage | V _{DS} | 500 | V |
| Gate-Source Voltage | V _{GS} | ± 30 | |
| Continuous Drain Current | V _{GS} at 10 V | 14 | A |
| | | 8.7 | |
| Pulsed Drain Current ^a | I _{DM} | 56 | |
| Linear Derating Factor | | 1.5 | W/°C |
| Single Pulse Avalanche Energy ^b | E _{AS} | 760 | mJ |
| Repetitive Avalanche Current ^a | I _{AR} | 14 | A |
| Repetitive Avalanche Energy ^a | E _{AR} | 19 | mJ |
| Maximum Power Dissipation | P _D | 190 | W |
| Peak Diode Recovery dV/dt ^c | dV/dt | 4.1 | V/ns |
| Operating Junction and Storage Temperature Range | T _J , T _{stg} | - 55 to + 150 | °C |
| Soldering Recommendations (Peak Temperature) | for 10 s | 300 ^d | |
| Mounting Torque | 6-32 or M3 screw | 10 | lbf · in |
| | | 1.1 | N · m |

Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- Starting T_J = 25 °C, L = 7.8 mH, R_G = 25 Ω, I_{AS} = 14 A (see fig. 12).
- I_{SD} ≤ 14 A, dI/dt ≤ 130 A/μs, V_{DD} ≤ V_{DS}, T_J ≤ 150 °C.
- 1.6 mm from case.

* Pb containing terminations are not RoHS compliant, exemptions may apply

THERMAL RESISTANCE RATINGS





| PARAMETER | SYMBOL | TYP. | MAX. | UNIT |
|-------------------------------------|------------|------|------|-----------------------------|
| Maximum Junction-to-Ambient | R_{thJA} | - | 40 | $^{\circ}\text{C}/\text{W}$ |
| Case-to-Sink, Flat, Greased Surface | R_{thCS} | 0.24 | - | |
| Maximum Junction-to-Case (Drain) | R_{thJC} | - | 0.65 | |

SPECIFICATIONS $T_J = 25 \text{ }^{\circ}\text{C}$, unless otherwise noted

| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT | |
|------------------------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------|------|-----------|-----------------------------|--|
| Static | | | | | | | | |
| Drain-Source Breakdown Voltage | V_{DS} | $V_{GS} = 0 \text{ V}$ | $I_D = 250 \mu\text{A}$ | 500 | - | - | V | |
| V_{DS} Temperature Coefficient | $\Delta V_{DS}/T_J$ | Reference to $25 \text{ }^{\circ}\text{C}$, $I_D = 1 \text{ mA}$ | | - | 0.58 | - | $\text{V}/^{\circ}\text{C}$ | |
| Gate-Source Threshold Voltage | $V_{GS(\text{th})}$ | $V_{DS} = V_{GS}$, $I_D = 250 \mu\text{A}$ | | 2.0 | - | 4.0 | V | |
| Gate-Source Leakage | I_{GSS} | $V_{GS} = \pm 30 \text{ V}$ | | - | - | ± 100 | nA | |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = 500 \text{ V}$, $V_{GS} = 0 \text{ V}$ | | - | - | 25 | μA | |
| | | $V_{DS} = 400 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_J = 125 \text{ }^{\circ}\text{C}$ | | - | - | 250 | | |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS} = 10 \text{ V}$ | $I_D = 8.4 \text{ A}^b$ | - | - | 0.40 | Ω | |
| Forward Transconductance | g_{fs} | $V_{DS} = 50 \text{ V}$, $I_D = 8.4 \text{ A}^b$ | | 7.8 | - | - | S | |
| Dynamic | | | | | | | | |
| Input Capacitance | C_{iss} | $V_{GS} = 0 \text{ V}$, $V_{DS} = 25 \text{ V}$, $f = 1.0 \text{ MHz}$, see fig. 5 | | - | 2038 | - | pF | |
| Output Capacitance | C_{oss} | | | - | 307 | - | | |
| Reverse Transfer Capacitance | C_{rss} | | | - | 10 | - | | |
| Output Capacitance | C_{oss} | $V_{GS} = 0 \text{ V}$; $V_{DS} = 1.0 \text{ V}$, $f = 1.0 \text{ MHz}$ | | | 2859 | | nC | |
| Output Capacitance | C_{oss} | $V_{GS} = 0 \text{ V}$; $V_{DS} = 400 \text{ V}$, $f = 1.0 \text{ MHz}$ | | | 81 | | | |
| Effective Output Capacitance | $C_{oss \text{ eff.}}$ | $V_{GS} = 0 \text{ V}$; $V_{DS} = 0 \text{ V}$ to 400 V^c | | | 96 | | | |
| Total Gate Charge | Q_g | $V_{GS} = 10 \text{ V}$ | $I_D = 14 \text{ A}$, $V_{DS} = 400 \text{ V}$, see fig. 6 and 13 ^b | - | - | 64 | ns | |
| Gate-Source Charge | Q_{gs} | | | - | - | 16 | | |
| Gate-Drain Charge | Q_{gd} | | | - | - | 26 | | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{DD} = 250 \text{ V}$, $I_D = 14 \text{ A}$, $R_G = 6.2 \Omega$, $R_D = 17 \Omega$, see fig. 10 ^b | | - | 15 | - | ns | |
| Rise Time | t_r | | | - | 36 | - | | |
| Turn-Off Delay Time | $t_{d(off)}$ | | | - | 35 | - | | |
| Fall Time | t_f | | | - | 29 | - | | |
| Drain-Source Body Diode Characteristics | | | | | | | | |
| Continuous Source-Drain Diode Current | I_S | MOSFET symbol showing the integral reverse p - n junction diode | | - | - | 14 | A | |
| Pulsed Diode Forward Current ^a | I_{SM} | | | - | - | 56 | | |
| Body Diode Voltage | V_{SD} | $T_J = 25 \text{ }^{\circ}\text{C}$, $I_S = 14 \text{ A}$, $V_{GS} = 0 \text{ V}^b$ | | - | - | 1.4 | V | |
| Body Diode Reverse Recovery Time | t_{rr} | $T_J = 25 \text{ }^{\circ}\text{C}$, $I_F = 14 \text{ A}$, $dI/dt = 100 \text{ A}/\mu\text{s}^b$ | | - | 487 | 731 | ns | |
| Body Diode Reverse Recovery Charge | Q_{rr} | | | - | 3.9 | 5.8 | μC | |
| Forward Turn-On Time | t_{on} | Intrinsic turn-on time is negligible (turn-on is dominated by L_S and L_D) | | | | | | |

Notes

- a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- b. Pulse width $\leq 300 \mu\text{s}$; duty cycle $\leq 2 \%$.
- c. $C_{oss \text{ eff.}}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80 % V_{DS} .

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Fig. 1 - Typical Output Characteristics

Fig. 3 - Typical Transfer Characteristics

Fig. 2 - Typical Output Characteristics

Fig. 4 - Normalized On-Resistance vs. Temperature

IRFP450A, SiHFP450A

Vishay Siliconix




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage










Fig. 8 - Maximum Safe Operating Area


Fig. 9 - Maximum Drain Current vs. Case Temperature

Fig. 10a - Switching Time Test Circuit

Fig. 10b - Switching Time Waveforms

Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case

Fig. 12a - Unclamped Inductive Test Circuit

Fig. 12b - Unclamped Inductive Waveforms

IRFP450A, SiHFP450A

Vishay Siliconix




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 12d - Typical Drain-to-Source Voltage vs. Avalanche Current




Fig. 13a - Basic Gate Charge Waveform






Fig. 13b - Gate Charge Test Circuit

Peak Diode Recovery dV/dt Test Circuit




* $V_{GS} = 5\text{ V}$ for logic level devices

Fig. 14 - For N-Channel

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?91230>.

TO-247AC (High Voltage)



| | MILLIMETERS | | INCHES | |
|------|-------------|-------|--------|-------|
| DIM. | MIN. | MAX. | MIN. | MAX. |
| A | 4.58 | 5.31 | 0.180 | 0.209 |
| A1 | 2.21 | 2.59 | 0.087 | 0.102 |
| A2 | 1.17 | 2.49 | 0.046 | 0.098 |
| b | 0.99 | 1.40 | 0.039 | 0.055 |
| b1 | 0.99 | 1.35 | 0.039 | 0.053 |
| b2 | 1.53 | 2.39 | 0.060 | 0.094 |
| b3 | 1.65 | 2.37 | 0.065 | 0.093 |
| b4 | 2.42 | 3.43 | 0.095 | 0.135 |
| b5 | 2.59 | 3.38 | 0.102 | 0.133 |
| c | 0.38 | 0.86 | 0.015 | 0.034 |
| c1 | 0.38 | 0.76 | 0.015 | 0.030 |
| D | 19.71 | 20.82 | 0.776 | 0.820 |
| D1 | 13.08 | - | 0.515 | - |

ECN: X13-0045-Rev. C, 18-Mar-13
 DWG: 5971

| | MILLIMETERS | | INCHES | |
|------|-------------|-------|-----------|-------|
| DIM. | MIN. | MAX. | MIN. | MAX. |
| D2 | 0.51 | 1.30 | 0.020 | 0.051 |
| E | 15.29 | 15.87 | 0.602 | 0.625 |
| E1 | 13.72 | - | 0.540 | - |
| e | 5.46 BSC | | 0.215 BSC | |
| Ø k | 0.254 | | 0.010 | |
| L | 14.20 | 16.25 | 0.559 | 0.640 |
| L1 | 3.71 | 4.29 | 0.146 | 0.169 |
| N | 7.62 BSC | | 0.300 BSC | |
| Ø P | 3.51 | 3.66 | 0.138 | 0.144 |
| Ø P1 | - | 7.39 | - | 0.291 |
| Q | 5.31 | 5.69 | 0.209 | 0.224 |
| R | 4.52 | 5.49 | 0.178 | 0.216 |
| S | 5.51 BSC | | 0.217 BSC | |

Notes

- Dimensioning and tolerancing per ASME Y14.5M-1994.
- Contour of slot optional.
- Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outermost extremes of the plastic body.
- Thermal pad contour optional with dimensions D1 and E1.
- Lead finish uncontrolled in L1.
- Ø P to have a maximum draft angle of 1.5 to the top of the part with a maximum hole diameter of 3.91 mm (0.154").
- Outline conforms to JEDEC outline TO-247 with exception of dimension c.
- Xian and Mingxin actually photo.





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.