

3M™ Dual-Touch Chassis Displays

Sleek Industrial Design Made Simple

3M™ Dual-Touch Chassis Displays, available in 15-, 17- and 19-inch display sizes, are an ideal solution for kiosk applications that require the modern flat front surface design and dual touch gesture performance found in popular smart phone and tablet devices today. These displays, specifically designed for kiosk and enclosure integrations, feature a unique flat front surface-ready design to allow for easy integration and upgrading current kiosk designs. In addition, the chemically-strengthened glass and anti-glare treatment are an ideal combination to support heavy-use public applications while maintaining the kiosk's functional, optical and aesthetic characteristics.

Dual-touch projected capacitive technology enables applications and operating systems to create user experiences beyond traditional single touch interactions. The projected capacitive sensor allows the system to quickly and accurately track two simultaneous touches across the entire touch screen. The responsive, accurate, and easy-to-use dual-touch system enables program designers to migrate existing single touch applications to a gesture-based interface to create and deliver popular user interactions such as pan, zoom and rotate. As a plug-and-play device, application programmers will be able to leverage dual-touch capabilities built into Windows 7 and other popular programming languages.

3M Dual-Touch Chassis Displays, with chemically-strengthened glass, provides a durable, impact-resistant touch surface while the virtual bezel glass seals the display from dust and liquids (according to the IP54 standard). The flat front surface design also helps make the display easy to clean and maintain. The anti-glare treatment helps reduce reflections on the display and increases content readability. The chemically-strengthened glass and anti-glare treatment provide the durability and readability essential for unattended high traffic kiosks.



Recommended Multi-Touch Applications

- Self Service Kiosks
- Bill Pay Kiosks
- Point of Information (POI)
- Interactive Point of Purchase (iPOP)
- Retail Product Selector
- Industrial Automation
- Hospitality
- Security Systems

The Dual-Touch chassis display is available in common kiosk display sizes:

- 15" 3M Dual-Touch Display C1510PS
- 17" 3M Dual-Touch Display C1710PS
- 19" 3M Dual-Touch Display C1910PS

| Feature | Benefit |
|--|--|
| Flat front surface design with chemically-strengthened glass | <ul style="list-style-type: none">• Sophisticated bezel-free design enables contemporary flat front surface aesthetics• Designed to eliminate dust and debris build up at the edge and corners of the display making it easy to clean• Superior glass durability maintains functional performance over the life of the product |
| Dual-Touch Projected Capacitive | <ul style="list-style-type: none">• 2-finger dual-touch input capability enables smart phone and tablet-like gestures (pan, zoom, rotate)• Works with finger and thin glove• Unaffected by most surface contaminants |
| Versatile Product Design | <ul style="list-style-type: none">• Easy to integrate with multiple mounting options (brackets, VESA)• Anti-glare surface treatment to reduce reflections and maximize readability• Compatible with Windows 7 / Vista / XP, Linux and Mac |



3M™ Dual-Touch Chassis Displays Specifications

| DISPLAY DETAILS | 3M Dual-Touch Display C1510PS | 3M Dual-Touch Display C1710PS | 3M Dual-Touch Display C1910PS |
|------------------------------------|--|--|--|
| Diagonal Size | 15" | 17" | 19" |
| LCD Technology | Twisted Nematic (TN) | Twisted Nematic (TN) | Twisted Nematic (TN) |
| Backlight | CCFL | CCFL | CCFL |
| Control Type | OSD | OSD | OSD |
| Aspect Ratio | 4:3 | 5:4 | 5:4 |
| Display Colors | 16.2 Million | 16.7 Million | 16.7 Million |
| Pixel Pitch | 0.297 mm x 0.297 mm | 0.264 mm x 0.264 mm | 0.294 mm x 0.294 mm |
| Brightness with touchscreen (1) | 250 cd/m2 (nit) (typical) 225 cd/m2 (nit) | 250 cd/m2 (nit) (typical) 225 cd/m2 (nit) | 250 cd/m2 (nit) (typical) 225 cd/m2 (nit) |
| Contrast Ratio (2) | 500:1 typical | 1000:1 typical | 800:1 typical |
| Viewing Angle (Horiz./Vert.): | 140/125 degrees typical | 160/160 degrees typical | 170/160 degrees typical |
| Video Response Time (3) | 8 milliseconds (typical) | 5 milliseconds (typical) | 5 milliseconds (typical) |
| Native Resolution | 1024 x 768 (maximum) | 1280 x 1024 (maximum) | 1280 x 1024 (maximum) |
| VESA Pattern | 75mm x 75mm | 100mm x 100mm | 100mm x 100mm |
| Power Consumption | 22 watts (typical) | 25 watts (typical) | 25 watts (typical) |
| TOUCH DETAILS | | | |
| Number of Inputs | 2 inputs | 2 inputs | 2 inputs |
| Touch Point Speed | <12 ms | <12 ms | <12 ms |
| Input Type | Finger, Thin Glove | Finger, Thin Glove | Finger, Thin Glove |
| Touch Communication | USB | USB | USB |
| Operating System Support | Windows7/Vista/XP, Linux, Mac | Windows7/Vista/XP, Linux, Mac | Windows7/Vista/XP, Linux, Mac |
| PHYSICAL SPECIFICATIONS | | | |
| Operating Environment | 0 to +40 degrees C, Relative Humidity, non-condensing 80% | 0 to +40 degrees C, Relative Humidity, non-condensing 80% | 0 to +40 degrees C, Relative Humidity, non-condensing 80% |
| Storage Environment | -20 to +60 degrees C, Relative Humidity, non-condensing 90% | -20 to +60 degrees C, Relative Humidity, non-condensing 90% | -20 to +60 degrees C, Relative Humidity, non-condensing 90% |
| Video Input | VGA | VGA | VGA |
| Power Supply | External, 12 VDC Power Supply | External, 12 VDC Power Supply | External, 12 VDC Power Supply |
| Physical (WxHxD) | 355.93 x 280.93 x 52.1 mm 14.0 x 11.1 x 2.1 inches | 394.0 x 330.0 x 57.1 mm 15.5 x 13.0 x 2.2 inches | 432.9 x 360.3 x 58.4 mm 17.0 x 14.2 x 2.3 inches |
| Display Area (WxH) | 304.1 x 228.1 mm (viewing area) 12.0 x 9.0 inches | 337.9 x 270.3 mm (viewing area) 13.3 x 10.6 inches | 376.3 x 301.1 mm (viewing area) 14.8 x 11.9 inches |
| Packaging (WxHxD) | 435 x 355 x 165 mm 17.1 x 14.0 x 6.5 inches | 480 x 415 x 160 mm 18.9 x 16.3 x 6.3 inches | 460 x 525 x 165 mm 18.1 x 20.7 x 6.5 inches |
| Packaging/Display Weight | 3.3 Kg / 7.3 lbs | 4.8 Kg / 10.6 lbs | 5.8 Kg / 12.8 lbs |
| Display Weight | 5.5 Kg / 12.1 lbs | 7.0 Kg / 15.4 lbs | 8.2 Kg / 18.1 lbs |
| RoHS Compliant | Yes | Yes | Yes |
| Agency Approvals | FCC-B, CE, UL | FCC-B, CE, UL | FCC-B, CE, UL |
| Warranty | 1 year | 1 year | 1 year |
| Part Number | 98-0003-4096-2 | 98-0003-4097-0 | 98-0003-4098-8 |

(1) Brightness measured on a display with Projected Capacitive sensor

(2) Measured at a contrast

(3) Gray to Gray

3M Touch Systems
Subsidiary of 3M Company
501 Griffin Brook Park Drive
Methuen, MA 01844 U.S.A.
1-888-659-1080
www.3M.com/touch

RoHS Directive compliant: In accordance with European Directive 2002/95/EC, "RoHS Directive compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M. (9/06)

IMPORTANT NOTICE TO PURCHASER: Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. 3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. 3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.