

Chip Inductors - 0302CS (0805)



- 0302 size – 20% smaller than our 0402CS inductors
- 35 inductance values from 0.67 to 34 nH
- High Q values – up to 131 at 2.4 GHz!

Request free evaluation samples by contacting Coilcraft or visiting www.coilcraft.com.

| Part number ¹ | Inductance ² (nH) | Percent tolerance | 900 MHz | | 1.7 GHz | | 2.4 GHz | | SRF typ ⁴ (GHz) | DCR max ⁵ (Ohms) | Irms ⁶ (mA) |
|--------------------------|---------------------------------|----------------------|---------|--------------------|---------|--------------------|---------|--------------------|----------------------------------|-----------------------------------|---------------------------|
| | | | L typ | Q typ ³ | L typ | Q typ ³ | L typ | Q typ ³ | | | |
| 0302CS-N67XKL_ | 0.67 | 10 | 0.66 | 42 | 0.66 | 56 | 0.67 | 70 | >26 | 0.021 | 1600 |
| 0302CS-1N7XJL_ | 1.7 | 5 | 1.7 | 57 | 1.7 | 78 | 1.7 | 95 | 16.14 | 0.038 | 1140 |
| 0302CS-1N9XJL_ | 1.9 | 5 | 1.9 | 42 | 1.9 | 65 | 1.9 | 83 | 16.06 | 0.065 | 910 |
| 0302CS-2N1XJL_ | 2.1 | 5 | 2.1 | 38 | 2.1 | 57 | 2.1 | 72 | 15.94 | 0.082 | 830 |
| 0302CS-3N0XJL_ | 3.0 | 5 | 3.0 | 56 | 3.0 | 92 | 3.0 | 131 | 15.10 | 0.060 | 950 |
| 0302CS-3N3XJL_ | 3.3 | 5 | 3.3 | 56 | 3.3 | 88 | 3.3 | 129 | 11.50 | 0.060 | 950 |
| 0302CS-3N5XJL_ | 3.5 | 5 | 3.5 | 60 | 3.5 | 84 | 3.5 | 110 | 11.53 | 0.070 | 870 |
| 0302CS-3N8XJL_ | 3.8 | 5 | 3.8 | 60 | 3.8 | 89 | 3.8 | 105 | 10.67 | 0.090 | 830 |
| 0302CS-4N0XJL_ | 4.0 | 5 | 4.0 | 52 | 4.0 | 80 | 4.1 | 98 | 11.21 | 0.100 | 760 |
| 0302CS-4N7XJL_ | 4.7 | 5 | 4.6 | 55 | 4.6 | 88 | 4.7 | 120 | 12.07 | 0.074 | 830 |
| 0302CS-5N1XJL_ | 5.1 | 5 | 5.1 | 62 | 5.1 | 92 | 5.2 | 118 | 9.65 | 0.074 | 830 |
| 0302CS-5N6XJL_ | 5.6 | 5 | 5.5 | 50 | 5.5 | 71 | 5.6 | 108 | 6.40 | 0.120 | 730 |
| 0302CS-6N0XJL_ | 6.0 | 5 | 6.0 | 58 | 6.0 | 82 | 6.2 | 105 | 8.60 | 0.140 | 700 |
| 0302CS-6N3XJL_ | 6.3 | 5 | 6.3 | 56 | 6.3 | 80 | 6.5 | 100 | 9.34 | 0.155 | 620 |
| 0302CS-6N5XJL_ | 6.5 | 5 | 6.5 | 56 | 6.5 | 80 | 6.8 | 100 | 8.19 | 0.200 | 620 |
| 0302CS-7N0XJL_ | 7.0 | 5 | 7.0 | 62 | 7.1 | 84 | 7.2 | 112 | 8.50 | 0.103 | 760 |
| 0302CS-7N2XJL_ | 7.2 | 5 | 7.2 | 60 | 7.2 | 82 | 7.4 | 110 | 9.12 | 0.112 | 690 |
| 0302CS-7N4XJL_ | 7.4 | 5 | 7.3 | 60 | 7.4 | 82 | 7.6 | 110 | 7.98 | 0.112 | 690 |
| 0302CS-8N3XJL_ | 8.3 | 5 | 8.2 | 58 | 8.3 | 80 | 8.5 | 104 | 8.19 | 0.150 | 590 |
| 0302CS-9N2XJL_ | 9.2 | 5 | 8.9 | 58 | 9.0 | 83 | 9.2 | 120 | 7.92 | 0.115 | 690 |
| 0302CS-10NXJL_ | 10.0 | 5 | 10.0 | 58 | 10.1 | 91 | 10.2 | 119 | 7.45 | 0.140 | 620 |
| 0302CS-11NXJL_ | 11.0 | 5 | 11.0 | 57 | 11.2 | 83 | 11.6 | 105 | 6.85 | 0.210 | 590 |
| 0302CS-12NXJL_ | 12.0 | 5 | 12.0 | 59 | 12.6 | 88 | 12.7 | 110 | 6.86 | 0.170 | 560 |
| 0302CS-13NXJL_ | 13.0 | 5 | 13.0 | 53 | 13.3 | 83 | 13.8 | 104 | 6.94 | 0.230 | 480 |
| 0302CS-15NXJL_ | 15.0 | 5 | 15.0 | 55 | 15.4 | 84 | 15.9 | 106 | 6.20 | 0.174 | 560 |
| 0302CS-16NXJL_ | 16.0 | 5 | 16.0 | 54 | 16.4 | 85 | 17.0 | 102 | 6.13 | 0.210 | 480 |
| 0302CS-17NXJL_ | 17.0 | 5 | 16.9 | 52 | 17.4 | 82 | 18.2 | 118 | 6.26 | 0.280 | 440 |
| 0302CS-18NXJL_ | 18.0 | 5 | 17.9 | 55 | 18.5 | 80 | 19.3 | 111 | 6.03 | 0.350 | 390 |
| 0302CS-19NXJL_ | 19.0 | 5 | 18.9 | 53 | 19.6 | 85 | 20.5 | 104 | 5.79 | 0.260 | 480 |
| 0302CS-20NXJL_ | 20.0 | 5 | 19.9 | 56 | 20.2 | 88 | 20.8 | 112 | 5.68 | 0.300 | 430 |
| 0302CS-21NXJL_ | 21.0 | 5 | 20.9 | 53 | 22.0 | 82 | 24.1 | 95 | 5.16 | 0.370 | 370 |
| 0302CS-22NXJL_ | 22.0 | 5 | 22.0 | 52 | 23.1 | 79 | 25.2 | 94 | 4.95 | 0.420 | 340 |
| 0302CS-23NXJL_ | 23.5 | 5 | 23.5 | 54 | 24.6 | 84 | 27.4 | 92 | 5.18 | 0.400 | 430 |
| 0302CS-29NXJL_ | 29.0 | 5 | 29.0 | 51 | 30.5 | 75 | 33.0 | 90 | 4.83 | 0.470 | 330 |
| 0302CS-34NXJL_ | 34.0 | 5 | 34.0 | 55 | 35.5 | 78 | 38.1 | 94 | 4.45 | 0.530 | 310 |

1. When ordering, please specify **termination** and **packaging** codes:

0302CS-34NXJLW

- Termination:** L = RoHS compliant silver-platinum-glass frit.
E = Halogen free component. RoHS compliant silver-platinum-glass frit terminations.
- Packaging:** W = 7" machine-ready reel. EIA-481 punched paper tape (2000 parts per full reel).
U = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter W instead.

- Inductance measured at 250 MHz using a Coilcraft SMD-F fixture in an Agilent/HP 4286 impedance analyzer with Coilcraft-provided correlation pieces.
 - Q measured using an Agilent/HP 4287A with an Agilent/HP 16193 test fixture.
 - SRF measured using an Agilent/HP 8722ES network analyzer and a test fixture with a 0.017" air gap.
 - DCR measured on a micro-ohmmeter and a Coilcraft CCF858 test fixture.
 - Current that causes a 30°C temperature rise from 25°C ambient.
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 302-1 Revised 11/01/12

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

COILCRAFT ACCURATE
PRECISION REPEATABLE
 MEASUREMENTS
 SEE WEB SITE **TEST FIXTURES**



0302CS Series (0805)

Typical L vs Frequency



S-Parameter files
ON OUR WEB SITE
SPICE models
ON OUR WEB SITE

Typical Q vs Frequency



Irms Derating



Designer's Kit C370 contains 20 each of all values

Core material Ceramic

Environmental RoHS compliant, halogen free optional

Terminations RoHS compliant silver-platinum-glass frit.

Weight 0.4 – 0.5 mg

Ambient temperature -40°C to +125°C with Irms current, +125°C to +155°C with derated current

Storage temperature Component: -40°C to +155°C. Tape and reel packaging: -40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Temperature Coefficient of Inductance (TCL) +25 to +125 ppm/°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

One per billion hours / one billion hours, calculated per Telcordia SR-332

Packaging 2000 per 7" reel. Paper tape: 8 mm wide, 0.5 mm thick, 2 mm pocket spacing

PCB washing Tested with pure water or alcohol only. For other solvents, see Doc787_PCB_Washing.pdf.



| Amax | Bmax | Cmax | D | E | F | G | H |
|-------|-------|-------|-------|-------|-------|-------|--------------|
| 0.034 | 0.021 | 0.018 | 0.006 | 0.015 | 0.010 | 0.014 | 0.021 inches |
| 0,86 | 0,53 | 0,45 | 0,20 | 0,38 | 0,25 | 0,36 | 0,53 mm |



US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 302-2 Revised 11/01/12
 © Coilcraft Inc. 2013
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.