# Amphenol Pcd Relay Sockets
MIL-PRF-12883



## Amphenol Pcd MIL-PRF-12883 Relay Sockets

Amphenol Pcd offers the industry's broadest line of pluggable relay sockets for commercial and miltary airborne, ground and shipboard equipment. Sockets are to MIL-PRF-12883 specifications, plus specialized requirements, and are supplied in a broad range of miltary standard and special configurations and styles for 2 through 25 amp operations.

Amphenol Pcd relay Sockets feature state of the art ultrasonically bonded interfaces between the dielectric components, which eliminate air paths and provide protection against moisture and degradation.



**Low Profile Relay Sockets**



**Extended Height Relay Sockets**

**Microminiature Relay Sockets**

**Board Mount Relay Sockets**

**Track Mount Relay Sockets**



**Solder Terminaiton Relay Sockets**

## Key Features and Benefits

### Socket Selection

Reference tanles of QPL listings on Page 5, relays utilized with specific sockets on pages 6-7 and socket recomendations for military and commercial relays on pages 8-9 will assist in and simplify socket selection.

### Socket Variations

**Low Profile**

Low Profile Relay Sockets are provided in all military configurations, are configured to a minimum size and weight, and accept the MIL-C-39029/92 contact family.

**Extended Height**

Extended Height Sockets are configured to accept the longer MIL-C-39029/5 contact - which is standard on many cylindrical connectors and other avionic interconnect systems - and allow contact standardization.

**Mounting Hardware**

Sockets are available with either fixed or loose mounting studs. Studs and hardware supplied with standard Ampehnol Pcd QPL-listed sockets are cold rolled steel. Stainless steel is available as an alternate. To specify stainless steel, an "S" is added to both the QPL number and the Amphenol Pcd catalog number.

**Mounting Style**

Relay sockets can be top or bottom mounted. See appropriate catalog pages for mounting instructions.

**Polarization**

Relay-to-socket positive polarization is provided by specific contact configurations and/or polarizing pins, in accordance with MIL-Spec requirements.

**Contact**

Closed entry socket contacts qualified to MIL-C-39029 are utilized and supplied with Amphenol Pcd Relay Sockets. Note: Relay Socket catalog numbers include the appropriate number of contacts as defined in the applicable military specification.

# Military Qualified, QPL Listed
## Relay Socket Part Numbers

| Military Socket P/N | PCD Socket P/N | Page |
|---|---|---|
| M12883/40-01 | RSL116079 | 10 |
| M12883/40-02 | RSL116081 | 10 |
| M12883/40-03 | RSL116083 | 10 |
| M12883/40-04 | RSL116085 | 10 |
| M12883/40-05 | RSL116087 | 10 |
| M12883/40-06 | RSL116089 | 10 |
| M12883/40-07 | RSL116051 | 10 |
| M12883/40-08 | RSL116053 | 10 |
| M12883/40-09 | RSL116055 | 10 |
| M12883/40-10 | RSL116057 | 10 |
| M12883/40-11 | RSL116059 | 10 |
| M12883/40-12 | RSL116061 | 10 |
| M12883/40-13 | RSE116661 | 11 |
| M12883/40-14 | RSE116663 | 11 |
| M12883/40-15 | RSE116665 | 11 |
| M12883/40-16 | RSE116667 | 11 |
| M12883/40-17 | RSE116669 | 11 |
| M12883/40-18 | RSE116671 | 11 |
| M12883/40-19 | RSE116673 | 11 |
| M12883/40-20 | RSE116675 | 11 |
| M12883/40-21 | RSE116677 | 11 |
| M12883/40-22 | RSE116679 | 11 |
| M12883/40-23 | RSE116681 | 11 |
| M12883/40-24 | RSE116683 | 11 |
| M12883/41-01 | RSL116091 | 12 |
| M12883/41-02 | RSL116093 | 12 |
| M12883/41-03 | RSL116095 | 12 |
| M12883/41-04 | RSL116097 | 12 |
| M12883/41-05 | RSL116099 | 12 |
| M12883/41-06 | RSL116063 | 12 |
| M12883/41-07 | RSL116065 | 12 |
| M12883/41-08 | RSL116067 | 12 |
| M12883/41-09 | RSL116069 | 12 |
| M12883/41-10 | RSL116071 | 12 |
| M12883/41-11 | RSE116685 | 13 |
| M12883/41-12 | RSE116687 | 13 |
| M12883/41-13 | RSE116689 | 13 |
| M12883/41-14 | RSE116691 | 13 |
| M12883/41-15 | RSE116693 | 13 |
| M12883/41-16 | RSE116695 | 13 |
| M12883/41-17 | RSE116697 | 13 |
| M12883/41-18 | RSE116699 | 13 |
| M12883/41-19 | RSE116701 | 13 |

| Military Socket P/N | PCD Socket P/N | Page |
|---|---|---|
| M12883/41-20 | RSE116703 | 13 |
| M12883/44-01 | RSE120151 | 14 |
| M12883/44-02 | RSE120153 | 14 |
| M12883/44-03 | RSE120155 | 14 |
| M12883/44-04 | RSE120157 | 14 |
| M12883/45-01 | RSE120159 | 15 |
| M12883/45-02 | RSE120161 | 15 |
| M12883/45-03 | RSE120163 | 15 |
| M12883/45-04 | RSE120165 | 16 |
| M12883/45-05 | RSE120167 | 16 |
| M12883/45-06 | RSE120169 | 16 |
| M12883/46-01 | RSE116747 | 17 |
| M12883/46-02 | RSE116749 | 17 |
| M12883/46-03 | RSE116751 | 17 |
| M12883/46-04 | RSE116753 | 17 |
| M12883/47-01 | RSE116755 | 18 |
| M12883/47-02 | RSE116757 | 18 |
| M12883/47-04 | RSE116761 | 18 |
| M12883/47-05 | RSE116763 | 18 |
| M12883/47-07 | RSL116101 | 18 |
| M12883/47-08 | RSL116103 | 18 |
| M12883/47-10 | RSL116073 | 18 |
| M12883/47-11 | RSL116075 | 18 |
| M12883/48-01 | RSE112061 | 19 |
| M12883/48-02 | RSE112063 | 19 |
| M12883/48-03 | RSL112105 | 19 |
| M12883/48-04 | RSL112101 | 19 |
| M12883/48-05 | RSE112065 | 19 |
| M12883/48-06 | RSE112067 | 19 |
| M12883/48-07 | RSL112107 | 19 |
| M12883/48-08 | RSL112103 | 19 |
| M12883/52-001 | RSE116175 | 20 |
| M12883/52-002 | RSE116185 | 20 |
| M12883/52-003 | RSE116195 | 20 |
| M12883/53-001 | RST145005 | 20 |
| M12883/54-01 | RSE116627 | 21 |
| M12883/54-02 | RSE116631 | 21 |
| M12883/54-03 | RSE116629 | 21 |
| M12883/54-04 | RSE116635 | 21 |
| M12883/55-01 | RSE112035 | 22 |
| M12883/55-02 | RSE112036 | 22 |
| M12883/55-03 | RSE112044 | 22 |

**Stainless Steel Hardware**
To specify Relay Sockets with Stainless Steel hardware, the suffix “S” is added to both the military and Aphenol Pcd part Numbers. For example, M12883/40-01 becomes M12883/40-01S, and the Amphenol Pcd equivalent RSL116079 becomes RSL116079-S.

Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

# Relay Socket Cross Reference Chart

## Relay to Relay Socket

| Military Relay Part Number | Military Socket Part Number | APCD Socket Part Number | Relay Type | Page |
|---|---|---|---|---|
| M83536/15-002<br>M83536/16-006, -014, -031, -034<br>M83726/1, /2, /3, /4, /28, /29, /30, /31*<br>MS27709-2 | M12883/40-01<br>M12883/40-05<br>M12883/40-07<br>M12883/40-11<br>M12883/40-13<br>M12883/40-17<br>M12883/40-19<br>M12883/40-23 | RSL116079<br>RSL116087<br>RSL116051<br>RSL116059<br>RSE116661<br>RSE116669<br>RSE116673<br>RSE116681 | 4 Pole / 10 Amp | 10-11 |
| M83536/17-002, 17-005 | M12883/40-02<br>M12883/40-08<br>M12883/40-14<br>M12883/40-20 | RSL116081<br>RSL116053<br>RSE116663<br>RSE116675 | 4 Pole / 10 Amp | 10-11 |
| M83536/18-002, -005, -008, -012<br>M83536/19-002, -005, -008, -012<br>M83536/20-002 | M12883/40-06<br>M12883/40-12<br>M12883/40-18<br>M12883/40-24 | RSL116089<br>RSL116061<br>RSL116671<br>RSE116683 | 4 Pole / 10 Amp | 10-11 |
| M83536/21-006, -014, -022, -030<br>M83536/22-006, -014, -022, -031 | M12883/46-01 | RSE116747 | 3 Pole / 10 Amp | 17 |
| M83536/25-002<br>M83536/26-002 | M12883/47-01<br>M12883/47-04<br>M12883/47-07<br>M12883/47-10 | RSE116755<br>RSE116761<br>RSL116101<br>RSL116073 | 6 Pole / 10 Amp | 18 |
| M6106/27-002 | M12883/47-02<br>M12883/47-05<br>M12883/47-08<br>M12883/47-11 | RSE116757<br>RSE116763<br>RSL116103<br>RSL116075 | 6 Pole / 10 Amp | 18 |
| MS27742-2 | M12883/54-04 | RSE116635 | 3 Pole / 25 Amp | 21 |
| MS27743-06, -12, -18, -24 | M12883/48-01<br>M12883/48-02<br>M12883/48-03<br>M12883/48-04 | RSE112061<br>RSE112063<br>RSL112105<br>RSL112101 | 3 Pole / 25 Amp | 19 |
| MS27743-09, -15, -21, -27 | M12883/48-05<br>M12883/48-06<br>M12883/48-07<br>M12883/48-08 | RSE112065<br>RSE112067<br>RSL112107<br>RSL112103 | 3 Pole / 25 Amp | 19 |
| Leach Corp. JA-D4E & J | M12883/41-03<br>M12883/41-08<br>M12883/41-13<br>M12883/41-18 | RSL116095<br>RSL116067<br>RSE116689<br>RSE116699 | 2 Pole / 10 Amp | 12-13 |
| Leach Corp. KA-D4E & J | M12883/40-04<br>M12883/40-10<br>M12883/40-16<br>M12883/40-22 | RSL116085<br>RSL116057<br>RSE116667<br>RSE116679 | 4 Pole / 10 Amp | 10-11 |

* *Applies to all plug-in dash numbered relays of these documents*

# Relay Socket Cross Reference Chart

## Relay to Relay Socket

| Military Relay Part Number | Military Socket Part Number | APCD Socket Part Number | Relay Type | Page |
|---|---|---|---|---|
| M6106/12-002 | M12883/54-03 | RSE116629 | 3 Pole / 25 Amp | 21 |
| M6106/13-002,-008,-011,-013,-015 | M12883/54-01 | RSE116627 | 3 Pole / 25 Amp | 21 |
| M6106/13-004 | M12883/54-02 | RSE116631 | 3 Pole / 25 Amp | 21 |
| M6106/19-004,-007,-012,-017,-022 | M12883/55-01, M12883/55-02 | RSE112035, RSE112036 | 1 Pole / 25 Amp | 22 |
| M6106/20-002 | M12883/55-03 | RSE112044 | 1 Pole / 25 Amp | 22 |
| M6106/38-002 | M12883/45-04 | RSE120165 | 2 Pole / 5 Amp | 15-16 |
| M6106/40-002 | M12883/46-02 | RSE116749 | 3 Pole / 5 Amp | 17 |
| M83536/1-006,-015,-024,-033<br>M83536/2-006,-015,-024,-035 | M12883/45-01 | RSE120159 | 2 Pole / 5 Amp | 15-16 |
| M83536/2-028, M83726/24, /25 | M12883/52-001 | RSE116175 | Track Mount<br>2 Pole / 5 Amp | 20 |
| M83536/5-006,-014, -022, -030<br>M83536/6-006, -015, -022, -032 | M12883/44-01 | RSE120151 | 4 Pole / 5 Amp | 14 |
| M83536/6-025 | M12883/52-002 | RSE116185 | Track Mount<br>4 Pole / 5 Amp | 20 |
| M83536/7-022 | M12883/44-02 | RSE120153 | 4 Pole / 5 Amp | 14 |
| M83536/9, -006, -015, -024, -035<br>M83536/10-006,-015,-024,<br>-034,-038 | M12883/41-01<br>M12883/41-04<br>M12883/41-06<br>M12883/41-09<br>M12883/41-11<br>M12883/41-14<br>M12883/41-16<br>M12883/41-19 | RSL116091<br>RSL116097<br>RSL116063<br>RSL116069<br>RSE116685<br>RSE116691<br>RSE116695<br>RSE116701 | 2 Pole / 10 Amp | 12-13 |
| M83536/11-002, 004, 007 | M12883/41-02<br>M12883/41-07<br>M12883/41-12<br>M12883/41-17 | RSL116093<br>RSL116065<br>RSE116687<br>RSE116697 | 2 Pole / 10 Amp | 12-13 |
| M83536/13-002, 005, 008, 012<br>M83536/14-002 | M12883/41-05<br>M12883/41-10<br>M12883/41-15<br>M12883/41-20 | RSL116099<br>RSL116071<br>RSE116693<br>RSE116703 | 2 Pole / 10 Amp | 12-13 |

* *Applies to all plug-in dash numbered relays of these documents*

## Relay Sockets

**Mates with M83536, M6106, M27709, M83726 Relays**

# MIL-PRF-12883/40
# Extended Height RSL 4 Pole/10 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Stainless Steel, Hard Gold Plated in
Accordance with SAE-AMS-2422

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Extended Height | .132 | 60 |

## Recommended Mounting Panel Cutout




## Extended Height Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact Config. P/N | | Mating Relay |
|---|---|---|---|---|---|---|---|
| /40-01 | RSL116079 | Loose | 14 | 16/16 | /5-116 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,30,31*, M27709-02 |
| /40-02 | RSL116081 | Loose | 14 | 16/16 | /5-116 | B | M83536/17-002,-005 |
| /40-03 | RSL116083 | Loose | 14 | 16/16 | /5-116 | C | |
| /40-04 | RSL116085 | Loose | 14 | 16/16 | /5-116 | D | Leach Corp KA-D4E & J |
| /40-05 | RSL116087 | Loose | 14 | 16/20 | /5-117 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,31,31, N27709-02 |
| /40-06 | RSL116089 | Loose | 16 | 16/16 | /5-116 | E | M83536/18-002,005,008,012 M83536/19-002,008,012, M83536/20-002 |
| /40-07 | RSL116051 | Fixed | 14 | 16/16 | /5-116 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,31,31, N27709-02 |
| /40-08 | RSL116053 | Fixed | 14 | 16/16 | /5-116 | B | M83536/17-002,-005 |
| /40-09 | RSL116055 | Fixed | 14 | 16/16 | /5-116 | C | |
| /40-10 | RSL116057 | Fixed | 14 | 16/16 | /5-116 | D | Leach Corp KA-D4E & J |
| /40-11 | RSL116059 | Fixed | 14 | 16/20 | /5-117 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,31,31, N27709-02 |
| /40-12 | RSL116061 | Fixed | 16 | 16/16 | /5-116 | E | M83536/18-002,-005,-008,-012 M83536/19-002,-008,-012, M83536/20-002 |

[1] *Mating End / Wire Barrel*
* *Applies to all plug-in type relays of these documents*

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Side View




### Top View



# MIL-PRF-12883/40
## Low Profile RSE 4 Pole/10 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Stainless Steel, Hard Gold Plated in
Accordance with SAE-AMS-2422

### Relay Sockets

**Mates with M83536, M6106, M27709, M83726 Relays**

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /40-13 | RSE116661 | Loose | 14 | 16/16 | /92-533 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,30,31*, M27709-02 |
| /40-14 | RSE116663 | Loose | 14 | 16/16 | /92-533 | B | M83536/17-002, 005 |
| /40-15 | RSE116665 | Loose | 14 | 16/16 | /92-533 | C | |
| /40-16 | RSE116667 | Loose | 14 | 16/16 | /92-533 | D | Leach Corp KA-D4E & J |
| /40-17 | RSE116669 | Loose | 14 | 16/20 | /92-594 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,30,31*, M27709-02 |
| /40-18 | RSE116671 | Loose | 16 | 16/16 | /92-533 | E | M83836/18-002,-005,-012 M83536/19-002,-005,-008,-012, M83536/20-002 |
| /40-19 | RSE116673 | Fixed | 14 | 16/16 | /92-533 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,30,31*, M27709-02 |
| /40-20 | RSE116675 | Fixed | 14 | 16/16 | /92-533 | B | M83536/17-002, 005 |
| /40-21 | RSE116677 | Fixed | 14 | 16/16 | /92-533 | C | |
| /40-22 | RSE116679 | Fixed | 14 | 16/16 | /92-533 | D | Leach Corp KA-D4E & J |
| /40-23 | RSE116681 | Fixed | 14 | 16/20 | /92-534 | A | M83536/15-022, M83536/16-006,-014,-031,-034 M83726/1,2,3,4,28,29,30,31*, M27709-02 |
| /40-24 | RSE116683 | Fixed | 16 | 16/16 | /92-533 | E | M83836/18-002,-005,-012 M83536/19-002,-005,-008,-012, M83536/20-002 |

[1] *Mating End / Wire Barrel*
**Applies to all plug-in type relays of these documents*

*Mounting instructions can be found on page 26*

### Socket Configurations



### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .100 | 45 |

### Recommended Mounting Panel Cutout



### Relay Socket Dimensions

#### Side View



#### Top View



Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

# MIL-PRF-12883/41
# Extended Height RSL 2 Pole/10 Amp

## Relay Sockets

**Mates with M83536, M6106 Relays**

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Stainless Steel, Hard Gold Plated in
Accordance with SAE-AMS-2422

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Extended Height | .073 | 33 |

## Recommended Mounting Panel Cutout




## Extended Height Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size* | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /41-01 | RSL116091 | Loose | 8 | 16/16 | /5-116 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /41-02 | RSL116093 | Loose | 8 | 16/16 | /5-116 | B | M83536/11-002, 004, 007 |
| /41-03 | RSL116095 | Loose | 8 | 16/16 | /5-116 | A | Leach Corp JA-D4E & J |
| /41-04 | RSL116097 | Loose | 8 | 16/20 | /5-117 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /41-06 | RSL116063 | Fixed | 8 | 16/16 | /5-116 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /41-07 | RSL116065 | Fixed | 8 | 16/16 | /5-116 | B | M83536/11-002, 004, 007 |
| /41-08 | RSL116067 | Fixed | 8 | 16/16 | /5-116 | A | Leach Corp JA-D4E & J |
| /41-09 | RSL116069 | Fixed | 8 | 16/20 | /5-117 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /41-05 | RSL116099 | Loose | 8 | 16/16 | /5-116 | D | M83536/13-002,-005,-008,-012 |
| | | | 2 | 22/22 | /101-553 | | M83536/13-002,-005,-008,-012 |
| /41-10 | RSL116071 | Fixed | 8 | 16/16 | /5-116 | D | M83536/13-002,-005,-008,-012 |
| | | | 2 | 22/22 | /101-553 | | M83536/13-002,-005,-008,-012 |

*Mating End / Wire Barrel

*Mounting instructions can be found on page 25*

## Relay Socket Dimensions

### Side View




### Top View



# MIL-PRF-12883/41
## Low Profile RSE 2 Pole/10 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-213, Method 213
Test Condition C

### Materials
**Module Body:**
Polytherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets

**Mates with M83536, M6106 Relays**

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size* | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /40-11 | RSE116685 | Loose | 8 | 16/16 | /92-533 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /40-12 | RSE116687 | Loose | 8 | 16/16 | /92-533 | B | M83536/11-002, 004, 007 |
| /40-13 | RSE116691 | Loose | 8 | 16/16 | /92-533 | A | Leach Corp JA-D4E & J |
| /40-14 | RSE116693 | Loose | 8 | 16/20 | /92-534 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /40-16 | RSE116695 | Fixed | 8 | 16/16 | /92-533 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /40-17 | RSE116697 | Fixed | 8 | 16/16 | /92-533 | B | M83536/11-002, 004, 007 |
| /40-18 | RSE116699 | Fixed | 8 | 16/16 | /92-533 | A | Leach Corp JA-D4E & J |
| /40-19 | RSE116701 | Fixed | 8 | 16/20 | /92-534 | C | M83536/9-006, 015, 024, 035<br>M83536/10-006, 015, 024, 034, 038 |
| /41-15 | RSE116693 | Loose | 8 | 16/16 | /92-553 | D | M83536/13-002,-005,-008,-012<br>M83536/13-002,-005,-008,-012 |
| | | | 2 | 22/22 | /92-551 | | |
| /41-20 | RSE116703 | Fixed | 8 | 16/16 | /92-553 | D | M83536/13-002,-005,-008,-012<br>M83536/13-002,-005,-008,-012 |
| | | | 2 | 22/22 | /92-551 | | |

*Mating End / Wire Barrel

*Mounting instructions can be found on page 26*

### Socket Configurations



### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .055 | 25 |

### Recommended Mounting Panel Cutout



### Relay Socket Dimensions

#### Side View



#### Top View



Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

## Relay Sockets



**Mates with M6106, M83536 Relays**

# MIL-PRF-12883/44
# RSE 4 Pole/5 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1000 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .055 | 25 |

## Recommended Mounting Panel Cutout




## Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | QTY | Size* | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|
| /44-01 | RSE120151 | 14 | 20/20 | /101-553 | A | M83536/5-006,-014,-022,-030<br>M83536/6,-006,-014,-022,-032 |
| /44-02 | RSE120153 | 16 | 20/20 | /101-553 | B | M83536/7-002 |
| /44-03 | RSE120155 | 16 | 20/20 | /101-553 | C | |
| /44-04 | RSE120157 | 16 | 20/20 | /101-553 | D | |

*Mating End / Wire Barrel

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Side View




### Top View



# MIL-PRF-12883/45
## RSE 2 Pole/5 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1000 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Socket Body:**
Polyetherimide per ASTM -D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets

**Mates with M6106, M83536 Relays**

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|
| /45-01 | RSE120159 | 8 | 20/20 | /101-553 | A | M83536/1-006, -015, -024, -033<br>M83536/2-006, -015, -024, -035 |
| /45-02 | RSE120161 | 8 | 20/20 | /101-553 | B | |
| /45-03 | RSE120163 | 8 | 20/20 | /101-553 | C | |

*Mating End / Wire Barrel

*Mounting instructions can be found on page 26*

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .033 | 15 |

### Recommended Mounting Panel Cutout




### Relay Socket Dimensions

#### Side View




#### Top View




Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

# Relay Sockets

# MIL-PRF-12883/45
## RSE 2 Pole/5 Amp



**Mates with M6106/38 Relays**

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1000 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with with SAE-AMS 2422

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .033 | 15 |

## Recommended Mounting Panel Cutout




## Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|
| /45-04 | RSE120165 | 6 | 20/20 | /101-553 | A | M6106/38-002 |
| | | 4 | 22/22 | /101-552 | | |
| /45-05 | RSE120167 | 6 | 20/20 | /101-553 | B | |
| | | 4 | 22/22 | /101-552 | | |
| /45-06 | RSE120169 | 6 | 20/20 | /101-553 | C | |
| | | 4 | 22/22 | /101-552 | | |

[1] *Mating End / Wire Barrel*

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Side View




### Top View



# MIL-PRF-12883/46
## RSE 3 Pole/10 Amp

### Relay Sockets



**Mates with M83536, M6106 Relays**

### Operating Range

**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1250 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials

**Socket Body:**
Polyetherimide per ASTM -D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|
| /46-01 | RSE116747 | 9 | 16/16 | /101-554 | A | M83536/21-006,-014,-022,-030<br>M83536/22-006,-014,-022,-030 |
| | | 2 | 20/20 | /101-553 | | |
| /46-02 | RSE116749 | 9 | 16/16 | /101-554 | B | M6106/40-002 |
| | | 2 | 20/20 | /101-553 | | |
| /46-03 | RSE116751 | 9 | 16/16 | /101-554 | C | |
| | | 2 | 20/20 | /101-553 | | |
| /46-04 | RSE116753 | 9 | 16/16 | /101-554 | D | |
| | | 2 | 20/20 | /101-553 | | |

[1] *Mating End / Wire Barrel*

*Mounting instructions can be found on page 26*

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .055 | 25 |

### Recommended Mounting Panel Cutout




### Relay Socket Dimensions

#### Side View




#### Top View




Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

## Relay Sockets

**Mates with M83536, M83536 Relays**

# MIL-PRF-12883/47
# RSE/RSL 6 Pole/10 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/ Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in Accordance with SAE-AMS 2422

## Socket Configurations



A B

## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Extended Height | .176 | 80 |
| Low Profile | .144 | 65 |

## Recommended Mounting Panel Cutout




## Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /47-01 | RSE116755 | Loose | 20 | 16/16 | /92-533 | A | M83536/25-002, M83536/26-002 |
| /47-02 | RSE116757 | Loose | 20 | 16/16 | /92-533 | B | M83536/27-002 |
| /47-04 | RSE116761 | Fixed | 20 | 16/16 | /92-533 | A | M83536/25-002, M83536/26-002 |
| /47-05 | RSE116763 | Fixed | 20 | 16/16 | /92-533 | B | M83536/27-002 |

## Extended Height Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /47-07 | RSL116101 | Loose | 20 | 16/16 | /5-116 | A | M83536/25-002, M83536/26-002 |
| /47-08 | RSL116103 | Loose | 20 | 16/16 | /5-116 | B | M83536/27-002 |
| /47-10 | RSL116073 | Fixed | 20 | 16/16 | /5-116 | A | M83536/25-002, M83536/26-002 |
| /47-11 | RSL116075 | Fixed | 20 | 16/16 | /5-116 | B | M83536/27-002 |

[1] *Mating End / Wire Barrel*

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Side View




| Relay Socket | A | B | C Max | D |
|---|---|---|---|---|
| Extended Height | 1.03 | .140-.135 | 1.25 | .318 |
| Low Profile | 1.08 | .093 | .890 | .290 |

### Top View






www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

# MIL-PRF-12883/48
## RSE/RSL 3 Pole/25 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets

**Mates with MS27743 Relays**

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /48-01 | RSE112061 | Loose | 2 | 16/16 | /92-533 | A | MS27743-06, -12, -18, -24 |
| | | | 9 | 12/12 | /92-535 | | |
| /48-02 | RSE112063 | Fixed | 2 | 16/16 | /92-533 | A | MS27743-06, -12, -18, -24 |
| | | | 9 | 12/12 | /92-535 | | |
| /48-05 | RSE112065 | Loose | 2 | 16/16 | /92-533 | B | MS27743-09, -15, -21, -27 |
| | | | 9 | 12/12 | /92-535 | | |
| /48-06 | RSE112067 | Fixed | 2 | 16/16 | /92-533 | B | MS27743-09, -15, -21, -27 |
| | | | 9 | 12/12 | /92-535 | | |

### Extended Height Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /48-03 | RSL112105 | Loose | 2 | 16/16 | /5-116 | A | MS27743-06, -12, -18, -24 |
| | | | 9 | 12/12 | /5-118 | | |
| /48-04 | RSL112101 | Fixed | 2 | 16/16 | /5-116 | A | MS27743-06, -12, -18, -24 |
| | | | 9 | 12/12 | /5-118 | | |
| /48-07 | RSL112107 | Loose | 2 | 16/16 | /5-116 | B | MS27743-09, -15, -21, -27 |
| | | | 9 | 12/12 | /5-118 | | |
| /48-08 | RSL112103 | Fixed | 2 | 16/16 | /5-116 | B | MS27743-09, -15, -21, -27 |
| | | | 9 | 12/12 | /5-118 | | |

[1] *Mating End / Wire Barrel*

*Mounting instructions can be found on page 25*

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Extended Height | .129 | 55 |
| Low Profile | .109 | 49 |

### Recommended Mounting Panel Cutout




### Relay Socket Dimensions

#### Side View




| Relay Socket | A | B | C Max | D |
|---|---|---|---|---|
| Extended Height | 1.03 | .140-.135 | 1.25 | .318 |
| Low Profile | 1.00 | .093 | .890 | .290 |

#### Top View




Amphenol Pcd



www.amphenolpcd.com Milaero@amphenolpcd.com 1-978-624-3400 72 Cherry Hill Drive Beverly, MA 01915

# MIL-PRF-12883/52, MIL-PRF-12883/53

## RSE Track Mount 2, 3, & 4 Pole & Mounting Track

## Relay Sockets

**Mates with MS83726, M83536 & M6106 Relays**

### Operating Range

**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
700 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials

**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Contact Retainers:**
Beryllium Copper
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in Accordance with MIL-G-45204

## Socket Dimensions




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| RSE116175 | .016 | 7 |
| RSE116185 | .031 | 14 |
| RSE116195 | .031 | 14 |

## Low Profile Relay Sockets

| MIL P/N M12883* | APCD P/N* | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|
| /52-001 | RSE116175 | 8 | 20/20 | /101-553 | A | M83536/2-028, M83726/27, /25 |
| /52-002 | RSE116185 | 14 | 20/20 | /101-533 | B | M8536/6-025 |
| /52-003 | RSE116195 | 9 | 16/16 | /101-554 | C | M83536/22-025 |
| | | 2 | 20/20 | /101-553 | | |

*These Relay Sockets are used in the track mount system with track M12883/53-001, Amphenol Pcd P/N RST145005

[1] *Mating End / Wire Barrel*

## M12883/53-001 Mounting Track Dimensions

### Track Dimensions




### Track Materials

**Outer Track:**
Aluminum Alloy per QQ-A-225.
Chemical Coating per
MIL-C-5541, Class 3
**Inner Brackets and Rivets:**
Stainless Steel per QQ-S-766, Passivated
**Latch:**
Beryllium copper #172 per QQ-C-533
Bright Finish
**Wiring Protector:**
Aramid Paper per MIL-I-24202 AX
**Track Operating Range:**
-65ºC to 125ºC

### Track Weight

| Part Number | Pounds | Grams |
|---|---|---|
| RST145005 | .053 | 24 |

Use tool M6106/32-001 to remove M1288/52 sockets.
Use tool M6106/31-001 to remove relays from this mounting bracket.

# MIL-PRF-12883/54
## RSE 3 Pole/25 Amp

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets



**Mates with M6106/12, /13 & MS27742 Relays**

### Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size* | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /54-01 | RSE116627 | Fixed | 5 | 16/16 | /92-533 | A | M6106/13-002,-008,-011,-013,-015 |
| | | | 6 | 12/12 | /92-535 | | |
| /54-02 | RSE116631 | Fixed | 5 | 16/16 | /92-533 | B | M6106/13-004 |
| | | | 6 | 12/12 | /92-535 | | |
| /54-03 | RSE116629 | Fixed | 2 | 20/20 | /92-532 | C | M6106/12-002 |
| | | | 5 | 16/16 | /92-533 | | |
| | | | 6 | 12/12 | /92-535 | | |
| /54-04 | RSE116635 | Fixed | 2 | 20/20 | /92-532 | D | MS27742-2 |
| | | | 2 | 16/16 | /92-535 | | |
| | | | 9 | 12/12 | /92-535 | | |

*Mounting instructions can be found on page 26*

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| RSE116627 | .132 | 60 |
| RSE116631 | .132 | 60 |
| RSE116629 | .154 | 70 |
| RSE116635 | .154 | 70 |

### Recommended Mounting Panel Cutout




### Relay Socket Dimensions

#### Side View




#### Top View




Amphenol Pcd

## Relay Sockets

# MIL-PRF-12883/55
# RSE 1 Pole/25 Amp

**Mates with M6106/19, /20 Relays**

### Operating Range

**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials

**Socket Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| Low Profile | .073 | 33 |

## Recommended Mounting Panel Cutout




## Low Profile Relay Sockets

| MIL P/N M12883 | APCD P/N | Mounting Stud | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|---|---|
| /55-01 | RSE112035 | Fixed | 2 | 16/16 | /92-533 | A | M6106/19-004, -007, -012, -017, -022 |
| | | | 3 | 12/12 | /92-535 | | |
| /55-02 | RSE112036 | Fixed | 2 | 16/16 | /92-533 | A | M6106/19-004, -007, -012, -017, -022 |
| | | | 3 | 12/12 | /92-535 | | |
| /55-03 | RSE112044 | Fixed | 2 | 22/22 | /92-531 | B | M6106/20-002 |
| | | | 2 | 16/16 | /92-533 | | |
| | | | 3 | 12/12 | /92-535 | | |

[1] *Mating End / Wire Barrel*

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Side View




### Top View



# Microminiature Relay Sockets
## RSE 2 & 3 Pole, 2 Amp

### Relay Sockets

**Mates with M39016 & M5757 Relays**

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
2500 VRMS at Sea Level
700 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Grommet:**
Silicone Rubber per A-A-59588
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets for 2 Pole/ 2 Amp Microminiature Relays

| APCD P/N | QTY | Size | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|
| RSE120020 | 8 | 22/20 | CNS109900 | A | MIL-R-5757/10-022,-044 |
| RSE120074 | 8 | 22/20 | CNS109900 | B | MIL-R-39016/55-001,-013,-025,-037 |

### Relay Sockets for 3 Pole/ 2 Amp Microminiature Relays

| APCD P/N | QTY | Size | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|
| RSE120070 | 14 | 22/20 | CNS109900 | C | MIL-R-39016/39-002,-008,-014 |

*Mounting instructions can be found on page 26*

### Product Description

Microminiature Relay Sockets are designed to mate with M39016 & M5757 Microminiature Relays. Amphenol Pcd supplies three separate relay sockets for customers using Microminiature Relays.

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| RSE120020 | .024 | 11 |
| RSE120074 | .024 | 11 |
| RSN120070 | .044 | 20 |

### Relay Socket Dimensions

**RSE120020**

Side View




Top View




**RSE120074**

Side View




Top View




**RSE120070**

Side View




Top View




Amphenol Pcd

# Board Mount MIL-PRF-12883
## RSN 2,4 Pole/10 Amp, 3 Pole/25 Amp

**Mates with MIL-R-6106 & MS27743 Relays**

### Operating Range
**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials
**Module Body:**
Polyetherimide per ASTM-D5205
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

## Product Description

Product Line of pluggable, PC board mount relay sockets allows separable mounting of relays direct to boards in airborne or ground applications. Polyetherimide body and scalloped mounting flange reduce weight and improve strength. Mounting hardware supplied with connector secures firmly to board and eliminates stress on solder contacts. Gold-plated contacts and solder-dipped contact tails are available. Meets all applicable specifications.

## Socket Configurations




## Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| RSN116140 | .055 | 25 |
| RSN116130 | .033 | 15 |
| RSN112010 | .057 | 26 |

## Board Mount Relay Sockets

| APCD P/N | QTY | Size[1] | Contact P/N | Config. | Mating Relay |
|---|---|---|---|---|---|
| RSN116140 | 14 | 16/16 | /92-533 | A | MIL-R-6106, MS27400 |
| RSN116130 | 8 | 16/16 | /92-533 | B | MIL-R-6106, MS27401 |
| RSN112010 | 9 | 12/12 | /92-535 | C | MIL-R-6106, MS27743 |
| | 2 | 16/16 | /92-533 | | |

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

**RSN116140**

Side View




Top View




**RSN116130**

Side View




Top View




**RSN112010**

Side View




Top View



# Non-Environmental Relay Sockets

## Solder Termination

6 Pole/5 Amp, 4 Pole/10 Amp, 2 & 4 Pole/5 Amp, 2 Pole /10Amp

### Operating Range

**Temperature:**
-65ºC to 125ºC
**Insulation Resistance:**
1000 Megaohms Min.
**Dielectric Withstanding Voltage:**
1500 VRMS at Sea Level
500 VRMS at 80,000 ft.
**Vibration:**
MIL-STD-202, Method 204
Test Condition G
**Shock:**
MIL-STD-202, Method 213
Test Condition C

### Materials

**Socket Body:**
Polyetherimide per ASTM-D5205
**Hardware:**
Stainless Steel or Steel w/
Cadmium Chromate Finish
**Contact Retainers:**
Stainless Steel
**Socket Contacts:**
Copper Alloy, Hard Gold Plated in
Accordance with SAE-AMS 2422

### Relay Sockets

**Mates with M25027 & Series 9226, 9224, 9225, 9220, 9229, 9927 Leach Corp. Relays**

## Solder Termination Relay Sockets

| APCD P/N | Ref MIL STD Socket | MIL STD Relay | Leach Corp Relay |
|---|---|---|---|
| RSN116820 | MS25330 | MS25329 (6 Pole/5 Amp) | 9226 Series |
| RSN116890 | MS25328 | MS25327 (4 Pole/10 Amp) | 9224 Series |
| RSN116891 | MS25462 | MS25461 (4 Pole/10 Amp) | 9225 Series |
| RSN116800 | MS25326 | MS25325 (4 Pole/5 Amp) | 9220 Series |
| RSN116810 | MS25322 | MS25321 (2 Pole/10 Amp) | 9229 Series |
| RSN116825 | MS25324 | MS25323 (2 Pole/10 Amp) | 9227 Series |

*Mounting instructions can be found on page 26*

## Relay Socket Dimensions

### Solder Termination

**RSN116820**




**RSN116890**




**RSN116891**




**RSN116800**




**RSN116810**




**RSN116825**




### Product Description

Solder Termination Relay Sockets with Polyetherimide body and scalloped mounting flange to reduce weight and improve strength. Mounting hardware supplied with product.

### Socket Configurations




### Relay Socket Weight

| Relay Socket | Pounds | Grams |
|---|---|---|
| RSE120020 | .024 | 11 |
| RSE120074 | .024 | 11 |
| RSN120070 | .044 | 20 |

Amphenol Pcd

# Relay Socket Mounting Instructions
## Top Mount & Bottom Mount

### Mounting Instructions

**MIL-PRF-12883/40, MIL-PRF-12883/41**
**MIL-PRF-12883/47, MIL-PRF-12883/48**
**MIL-PRF-12883/54, MIL-PRF-12883/55**

**TOP MOUNT**




**BOTTOM MOUNT**




### Mounting Instructions

**MIL-PRF-12883/44, MIL-PRF-12883/45**
**MIL-PRF-12883/46**

**TOP MOUNT**




**BOTTOM MOUNT**




### Mounting Instructions

**Mircominature Relay Sockets**

**TOP MOUNT**




**BOTTOM MOUNT**




### Mounting Instructions

**Non-Enviromental Solder Termination Relay Sockets**

**TOP MOUNT**




**BOTTOM MOUNT**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.