

# Fluke 971

## Temperature Humidity Meter

### Technical Data



Quickly take accurate humidity and temperature readings in the air. Temperature and humidity are two important factors in maintaining optimal comfort levels and good indoor air quality. The Fluke 971 is

invaluable for facility maintenance and utility technicians, HVAC-service contractors, and specialists who assess indoor air quality (IAQ). Lightweight, rugged, and easy to hold, the Fluke 971 is the perfect tool for monitoring problem areas.

#### The Fluke 971 has:

- Backlit dual display of humidity and temperature
- 99 record storage capacity
- Ergonomic design with belt clip and protective holster
- Quick-response capacitance sensor with twist-open protective cover

#### General Features

- Compact and lightweight (190 g/6.7 oz)
- Temperature range from -20 °C to 60 °C (-4 °F to 140 °F)
- Measures dew point and wet bulb
- Relative humidity from 5 % to 95 %
- Min/Max/Avg data hold
- Low battery indicator

#### Specifications

|                                      |   |
|--------------------------------------|---|
| <b>Temperature range</b>             | -20 °C to 60 °C (-4 °F to 140 °F)                         |
| <b>Temperature accuracy</b>          |   |
| 0 °C to 45 °C                        | ± 0.5 °C  |
| -20 °C to 0 °C and 45 °C to 60 °C    | ± 1.0 °C  |
| 32 °F to 113 °F                      | ± 1.0 °F  |
| -4 °F to 32 °F and 113 °F to 140 °F  | ± 2.0 °F  |
| <b>Resolution</b>                    | 0.1 °C / 0.1 °F   |
| <b>Temperature update rate</b>       | 500 ms  |
| <b>Temperature sensor type</b>       | NTC   |
| <b>Relative humidity range</b>       | 5 % to 95 % R.H.  |
| <b>Relative humidity accuracy</b>    |   |
| 10 % to 90 % R.H. @ 23 °C (73.4 °F)  | ± 2.5 % R.H.  |
| <10 %, > 90 % R.H. @ 23 °C (73.4 °F) | ± 5.0 % R.H.  |
| <b>Resolution</b>                    | 0.1 % R.H.  |
| <b>Response time (humidity)</b>      | For 90 % of total range - 60 sec. with 1 m/s air movement |
| <b>Humidity sensor</b>               | Electronic capacitance polymer film sensor                |
| <b>Data storage</b>                  | 99 points   |

**Specifications** cont.

|                              |   |
|------------------------------|---|
| <b>Operating temperature</b> |   |
| Temperature                  | -20 °C to 60 °C (-4 °F to 140 °F)                                       |
| Humidity                     | 0 °C to 55 °C (32 °F to 131 °F)   |
| <b>Storage temperature</b>   | -20 °C to 60 °C (-4 °F to 140 °F) at < 80 % R.H. (with battery removed) |
| <b>Weight</b>                | 190 g (6.7 oz)  |
| <b>Dimensions (HxWxD)</b>    | 194 mm x 60 mm x 34 mm (7.6 in x 2.4 in x 1.3 in)                       |
| <b>Battery type</b>          | 4 AAA alkaline batteries  |
| <b>Battery life</b>          | 200 Hours   |
| <b>Safety approval</b>       | Electromagnetic compatibility: Complies with EN 61326-1                 |
| <b>Warranty</b>              | 12 months   |

\* Humidity sensor hysteresis (excursion of 10 % to 90 % to 10 % R.H.): ± 1 % R.H. with 1 m/s air movement  
 \* Temperature coefficient: 0.1 times the applicable accuracy specification per °C from 0 °C to 18 °C and 28 °C to 50 °C (32 °F to 64 °F and 83 °F to 122 °F)

**Other IAQ Tools from Fluke**

**Fluke 983 Particle Counter**

- Simultaneous display of six size channels on a bright, backlit LCD
- 5000 sample record capacity
- Logged samples include date, time, particle counts, sample volume, temperature and relative humidity
- Rechargeable NiMH battery providing up to 8 hours continuous operation
- Selectable sample time, count data, programmable delay
- Built-in relative humidity and temperature sensors



**CO-210 Carbon Monoxide Probe**

- Use as an accessory to a digital multimeter with DC millivolt inputs
- Displays CO level readings from 0 to 999 ppm, with a resolution of 1 ppm and accuracy of ± 3 %.
- Also used as a standalone device with an LED indicator and beeper that triggers with increasing frequency as CO levels rise.



**CO-205 Aspirator Kit**

The CO-205 flue gas sampling accessory kit contains all the components necessary to provide a clean sample for the Fluke family of gas measuring devices. The CO-205 accessory kit includes:

- Stainless steel sampling tube
- Industrial-grade hand operated aspirator to draw flue sample
- Easily replaceable particulate filter
- Specially designed nose cap for connection to the Fluke CO-210/CO-220.



**CO-220 Carbon Monoxide Meter**

- Standalone CO meter that does not require a digital multimeter
- Large backlit LCD displays CO levels from 0 to 1000 ppm.
- Beeper triggers with increasing frequency as CO levels rise.
- MAX hold function stores and displays the maximum CO level.
- Automatic sensor zeroing and self-test upon startup.



**Fluke.** *Keeping your world up and running.*

**Fluke Corporation**  
 PO Box 9090, Everett, WA USA 98206  
 Fluke Europe B.V.  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands  
 For more information call:  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa (31 40) 2 675 200 or  
 Fax (31 40) 2 675 222  
 In Canada (800) 36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1 (425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

©2005 Fluke Corporation. All rights reserved.  
 Printed in U.S.A. 11/2005 2457037 D-EN-N Rev C

**Ordering Information**

- Fluke-971** Temperature Humidity Meter
- Fluke-983** Particle Counter
- Fluke-CO-205** Aspirator Kit
- Fluke-CO-210** Carbon Monoxide Probe
- Fluke-CO-220** Carbon Monoxide Meter



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.