

Intel® Ethernet Controller I217

High-performance gigabit network connectivity with support for Intel® vPro[™] technology.



Overview

The Intel® Ethernet Controller I217 provides compact, single-port integrated physical layer devices that connect to the Intel® C220 Series Chipset and the network. The Intel® Ethernet Controller I217 is a gigabit copper networking component for mobile, desktop, workstation, and value-server designs that have critical space and power constraints.

Key Details

Design is Highly Compatible with the Intel® 82579 GbE Controller

The Intel[®] Ethernet Controller I217 is highly compatible with the Intel[®] 82579 GbE Controller, making new designs easy to generate while gaining the improvements of features now available on the Intel[®] Ethernet Controller I217.

Simplified Installation and Mainte-

nance: The Intel[®] Ethernet Controller I217 also supports the Intel Stable Image Platform Program (SIPP), which provides system image stability (both hardware and software) and consistency for at least 12 months from the product launch date, helping IT better manage their client environment.

Performance-Enhancing Features:

The Intel[®] Ethernet Controller I217 includes advanced interrupt-handling features to reduce CPU overheard. Other performance-enhancing features include offloading TCP/UDP (for both IPv4 and IPv6) checksum calculations and performing TCP segmentation. Advanced features such as Jumbo Frame support for extralarge packets and Receive Side Scaling are also supported. **Reduced Power and Energy Savings:** With the addition of platform low power management support and the addition of a pin that will wake the Intel® Ethernet Controller I217 from low-power states, the Intel® Ethernet Controller I217 reduces power requirements, leading to energy savings.

Besides the savings from working with the platform power management feature, the Intel® Ethernet Controller I217 reduces the power consumption in all power states compared to previous generations of Intel controllers. While in active-idle, Intel® has implemented Energy Efficient Ethernet (EEE)¹, a new IEEE* standard. With EEE, Intel has reduced the idle power of the gigabit link from about 500 mW to just over 50 mW, providing a significant energy savings. For mobile designs, Intel's Auto Connect Battery Saver (ACBS) can help reduce the cable-disconnected power of the chip to about 30 mW while still maintaining full functionality. It also supports advanced link downshifting capabilities to provide additional power headroom for system regulatory compliance (such as Energy Star*) by lowering the link speed under certain conditions to save power.

Single-pin LAN disable enables easier BIOS implementation and Low-power Link-up (LPLU) enables the system to stay in lowpower modes until a link is required.

Flexible, Low-Cost System Design: The Intel® Ethernet Controller I217 provides a small package (6 mm x 6 mm) networking option for convenient board layout. The Intel® Ethernet Controller I217 has an integrated switching voltage regulator (iSVR), removing the need for an external regulator and reducing both the overall cost and the board space required. Additionally, the Intel® Ethernet Controller I217 further helps to reduce board space requirements by using a shared FLASH design. Finally, low thermal design power (TDP) helps improve board placement flexibility.

Environmentally friendly design: The Intel[®] Ethernet Controller I217 family of products are all lead free³ and halogen free⁴ in their silicon and package design to reduce the potential for environmental impact.

| Comparison of Controller Features | | |
|--|-------|--------|
| Features | I217V | 1217LM |
| 10 Base T (IEEE 802.3 specification conformance) | ✓ | ~ |
| 100 Base TX (IEEE 802.3 specification conformance) | ✓ | ~ |
| 1000 Base T (IEEE 802.3 specification conformance) | ✓ | ~ |
| Auto-Negotiation (IEEE 802.3u) | ✓ | ~ |
| Intel® vPro™ ² technology | | ~ |
| Intel® Stable Image Platform Program (SIPP) | | ~ |
| Intel® Standard Manageablity | ✓ | ~ |
| Power optimizer platform low-power management systems | ✓ | ~ |
| Energy Efficient Ethernet ¹ (IEEE 802.3az) | ✓ | ~ |
| iSCSI Boot Support | | ~ |
| TCP/UDP checksum and segmentation offload (IPv4 and IPv6) | ✓ | ~ |
| Receive Side Scaling | ✓ | ~ |
| Dual TX and RX queues | ✓ | ~ |
| Jumbo Frames (up to 9K) | ✓ | ~ |
| Teaming | ✓ | ~ |
| Integrated Auto Connect Battery Saver (ACBS) battery savings | ✓ | ~ |
| Timing and Synchronization (802.1as / 1588) | ✓ | ~ |
| Integrated Switched Voltage Regulator (iSVR) | ✓ | ~ |
| Shared FLASH with system BIOS | ✓ | ~ |
| Wake from Deep Sx | ✓ | ~ |
| Server OS support | | ✓ |
| Network proxy/ARP support | ✓ | ✓ |

For more information on the Intel® Ethernet Controller I217, please visit www.intel.com/go/connectivity.

| Component Summary | | |
|-----------------------------------|--|-------------|
| CONTROLLER [△] | DISTINGUISHING FEATURES | ORDER CODES |
| Intel® Ethernet Controller I217LM | Corporate LAN product with support for Intel[®] vPro[™] technology, Intel[®] AMT², Energy Efficient Ethernet (802.3AZ)¹, Intel[®] SIPP, iSCSI Boot, Server OS support. | WGI217LM |
| | • Intended for mobile, desktop, workstation, entry server and embedded designs. | |
| Intel® Ethernet Controller I217V | Consumer LAN product with support for Energy Efficient Ethernet (802.3AZ)¹, Intel[®] Standard Manageablity, ACBS and standard Gigabit networking features | WGI217V |
| | Intended for mobile, desktop, and embedded design | |

1 Energy Efficient Ethernet (EEE) low-power idle requires that both link partners support IEEE802.3az.

2 Intel® Active Management Technology (AMT) requires specific Intel chipsets in addition to the Intel networking component. Intel Standard Manageability requires specific Intel chipsets in addition to the Intel networking component.

3 Lead has not been intentionally added, but lead may still exist as an impurity below 1000 ppm.

4 Lead and other materials banned in the RoHS Directive are either: (1) below all applicable substance thresholds as proposed by the EU or (2) an approved/pending exemption applies.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WAR-RANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

A "Mission Critical Application" is any application in which failure of the Intel Product could result, directly or indirectly, in personal injury or death. SHOULD YOU PURCHASE OR USE INTEL'S PRODUCTS FOR ANY SUCH MISSION CRITICAL APPLICATION, YOU SHALL INDEMNIFY AND HOLD INTEL AND ITS SUBSIDIARIES, SUBCONTRACTORS AND AFFILIATES, AND THE DIRECTORS, OFFICERS, AND EMPLOYEES OF EACH, HARMLESS AGAINST ALL CLAIMS COSTS, DAMAGES, AND EXPENSES AND REASONABLE ATTORNEYS' FEES ARISING OUT OF, DIRECTLY OR INDIRECTLY, ANY CLAIM OF PRODUCT LIABILITY, NEGLIGENT IN THE DESIGN, MANUFACTURE, OR WARNING OF THE INTEL PRODUCT OR ANY OF ITS PARTS.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined". Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order

Copies of documents that have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or go to: http://www.intel.com/design/literature.htm%20

Copyright © 2012 Intel Corporation. All rights reserved. Intel, vPro, and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries. *Other names and brands may be claimed as the property of others. Printed in USA 1112/SU/PDF Please Recycle (intel)

327968-001US

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Intel: WGI217V S LJWG



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.