MC74HC4316A

Quad Analog Switch/ Multiplexer/Demultiplexer with Separate Analog and Digital Power Supplies

High−Performance Silicon−Gate CMOS

The MC74HC4316A utilizes silicon−gate CMOS technology to achieve fast propagation delays, low ON resistances, and low OFF−channel leakage current. This bilateral switch/multiplexer/ demultiplexer controls analog and digital voltages that may vary across the full analog power−supply range (from V_{CC} to V_{EE}).

The HC4316A is similar in function to the metal−gate CMOS MC14016 and MC14066, and to the High−Speed CMOS HC4066A. Each device has four independent switches. The device control and Enable inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LSTTL outputs. The device has been designed so that the ON resistances (R_{ON}) are much more linear over input voltage than R_{ON} of metal−gate CMOS analog switches. Logic−level translators are provided so that the On/Off Control and Enable logic−level voltages need only be V_{CC} and GND, while the switch is passing signals ranging between V_{CC} and V_{EE}. When the Enable pin (active−low) is high, all four analog switches are turned off.

Features


- Logic−Level Translator for On/Off Control and Enable Inputs
- Fast Switching and Propagation Speeds
- High ON/OFF Output Voltage Ratio
- Diode Protection on All Inputs/Outputs
- Analog Power−Supply Voltage Range (V_{CC} − V_{EE}) = 2.0 to 12.0 V
- Digital (Control) Power−Supply Voltage Range (V_{CC} − GND) = 2.0 V to 6.0 V, Independent of V_{EE}
- Improved Linearity of ON Resistance
- Chip Complexity: 66 FETs or 16.5 Equivalent Gates
- Pb−Free Packages are Available*


*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


ON Semiconductor®

http://onsemi.com

MARKING DIAGRAMS







A	=	Assembly Location
L, WL	=	Wafer Lot
Y, YY	=	Year
W, WW	=	Work Week
G	=	Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping†
MC74HC4316AN	PDIP−16	500 Units / Box
MC74HC4316ANG	PDIP−16 (Pb−Free)	500 Units / Box
MC74HC4316ADR2	SOIC−16	2500/Tape&Reel
MC74HC4316ADR2G	SOIC−16 (Pb−Free)	2500/Tape&Reel
MC74HC4316AFEL	SOEIAJ−16	50/Tape&Reel
MC74HC4316AFELG	SOEIAJ−16 (Pb−Free)	50/Tape&Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2005




Figure 1. Pin Assignment

FUNCTION TABLE

Inputs		State of Analog Switch
Enable	**On/Off Control**	
L	H	On
L	L	Off
H	X	Off

X = Don't Care.




Figure 2. Logic Diagram

MAXIMUM RATINGS

Symbol	Parameter		Value	Unit
V_{CC}	Positive DC Supply Voltage	(Ref. to GND) (Ref. to V_{EE})	– 0.5 to + 7.0 – 0.5 to + 14.0	V
V_{EE}	Negative DC Supply Voltage (Ref. to GND)		– 7.0 to + 0.5	V
V_{IS}	Analog Input Voltage		V_{EE} – 0.5 to V_{CC} + 0.5	V
V_{in}	DC Input Voltage (Ref. to GND)		– 0.5 to V_{CC} + 0.5	V
I	DC Current Into or Out of Any Pin		± 25	mA
P_D	Power Dissipation in Still Air	Plastic DIP* EIAJ/SOIC Package* TSSOP Package*	750 500 450	mW
T_{stg}	Storage Temperature		– 65 to + 150	°C
T_L	Lead Temperature, 1 mm from Case for 10 Seconds (Plastic DIP, SOIC or TSSOP Package)		260	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

*Derating − Plastic DIP: – 10 mW/°C from 65° to 125°C
EIAJ/SOIC Package: – 7 mW/°C from 65° to 125°C
TSSOP Package: − 6.1 mW/°C from 65° to 125°C

For high frequency or heavy load considerations, see Chapter 2 of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Max	Unit
V_{CC}	Positive DC Supply Voltage (Ref. to GND)		2.0	6.0	V
V_{EE}	Negative DC Supply Voltage (Ref. to GND)		– 6.0	GND	V
V_{IS}	Analog Input Voltage		V_{EE}	V_{CC}	V
V_{in}	Digital Input Voltage (Ref. to GND)		GND	V_{CC}	V
V_{IO}*	Static or Dynamic Voltage Across Switch		−	1.2	V
T_A	Operating Temperature, All Package Types		– 55	+ 125	°C
t_r, t_f	Input Rise and Fall Time (Control or Enable Inputs) (Figure 10)	V_{CC} = 2.0 V V_{CC} = 3.0 V V_{CC} = 4.5 V V_{CC} = 6.0 V	0 0 0 0	1000 600 500 400	ns

*For voltage drops across the switch greater than 1.2 V (switch on), excessive V_{CC} current may be drawn; i.e., the current out of the switch may contain both V_{CC} and switch input components. The reliability of the device will be unaffected unless the Maximum Ratings are exceeded.

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high−impedance circuit. For proper operation, V_{in} and V_{out} should be constrained to the range GND ≤ (V_{in} or V_{out}) ≤ V_{CC}.

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or V_{CC}). Unused outputs must be left open. I/O pins must be connected to a properly terminated line or bus.

DC ELECTRICAL CHARACTERISTICS Digital Section (Voltages Referenced to GND) V_{EE} = GND Except Where Noted

Symbol	Parameter	Test Conditions	V_{CC} V	Guaranteed Limit			Unit
				– 55 to 25°C	≤ 85°C	≤ 125°C	
V_{IH}	Minimum High−Level Voltage, Control or Enable Inputs	R_{on} = Per Spec	2.0 3.0 4.5 6.0	1.5 2.1 3.15 4.2	1.5 2.1 3.15 4.2	1.5 2.1 3.15 4.2	V
V_{IL}	Maximum Low−Level Voltage, Control or Enable Inputs	R_{on} = Per Spec	2.0 3.0 4.5 6.0	0.5 0.9 1.35 1.8	0.5 0.9 1.35 1.8	0.5 0.9 1.35 1.8	V
I_{in}	Maximum Input Leakage Current, Control or Enable Inputs	V_{in} = V_{CC} or GND V_{EE} = – 6.0 V	6.0	± 0.1	± 1.0	± 1.0	μA
I_{CC}	Maximum Quiescent Supply Current (per Package)	V_{in} = V_{CC} or GND V_{IO} = 0 V V_{EE} = GND V_{EE} = – 6.0	 6.0 6.0	 2 4	 20 40	 40 160	μA

NOTE: Information on typical parametric values can be found in Chapter 2 of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).

DC ELECTRICAL CHARACTERISTICS Analog Section (Voltages Referenced to V_{EE})

Symbol	Parameter	Test Conditions	V_{CC} V	V_{EE} V	Guaranteed Limit			Unit
					– 55 to 25°C	≤ 85°C	≤ 125°C	
R_{on}	Maximum “ON” Resistance	V_{in} = V_{IH} V_{IS} = V_{CC} to V_{EE} I_S ≤ 2.0 mA (Figures 1, 2)	2.0* 4 5 4.5 6.0	0.0 0.0 − 4.5 − 6.0	– 160 90 90	– 200 110 110	– 240 130 130	Ω
		V_{in} = V_{IH} V_{IS} = V_{CC} or V_{EE} (Endpoints) I_S ≤ 2.0 mA (Figures 1, 2)	2.0 4.5 4.5 6.0	0.0 0.0 − 4.5 − 6.0	– 90 70 70	– 115 90 90	– 140 105 105	
ΔR_{on}	Maximum Difference in “ON” Resistance Between Any Two Channels in the Same Package	V_{in} = V_{IH} V_{IS} = 1/2 (V_{CC} − V_{EE}) I_S ≤ 2.0 mA	2.0 4.5 4.5 6.0	0.0 0.0 – 4.5 – 6.0	– 20 15 15	– 25 20 20	– 30 25 25	Ω
I_{off}	Maximum Off−Channel Leakage Current, Any One Channel	V_{in} = V_{IL} V_{IO} = V_{CC} or V_{EE} Switch Off (Figure 3)	6.0	– 6.0	0.1	0.5	1.0	μA
I_{on}	Maximum On−Channel Leakage Current, Any One Channel	V_{in} = V_{IH} V_{IS} = V_{CC} or V_{EE} (Figure 4)	6.0	– 6.0	0.1	0.5	1.0	μA

NOTE: Information on typical parametric values can be found in Chapter 2 of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).

*At supply voltage (V_{CC} − V_{EE}) approaching 2.0 V the analog switch−on resistance becomes extremely non−linear. Therefore, for low−voltage operation, it is recommended that these devices only be used to control digital signals.

AC ELECTRICAL CHARACTERISTICS (C_L = 50 pF, Control or Enable $t_r = t_f$ = 6 ns, V_{EE} = GND)

Symbol	Parameter	V_{CC} V	Guaranteed Limit			Unit
			– 55 to 25°C	≤ 85°C	≤ 125°C	
t_{PLH}, t_{PHL}	Maximum Propagation Delay, Analog Input to Analog Output (Figures 8 and 9)	2.0 4.5 6.0	40 6 5	50 8 7	60 9 8	ns
t_{PLZ}, t_{PHZ}	Maximum Propagation Delay, Control or Enable to Analog Output (Figures 10 and 11)	2.0 4.5 6.0	130 40 30	160 50 40	200 60 50	ns
t_{PZL}, t_{PZH}	Maximum Propagation Delay, Control or Enable to Analog Output (Figures 10 and 11)	2.0 4.5 6.0	140 40 30	175 50 40	250 60 50	ns
C	Maximum Capacitance — ON/OFF Control and Enable Inputs	–	10	10	10	pF
	Control Input = GND Analog I/O Feedthrough	 – –	 35 1.0	 35 1.0	 35 1.0	

1. For propagation delays with loads other than 50 pF, see Chapter 2 of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).
2. Information on typical parametric values can be found in Chapter 2 of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).

		Typical @ 25°C, V_{CC} = 5.0 V	
C_{PD}	Power Dissipation Capacitance (Per Switch) (Figure 13)*	15	pF

*Used to determine the no−load dynamic power consumption: $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$. For load considerations, see Chapter 2of the ON Semiconductor High−Speed CMOS Data Book (DL129/D).

ADDITIONAL APPLICATION CHARACTERISTICS (GND = 0 V)

Symbol	Parameter	Test Conditions	V_{CC} V	V_{EE} V	Limit* 25°C	Unit
BW	Maximum On–Channel Bandwidth or Minimum Frequency Response (Figure 5)	f_{in} = 1 MHz Sine Wave Adjust f_{in} Voltage to Obtain 0 dBm at V_{OS} Increase f_{in} Frequency Until dB Meter Reads – 3 dB R_L = 50 Ω, C_L = 10 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	150 160 160	MHz
–	Off–Channel Feedthrough Isolation (Figure 6)	f_{in} ≡ Sine Wave Adjust f_{in} Voltage to Obtain 0 dBm at V_{IS} f_{in} = 10 kHz, R_L = 600 Ω, C_L = 50 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	– 50 – 50 – 50	dB
		f_{in} = 1.0 MHz, R_L = 50 Ω, C_L = 10 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	– 40 – 40 – 40	
–	Feedthrough Noise, Control to Switch (Figure 7)	V_{in} ≤ 1 MHz Square Wave ($t_r = t_f$ = 6 ns) Adjust R_L at Setup so that I_S = 0 A R_L = 600 Ω, C_L = 50 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	60 130 200	mV_{PP}
		R_L = 10 kΩ, C_L = 10 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	30 65 100	
–	Crosstalk Between Any Two Switches (Figure 12)	f_{in} ≡ Sine Wave Adjust f_{in} Voltage to Obtain 0 dBm at V_{IS} f_{in} = 10 kHz, R_L = 600 Ω, C_L = 50 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	– 70 – 70 – 70	dB
		f_{in} = 1.0 MHz, R_L = 50 Ω, C_L = 10 pF	2.25 4.50 6.00	– 2.25 – 4.50 – 6.00	– 80 – 80 – 80	
THD	Total Harmonic Distortion (Figure 14)	f_{in} = 1 kHz, R_L = 10 kΩ, C_L = 50 pF $THD = THD_{Measured} - THD_{Source}$ V_{IS} = 4.0 V_{PP} sine wave V_{IS} = 8.0 V_{PP} sine wave V_{IS} = 11.0 V_{PP} sine wave	 2.25 4.50 6.00	 – 2.25 – 4.50 – 6.00	 0.10 0.06 0.04	%

*Limits not tested. Determined by design and verified by qualification.

TBD

Figure 1a. Typical On Resistance, $V_{CC} - V_{EE}$ = 2.0 V

TBD

Figure 1b. Typical On Resistance, $V_{CC} - V_{EE}$ = 4.5 V

TBD

Figure 1c. Typical On Resistance, $V_{CC} - V_{EE}$ = 6.0 V

TBD

Figure 1d. Typical On Resistance, $V_{CC} - V_{EE}$ = 9.0 V

TBD

Figure 1e. Typical On Resistance, $V_{CC} - V_{EE}$ = 12.0 V




Figure 2. On Resistance Test Set−Up




Figure 3. Maximum Off Channel Leakage Current, Any One Channel, Test Set−Up






Figure 4. Maximum On Channel Leakage Current, Test Set−Up




*Includes all probe and jig capacitance.

Figure 5. Maximum On−Channel Bandwidth Test Set−Up



*Includes all probe and jig capacitance.

Figure 6. Off−Channel Feedthrough Isolation, Test Set−Up



*Includes all probe and jig capacitance.

Figure 7. Feedthrough Noise, Control to Analog Out, Test Set−Up





Figure 8. Propagation Delays, Analog In to Analog Out



*Includes all probe and jig capacitance.

Figure 9. Propagation Delay Test Set−Up






Figure 10. Propagation Delay, ON/OFF Control to Analog Out



*Includes all probe and jig capacitance.

Figure 11. Propagation Delay Test Set−Up



*Includes all probe and jig capacitance.

Figure 12. Crosstalk Between Any Two Switches, Test Set−Up (Adjacent Channels Used)





Figure 13. Power Dissipation Capacitance Test Set−Up



*Includes all probe and jig capacitance.

Figure 14. Total Harmonic Distortion, Test Set−Up

APPLICATIONS INFORMATION




Figure 15. Plot, Harmonic Distortion

The Enable and Control pins should be at V_{CC} or GND logic levels, V_{CC} being recognized as logic high and GND being recognized as a logic low. Unused analog inputs/outputs may be left floating (not connected). However, it is advisable to tie unused analog inputs and outputs to V_{CC} or V_{EE} through a low value resistor. This minimizes crosstalk and feedthrough noise that may be picked up by the unused I/O pins.

The maximum analog voltage swings are determined by the supply voltages V_{CC} and V_{EE}. The positive peak analog voltage should not exceed V_{CC}. Similarly, the negative peak analog voltage should not go below V_{EE}. In the example below, the difference between V_{CC} and V_{EE} is 12 V. Therefore, using the configuration in Figure 16, a maximum analog signal of twelve volts peak−to−peak can be controlled.

When voltage transients above V_{CC} and/or below V_{EE} are anticipated on the analog channels, external diodes (Dx) are recommended as shown in Figure 17. These diodes should be small signal, fast turn−on types able to absorb the maximum anticipated current surges during clipping. An alternate method would be to replace the Dx diodes with MOSORBs (MOSORB™ is an acronym for high current surge protectors). MOSORBs are fast turn−on devices ideally suited for precise dc protection with no inherent wear out mechanism.




Figure 16.





Figure 17. Transient Suppressor Application



a. Using Pull−Up Resistors **b. Using HCT Buffer**

Figure 18. LSTTL/NMOS to HCMOS Interface




Figure 19. Switching a 0−to−12 V Signal Using a Single Power Supply (GND ≠ 0 V)




Figure 20. 4−Input Multiplexer





Figure 21. Sample/Hold Amplifier

PACKAGE DIMENSIONS


PDIP−16
N SUFFIX
CASE 648−08
ISSUE T



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.740	0.770	18.80	19.55
B	0.250	0.270	6.35	6.85
C	0.145	0.175	3.69	4.44
D	0.015	0.021	0.39	0.53
F	0.040	0.70	1.02	1.77
G	0.100 BSC		2.54 BSC	
H	0.050 BSC		1.27 BSC	
J	0.008	0.015	0.21	0.38
K	0.110	0.130	2.80	3.30
L	0.295	0.305	7.50	7.74
M	0 °	10 °	0 °	10 °
S	0.020	0.040	0.51	1.01

SOIC−16
D SUFFIX
CASE 751B−05
ISSUE J




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	9.80	10.00	0.386	0.393
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0 °	7 °	0 °	7 °
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

PACKAGE DIMENSIONS

SOEIAJ−16
F SUFFIX
CASE 966−01
ISSUE O



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	---	2.05	---	0.081
A_1	0.05	0.20	0.002	0.008
b	0.35	0.50	0.014	0.020
c	0.18	0.27	0.007	0.011
D	9.90	10.50	0.390	0.413
E	5.10	5.45	0.201	0.215
e	1.27 BSC		0.050 BSC	
H_E	7.40	8.20	0.291	0.323
L	0.50	0.85	0.020	0.033
L_E	1.10	1.50	0.043	0.059
M	0 °	10 °	0 °	10 °
Q_1	0.70	0.90	0.028	0.035
Z	---	0.78	---	0.031

MOSORB is a trademark of Semiconductor Components Industries, LLC (SCILLC).

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082−1312 USA
Phone: 480−829−7710 or 800−344−3860 Toll Free USA/Canada
Fax: 480−829−7709 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2−9−1 Kamimeguro, Meguro−ku, Tokyo, Japan 153−0051
Phone: 81−3−5773−3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.