

BCM™ Bus Converter



FEATURES

- 270 Vdc – 45.0 Vdc 270 W Bus Converter
- MIL-STD-704E/F Compliant
- High efficiency (>96.0%) reduces system power consumption
- High power density (>919 W/in³) reduces power system footprint by >40%
- Contains built-in protection features:
 - Undervoltage
 - Overvoltage Lockout
 - Overcurrent Protection
 - Short Circuit Protection
 - Overtemperature Protection
- Provides enable/disable control, internal temperature monitoring
- Can be paralleled to create multi-kW arrays

DESCRIPTION

The MIL-COTS V·I Chip™ bus converter is a high efficiency (>96.0%) Sine Amplitude Converter™ (SAC™) operating from a 230 to 330 V primary bus to deliver an isolated 38.3 – 55.0 V secondary.

The MBCM270F450M270A00 is provided in a V·I Chip package compatible with standard pick-and-place and surface mount assembly processes.


$V_{IN} = 230 - 330$ V	$P_{OUT} = 270$ W(NOM)
$V_{OUT} = 38.3 - 55.0$ V(NO LOAD)	$K = 1/6$

PART NUMBER	DESCRIPTION
MBCM270F450M270A00	-55°C – 125°C T_J operating, J-lead
MBCM270T450M270A00	-55°C – 125°C T_J operating, Through-hole

TYPICAL APPLICATIONS

- High Voltage 270 V Aircraft Distributed Power
- Provides Interface for high power density PRM modules
- High Density Power Supplies
- Communications Systems

TYPICAL APPLICATION



1.0 ABSOLUTE MAXIMUM VOLTAGE RATINGS

The absolute maximum ratings below are stress ratings only. Operation at or beyond these maximum ratings can cause permanent damage to the device.

	MIN	MAX	UNIT		MIN	MAX	UNIT
+IN to -IN	-1	400	V	Output current average	-2	8	A
VIN slew rate (operational)	-1	1	V/ μ s	PC to -IN	-0.3	20	V
Isolation voltage, input to output	4242		V	TM to -IN	-0.3	7	V
+OUT to -OUT	-1	80	V	Operating IC junction temperature ..	-55	125	°C
Output current transient ($<= 10$ ms, $<= 10\%$ DC)	-3	12	A	Storage temperature	-65	125	°C

2.0 ELECTRICAL CHARACTERISTICS

Specifications apply over all line and load conditions unless otherwise noted; **Boldface** specifications apply over the temperature range of $-55^\circ\text{C} < T_C < 100^\circ\text{C}$ (**T-Grade**); All other specifications are at $T_C = 25^\circ\text{C}$ unless otherwise noted.

ATTRIBUTE	SYMBOL	CONDITIONS / NOTES	MIN	TYP	MAX	UNIT
POWERTRAIN						
Input voltage range, continuous	V_{IN_DC}		230		330	V
Input voltage range, transient	V_{IN_TRANS}	Full current or power supported, 50 ms max, 10% duty cycle max	200		350	V
Quiescent current	I_Q	Disabled, PC Low		0.65	1.00	mA
V_{IN} to V_{OUT} time	T_{ON1}	$V_{IN} = 270$ V, PC floating	430	505	575	ms
No load power dissipation	P_{NL}	$V_{IN} = 270$ V, $T_C = 25^\circ\text{C}$		7	10	W
		$V_{IN} = 270$ V	4		14	
		$V_{IN} = 230$ V to 330 V, $T_C = 25^\circ\text{C}$			12	
		$V_{IN} = 230$ V to 330 V			16	
Inrush current peak	I_{INR_P}	Worse case of: $V_{IN} = 330$ V, $C_{OUT} = 50$ μF , $R_{LOAD} = 7078$ m Ω		2	3	A
DC input current	I_{IN_DC}	At $P_{OUT} = 350$ W			1.37	A
Transformation ratio	K	$K = V_{OUT}/V_{IN}$, at no load		1/6		V/V
Output power (average)	P_{OUT_AVG}				270	W
Output power (average), reduced temperature	$P_{OUT_AVG_RED_T}$	$-55^\circ\text{C} < T_C < 85^\circ\text{C}$			350	W
Output power (peak)	P_{OUT_PK}	10 ms max, $P_{OUT_AVG} \leq 270$ W or $P_{OUT_AVG_RED_T} \leq 350$ W			525	W
Output current (average)	I_{OUT_AVG}				6.25	A
Output current (average), reduced temperature	$I_{OUT_AVG_RED_T}$	$-55^\circ\text{C} < T_C < 85^\circ\text{C}$			8.00	A
Output current (peak)	I_{OUT_PK}	10 ms max, $I_{OUT_AVG} \leq 6.25$ A or $I_{OUT_AVG_RED_T} \leq 8.00$ A			11.67	A
Efficiency (ambient)	η_{AMB}	$V_{IN} = 270$ V, $I_{OUT} = 6.25$ A; $T_C = 25^\circ\text{C}$; $T_C = 25^\circ\text{C}$	94.5	96.0		%
		$V_{IN} = 230$ V to 330 V, $I_{OUT} = 6.25$ A; $T_C = 25^\circ\text{C}$	93.5			
		$V_{IN} = 270$ V, $I_{OUT} = 3.13$ A; $T_C = 25^\circ\text{C}$	93.5	95.2		
Efficiency (hot)	η_{HOT}	$V_{IN} = 270$ V, $I_{OUT} = 6.25$ A; $T_C = 100^\circ\text{C}$	94.0	95.6		%
Efficiency (over load range)	$\eta_{20\%}$	$1.25 \text{ A} < I_{OUT} < 6.25 \text{ A}$	90.0			%
Output resistance	R_{OUT_COLD}	$I_{OUT} = 6.25$ A, $T_C = -55^\circ\text{C}$	60.0	82.0	110	m Ω
	R_{OUT_AMB}	$I_{OUT} = 6.25$ A, $T_C = 25^\circ\text{C}$	100	122	150	m Ω
	R_{OUT_HOT}	$I_{OUT} = 6.25$ A, $T_C = 100^\circ\text{C}$	130	158	190	m Ω
Switching frequency	F_{SW}		1.6	1.7	1.8	MHz

2.0 ELECTRICAL CHARACTERISTICS (CONT.)

ATTRIBUTE	SYMBOL	CONDITIONS / NOTES	MIN	TYP	MAX	UNIT
Output voltage ripple	V_{OUT_PP}	$C_{OUT} = 0 \text{ F}$, $I_{OUT} = 6.25 \text{ A}$, $V_{IN} = 270 \text{ V}$, 20 MHz BW, Section 10		190	400	mV
Output inductance (parasitic)	L_{OUT_PAR}	Frequency up to 30 MHz, Simulated J-lead model		500		pH
Output capacitance (internal)	C_{OUT_INT}	Effective Value at 45.0 V_{OUT}		4.8		μF
Output capacitance (external)	C_{OUT_EXT}		0		50	μF
PROTECTION						
Input overvoltage lockout threshold	V_{IN_OVLO+}		360	370	380	V
Input overvoltage recovery threshold	V_{IN_OVLO-}		351	363	375	V
Input overvoltage lockout hysteresis	$V_{IN_OVLO_HYST}$			7.9		V
Overvoltage lockout response time	T_{OVLO}			50		μs
Fault recovery time	$T_{AUTO_RESTART}$		255	300	355	ms
Input undervoltage lockout threshold	V_{IN_UVLO-}		160	168	176	V
Input undervoltage recovery threshold	V_{IN_UVLO+}		167	177	190	V
Input undervoltage lockout hysteresis	$V_{IN_UVLO_HYST}$			8.5		V
Undervoltage lockout response time	T_{UVLO}			50		μs
Output overcurrent trip threshold	I_{OCP}		8.5	11	12.5	A
Output overcurrent response time constant	T_{OCP}	Effective internal RC filter		5.0		ms
Short circuit protection trip threshold	I_{SCP}		14			A
Short circuit protection response time	T_{SCP}			1		μs
Thermal shutdown threshold	T_{J_OTP}		125			$^{\circ}\text{C}$




Figure 1 – Safe operating area

3.0 SIGNAL CHARACTERISTICS

Specifications apply over all line and load conditions unless otherwise noted; **Boldface** specifications apply over the temperature range of $-55^{\circ}\text{C} < T_{\text{C}} < 100^{\circ}\text{C}$ (T-Grade); All other specifications are at $T_{\text{C}} = 25^{\circ}\text{C}$ unless otherwise noted.

PRIMARY CONTROL : PC

- The PC pin enables and disables the BCM. When held low, the BCM is disabled.
- In an array of BCMs, PC pins should be interconnected to synchronize start up and permit start up in to full load conditions.
- PC pin outputs 5 V during normal operation. PC pin internal bias level drops to 2.5 V during fault mode, provided V_{IN} remains in the valid range.

SIGNAL TYPE	STATE	ATTRIBUTE	SYMBOL	CONDITIONS / NOTES	MIN	TYP	MAX	UNIT
ANALOG OUTPUT	Regular Operation	PC voltage	V_{PC}		4.7	5.0	5.3	V
		PC available current	$I_{\text{PC_OP}}$		2.0	3.5	5.0	mA
	Standby	PC source (current)	$I_{\text{PC_EN}}$		50	100		μA
		PC resistance (internal)	$R_{\text{PC_INT}}$	Internal pull down resistor	50	150	400	$\text{k}\Omega$
	Transition	PC capacitance (internal)	$C_{\text{PC_INT}}$	Section 7			1000	pF
DIGITAL INPUT / OUPUT	Start Up	PC load resistance	$R_{\text{PC_S}}$	To permit regular operation	60			$\text{k}\Omega$
	Start Up	PC time to start	T_{ON1}		460	540	620	ms
	Regular Operation	PC enable threshold	$V_{\text{PC_EN}}$		2.0	2.5	3.0	V
	Transition	PC disable duration	$T_{\text{PC_DIS_T}}$	Minimum time before attempting re-enable	1			s
		PC threshold hysteresis	$V_{\text{PC_HYSTER}}$			50		mV
		PC enable to V_{OUT} time	T_{ON2}	$V_{\text{IN}} = 270 \text{ V}$ for at least T_{ON1} ms	50	100	150	μs
		PC disable to standby time	$T_{\text{PC_DIS}}$			4	10	μs
		PC fault response time	$T_{\text{FR_PC}}$	From fault to PC = 2 V		100		μs

TEMPERATURE MONITOR : TM


- The TM pin monitors the internal temperature of the controller IC within an accuracy of $\pm 5^{\circ}\text{C}$.
- Can be used as a "Power Good" flag to verify that the BCM is operating.
- Is used to drive the internal comparitor for Over Temperature Shutdown.

SIGNAL TYPE	STATE	ATTRIBUTE	SYMBOL	CONDITIONS / NOTES	MIN	TYP	MAX	UNIT
ANALOG OUTPUT	Regular Operation	TM voltage range	V_{TM}		2.12		4.04	V
		TM voltage reference	$V_{\text{TM_AMB}}$	$T_{\text{J}} \text{ controller} = 27^{\circ}\text{C}$	2.95	3.00	3.05	V
		TM available current	I_{TM}		100			μA
		TM gain	A_{TM}			10		$\text{mV}/^{\circ}\text{C}$
		TM voltage ripple	$V_{\text{TM_PP}}$	$C_{\text{TM}} = 0 \text{ pF}$, $V_{\text{IN}} = 270 \text{ V}$, $I_{\text{OUT}} = 6.25 \text{ A}$	120	200		mV
DIGITAL OUTPUT (FAULT FLAG)	Transition	TM capacitance (external)	$C_{\text{TM_EXT}}$				50	pF
		TM fault response time	$T_{\text{FR_TM}}$	From fault to TM = 1.5 V		10		μs
	Standby	TM voltage	$V_{\text{TM_DIS}}$			0		V
		TM pull down (internal)	$R_{\text{TM_INT}}$	Internal pull down resistor	25	40	50	$\text{k}\Omega$

RESERVED : RSV

Reserved for factory use. No connection should be made to this pin.

4.0 TIMING DIAGRAM



Notes:

- Timing and signal amplitudes are not to scale
- Error pulse width is load dependent

A: T_{on1}
 B: T_{vo10*}
 C: T_{auto_restart}
 D: T_{uvlo}
 E: T_{on2}
 F: T_{ocp}
 G: T_{pc-dis}
 H: T_{scp**}

*Min value switching off
 **From detection of error to power train shutdown

5.0 APPLICATION CHARACTERISTICS

The following values, typical of an application environment, are collected at $T_C = 25^\circ\text{C}$ unless otherwise noted. See associated figures for general trend data.




Figure 2 – No load power dissipation vs. V_{IN}




Figure 3 – Full load efficiency vs. full T_{MAX} range




Figure 4 – Full load efficiency vs. T_{MAX} restricted




Figure 5 – Efficiency and power dissipation at $T_C = -55^\circ\text{C}$




Figure 6 – Efficiency and power dissipation at $T_C = 25^\circ\text{C}$




Figure 7 – Efficiency and power dissipation at $T_C = 100^\circ\text{C}$




Figure 8 – Efficiency and power dissipation at $T_C = 85^\circ\text{C}$




Figure 9 – R_{OUT} vs. temperature




Figure 10 – V_{RIPPLE} vs. I_{OUT} ; No external C_{OUT} .
Board mounted module, scope setting : 20 MHz analog BW




Figure 11 – Full load ripple, 100 μF C_{IN} ; No external C_{OUT} .
Board mounted module, scope setting : 20 MHz analog BW




Figure 12 – Start up from application of PC; V_{IN} pre-applied
 $C_{\text{OUT}} = 50\text{ }\mu\text{F}$




Figure 13 – 0 A– 6.25 A transient response:
 $C_{IN} = 100 \mu F$, no external C_{OUT}




Figure 14 – 6.25 A – 0 A transient response:
 $C_{IN} = 100 \mu F$, no external C_{OUT}




Figure 15 — Envelope of normal voltage transient for 270 V_{DC} system.

6.0 GENERAL CHARACTERISTICS

Specifications apply over all line and load conditions unless otherwise noted; **Boldface** specifications apply over the temperature range of $-55^{\circ}\text{C} < T_{\text{J}} < 100^{\circ}\text{C}$ (M-Grade); All Other specifications are at $T_{\text{J}} = 25^{\circ}\text{C}$ unless otherwise noted.

ATTRIBUTE	SYMBOL	CONDITIONS / NOTES	MIN	TYP	MAX	UNIT
MECHANICAL						
Length	L		32.25 / [1.270]	32.50 / [1.280]	32.75 / [1.289]	mm/[in]
Width	W		21.75 / [0.856]	22.00 / [0.866]	22.25 / [0.876]	mm/[in]
Height	H		6.48 / [0.255]	6.73 / [0.265]	6.98 / [0.275]	mm/[in]
Volume	Vol	No heat sink		4.81 / [0.294]		cm ³ /[in ³]
Weight	W			14.5 / [0.512]		g/[oz]
Lead finish		Nickel Palladium Gold	0.51 0.02 0.003		2.03 0.15 0.051	µm
THERMAL						
Operating temperature	T _J	T-Grade MBCM270F450M270A00 (M-Grade)	N/A -55		N/A 125	°C
Thermal resistance	Φ _{JC}	Isothermal heatsink and isothermal internal PCB		1		°C/W
Thermal capacity				9		Ws/°C
ASSEMBLY						
Peak compressive force applied to case (Z-axis)		Supported by J-lead only			6 5.41	lbs lbs/in ²
Storage temperature	T _{ST}	T-Grade MBCM270F450M270A00 (M-Grade)	N/A -65		N/A 125	°C
Moisture sensitivity level	MSL	MSL 6, 4 hours out of bag maximum MSL 5				
ESD withstand	ESD _{HBM} ESD _{CDM}	Human Body Model, "JEDEC JESD 22-A114C.01" Class 1C Charge Device Model, "JEDEC JESD 22-C101-C"	1000 400			V
SOLDERING						
Peak temperature during reflow		Under MSL 6 conditions above Under MSL 5 conditions above			245 225	°C
Peak time above 217°C					150	s
Peak heating rate during reflow				1.5	2	°C/s
Peak cooling rate post reflow				2.5	3	°C/s
SAFETY						
Working voltage (IN – OUT)	V _{IN_OUT}				410	Vdc
Isolation voltage (hipot)	V _{HIPOT}		4,242			Vdc
Isolation capacitance	C _{IN_OUT}	Unpowered unit	500	600	700	pF
Isolation resistance	R _{IN_OUT}	At 500 Vdc	10			MΩ
MTBF		MIL-HDBK-217Plus Parts Count - 25°C Ground Benign, Stationary, Indoors / Computer Profile Telcordia Issue 2 - Method I Case III; 25°C Ground Benign, Controlled		3.81 7.84		MHrs MHrs
Agency approvals / standards		cTUVus cURus CE Mark RoHS 6 of 6				

7.0 USING THE CONTROL SIGNALS PC, TM

Primary Control (PC) pin can be used to accomplish the following functions:


- Logic enable and disable for module: Once Ton1 time has been satisfied, a PC voltage greater than Vpc_en will cause the module to start. Bringing PC lower than Vpc_dis will cause the module to enter standby.
- Auxiliary voltage source: Once enabled in regular operational conditions (no fault), each BCM module PC provides a regulated 5 V, 3.5 mA voltage source.
- Synchronized start up: In an array of parallel modules, PC pins should be connected to synchronize start up across units. This permits the maximum load and capacitance to scale by the number of paralleled modules.
- Output disable: PC pin can be actively pulled down in order to disable the module. Pull down impedance shall be lower than 60 Ω .
- Fault detection flag: The PC 5 V voltage source is internally turned off as soon as a fault is detected.
- Note that PC can not sink significant current during a fault condition. The PC pin of a faulted module will not cause interconnected PC pins of other modules to be disabled.

Temperature Monitor (TM) pin provides a voltage proportional to the absolute temperature of the converter control IC.

It can be used to accomplish the following functions:

- Monitor the control IC temperature: The temperature in Kelvin is equal to the voltage on the TM pin scaled by 100. (i.e. 3.0 V = 300 K = 27°C). If a heat sink is applied, TM can be used to protect the system thermally.
- Fault detection flag: The TM voltage source is internally turned off as soon as a fault is detected. For system monitoring purposes microcontroller interface faults are detected on falling edges of TM signal.

8.0 MBCM270F450M270A00 BLOCK DIAGRAM



9.0 SINE AMPLITUDE CONVERTER™ POINT OF LOAD CONVERSION




Figure 14 – V•I Chip™ AC model

The Sine Amplitude Converter (SAC™) uses a high frequency resonant tank to move energy from input to output. (The resonant tank is formed by C_r and leakage inductance L_r in the power transformer windings as shown in the BCM™ module Block Diagram. See Section 8). The resonant LC tank, operated at high frequency, is amplitude modulated as a function of input voltage and output current. A small amount of capacitance embedded in the input and output stages of the module is sufficient for full functionality and is key to achieving power density.

The MBCM270F450M270A00 SAC can be simplified into the preceding model.

At no load:

$$V_{OUT} = V_{IN} \cdot K \quad (1)$$

K represents the “turns ratio” of the SAC. Rearranging Eq (1):

$$K = \frac{V_{OUT}}{V_{IN}} \quad (2)$$

In the presence of load, V_{OUT} is represented by:

$$V_{OUT} = V_{IN} \cdot K - I_{OUT} \cdot R_{OUT} \quad (3)$$

and I_{OUT} is represented by:

$$I_{OUT} = \frac{I_{IN} - I_Q}{K} \quad (4)$$

R_{OUT} represents the impedance of the SAC, and is a function of the R_{DSON} of the input and output MOSFETs and the winding resistance of the power transformer. I_Q represents the quiescent current of the SAC control, gate drive circuitry, and core losses.

The use of DC voltage transformation provides additional interesting attributes. Assuming that $R_{OUT} = 0 \Omega$ and $I_Q = 0 A$, Eq. (3) now becomes Eq. (1) and is essentially load independent, resistor R is now placed in series with V_{IN} as shown in Figure 15.




Figure 15 – $K = 1/6$ Sine Amplitude Converter™ with series input resistor

The relationship between V_{IN} and V_{OUT} becomes:

$$V_{OUT} = (V_{IN} - I_{IN} \cdot R) \cdot K \quad (5)$$

Substituting the simplified version of Eq. (4) (I_Q is assumed = 0 A) into Eq. (5) yields:

$$V_{OUT} = V_{IN} \cdot K - I_{OUT} \cdot R \cdot K^2 \quad (6)$$

This is similar in form to Eq. (3), where R_{OUT} is used to represent the characteristic impedance of the SAC™. However, in this case a real R on the input side of the SAC is effectively scaled by K^2 with respect to the output.

Assuming that $R = 1 \Omega$, the effective R as seen from the secondary side is $27.8 \text{ m}\Omega$, with $K = 1/6$ as shown in Figure 15.

A similar exercise should be performed with the addition of a capacitor or shunt impedance at the input to the SAC. A switch in series with V_{IN} is added to the circuit. This is depicted in Figure 16.




Figure 16 – Sine Amplitude Converter™ with input capacitor

A change in V_{IN} with the switch closed would result in a change in capacitor current according to the following equation:

$$I_C(t) = C \frac{dV_{IN}}{dt} \quad (7)$$

Assume that with the capacitor charged to V_{IN} , the switch is opened and the capacitor is discharged through the idealized SAC. In this case,

$$I_C = I_{OUT} \cdot K \quad (8)$$

substituting Eq. (1) and (8) into Eq. (7) reveals:

$$I_{OUT} = \frac{C}{K^2} \cdot \frac{dV_{OUT}}{dt} \quad (9)$$

The equation in terms of the output has yielded a K^2 scaling factor for C , specified in the denominator of the equation. A K factor less than unity results in an effectively larger capacitance on the output when expressed in terms of the input. With a $K = 1/6$ as shown in Figure 16, $C = 1 \mu\text{F}$ would appear as $C = 1024 \mu\text{F}$ when viewed from the output.

Low impedance is a key requirement for powering a high-current, low-voltage load efficiently. A switching regulation stage should have minimal impedance while simultaneously providing appropriate filtering for any switched current. The use of a SAC between the regulation stage and the point of load provides a dual benefit of scaling down series impedance leading back to the source and scaling up shunt capacitance or energy storage as a function of its K factor squared. However, the benefits are not useful if the series impedance of the SAC is too high. The impedance of the SAC must be low, i.e. well beyond the crossover frequency of the system.

A solution for keeping the impedance of the SAC low involves switching at a high frequency. This enables small magnetic components because magnetizing currents remain low. Small magnetics mean small path lengths for turns. Use of low loss core material at high frequencies also reduces core losses.

The two main terms of power loss in the BCM™ module are:

- No load power dissipation (P_{NL}): defined as the power used to power up the module with an enabled powertrain at no load.
- Resistive loss (R_{OUT}): refers to the power loss across the BCM module modeled as pure resistive impedance.

$$P_{DISSIPATED} = P_{NL} + P_{R_{OUT}} \quad (10)$$

Therefore,

$$P_{OUT} = P_{IN} - P_{DISSIPATED} = P_{IN} - P_{NL} - P_{R_{OUT}} \quad (11)$$

The above relations can be combined to calculate the overall module efficiency:

$$\eta = \frac{P_{OUT}}{P_{IN}} = \frac{P_{IN} - P_{NL} - P_{R_{OUT}}}{P_{IN}} \quad (12)$$

$$\begin{aligned} &= \frac{V_{IN} \cdot I_{IN} - P_{NL} - (I_{OUT})^2 \cdot R_{OUT}}{V_{IN} \cdot I_{IN}} \\ &= 1 - \left(\frac{P_{NL} + (I_{OUT})^2 \cdot R_{OUT}}{V_{IN} \cdot I_{IN}} \right) \end{aligned}$$

10.0 INPUT AND OUTPUT FILTER DESIGN

A major advantage of SAC™ systems versus conventional PWM converters is that the transformers do not require large functional filters. The resonant LC tank, operated at extreme high frequency, is amplitude modulated as a function of input voltage and output current and efficiently transfers charge through the isolation transformer. A small amount of capacitance embedded in the input and output stages of the module is sufficient for full functionality and is key to achieve power density.

This paradigm shift requires system design to carefully evaluate external filters in order to:

1. Guarantee low source impedance:

To take full advantage of the BCM™ module's dynamic response, the impedance presented to its input terminals must be low from DC to approximately 5 MHz. The connection of the bus converter module to its power source should be implemented with minimal distribution inductance. If the interconnect inductance exceeds 100 nH, the input should be bypassed with a RC damper to retain low source impedance and stable operation. With an interconnect inductance of 200 nH, the RC damper may be as high as 1 μ F in series with 0.3 Ω . A single electrolytic or equivalent low-Q capacitor may be used in place of the series RC bypass.

2. Further reduce input and/or output voltage ripple without sacrificing dynamic response:

Given the wide bandwidth of the module, the source response is generally the limiting factor in the overall system response. Anomalies in the response of the source will appear at the output of the module multiplied by its K factor. This is illustrated in Figures 13 and 14.

3. Protect the module from overvoltage transients imposed by the system that would exceed maximum ratings and cause failures:

The module input/output voltage ranges shall not be exceeded. An internal overvoltage lockout function prevents operation outside of the normal operating input range. Even during this condition, the powertrain is exposed to the applied voltage and power MOSFETs must withstand it. A criterion for protection is the maximum amount of energy that the input or output switches can tolerate if avalanched.

Total load capacitance at the output of the BCM module shall not exceed the specified maximum. Owing to the wide bandwidth and low output impedance of the module, low-frequency bypass capacitance and significant energy

storage may be more densely and efficiently provided by adding capacitance at the input of the module. At frequencies <500 kHz the module appears as an impedance of R_{OUT} between the source and load.

Within this frequency range, capacitance at the input appears as effective capacitance on the output per the relationship defined in Eq. 5.

$$C_{OUT} = \frac{C_{IN}}{K^2} \quad \text{Eq. 6}$$

This enables a reduction in the size and number of capacitors used in a typical system.

11.0 THERMAL CONSIDERATIONS

V•I Chip™ products are multi-chip modules whose temperature distribution varies greatly for each part number as well as with the input / output conditions, thermal management and environmental conditions. Maintaining the top of the MBCM270F450M270A00 case to less than 100°C will keep all junctions within the V•I Chip module below 125°C for most applications.

The percent of total heat dissipated through the top surface versus through the J-lead is entirely dependent on the particular mechanical and thermal environment. The heat dissipated through the top surface is typically 60%. The heat dissipated through the J-lead onto the PCB surface is typically 40%. Use 100% top surface dissipation when designing for a conservative cooling solution.

It is not recommended to use a V•I Chip module for an extended period of time at full load without proper heat sinking.

12.0 CURRENT SHARING

The SAC™ topology bases its performance on efficient transfer of energy through a transformer without the need of closed loop control. For this reason, the transfer characteristic can be approximated by an ideal transformer with a positive temperature coefficient series resistance.

This type of characteristic is close to the impedance characteristic of a DC power distribution system, both in dynamic (AC) behavior and for steady state (DC) operation.

When multiple BCM modules of a given part number are connected in an array they will inherently share the load current according to the equivalent impedance divider that the system implements from the power source to the point of load.

Some general recommendations to achieve matched array impedances include:

- Dedicate common copper planes within the PCB to deliver and return the current to the modules.
- Provide as symmetric a PCB layout as possible among modules
- Apply same input / output filters (if present) to each unit.

For further details see [AN:016 Using BCM™ Bus Converters in High Power Arrays](#).




Figure 17 – BCM™ module array

13.0 FUSE SELECTION

In order to provide flexibility in configuring power systems V•I Chip™ products are not internally fused. Input line fusing of V•I Chip products is recommended at system level to provide thermal protection in case of catastrophic failure.

The fuse shall be selected by closely matching system requirements with the following characteristics:

- Current rating (usually greater than maximum current of BCM module)
- Maximum voltage rating (usually greater than the maximum possible input voltage)
- Ambient temperature
- Nominal melting I^2t
- Recommended fuse: ≤ 2.5 A Bussmann PC-Tron or SOC type 36CFA.

14.0 REVERSE OPERATION

BCM modules are capable of reverse power operation. Once the unit is started, energy will be transferred from secondary back to the primary whenever the secondary voltage exceeds $V_{IN} \bullet K$. The module will continue operation in this fashion for as long as no faults occur.

The MBCM270F450M270A00 has not been qualified for continuous operation in a reverse power condition.


Furthermore fault protections which help protect the module in forward operation will not fully protect the module in reverse operation.

Transient operation in reverse is expected in cases where there is significant energy storage on the output and transient voltages appear on the input. Transient reverse power operation of less than 10 ms, 10% duty cycle is permitted and has been qualified to cover these cases.

15.1 J-LEAD PACKAGE MECHANICAL DRAWING


[Click here to view original mechanical drawings on the Vicor website.](#)

TOP VIEW (COMPONENT SIDE SHOWN)








TOP VIEW (COMPONENT SIDE SHOWN)

BOTTOM VIEW



BOTTOM VIEW




NOTES:

1. DIMENSIONS ARE mm.
2. UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE:
 $X/[XX] = +/-0.25 / [.01]; XX/[XXX] = +/-0.13 / [.005]$
3. PRODUCT MARKING ON TOP SURFACE

DXF and PDF files are available on vicorpower.com

15.2 J-LEAD PACKAGE RECOMMENDED LAND PATTERN


RECOMMENDED LAND PATTERN
(COMPONENT SIDE SHOWN)RECOMMENDED LAND PATTERN
(COMPONENT SIDE SHOWN)

NOTES:


1. DIMENSIONS ARE mm.
2. UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE:
 $X/[XX] = +/-0.25 / [.01]; XX/[XXX] = +/-0.13 / [.005]$
3. PRODUCT MARKING ON TOP SURFACE

DXF and PDF files are available on vicorpower.com


15.3 THROUGH-HOLE PACKAGE MECHANICAL DRAWING

[Click here to view original mechanical drawings on the Vicor website.](#)


15.4 THROUGH-HOLE PACKAGE RECOMMENDED LAND PATTERN



15.5 RECOMMENDED HEAT SINK PUSH PIN LOCATION

[Click here to view original mechanical drawings on the Vicor website.](#)

(NO GROUNDING CLIPS)




(WITH GROUNDING CLIPS)

Notes:

1. Maintain 3.50 (0.138) Dia. keep-out zone free of copper, all PCB layers.
2. (A) minimum recommended pitch is 39.50 (1.555) this provides 7.00 (0.275) component edge-to-edge spacing, and 0.50 (0.020) clearance between Vicor heat sinks.
(B) Minimum recommended pitch is 41.00 (1.614). This provides 8.50 (0.334) component edge-to-edge spacing, and 2.00 (0.079) clearance between Vicor heat sinks.
3. V•I Chip™ module land pattern shown for reference only, actual land pattern may differ. Dimensions from edges of land pattern to push-pin holes will be the same for all full size V•I Chip products.
4. RoHS compliant per CST-0001 latest revision.
5. Unless otherwise specified: Dimensions are mm (inches) tolerances are:
x.x (x.xx) = ±0.3 (0.01)
x.xx (x.xxx) = ±0.13 (0.005)
6. Plated through holes for grounding clips (33855) shown for reference, heat sink orientation and device pitch will dictate final grounding solution.

15.6 BCM™ MODULE PIN CONFIGURATION



Bottom View

Signal Name	Designation
+In	A1-E1, A2-E2
-In	L1-T1, L2-T2
TM	H1, H2
RSV	J1, J2
PC	K1, K2
+Out	A3-D3, A4-D4, J3-M3, J4-M4
-Out	E3-H3, E4-H4, N3-T3, N4-T4

Warranty

Vicor products are guaranteed for two years from date of shipment against defects in material or workmanship when in normal use and service. This warranty does not extend to products subjected to misuse, accident, or improper application or maintenance. Vicor shall not be liable for collateral or consequential damage. This warranty is extended to the original purchaser only.

EXCEPT FOR THE FOREGOING EXPRESS WARRANTY, VICOR MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Vicor will repair or replace defective products in accordance with its own best judgement. For service under this warranty, the buyer must contact Vicor to obtain a Return Material Authorization (RMA) number and shipping instructions. Products returned without prior authorization will be returned to the buyer. The buyer will pay all charges incurred in returning the product to the factory. Vicor will pay all reshipment charges if the product was defective within the terms of this warranty.

Information published by Vicor has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Vicor reserves the right to make changes to any products without further notice to improve reliability, function, or design. Vicor does not assume any liability arising out of the application or use of any product or circuit; neither does it convey any license under its patent rights nor the rights of others. Vicor general policy does not recommend the use of its components in life support applications wherein a failure or malfunction may directly threaten life or injury. Per Vicor Terms and Conditions of Sale, the user of Vicor components in life support applications assumes all risks of such use and indemnifies Vicor against all damages.

Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor components are not designed to be used in applications, such as life support systems, wherein a failure or malfunction could result in injury or death. All sales are subject to Vicor's Terms and Conditions of Sale, which are available upon request.

Specifications are subject to change without notice.

Intellectual Property Notice

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. Interested parties should contact Vicor's Intellectual Property Department.

The products described on this data sheet are protected by the following U.S. Patents Numbers: 5,945,130; 6,403,009; 6,710,257; 6,911,848; 6,930,893; 6,934,166; 6,940,013; 6,969,909; 7,038,917; 7,145,186; 7,166,898; 7,187,263; 7,202,646; 7,361,844; D496,906; D505,114; D506,438; D509,472; and for use under 6,975,098 and 6,984,965.

Vicor Corporation

25 Frontage Road
Andover, MA, USA 01810
Tel: 800-735-6200
Fax: 978-475-6715

email

Customer Service: custserv@vicorpower.com
Technical Support: apps@vicorpower.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.