



**ULTRAVOLT® E SERIES**  
PRECISION HIGH VOLTAGE POWER SUPPLIES





---

**Single-output  
precision** high  
voltage power  
supply modules

The E series of precision high voltage power supplies has very low ripple, excellent linearity, and very stable temperature characteristics. Models in this series are offered at two levels of performance; the best delivers 10 ppm characteristics. This series is ideal for applications where system performance is directly linked to high voltage power quality and performance.

## Features

- › Precision output voltage from 0 to 1 kV through 0 to 15 kV
- › PPM level ripple, regulation, and stability
- › As low as 10 ppm temperature coefficient and reference
- › 0 to 4, 15/20, or 30 W of output power
- › Maximum load capability down to 0 V
- › Voltage and current regulation/limit capability
- › Precision output voltage and current monitors

## Typical Applications

- › Bias supplies
- › Mass spectrometry
- › SEM/FIB
- › Electron beams
- › Ion beams



| PARAMETER                                   | CONDITIONS                          | MODELS  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | UNITS       |
|---|-------------------------------------|---|------|------|-----------|------|------|-----------|------|------|-----------|------|------|------------|------|------|------------|------|------|-------------|
| <b>Input</b>                                |                                     | <b>All Types</b>  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      |             |
| <b>Voltage Range</b>                        | Full Power                          | +23 to 30   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Current</b>                              | Standby/Disable                     | < 50  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | mA          |
| <b>Current</b>                              | No Load, Max Eout                   | < 325   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | mA          |
| <b>Current</b>                              | Full Load, Max Eout                 | 2.5   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | A           |
| <b>AC Ripple Current</b>                    | Nominal Input, Full Load            | < 10  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | mA pk to pk |
| <b>Output</b>                               |                                     | <b>1E</b>   |      |      | <b>2E</b> |      |      | <b>4E</b> |      |      | <b>6E</b> |      |      | <b>10E</b> |      |      | <b>15E</b> |      |      |             |
| <b>Voltage Range</b>                        | Nominal Input                       | 0 to 1000   |      |      | 0 to 2000 |      |      | 0 to 4000 |      |      | 0 to 6000 |      |      | 0 to 10000 |      |      | 0 to 15000 |      |      | VDC         |
| <b>Nominal Input Voltage/Model</b>          |                                     | 24  | 24   | 24   | 24        | 24   | 24   | 24        | 24   | 24   | 24        | 24   | 24   | 24         | 24   | 24   | 24         | 24   | 24   | VDC         |
| <b>Power</b>                                | Nominal Input, Max Eout             | 4   | 20   | 30   | 4         | 20   | 30   | 4         | 20   | 30   | 4         | 20   | 30   | 4          | 15   | 30   | 4          | 15   | 30   | Watts       |
| <b>Current</b>                              | lout Entire Output Voltage Range    | 4   | 20   | 30   | 2         | 10   | 15   | 1         | 5    | 7.5  | 0.67      | 3.3  | 5    | 0.4        | 1.5  | 3    | 0.26       | 1    | 2    | mA          |
| <b>Voltage Monitor</b>                      | Normal Operating Conditions         | 0 to 10 ±0.5%   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Current Monitor</b>                      | Normal Operating Conditions         | 0 to 10 ±0.5%   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Ripple</b>                               | Full Load, Max Eout                 | ≤ 10  | ≤ 10 | ≤ 10 | ≤ 10      | ≤ 10 | ≤ 10 | ≤ 10      | ≤ 10 | ≤ 10 | ≤ 10      | ≤ 10 | ≤ 10 | ≤ 10       | ≤ 10 | ≤ 10 | ≤ 10       | ≤ 10 | ≤ 10 | ppm         |
| <b>Line Regulation</b>                      | Nom Input, Max Eout, Full Power     | < 25 ppm or < 10 ppm                                      |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Static Load Regulation</b>               | No Load to Full Load, Max Eout      | < 25 ppm or < 10 ppm                                      |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Stability</b>                            | 30 Min Warmup, Per 8 h, Per Day     | < 25 ppm or < 10 ppm                                      |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Programming and Controls</b>             |                                     | <b>All Types</b>  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      |             |
| <b>Input Impedance</b>                      | Nominal Input                       | 10  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | MΩ          |
| <b>Adjust Accuracy and Adjust Linearity</b> | 10 to 100%                          | ±0.05%  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | %           |
| <b>Adjust Voltage</b>                       | Differential                        | 0 to +10  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Output Voltage</b>                       | T = +25°C, Initial Value            | +10.00 ±0.05%   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Max Source Current</b>                   | T = +25°C                           | 5   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | mA          |
| <b>Output Impedance</b>                     | Normal Operating Conditions         | Buffered, low impedance, 2 mA max for source/sink current |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | -           |
| <b>Enable/Disable</b>                       |                                     | 0 to +0.8 disable, +2.5 to 10 enable (default = disable)  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | VDC         |
| <b>Environmental</b>                        |                                     | <b>All Types</b>  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      |             |
| <b>Operating</b>                            | Full Load, Max Eout, Case Temp.     | +10 to +45  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | °C          |
| <b>Temperature Coefficient</b>              | Over the Specified Temperature      | ±25 or ±10  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | ppm/°C      |
| <b>Thermal Shock</b>                        | Mil-Std-810, Method 504, Class 2    | -40 to +65  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | °C          |
| <b>Storage</b>                              | Non-Operating, Case Temp.           | -55 to +105   |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | °C          |
| <b>Humidity</b>                             | All Conditions, Standard Package    | 0 to 95%, non-condensing                                  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | -           |
| <b>Altitude</b>                             | Standard Package, All Conditions    | Sea level through 10,000                                  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | ft          |
| <b>Shock</b>                                | Mil-Std-810, Method 516, Proc. 4    | 20  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | Gs          |
| <b>Vibration</b>                            | Mil-Std-810, Method 514, Fig. 514-3 | 10  |      |      |           |      |      |           |      |      |           |      |      |            |      |      |            |      |      | Gs          |



Note: Downloadable drawings (complete with mounting and pin information) and 3D models are available online.

## PHYSICAL SPECIFICATIONS

### Construction

|                 |                          |
|-----------------|--------------------------|
| <b>Material</b> | Aluminum alloy 5052-H32  |
| <b>Finish</b>   | Anodize MIL-A-8625E blue |

### Size

|               |                                   |
|---------------|-----------------------------------|
| <b>Volume</b> | 561.9 cc (34.29 in <sup>3</sup> ) |
| <b>Weight</b> | 1.1 kg (2.4 lb)                   |

### Tolerance

|                               |                   |
|-------------------------------|-------------------|
| <b>Overall</b>                | ±1.27 mm (0.030") |
| <b>Pin to Pin</b>             | ±0.38 mm (0.015") |
| <b>Mounting Hole Location</b> | ±0.64 mm (0.025") |

### Connections

|                     |                                  |
|---------------------|----------------------------------|
| <b>D-Sub</b>        | 15-pin, female                   |
| <b>HV Connector</b> | LGH1/2L                          |
| <b>HV Return</b>    | #6-32 x 0.437 long threaded post |



## E SERIES INPUT CONNECTOR PINOUT AND FUNCTIONS

| Pin | Description            | Function  |
|-----|------------------------|---|
| 1   | Reference Voltage      | (+)10.00 V PRECISION REFERENCE                              |
| 2   | Voltage Programming -  | 0 TO 10 V TO PROGRAM FULL OUTPUT VOLTAGE                    |
| 3   | Voltage Programming +  | PROGRAMMING INPUT IS DIFFERENTIAL BETWEEN PINS 2 AND 3.     |
| 4   | Voltage Monitor        | 0 TO +10 V REPRESENTS 0 TO FULL OUTPUT VOLTAGE              |
| 5   | Voltage Mode Indicator | OPEN DRAIN ACTIVE LOW WHEN IN VOLTAGE CONTROL               |
| 6   | Signal Ground          | REFERENCE ALL CONTROL SIGNALS HERE.                         |
| 7   | Input Power            | +23 TO +30 V  |
| 8   | Input Power            |   |
| 9   | Power Ground           | INPUT POWER RETURN  |
| 10  | Power Ground           |   |
| 11  | Enable                 | TTL HIGH TO ENABLE, LOW TO DISABLE, DEFAULT IS OFF          |
| 12  | Current Monitor        | 0 TO +10 V REPRESENTS 0 TO FULL OUTPUT CURRENT              |
| 13  | Current Programming    | 0 TO +10 V SETS CURRENT FROM 0 TO FULL RATED OUTPUT CURRENT |
| 14  | Current Mode Indicator | OPEN DRAIN ACTIVE LOW WHEN IN CURRENT CONTROL               |
| 15  | Signal Ground          | REFERENCE ALL CONTROL SIGNALS HERE.                         |

NOTE: Use stud next to high voltage output connector as HV return. A secure ground connection here is critical to safety and proper operation.

## ORDERING INFORMATION

|                 |                                 |     |
|-----------------|---------------------------------|-----|
| <b>Type</b>     | 0 to 1000 VDC Output            | 1E  |
|                 | 0 to 2000 VDC Output            | 2E  |
|                 | 0 to 4000 VDC Output            | 4E  |
|                 | 0 to 6000 VDC Output            | 6E  |
|                 | 0 to 10,000 VDC Output          | 10E |
|                 | 0 to 15,000 VDC Output          | 15E |
| <b>Input</b>    | 24 V Input                      | 24  |
| <b>Polarity</b> | Positive Output                 | -P  |
|                 | Negative Output                 | -N  |
| <b>Power</b>    | 4 W Output                      | 4   |
|                 | 15 W Output (10 and 15 kV only) | 15  |
|                 | 20 W Output (1 to 6 kV only)    | 20  |
|                 | 30 W Output                     | 30  |

## Performance

|                   |   |            |
|-------------------|---|------------|
| <b>Level</b>      | 10 ppm Line/Load Regulation, Stability, and Temp. Coefficient | -10 ppm    |
|                   | 25 ppm Line/Load Regulation, Stability, and Temp. Coefficient | -25 ppm    |
| <b>Connectors</b> | LGH   | (Standard) |
|                   | 5 kV, SHV Type  | -SHV-5 kV  |
|                   | 10 kV, BNC Type   | -BNC-10 kV |

Popular accessories ordered with this product include our full range of high voltage output connectors. (See Accessories and Connectors datasheet.)



Non-RoHS compliant units are available. Please contact the factory for more information.





For international contact information, visit  
[advanced-energy.com](http://advanced-energy.com).



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.