XMPL

Aluminum Polymer Capacitors

SMD Solid Conductive (multilayer-type)




FEATURES

Small size – Low impedance – Halogen free epoxy – RoHS compliant – Stable with temperature, applied voltage and frequency

APPLICATIONS

Decoupling – Noise suppression

Operating Temperature Range		**-40°C to +105°C**							
Capacitance Tolerance		**±20% (M), -35% +10% (Y) 120 Hz, 20°C**							
Surge Voltage	**WVDC**	**2**	**2.5**	**4**	**6.3**	**10**	**12.5**	**16**	
	SVDC	1.25*WVDC							
Dissipation Factor	**WVDC**	**2**	**2.5**	**4**	**6.3**	**10**	**12.5**	**16**	
	Tan δ	.06							
Leakage Current (25°C) MAX		**Time**	**≤10 VDC**				**≥12.5 VDC**		
		2 Minutes	0.04CV				0.1CV		
Load Life		**1000 hours at 105°C with rated WVDC applied**							
		Capacitance Change	≤10% of initial measured value						
		Dissipation Factor	≤100% of maximum specified value						
		Leakage Current	≤100% of maximum specified value						
Moisture Resistance Test		**500 hours at 60°C and 90% relative Humidity with no voltage applied**							
		Capacitance Change	≤20% to +70% of initially measured value						
		Dissipation Factor	≤200% of maximum specified value						
		Leakage Current	≤100% of maximum specified value						
Moisture Sensitivity Level (MSL)		**3**							



Case size	EIA Code	L±0.2	W±0.2	T±0.2	W1±0.1	S±0.3
G19	7343	7.3	4.3	1.9	2.4	1.3
G28	7343	7.3	4.3	2.8	2.4	1.3

Markings

Recommended soldering profile

ILLINOIS CAPACITOR
Your Global Source for World-Class Capacitors

©2013 Illinois Capacitor, Inc.

North America
Tel: 847.675.1760
sales@illcap.com


Asia
Tel: 852.2793 0931
sales@illcap.com.hk

XMPL


Aluminum Polymer Capacitors




SMD Solid Conductive (multilayer-type)



Example: 470µF/2V





ILLINOIS CAPACITOR
Your Global Source for World-Class Capacitors

©2013 Illinois Capacitor, Inc.

North America
Tel: 847.675.1760
sales@illcap.com

Asia
Tel: 852.2793 0931
sales@illcap.com.hk

XMPL

+105°C Multi-layer Low Profile Chip

Capacitance (µF)	WVDC	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum ESR (mΩ) 100 kHz, +20°C	Leakage Current (µA)	Maximum RMS Ripple Current (A) 100 kHz, +105°C	Dimensions LxHxT (mm)
6.8	16	685XMPL016MG19	14.6282	70	4.352	2	7.3x4.3x1.9
10	6.3	106XMPL6R3MG19	9.9472	40	2.52	1	7.3x4.3x1.9
10	10	106XMPL010MG19	9.9472	45	4	1	7.3x4.3x1.9
10	12	106XMPL012MG19	9.9472	55	4.8	1	7.3x4.3x1.9
10	16	106XMPL016MG19	9.9472	40	6.4	2	7.3x4.3x1.9
15	12	156XMPL012MG19	6.6315	45	7.2	1	7.3x4.3x1.9
15	16	156XMPL016MG19	6.6315	40	9.6	3	7.3x4.3x1.9
22	6.3	226XMPL6R3MG19	4.5214	35	5.544	1	7.3x4.3x1.9
22	10	226XMPL010MG19	4.5214	40	8.8	1.8	7.3x4.3x1.9
22	12	226XMPL012MG19	4.5214	30	10.56	1.8	7.3x4.3x1.9
22	16	226XMPL016MG19	4.5214	40	14.08	3	7.3x4.3x1.9
22	16	226XMPL016MG28	4.5214	40	14.08	3	7.3x4.3x2.8
33	6.3	336XMPL6R3MG19	3.0143	25	8.316	1.8	7.3x4.3x1.9
33	10	336XMPL010MG19	3.0143	40	13.2	2	7.3x4.3x1.9
33	12	336XMPL012MG28	3.0143	25	15.84	2	7.3x4.3x2.8
47	6.3	476XMPL6R3MG19	2.1164	25	11.844	1.8	7.3x4.3x1.9
47	10	476XMPL010MG19	2.1164	40	18.8	3	7.3x4.3x1.9
47	12	476XMPL012MG28	2.1164	20	22.56	2	7.3x4.3x2.8
68	4	686XMPL004MG19	1.4628	20	10.88	1.9	7.3x4.3x1.9
68	6.3	686XMPL6R3MG19	1.4628	15	17.136	2	7.3x4.3x1.9
68	10	686XMPL010MG28	1.4628	40	27.2	3	7.3x4.3x2.8
82	4	826XMPL004MG19	1.2131	9	13.12	3	7.3x4.3x1.9
100	2	107XMPL002MG19	0.9947	16	8	2	7.3x4.3x1.9
100	4	107XMPL004MG19	0.9947	9	16	3	7.3x4.3x1.9
100	6.3	107XMPL6R3MG19	0.9947	15	25.2	2.7	7.3x4.3x1.9
100	6.3	107XMPL6R3MG19H	0.9947	12	25.2	2.7	7.3x4.3x1.9
120	6.3	127XMPL6R3MG19	0.8289	15	30.24	2.7	7.3x4.3x1.9
120	6.3	127XMPL6R3MG19H	0.8289	12	30.24	2.7	7.3x4.3x1.9
120	6.3	127XMPL6R3MG19X	0.8289	9	30.24	2.7	7.3x4.3x1.9
150	2	157XMPL002MG19	0.6631	9	12	3	7.3x4.3x1.9
150	2.5	157XMPL2R5MG19	0.6631	9	15	3	7.3x4.3x1.9
150	2.5	157XMPL2R5MG28	0.6631	9	15	3	7.3x4.3x2.8
150	4	157XMPL004MG19	0.6631	12	24	3	7.3x4.3x1.9
150	4	157XMPL004MG19R	0.6631	7	24	3	7.3x4.3x1.9
150	4	157XMPL004MG19X	0.6631	9	24	3	7.3x4.3x1.9
150	6.3	157XMPL6R3MG19H	0.6631	12	37.8	3	7.3x4.3x1.9
150	6.3	157XMPL6R3MG19X	0.6631	9	37.8	3	7.3x4.3x1.9
150	6.3	157XMPL6R3MG28	0.6631	15	37.8	3	7.3x4.3x2.8
150	6.3	157XMPL6R3MG19	0.6631	15	37.8	3	7.3x4.3x1.9
150	6.3	157XMPL6R3MG28H	0.6631	12	37.8	3	7.3x4.3x2.8
150	6.3	157XMPL6R3MG28X	0.6631	9	37.8	3	7.3x4.3x2.8
180	2	187XMPL002MG19	0.5526	9	14.4	2.7	7.3x4.3x1.9
180	2.5	187XMPL2R5MG19	0.5526	9	18	3	7.3x4.3x1.9
180	2.5	187XMPL2R5MG28	0.5526	9	18	3	7.3x4.3x2.8
180	4	187XMPL004MG19H	0.5526	12	28.8	3	7.3x4.3x1.9
180	4	187XMPL004MG19R	0.5526	7	28.8	3	7.3x4.3x1.9
180	4	187XMPL004MG19X	0.5526	9	28.8	3	7.3x4.3x1.9
180	4	187XMPL004MG28H	0.5526	12	28.8	3	7.3x4.3x2.8
180	4	187XMPL004MG28R	0.5526	7	28.8	3	7.3x4.3x2.8
180	4	187XMPL004MG28X	0.5526	9	28.8	3	7.3x4.3x2.8
180	6.3	187XMPL6R3MG19	0.5526	15	45.36	2.7	7.3x4.3x1.9
220	2	227XMPL002MG19	0.4521	15	17.6	3	7.3x4.3x1.9
220	2.5	227XMPL2R5MG19X	0.4521	9	22	3	7.3x4.3x1.9
220	2.5	227XMPL2R5MG28H	0.4521	12	22	3	7.3x4.3x2.8
220	2.5	227XMPL2R5MG28R	0.4521	7	22	3	7.3x4.3x2.8
220	2.5	227XMPL2R5MG28X	0.4521	9	22	3	7.3x4.3x2.8
220	2.5	227XMPL2R5MG19H	0.4521	12	22	3	7.3x4.3x1.9
220	2.5	227XMPL2R5MG19R	0.4521	7	22	3	7.3x4.3x1.9

ILLINOIS CAPACITOR, INC.
Your Global Source for World-Class Capacitors

© 2013 Illinois Capacitor, Inc.

North America
Tel: 847.675.1760
sales@illcap.com

Asia
Tel: 852.2793 0931
sales@illcap.com.hk

XMPL

+105°C Multi-layer Low Profile Chip

Capacitance (µF)	WVDC	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum ESR (mΩ) 100 kHz, +20°C	Leakage Current (µA)	Maximum RMS Ripple Current (A) 100 kHz, +105°C	Dimensions LxHxT (mm)
220	4	227XMPL004MG28X	0.4521	9	35.2	3	7.3x4.3x2.8
220	4	227XMPL004MG19X	0.4521	9	35.2	3	7.3x4.3x1.9
220	4	227XMPL004MG28H	0.4521	12	35.2	3	7.3x4.3x2.8
220	4	227XMPL004MG28R	0.4521	7	35.2	3	7.3x4.3x2.8
220	4	227XMPL004MG19H	0.4521	12	35.2	3	7.3x4.3x1.9
220	4	227XMPL004MG19R	0.4521	7	35.2	3	7.3x4.3x1.9
220	6.3	227XMPL6R3MG19	0.4521	10	55.44	3	7.3x4.3x1.9
220	6.3	227XMPL6R3MG28	0.4521	10	55.44	3	7.3x4.3x2.8
270	2	277XMPL002MG19X	0.3684	9	21.6	3	7.3x4.3x1.9
270	2		0.3684	9	21.6	3	7.3x4.3x1.9
270	2	277XMPL002MG19H	0.3684	12	21.6	3	7.3x4.3x1.9
270	2	277XMPL002MG19R	0.3684	6	21.6	3	7.3x4.3x1.9
270	2.5	277XMPL2R5MG28X	0.3684	9	27	3	7.3x4.3x2.8
270	2.5	277XMPL2R5MG19X	0.3684	9	27	3	7.3x4.3x1.9
270	2.5	277XMPL2R5MG28H	0.3684	12	27	3	7.3x4.3x2.8
270	2.5	277XMPL2R5MG28R	0.3684	7	27	3	7.3x4.3x2.8
270	2.5	277XMPL2R5MG19H	0.3684	12	27	3	7.3x4.3x1.9
270	2.5	277XMPL2R5MG19R	0.3684	7	27	3	7.3x4.3x1.9
270	4	277XMPL004MG19H	0.3684	12	43.2	2.7	7.3x4.3x1.9
270	4	277XMPL004MG19R	0.3684	7	43.2	2.7	7.3x4.3x1.9
270	4	277XMPL004MG19X	0.3684	9	43.2	2.7	7.3x4.3x1.9
330	2	337XMPL002MG19R	0.3014	6	26.4	3	7.3x4.3x1.9
330	2	337XMPL002MG19X	0.3014	9	26.4	3	7.3x4.3x1.9
330	2	337XMPL002MG28H	0.3014	12	26.4	3	7.3x4.3x2.8
330	2	337XMPL002MG19H	0.3014	12	26.4	3	7.3x4.3x1.9
330	2	337XMPL002MG19A	0.3014	4.5	26.4	3	7.3x4.3x1.9
330	2	337XMPL002MG28X	0.3014	9	26.4	3	7.3x4.3x2.8
330	2	337XMPL002MG28A	0.3014	4.5	26.4	3	7.3x4.3x2.8
330	2	337XMPL002MG28R	0.3014	6	26.4	3	7.3x4.3x2.8
330	2.5	337XMPL2R5MG19R	0.3014	6	33	3	7.3x4.3x1.9
330	2.5	337XMPL2R5MG19H	0.3014	12	33	3	7.3x4.3x1.9
330	2.5	337XMPL2R5MG19A	0.3014	4.5	33	3	7.3x4.3x1.9
330	2.5	337XMPL2R5MG19X	0.3014	9	33	3	7.3x4.3x1.9
330	4	337XMPL004YG19R	0.3014	7	52.8	2.7	7.3x4.3x1.9
330	4	337XMPL004YG19H	0.3014	12	52.8	2.7	7.3x4.3x1.9
330	4	337XMPL004YG19X	0.3014	9	52.8	2.7	7.3x4.3x1.9
330	6.3	337XMPL6R3YG19	0.3014	10	83.2	3	7.3x4.3x1.9
330	6.3	337XMPL6R3YG28	0.3014	10	83.2	3	7.3x4.3x2.8
390	2	397XMPL002MG19X	0.2551	9	31.2	3	7.3x4.3x1.9
390	2	397XMPL002MG19A	0.2551	4.5	31.2	3	7.3x4.3x1.9
390	2	397XMPL002MG19R	0.2551	6	31.2	3	7.3x4.3x1.9
390	2.5	397XMPL2R5MG19X	0.2551	9	39	3	7.3x4.3x1.9
390	2.5	397XMPL2R5MG19R	0.2551	6	39	3	7.3x4.3x1.9
390	2.5	397XMPL2R5MG19H	0.2551	12	39	3	7.3x4.3x1.9
390	2.5	397XMPL2R5MG19A	0.2551	4.5	39	3	7.3x4.3x1.9
470	2	477XMPL002MG19A	0.2116	4.5	37.6	3	7.3x4.3x1.9
470	2	477XMPL002MG28R	0.2116	6	37.6	3	7.3x4.3x2.8
470	2	477XMPL002MG28A	0.2116	4.5	37.6	3	7.3x4.3x2.8
470	2	477XMPL002MG19X	0.2116	9	37.6	3	7.3x4.3x1.9
470	2	477XMPL002MG19R	0.2116	6	37.6	3	7.3x4.3x1.9
470	2	477XMPL002MG28X	0.2116	9	37.6	3	7.3x4.3x2.8
470	2.5	477XMPL2R5YG19H	0.2116	12	47	3	7.3x4.3x1.9
470	2.5	477XMPL2R5YG19A	0.2116	4.5	47	3	7.3x4.3x1.9
470	2.5	477XMPL2R5YG19R	0.2116	6	47	3	7.3x4.3x1.9
470	2.5	477XMPL2R5YG19X	0.2116	9	47	3	7.3x4.3x1.9
470	2.5	477XMPL2R5YG28A	0.2116	4.5	47	3	7.3x4.3x2.8
470	2.5	477XMPL2R5YG28H	0.2116	12	47	3	7.3x4.3x2.8
470	2.5	477XMPL2R5YG28R	0.2116	6	47	3	7.3x4.3x2.8

ILLINOIS CAPACITOR, INC.
Your Global Source for World-Class Capacitors

© 2013 Illinois Capacitor, Inc.

North America
Tel: 847.675.1760
sales@illcap.com

Asia
Tel: 852.2793 0931
sales@illcap.com.hk

XMPL

+105°C Multi-layer Low Profile Chip

Capacitance (µF)	WVDC	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum ESR (mΩ) 100 kHz, +20°C	Leakage Current (µA)	Maximum RMS Ripple Current (A) 100 kHz, +105°C	Dimensions LxHxT (mm)
470	2.5	477XMPL2R5YG28X	0.2116	9	47	3	7.3x4.3x2.8

ILLINOIS CAPACITOR, INC.
Your Global Source for World-Class Capacitors
© 2013 Illinois Capacitor, Inc.

North America
Tel: 847.675.1760
sales@illcap.com

Asia
Tel: 852.2793 0931
sales@illcap.com.hk


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.