



PRODUCT BRIEF

RS10003

Redpine Signals WiSeMCU™ RS10003: Multi-protocol Wireless and Secure Microcontroller for the Internet of Things

Redpine Signals' RS10003 WiSeMCU™ device is the industry's first Wireless MCU with a multi-protocol wireless (Wi-Fi+Bluetooth+Zigbee) sub-system. It is a fully integrated module with an ultra-low-power ARM Cortex M4F microcontroller as an application processor, a built-in wireless subsystem, advanced security, power-management, frequency reference, RF power-amplifiers, diversity RF Front-end and passives. The WiSeMCU™ comes with an SDK to enable plug-and-play hardware and software development for the wireless Internet of things.

The ultra-low-power microcontroller subsystem in RS10003 integrates an ARM Cortex M4F processor with 128 KB of on-chip SRAM and 1MB of on-chip flash available for application development. A slew of peripherals including multiple USB Host, USB Slave, CAN, ADC, DAC, Quadrature Position/Revolution counter, Multi-function Serial interface supporting UART, LIN, SPI, I²C, comprehensive Multi-function timer, PWM, RTC etc satisfy the interfacing needs of most IoT devices.

The comprehensive wireless networking subsystem in RS10003 integrates 1x1 802.11n, advanced TCP/IP networking stack, Bluetooth4.0 solution with integrated application profiles and ZigBee for Home Automation and Smart Energy applications.

Application Subsystem Features:

- ARM Cortex-M4F processor, running at a frequency of up to 160 MHz
- Integrated Floating Point Unit (FPU), Memory Protection Unit (MPU), Built-in Nested Vectored Interrupt Controller (NVIC), Non-maskable Interrupt (NMI) input
- Debug options: JATG and Embedded Trace Macrocells (ETM)
- 1MB on-chip flash program memory with flash accelerator and 32KB work flash memory
- 128 kB SRAM for code and data use
- USB2.0 (Function/Host) Full-Speed supported upto Max 6 EndPoint
- CAN Interface supports upto max two channels
- Upto 70 high speed general purpose I/O ports.
- Multi-function Serial Interface upto max eight channels(UART, CSIO(SPI), LIN, I²C)
- Base timer(Max Eight channels) supporting PWM, PPG, reload timer, PWC.
- Comprehensive Timers: Multi-function timer(MFT) upto max two units RTC,QPRC, Dual Timer, Watchdog Timer max upto two units
- Analog peripherals: 12-bit, 24-channel, Analog-to-Digital Converter (ADC)
- Security: Unique ID of the device (41 bit) is set
- Six low-power consumption modes, SLEEP, Timer, RTC, STOP, Deep Standby RTC, Deep Standby stop.
- 12-bit Digital to Analog (AD) supporting upto max two channels
- DMA Controller max upto 8 channels
- CRC (Cyclic Redundancy Check) Accelerator
- External interrupt input pin: Max upto 16 pins
- Low-Voltage Detector (LVD)

Wireless Subsystem Features:

- WLAN: Compliant to IEEE 802.11 a/b/g/n with dual band support.
- Bluetooth: Compliant to dual-mode Bluetooth V4.0
- ZigBee: Compliant to IEEE 802.15.4
- Supports both 20MHz and 40MHz bandwidth in WLAN.
- WLAN transmit power up to +18dBm and receiver with sensitivity of -97dBm.
- Support for Bluetooth Transmit power class-1 with integrated PA and high performance
- Bluetooth receiver with -94dBm Rx sensitivity.
- Support for multiple ZigBee output powers up to +15dBm with integrated PA and high performance ZigBee receiver with -102dBm Rx sensitivity.
- Dual external antenna (diversity supported).
- Embedded WLAN stack, ZigBee stack, BT stack and full-featured TCP/IP network stack.
- Support for Embedded Wi-Fi Direct, Enterprise Security, Client mode and Access Point mode.
- Supports advanced security features: WPA/WPA2-Personal and Enterprise (EAP-TLS, EAP-FAST, EAP-TTLS, PEAP-MSCHAP-V2)
- BT profile support
- Zigbee Pro stack embedded.

Power supply


- 3.0-3.6V

Package and Operating Temperature

- Module size: 21mm x 15mm
- Industrial Grade -40°C to +85°C

Module Specifications

Network Standard Support	IEEE 802.11 a/b/g/j, 802.11n, 802.11d/e/i/w, 802.1X, 802.11k/r/v, Bluetooth v2.1 EDR, v3.0 + HS, v4.0 802.15.4-2006 (2.4GHz)
Data Rates	802.11n: from 6.5 Mbps to 150 Mbps (MCS 0-7) 802.11b: from 1 Mbps to 11 Mbps Bluetooth: 1, 2, 3Mbps 802.15.4-2006: 250Kbps
Modulation Techniques	OFDM with BPSK, QPSK, 16-QAM, 64-QAM and 256-QAM 802.11b with CCK and DSSS Bluetooth: GFSK, DQPSK, 8DPSK 802.15.4-2006: DSSS
802.11n Advanced Features	1-SS, 40MHz bandwidth, Greenfield Preamble, Short-GI, 1 spatial stream STBC, RIFS, A-MSDU, A-MPDU, Aggregation with Block-ack, A-MSDU inside A-MPDU, PSMP, MTBA, Fragmentation and Virtual AP support
Bluetooth Advanced Features	Scatternet, Adaptive Frequency Hopping, Interlaced scanning, 15 active slaves in proprietary mode, hold, sniff and park modes
ZigBee Advanced Features	CCM* security, orphan scanning, coordinator realignment, mesh routing
Wi-Fi modes	Embedded Wi-Fi client, Access point, Wi-Fi Direct
Bluetooth Modes	Master, slave, scatternet
Zigbee Modes	Zigbee Coordinator, Router, End device
Network Protocols	TCP, UDP, DHCP, ARP, IGMP, DNS client. Integrated web server, ZigBee and BT Stack.
QoS	WMM and WMM Power Save Support
MCU Peripherals/Interfaces	I2C, LIN, CAN, USB2.0, I2S, CSIO(SPI), UART, GPIO, JTAG, ADC, DAC Timers, PWM,PPG, RTC, MFT, WDT CSV, LVD, CRC, DMA, EXTINT, QPRC
Supply Voltage	3.0-3.6V
Operating Temperature	Industrial Grade -40°C to +85°C
Tx Power(+/-2 dBm)	Wi-Fi: 18 dBm for 802.11b CCK 18 dBm for 802.11g/n OFDM Bluetooth: 15dBm ZigBee: 15dBm
Rx Power (+/-1 dBm)	Wi-Fi: 1 Mbps -97 dBm 54 Mbps -75 dBm MCS7: -72 dBm Bluetooth: -94 dBm ZigBee: 250 Kbps -102 dBm
Software and Regulatory	WiFi Alliance (802.11bgn, WPA, WPA2 Personal and Enterprise, WMM-PS, WPS, Wi-Fi Direct™, Voice-Personal, Protected management frames), Cisco CCX v5, Zigbee Certification Bluetooth Qualification, FIPS 140-2, World-Wide Regulatory Compliance (FCC, IC, CE, ETSI, TELEC)



21mm x 15mm Module

Applications

- Home Automation - Displays/Thermostats
- Home Appliances – Smart Meters
- Security Systems – IP Network Sensor Nodes
- Wi-Fi- BT Gateway, WiFi-ZB Gateway
- Portable fitness & health monitoring
- Fleet management and asset tracking
- Wireless Headsets and speakers
- Other M2M applications
- Medical Devices
- Gaming Consoles
- Intelligent Sensing
- Wearables
- Industrial monitoring and control

Evaluation Package

The evaluation package comprises WiSeMCU module based board, accompanied by SDK and source code for peripheral interfaces, API library and hardware and software documentation. For details on availability please contact sales

Device Ordering Information


The device numbering is based on the following naming convention. All the devices are labeled as RS10003-XYZ-D0M Where

RS10003 - X Y Z - D 0 M

D = "D" for Dual band (2.4/5 GHz)
0 = "0" for no antenna package
M = "M" for WiseMCU

X = "N" with Wi-Fi, "0" without Wi-Fi
Y = "B" with BT, "0" without BT
Z = "Z" with ZigBee, "0" without ZigBee

System Block Diagram



For additional information, please contact Sales at Redpine Signals, Inc.:

Redpine Signals, Inc. • 2107 North First Street • Suite 680 • San Jose, CA 95131

Phone: +1408 7483385 • Email:sales@redpinesignals.com

Redpine Signals, Inc. reserves the right to make changes to the product(s) or information contained herein without notice. No Liability is assumed as a result of their use or application.Redpine, Redpine Signals, the Redpine logo, Driving Wireless Convergence, WiSeConnect and Lite-Fi are trademarks of Redpine Signals, Inc. All other company names, products and logos are registered trademarks of their respective companies.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.