



Mn-Zn

Large Size Ferrite Cores for High Power

T series



REMINDERS FOR USING THESE PRODUCTS

Please be sure to read this manual thoroughly before using the products.

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

When using the products for specific purposes, please first make confirmations in areas such as safety, reliability, and quality.

Please understand that we are not in a position to be held responsible for any damage or the like caused by any use exceeding the range or conditions of this specification sheet or by any use in the specific applications.

- | | |
|---|--|
| (1) Aerospace/Aviation equipment | (8) Public information-processing equipment |
| (2) Transportation equipment (electric trains, ships, etc.) | (9) Military equipment |
| (3) Medical equipment | (10) Electric heating apparatus, burning equipment |
| (4) Power-generation control equipment | (11) Disaster prevention/crime prevention equipment |
| (5) Atomic energy-related equipment | (12) Safety equipment |
| (6) Seabed equipment | (13) Other applications that are not considered general-purpose applications |
| (7) Transportation control equipment | |

When using this product in general-purpose standard applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc to ensure higher safety.

Large Size Ferrite Cores for High Power

Product compatible with RoHS directive
Halogen-free

Overview of the T Series

FEATURES

- Large size cores for transformers with large power outputs.
- Can also be used in reactors.

APPLICATION

- Large size industrial equipment, transformers for consumer equipment
- Reactors


PART NUMBER CONSTRUCTION

| PE22 | T | 51 | × | 13 | × | 31 |
|----------|------------|------------------|---|-----------|---|-----------------|
| Material | Core shape | Outside Diameter | | Thickness | | Inside Diameter |
| PE22 | T | 51 | | 13 | | 31 |
| PC40 | | 62 | | 20 | | 39 |
| | | 72 | | | | 48 |
| | | 80 | | | | 50 |
| | | 96 | | | | 70 |
| | | 104 | | | | 80 |

RANGE OF USE AND STORAGE TEMPERATURE


| Temperature range | |
|----------------------------|--------------------------|
| Operating temperature (°C) | Storage temperature (°C) |
| -30 to +105 | -30 to +85 |

- RoHS Directive Compliant Product: See the following for more details.<https://product.tdk.com/info/en/environment/rohs/index.html>
- Halogen-free: Indicates that Cl content is less than 900ppm, Br content is less than 900ppm, and that the total Cl and Br content is less than 1500ppm.

 Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

Mn-Zn系 T Cores

SHAPES AND DIMENSIONS



| | | | | | | |
|----------|------------|------------------|---|-----------|---|-----------------|
| PE22 | T | 51 | × | 13 | × | 31 |
| Material | Core shape | Outside Diameter | | Thickness | | Inside Diameter |

| Part No. | Dimensions | | | Effective parameter | | | | | | Electrical characteristics |
|------------------------------------|------------|----------|-----------|------------------------------|---|---|--|--|--------------|--|
| | ϕA | ϕB | C | Core factor | | Effective cross-sectional area A_e (mm ²) | Effective magnetic path length ℓ_e (mm) | Effective core volume V_e (mm ³) | Weigh (g) | Al-value (nH/N ²) 1kHz 0.4A/m 23°C |
| | (mm) | (mm) | (mm) | C_1 (mm ⁻¹) | $C_2 \times 10^{-2}$ (mm ⁻³) | | | | | |
| PE22 T51×13×31 PC40 T51×13×31 | 51.0±1.0 | 31.0±0.6 | 13.0±0.5 | 0.97084 | 0.76235 | 127 | 124 | 15740 | 80 80 | 2330±25% 2980±25% |
| PE22 T62×13×39 PC40 T62×13×39 | 62.5±1.2 | 39.0±0.8 | 13.5±0.5 | 0.98689 | 0.63377 | 156 | 154 | 23930 | 121 121 | 2290±25% 2930±25% |
| PE22 T72×20×48 PC40 T72×20×48 | 72.0±1.5 | 48.0±0.9 | 20.0±0.5 | 0.77481 | 0.32729 | 237 | 183 | 43420 | 217 217 | 2920±25% 3730±25% |
| PE22 T80×20×50 PC40 T80×20×50 | 80.0±1.6 | 50.0±1.0 | 20.0±0.5 | 0.66842 | 0.22694 | 295 | 197 | 57990 | 294 294 | 3380±25% 4320±25% |
| PE22 T96×20×70 PC40 T96×20×70 | 96.0±1.9 | 70.0±1.4 | 20.0 ±0.5 | 0.99464 | 0.38574 | 258 | 256 | 66130 | 325 325 | 2270±25% 2910±25% |
| PE22 T104×20×80 PC40 T104×20×80 | 104.0±2.1 | 80.0±1.6 | 20.0±0.5 | 1.19742 | 0.50179 | 239 | 286 | 68180 | 333 333 | 1890±25% 2410±25% |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.