









## Cables and Connectors *FDD / HDD Cable*

SATA HDD Cable			
			
<b>Model Name</b>	<b>32801-000703-400-RS</b>	<b>32102-000100-100-RS</b>	<b>32000-080700-RS</b>
Cable Type	SATA HDD cable	SATA power cable	SATA + Power cable
Connector	SATA 7-pin	4-pin + 2 x SATA 15-pin	SATA 7-pin + 4-pin
Connector Type	Lockable	SATA power connector	
Length	50 cm	15 cm	SATA cable 20 cm Power cable 10 cm

SATA HDD Cable		
		
<b>Model Name</b>	<b>32801-000201-300-RS</b>	<b>32801-000100-300-RS</b>
Cable Type	SATA + Power cable	SATA + Power cable
Connector	SATA 7-pin + 2-pin wafer (P=2 mm)	SATA 7-pin + 4-pin wafer (P=2.54 mm)
Connector Type	2-pin PH 2.0	4-pin PH 2.54 mm
Length	SATA cable 15 cm Power cable 15 cm	SATA cable 20 cm Power cable 20 cm

IDE HDD Cable			
			
<b>Model Name</b>	<b>32200-000009-RS</b>	<b>32221-001000-101-RS</b>	<b>32200-025001-RS</b>
Cable Type	IDE HDD flat cable	IDE HDD flat cable	IDE HDD flat cable
Connector	44p-44p	44p-44p	44p-40p-40p
Connector Type	2.0mm -2.0mm	2.0mm -2.0mm	2.0mm-2.54mm-2.54mm
Length	40 cm	25 cm	20 cm + 15 cm

IDE HDD Cable			
			
<b>Model Name</b>	<b>32225-002000-200-RS</b>	<b>32221-001700-100-RS</b>	<b>CB-HD32-RS</b>
Cable Type	ATA-66 HDD flat cable	ATA-33 HDD flat cable	IDE HDD flat cable
Connector	40p-40p-40p	44p-40p-40p	40p-44p
Connector Type	2.54mm	2.0mm-2.54mm-2.54mm	2.54mm-2.0mm
Length	30 cm + 15 cm	20 cm + 15 cm	IDE cable: 39 cm Power cable: 20 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1  
Industrial  
Computing  
Solutions

2  
Video  
Capture  
Solutions






3  
Industrial  
Computer  
Chassis






4  
Open  
Frame  
Monitor






5  
Power Supply/  
Peripherals





6  
All-in-One  
System

# Cables and Connectors *Paralle / Serial Cable*

	Serial cable				
					
<b>Model Name</b>	<b>45002-008103-RS</b>	<b>19800-000300-100-RS</b>	<b>19800-010900-200-RS</b>	<b>19800-000051-RS</b>	<b>19800-003600-100-RS</b>
Cable Type	Serial port	Serial port cable	Serial port cable	Serial port cable	Serial port cable
Board Side	N/A	10-pin (2x5) connector (2.0 mm)	10-pin (2x5) connector (2.54 mm)	2 x 10-pin (2x5) connector (2.54 mm)	2 x 10-pin (2x5) connector (2.54mm)
Board Side Pitch	2.54 mm	2.0 mm	2.54 mm	2.54 mm	2.54 mm
Device Side	2 x DE9M	DE9M	DE9M	2 x DE9M	2 x DE9M
Bracket	Yes	Yes	Yes	Yes	Yes
Length	9 cm	30 cm	50 cm	23 cm	40 cm

	Serial cable				
					
<b>Model Name</b>	<b>19800-000112-RS</b>	<b>32205-000702-100-RS</b>	<b>32200-000049-RS</b>	<b>32205-001203-200-RS</b>	<b>32205-002000-100-RS</b>
Cable Type	Serial port cable	Serial port cable	Serial port cable	Serial port cable	Serial port cable
Board Side	2 x 10-pin (2x5) connector (2.0 mm)	10-pin (2x5) connector (2.54 mm)	10-pin (2x5) connector (2.0 mm)	40-pin (2x20) connector (2.54 mm)	40-pin (2x20) connector (2.0 mm)
Board Side Pitch	2.0 mm	2.54 mm	2.0 mm	2.54 mm	2.0 mm
Device Side	2 x DE9M	DE9M	DE9M	4 x DE9M	4 x DE9M
Bracket	Yes	No	No	No	No
Length	30 cm	23 cm	20 cm	40/40/40/40 cm	30 cm

	Serial cable				
					
<b>Model Name</b>	<b>32200-025401-RS</b>	<b>32205-002500-100-RS</b>	<b>19800-004400-200-RS</b>	<b>19800-004300-100-RS</b>	<b>32200-026500-RS</b>
Cable Type	Serial port cable	RS-422/485 cable	RS-232 & RS-422/485 cable	RS-232 & RS-422/485 cable	RS-232 & RS-422/485 cable
Board Side	40-pin (2x20) connector (2.0 mm)	16-pin (2x8) connector (2.54 mm)	14-pin (2x7) connector (2.54 mm)	14-pin (2x7) connector (2.0 mm)	14-pin (2x7) connector (2.0 mm)
Board Side Pitch	2.0 mm	2.54 mm	2.54 mm	2.0 mm	2.0 mm
Device Side	4 x DE9M	4 x DE9M	2 x DE9M	2 x DE9M	2 x DE9M
Bracket	No	No	Yes	Yes	No
Length	30 cm	12 cm	25.5 cm	25 cm	29 cm

	Serial cable	Paralle cable		
				
<b>Model Name</b>	<b>32205-003800-300-RS</b>	<b>19800-000049-RS</b>	<b>19800-003500-100-RS</b>	<b>32200-015100-RS</b>
Cable Type	RS-422/485 cable	Parallel port cable	Parallel and serial port cable	Parallel port cable
Board Side	4-pin (1x4) connector (2.0 mm)	26-pin (2x13) connector (2.54 mm)	26-pin (2x13) connector (2.0 mm) 10-pin (2x5) connector (2.0 mm)	26-pin (2x13) connector (2.0 mm)
Board Side Pitch	2.0 mm	2.54 mm	2.0 mm	2.0 mm
Device Side	DE9M	DB25F	DB25F + DE9M	DB25F
Bracket	No	Yes	Yes	No
Length	20 cm	24 cm	24 cm	28 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1 Industrial Computing Solutions

2 Video Capture Solutions





3 Industrial Computer Chassis





4 Open Frame Monitor





5 Power Supply/ Peripherals






6 All-in-One System

# Cables and Connectors *USB / Keyboard / Mouse / Power Cable*

USB cable				
				
<b>Model Name</b>	<b>32001-010800-100-RS</b>	<b>32001-006404-100-RS</b>	<b>19800-000100-200-RS</b>	<b>19800-003100-300-RS</b>
Cable type	USB cable	USB cable	USB cable	USB cable
Board side	2 x 4-pin connector (2.54 mm)	2 x 4-pin connector (2.0 mm)	2 x 8-pin (2x4) connector (2.54 mm)	2 x 4-pin (1x4) connector (2.54 mm)
Board side pitch	2.54 mm	2.00 mm	2.54 mm	2.54 mm
Device side	2 x USB	2 x USB	4 x USB	2 x USB
Bracket	No	No	Yes	Yes
Length	20 cm	22 cm	30 cm	30 cm

USB cable				
				
<b>Model Name</b>	<b>CB-USB02A-RS</b>	<b>32000-044300-RS</b>	<b>32000-073400-RS</b>	<b>32001-008600-200-RS</b>
Cable type	USB cable	USB cable	USB cable	USB cable
Board side	1 x 8-pin (2x4) connector (2.0 mm)	1 x 8-pin (2x4) connector (2.54 mm)	2 x 5-pin connector (2.0 mm) for WAFER-8523, WAFER-945GSE3 only	1 x 8-pin (2x4) connector (2.0 mm)
Board side pitch	2.0 mm	2.54 mm	2.0 mm	2.0 mm
Device side	2 x USB	2 x USB	2 x USB	2 x USB
Bracket	Yes	No	No	No
Length	30 cm	21 cm	40 cm	21 cm

Keyboard / Mouse cable				
				
<b>Model Name</b>	<b>19800-000066-RS</b>	<b>19800-000075-RS</b>	<b>32006-000300-100-RS</b>	<b>32000-023800-RS</b>
Cable type	Keyboard and mouse cable	Y-Cable	Y-Cable	Y-Cable
Board side	2 x 5-pin (1x5) connector (2.54 mm)	1 x 6-pin (1x6) connector (2.0 mm)	1 x male PS/2	1 x 6-pin (1x6) connector (2.0 mm)
Board side pitch	2.54 mm	2.0 mm		2.0 mm
Device side	2 x Female PS/2	2 x Female PS/2	2 x Female PS/2	2 x Female PS/2
Bracket	Yes	Yes	No	No
Length	30 cm	22 cm	12 cm (KB) + 14 (MS)	13 cm

Power cable					
					
<b>Model Name</b>	<b>32100-087100-RS</b>	<b>32102-022100-100-RS</b>	<b>32102-005100-200-RS</b>	<b>32100-192900-RS</b>	<b>32100-130300-RS</b>
Cable type	12V power cable	ATX function cable	12V power cable	12V power cable	Power cable for PC/104 CPU module
Board side	1 x 4-pin (2x2) connector	1 x 20-pin ATX power connector	1 x 4-pin (2x2) connector	1 x 4-pin (2x2) connector	1 x 4-pin (1x4) molex
Device side	2 x 4-pin (1x4) molex	1 x 4-pin (1x4) molex 1 x 3-pin PS_ON connector	With lock screw	4-pin 3.5 mm terminal block	3-pin 3.5 mm terminal block
Bracket	No	No	No	No	No
Length	13 cm	30 cm	25 cm	25 cm	10 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

## Cables and Connectors *Audio / LAN / VGA / Adapter Cable*

	Audio cable		
			
<b>Model Name</b>	<b>19800-000111-RS</b>	<b>32007-002600-100-RS</b>	<b>32000-028800-RS</b>
Cable type	Audio cable	Audio cable	Audio cable
Board side	10-pin (2x5) connector (2.0 mm)	10-pin (2x5) connector (2.0 mm)	12-pin (2x6) connector (2.54 mm)
Board side pitch	2.0 mm	2.0 mm	2.54 mm
Device side	3 x Audio jacks	3 x Audio jacks	4 x Audio jacks
Bracket	Yes	No	No
Length	30 cm	30 cm	25 cm

	LAN cable	VGA cable	
			
<b>Model Name</b>	<b>32013-001700-100-RS</b>	<b>32003-000800-100-RS</b>	<b>32000-033804-RS</b>
Cable type	LAN cable	VGA cable	VGA cable
Board side	10-pin (2x5) connector (2.0 mm)	10-pin (2x5) connector (2.54 mm)	10-pin (2x5) connector (2.0 mm)
Board side pitch	2.0 mm	2.54 mm	2.0 mm
Device side	1 x RJ-45	1 x DB15F	1 x DB15F
Bracket	No	No	No
Length	31 cm	30 cm	30 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

## Rackmount Slide *Optional Chassis Accessories*

	SLIDE		
			
<b>Model Name</b>	<b>SLIDE-18</b>	<b>SLIDE-24</b>	<b>EXTENDER-6</b>
Specification	18" rackmount slide	24" rackmount slide	6" extender
Description	For rackmount chassis w/ depth up to 500	For rackmount chassis w/ depth up to 600	For 18" or 24" slider

## DIN Rail Kit

	KIT	
		
<b>Model Name</b>	<b>DK-100-R10</b>	<b>DK-84MB</b>
Specification	110 mm (W) x 100 mm (D)	168 mm (W) x 96 mm (D)
Description	VESA 100 to DIN-rail kit	DIN mount kit for ECW-281 series, black, RoHS

1 Industrial Computing Solutions

2 Video Capture Solutions

3 Industrial Computer Chassis

4 Open Frame Monitor

5 Power Supply/ Peripherals

6 All-in-One System



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.