

**TO - 92 BIPOLAR TRANSISTORS
TRANSISTOR(NPN)**

FEATURES


- * Power dissipation
P_{CM}: 625mW(T_{amb}=25°C)
- * Collector current
I_{CM}: 0.6 A
- * Collector-base voltage
V_{(BR)CBO}: 75 V
- * Operating and storage junction temperature range
T_J, T_{stg}: -55°C to +150°C

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-O rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.008 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ T_A = 25°C unless otherwise noted)

RATINGS	SYMBOL	VALUE	UNITS
Max. Steady State Power Dissipation ⁽¹⁾ @T _A =25°C Derate above 25°C	P _D	625	mW
Max. Operating Temperature Range	T _J	150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (@ T_A = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	MIN.	TYP.	MAX.	UNITS
Thermal Resistance Junction to Ambient	R _{θJA}	-	-	200	°C/W

Notes : 1. Alumina=0.4*0.3*0.024in.99.5% alumina
2. "Fully ROHS Compliant", "100% Sn plating (Pb-free)".

ELECTRICAL CHARACTERISTICS (@TA=25°C unless otherwise noted)

Chatacteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage ($I_C = 10\text{mA}$, $I_B = 0$)	$V_{(BR)CEO}$	40	-	Vdc
Collector-Base Breakdown Voltage ($I_C = 10\text{uA}$, $I_E = 0$)	$V_{(BR)CBO}$	75	-	Vdc
Emitter-Base Breakdown Voltage ($I_E = 10\text{uA}$, $I_C = 0$)	$V_{(BR)EBO}$	6.0	-	Vdc
Collector Cutoff Current ($V_{CE} = 60\text{Vdc}$, $V_{EB(off)} = 3.0\text{Vdc}$)	I_{CEX}	-	0.01	μA
Collector Cutoff Current ($V_{CB} = 60\text{Vdc}$, $I_E = 0$) ($V_{CB} = 60\text{Vdc}$, $I_E = 0$, $T_A = 150^\circ\text{C}$)	I_{CBO}	-	0.01 10	μA
Emitter Cutoff Current ($V_{EB} = 3.0\text{Vdc}$, $I_C = 0$)	I_{EBO}	-	0.01	μA
Base Cutoff Current ($V_{CE} = 60\text{Vdc}$, $V_{EB(off)} = 3.0\text{Vdc}$)	I_{BL}	-	20	nA

ON CHARACTERISTICS

DC Current Gain ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $T_A = -55^\circ\text{C}$) ($I_C = 500\text{mA}$, $V_{CE} = 10\text{Vdc}$) (1)	hFE	35 40	- -	-
Collector-Emitter Saturation Voltage (1) ($I_C = 150\text{mA}$, $I_B = 15\text{mA}$) ($I_C = 500\text{mA}$, $I_B = 50\text{mA}$)	$V_{CE(sat)}$	- -	0.3 1.0	Vdc
Base-Emitter Saturation Voltage (1) ($I_C = 150\text{mA}$, $I_B = 15\text{mA}$) ($I_C = 500\text{mA}$, $I_B = 50\text{mA}$)	$V_{BE(sat)}$	0.6 -	1.2 2.0	Vdc

SMALL-SIGNAL CHARACTERISTICS

Current-Gain-Bandwidth Product (2) ($I_C = 20\text{mA}$, $V_{CE} = 20\text{Vdc}$, $f = 100\text{MHz}$)	f_T	300	-	MHz
Input Capacitance ($V_{EB} = 0.5\text{Vdc}$, $I_C = 0$, $f = 1.0\text{MHz}$)	C_{ibo}	-	25	pF
Input Impedance ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$)	h_{ie}	2.0 0.25	8.0 1.25	kohms
Voltage Feedback Ratio ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$)	h_{re}	- -	8.0 4.0	$\times 10^{-4}$
Small-Signal Current Gain ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$)	h_{fe}	50 75	300 375	-
Output Admittance ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$)	h_{oe}	5.0 25	35 200	μmhos
Collector Base Time Constant ($I_E = 20\text{mA}$, $V_{CB} = 20\text{Vdc}$, $f = 31.8\text{MHz}$)	$\tau_{b,Cc}$	-	150	ps
Noise Figure ($I_C = 100\text{uA}$, $V_{CE} = 10\text{Vdc}$, $R_S = 1.0\text{kohms}$, $f = 1.0\text{kHz}$)	NF	-	4.0	dB

SWITCHING CHARACTERISTICS

Delay Time Rise Time	($V_{CC} = 30\text{Vdc}$, $V_{BE(off)} = -0.5\text{Vdc}$, $I_C = 150\text{mA}$, $I_{B1} = 15\text{mA}$)	t_d t_r	- -	10 25	ns
Storage Time Fall Time	($V_{CC} = 30\text{Vdc}$, $I_C = 150\text{mA}$, $I_{B1} = I_{B2} = 15\text{mA}$)	t_s t_f	- -	225 60	ns

NOTES : 1. Pulse Test: Pulse Width $\leq 300\text{ms}$, Duty Cycle $\leq 2.0\%$
2. f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity

RATING AND CHARACTERISTICS CURVES (PN2222A)




Figure 1. DC Current Gain




Figure 2. Collector Saturation Region




Figure 3. Turn-On Time




Figure 4. Turn-Off Time

RATING AND CHARACTERISTICS CURVES (PN2222A)




Figure 5. Frequency Effects




Figure 6. Source Resistance Effects




Figure 7. Capacitances




Figure 8. Current-Gain Bandwidth Product




Figure 9. "On" Voltages




Figure 10. Temperature Coefficients

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.