

Waterproof USB Type C

SCALABLE, SUPERSPEED CONNECTOR SYSTEM

Waterproof USB Type C Connectors are expected to be widely used as a next-generation interface. They support a variety of protocols such as USB 2.0, USB 3.1 Gen 1, Gen 2 and meet SuperSpeed communication 10Gb/s, 5A and 20V power supply.

The usability for USB 3.1 Type C connector is enhanced also by its low profile and reversible product design. It is ideal for emerging product designs.

- Reversible plug and cable orientation
- Meets USB 3.1/3.0/2.0 speed performance
- Supports high speed transmission up to 10Gb/s
- Extended 5A current rating for USB Power delivery
- Right angle stand-off and straddle mount configurations and waterproof type available

FEATURES

- Tailored for emerging product designs
- Similar size as Micro USB
- Supports high speed transmission up to 10Gb/s
- Excellent copper alloy material for terminals design
- 24 pin assignment for different kinds of protocol requirements
- Up to 10,000 mating cycles
- Waterproof glue, O-ring added and liquid insert-mold implemented in the front end of the shell

NEW


TARGET MARKETS



BENEFITS

- Reversible plug and cable orientation for better user experience
- Smaller connector size saves space
- Meets USB 3.1 Gen 1 and Gen 2 specifications
- Backward compatible with USB 2.0
- Extended 5A current rating for USB Power delivery
- Supports audio and video signal output with alternate mode
- Enhanced durability
- Meets IPX2 to IPX8 ratings

TECHNICAL INFORMATION

MATERIAL

- Housing: High Temperature Polymer, UL94V-0, Black
- Contact: Copper Alloy
- Shell: Stainless Steel

MECHANICAL PERFORMANCE

- Insertion Force: 5N to 20N
- Extraction Force: 8N to 20N
- Extraction Force (after durability): 6N to 20N
- Durability: 10,000 mating cycles

ELECTRICAL PERFORMANCE

- Contact Resistance: 40mΩ max. initial for VBUS, GND and all other contacts
- Insulation Resistance: 100mΩ min. initial
- Dielectric Withstanding Voltage: 100V AC

PACKAGING

- Tray/Tape and Reel available upon request

SPECIFICATION

- Amphenol Specification: USB Type-C Receptacle

APPROVALS AND CERTIFICATIONS

- RoHS

ENVIRONMENTAL

- Humidity: 40±2°C, 90 to 95% (RH), for 96 hours
- Temperature Life: 105±2°C for 120 hours

TARGET MARKETS/APPLICATIONS



Charger
Car Media Player/Hub



Connector Hub
Flash Disk
Mobile Phone/Tablet
VR Camera



Hard Disk Drives
Solid State Drives



Industrial Computer
POS System



Medical

PART NUMBERS

USB Version	Data Rate	No. of Contacts	Orientation	Level of Liquid Ingress Protection	Center Height	Shell Feature	Termination Type	Part Numbers
USB 3.1 Gen 2	10Gb/s	24	Top	IPX4	1.58	DIP	Dual Row SMT	124018092112A
USB 3.1 Gen 1	5Gb/s	24	Middle	IPX8	0.40	DIP	Dual Row SMT	124018312112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX4	1.50	DIP	Dual Row SMT	124018462112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX8	1.50	DIP	Dual Row SMT	124018612112A
USB 3.1 Gen 2	10Gb/s	24	Middle	IPX3	0.37	Screw Hole Plate	Dual Row SMT	124018772112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX8	1.50	Screw Hole Plate	Dual Row SMT	124018792112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX8	1.50	DIP	Dual Row SMT	124018802112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX8	1.53	Screw Hole Plate	Dual Row SMT	124018882112A
USB 3.1 Gen 2	10Gb/s	24	Top	IPX2	1.75	DIP	Dual Row SMT	12401899E412A
USB 3.1 Gen 2	10Gb/s	24	Top, Short Body	IPX2	1.58	DIP	Dual Row SMT	12401902E212A
USB 3.1 Gen 1	5Gb/s	24	Middle, Short Body	IPX5	0.40	DIP	Dual Row SMT	124019032112A
USB 3.1 Gen 1	5Gb/s	24	Middle	IPX8	0.40	DIP	Dual Row SMT	124019142112A



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.