

## SmartOnline 208/240 & 120V 8kVA 5.6kW Double-Conversion UPS, 4U Rack/Tower, Extended Run, Network Card Options, USB, DB9, Bypass Switch

MODEL NUMBER: **SU8000RT4U**



### Description

Tripp Lite 8kVA SmartOnline Hot-Swappable Modular Rack/Tower UPS offers 8000VA on-line, double-conversion UPS support for server, network and telecommunications equipment. Maintains battery-derived AC output during blackouts with active, full-time power conditioning. Fault-tolerant auto-bypass prevents unexpected service interruptions during overload or internal fault conditions. Single all-in-one housing installs in 4 rack spaces (4U). Upright tower and two post rackmount installation supported with optional accessories. Maintains full-time sine wave output within 3% of selectable 208/120 or 240/120V AC. Corrects brownouts and overvoltages from 65V to 140V (L-N). Expandable runtime with optional external battery packs. Converts raw input from AC to DC, then resynthesizes output power back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Highly efficient operation in optional economy mode setting, saving BTU heat output and energy costs. Network-grade AC surge and noise suppression. Network management interfaces include combination DB9 RS-232 enabled and dry contact serial port, enhanced USB port and slot for network management card options. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces. PowerAlert monitoring software is available via free download. Supports Emergency Power Off (EPO) via built-in interface. Front panel LEDs and LCD readout with scroll controls support visual monitoring of all major UPS functions. LED/LCD display panel easily rotates for viewing in rackmount or tower configurations. Split phase 4 conductor hardwire input. UPS supported outlets include two L6-30R, two L6-20R and 4 low voltage 5-15/20R. Hardwire output is also supported. Hardwire connections and outlets are mounted on a detachable backplate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment. Internal batteries and optional external battery packs are field replaceable and hot swappable. Attractive

### Highlights

- 8000VA / 8kVA / 5600W on-line double-conversion UPS
- 208/120V or 240/120V +/-3% output at 60Hz
- Included maintenance bypass switch enables live replacement of UPS with zero downtime
- 4U Rack/Tower compatible, Hot-swap power and battery modules
- USB, RS232 & EPO ports, Network management card options
- Front panel LEDs with detailed LCD monitoring and control screen
- Expandable runtime with optional external battery packs
- Hardwire input (4 wire), L6-30R, L6-20R, 5-15/20R & Hardwire outputs

### Package Includes

- SU8000RT4U Smart Online UPS
- SUPDM8K Detachable PDU with Manual Bypass Switch
- USB, DB9 and EPO cables
- 4 post rackmount installation brackets

all-black color scheme. \$250,000 [Ultimate Lifetime Insurance](#) (U.S., Canada, and Puerto Rico only).

## Features

- True online, double-conversion UPS provides pure, full-time sine wave AC output free of surges, voltage fluctuations and line noise
- 8000VA/5600 watt output power capacity with dual voltage output of 208/120 or 240/120V
- 4U all-in-one high power density housing supports rackmount installation in only 4 rack spaces
- Dual conversion UPS actively converts raw input from AC to DC, then back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- Hardwire input/output connections and output receptacles are mounted on a detachable backplate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment
- Provides perfectly regulated, sine wave output power free of line noise, transient surges and frequency variation for the most efficient operation of critical servers, networking and telecommunications equipment
- Maintains output within 3% of selected 208/120 or 240/120V nominal voltage during brownouts and overvoltages
- Supports connected equipment during blackouts for 12/5 minutes at half/full load levels, runtime is further expandable with optional external battery packs
- Intelligent battery management system extends battery life
- Some external battery configurations require the use of Tripp Lite's External Battery Configuration Software (see manual)
- Network interfaces support simultaneous communications via [DB9](#) port, USB port and slot for network management card options
- Compatible with Tripp Lite UPS management card options [TLNETCARD](#), [WEBCARDLX](#), [SNMPWEBCARD](#), [MODBUSCARD](#) and [RELAYIOCARD](#)
- [DB9](#) port supports RS-232 and dry contact messaging
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X.
- USB & Serial ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)
- Built-in Emergency Power Off (EPO) interface with cable
- Includes hardwire output and 8 output receptacles (2 L6-30R, 2 L6-20R, 4 NEMA 5-15/20R), all of which are available for simultaneous use
- Split phase, 4 conductor hardwire connection (featured on included detachable PDU).
- Front panel LEDs and LCD readout with scroll button enables visual confirmation of all major UPS functions and current site electrical conditions



- Front panel switches enable power on/off control, self-test and alarm cancel functions
- Included adjustable mounting rails support installation in 4 post 19 inch rack enclosures
- Optional [2-9U STAND](#) set of tower stands supports upright tower installation
- Optional [2-POST RACK MOUNT KIT](#) accessory enables 2 post rackmount installation
- Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- \$250,000 [Ultimate Lifetime Insurance](#) (U.S., Canada, and Puerto Rico only)

## Specifications

| OUTPUT  |  |
|---|--|
| Output Volt Amp Capacity (VA)                 | 8000   |
| Output kVA Capacity (kVA)                     | 8  |
| Output Watt Capacity (Watts)                  | 5600   |
| Output kW Capacity (kW)                       | 5.6  |
| Output Capacity Details                       | 8,000VA / 5600W (240V), 7200VA / 5600W (208V); Supports up to 105% load continuously in double conversion mode, 106 to 125% for 3 minutes, 126 to 150% for 30 seconds; Loads over 150% trigger immediate bypass mode operation to support equipment directly from mains power; Double conversion mode is automatically restored as the overload is cleared |
| Power Factor                                  | 0.7  |
| Crest Factor                                  | 3:1  |
| Nominal Output Voltage(s) Supported           | 120V; 208V; 240V   |
| Nominal Voltage Details                       | 240/120V or 208/120V split phase output  |
| Frequency Compatibility                       | 60 Hz  |
| Frequency Compatibility Details               | Output frequency regulation +/- 0.05Hz (free running)  |
| Output Voltage Regulation (Line Mode)         | +/- 3%   |
| Output Voltage Regulation (Economy Line Mode) | +/- 10%  |
| Output Voltage Regulation (Battery Mode)      | +/- 3%   |
| Output Receptacles                            | (4) 5-15/20R; (2) L6-20R; (2) L6-30R; Hardwire   |
| Output Receptacle Details                     | Supports 208/120V or 240/120V hardwire output (L1, L2, N, G)   |
| Output Circuit Breakers                       | 20A branch rated breakers (x4) protect 1 5-15/20R outlet each, 20A double pole breakers (x2) protect one L6-20R each, L6-30R outlets are unbreakered   |
| Output AC Waveform (AC Mode)                  | Pure Sine wave   |
| Output AC Waveform (Battery Mode)             | Pure Sine wave   |



| <b>INPUT</b>                                 |   |
|--|---|
| Rated input current (Maximum Load)           | 34A   |
| Nominal Input Voltage(s) Supported           | 120/208V (Split phase L1,L2,N,G); 120/240V (Split phase L1,L2,N,G)  |
| UPS Input Connection Type                    | Hardwire  |
| UPS Input Connection Description             | 4 wire split-phase input (L1, L2, N, G)   |
| Recommended Electrical Service               | 40A 208/120V or 240/120V Split Phase  |
| Input Phase                                  | Single-Phase  |
| <b>BATTERY</b>                               |   |
| Full Load Runtime (min.)                     | 5 min. (5600w)  |
| Half Load Runtime (min.)                     | 12 min. (2800w)   |
| Expandable Battery Runtime                   | Supports extended runtime with optional external battery packs  |
| External Battery Pack Compatibility          | <a href="#">BP192V1037C-1PH</a> ; <a href="#">BP192V12-3U</a> ; <a href="#">BP192V1407C-1PH</a> ; <a href="#">BP192V557C-1PH</a> ; <a href="#">BP192V787C-1PH</a> ; <a href="#">BP192V5RT2U</a> (limit 1)   |
| DC System Voltage (VDC)                      | 192   |
| Battery Recharge Rate (Included Batteries)   | Less than 6 hours from 10% to 80% (typical, full load discharge)  |
| Internal UPS Replacement Battery Cartridge   | <a href="#">RBC9-192</a>  |
| Battery Access                               | Front panel battery access door   |
| Battery Replacement Description              | Hot-swappable, user replaceable batteries   |
| Expandable Runtime                           | Yes   |
| <b>VOLTAGE REGULATION</b>                    |   |
| Voltage Regulation Description               | Online, double-conversion power conditioning  |
| Overvoltage Correction                       | Corrects overvoltages to 140 (measured L1-N : L2-N)   |
| Undervoltage Correction                      | Corrects undervoltages to 65 (measured L1-N : L2-N)   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Selectable LCD display with scroll and selection buttons enables UPS control and detailed monitoring options; LED/LCD panel rotates for viewing in rack/tower formats   |
| Switches                                     | Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions. A manual bypass switch featured on the detachable PDU allows for complete removal of the UPS during routine maintenance without disrupting output power |
| Alarm Cancel Operation                       | Alarm cancel switch   |
| Audible Alarm                                | Unique audible alarms for all major UPS, environmental and power conditions (see manual)  |
| LED Indicators                               | 6 LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options  |



| <b>SURGE / NOISE SUPPRESSION</b>                              |  |
|---|--|
| UPS AC Suppression Response Time                              | Instantaneous  |
| EMI / RFI AC Noise Suppression                                | Yes  |
| AC Suppression Response Time                                  | Instantaneous  |
| <b>PHYSICAL</b>   |  |
| Included Mounting Accessory Description                       | 4 post rackmount installation accessories included   |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount ( <u>2POSTRMKITHD</u> ); Tower ( <u>2-9USTAND</u> )   |
| Primary Form Factor   | Rackmount  |
| UPS Power Module Dimensions (hwd, in.)                        | 7 x 17.5 x 32.6  |
| UPS Power Module Dimensions (hwd, cm)                         | 17.78 x 44.45 x 82.80  |
| Rack Height (U Spaces)  | 4  |
| Maximum Device Depth (in.)                                    | 32.6   |
| Minimum Required Rack Depth (inches)                          | 40.6   |
| Maximum Device Depth (cm)                                     | 82.80  |
| Minimum Required Rack Depth (cm)                              | 103.12   |
| UPS Power Module Weight (lbs.)                                | 177  |
| UPS Power Module Weight (kg)                                  | 80.29  |
| UPS Dimensions Details  | Includes 4U UPS/power module plus SUPDM8K detachable PDU with bypass; MAXIMUM DEVICE DEPTH specification refers to the whole UPS installed depth with bypass PDU installed |
| UPS Shipping Dimensions (hwd / in.)                           | 13 x 23 x 37   |
| UPS Shipping Dimensions (hwd / cm)                            | 33.02 x 58.42 x 93.98  |
| Shipping Weight (lbs.)  | 212  |
| Shipping Weight (kg)  | 96.2   |
| Cooling Method  | Fans   |
| UPS Housing Material  | Steel  |
| Maximum Device Depth (mm)                                     | 828  |
| Minimum Required Rack Depth (mm)                              | 1031   |
| Primary UPS Height (mm)                                       | 178  |
| Primary UPS Width (mm)  | 444  |



|   |  |
|---|--|
| Primary UPS Depth (mm)                                      | 828  |
| Shipping Height (mm)  | 330  |
| Shipping Width (mm)   | 584  |
| Shipping Depth (mm)   | 940  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                 | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                                   | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius   |
| Relative Humidity   | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                               | 2362   |
| AC Economy Mode BTU / Hr. (Full Load)                       | 1219   |
| Battery Mode BTU / Hr. (Full Load)                          | 1887   |
| AC Economy Mode Efficiency Rating (100% Load)               | 94%  |
| Operating Elevation (ft.)                                   | 0-3000m (0 to 10,000 ft.)  |
| Audible Noise   | 60 dBA at front side 1 meter   |
| Operating Elevation (m)                                     | 0-3000 m   |
| <b>COMMUNICATIONS</b>                                       |  |
| Communications Interface                                    | USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface   |
| Network Management Cards                                    | SNMPWEBCARD; TLNETCARD; WEBCARDLX; MODBUSCARD; RELAYIOCARD   |
| Network Monitoring Port Description                         | RS232 and contact closure communications are supported on one DB9 port   |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a> |
| Communications Cable  | USB and DB9 cabling included   |
| <b>LINE / BATTERY TRANSFER</b>                              |  |
| Transfer Time   | No transfer time (0 ms.) in online, double-conversion mode   |
| Low Voltage Transfer to Battery Power (Setpoint)            | 65V (L1-N:L2-N)  |
| High Voltage Transfer to Battery Power (Setpoint)           | 140V (L1-N:L2-N)   |
| <b>SPECIAL FEATURES</b>                                     |  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported   |
| High Availability UPS Features                              | Automatic inverter bypass; Hot swappable batteries; Hot swappable UPS power module; Manual bypass switch   |
| Green Energy-Saving Features                                | High efficiency economy mode operation; Schedulable daily hours of economy mode operation  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| <b>CERTIFICATIONS</b>                                      |  |
|--|--|
| UPS Certifications   | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI) |
| <b>WARRANTY</b>  |  |
| Product Warranty Period (Worldwide)                        | 2-year limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 <u>Ultimate Lifetime Insurance</u>   |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.