

3M™ Metal-Out Static Shielding Bag 1500


This transparent metal-out static shielding bag is designed to provide a static safe environment for sensitive electronic devices. Bags are printed with an ESD warning symbol and a lot code for traceability. Open top and ZipTop styles are available. The bags are heat sealable.

3M Static Shielding Bags are manufactured from a top coat, metal, polyester, polyethylene laminate. The proprietary top coating is designed to protect the metal layer. Polyester dielectric, in concert with the metal layer, is intended to provide shielding of Electrostatic Discharge (ESD) and to help minimize the penetration of electric field.

These bags are tested to meet or exceed certain electrical and physical requirements of ANSI/ESD S541 and to be ANSI/ESD S20.20 program compliant. Bags are RoHS Compliant* and lead-free**.



3M™ Metal-Out Static Shielding Bag1500



| Physical | Typical Value | Testing Method |
|---------------------|-------------------------|---------------------------|
| Tensile Strength | 4900 PSI, 34 MPa | ASTM D882 |
| Puncture Resistance | 10 lbs, 44 N | MIL-STD-3010C Method 2065 |
| Seal Strength | 14 lbs, 62 N | ASTM D882 |
| Thickness | 3 mils, .0762 mm +/-15% | MIL-STD-3010C Method 1003 |
| Marking Adhesion | Pass | IPC-TM-650 2.4.1 |
| Transparency | 40% | Tobias |

| Electrical | Typical Value | Testing Method |
|-------------------------------|--------------------------|-------------------|
| ESD Shielding | <10 nJ | ANSI/ESD STM11.31 |
| Surface Resistance - Interior | <1x10 ¹¹ ohms | ANSI/ESD STM11.11 |
| Surface Resistance - Exterior | <1x10 ⁶ ohms | ANSI/ESD STM11.11 |
| Static Decay | < 2 seconds | ETS 406D |
| Charge Retention | <100 volts | CPM-3M TP.21XX |

| Cleanliness | Typical Value | Testing Method |
|-------------|---------------|----------------|
| Silicone | Not Detected | FTIR |

| Heat Sealing Conditions | Typical Value |
|-------------------------|------------------------------|
| Temperature | 300°F – 375°F, 149°C – 190°C |
| Time | 0.5 – 3.5 seconds |
| Pressure | 30 – 70 PSI, 206 – 482 KPa |

This product is intended for commercial use only. This product is not on the Qualified Product Listing under the Defense Standardization Program.

3M™ Metal-Out Static Shielding Bag 1500

3M Metal-Out Static Shielding Bags, Open Top 1500

| Dimensions (W x L in.) | Part No. | Dimensions (W x L in.) | Part No. | Dimensions (W x L in.) | Part No. |
|------------------------|----------|------------------------|----------|------------------------|----------|
| 3 x 5 | 15035 | 8 x 12 | 150812 | 12 x 18 | 1501218 |
| 4 x 6 | 15046 | 9 x 12 | 150912 | 14 x 18 | 1501418 |
| 5 x 8 | 15058 | 10 x 12 | 1501012 | 15 x 18 | 1501518 |
| 6 x 8 | 15068 | 10 x 14 | 1501014 | 16 x 24 | 1501624 |
| 6 x 10 | 150610 | 10 x 24 | 1501024 | 18 x 18 | 1501818 |
| 6 x 30 | 150630 | 11 x 15 | 1501115 | 18 x 24 | 1501824 |
| 7 x 15 | 150715 | 12 x 16 | 1501216 | | |

Custom Sizes and Printing Available.

3M Metal-Out Static Shielding Bags, ZipTop 1500

| Dimensions (W x L in.) | Part No. | Dimensions (W x L in.) | Part No. | Dimensions (W x L in.) | Part No. |
|------------------------|----------|------------------------|----------|------------------------|----------|
| 3 x 5 | 150Z35 | 6 x 8 | 150Z68 | 10 x 12 | 150Z1012 |
| 4 x 4 | 150Z44 | 6 x 10 | 150Z610 | 12 x 18 | 150Z1218 |
| 4 x 6 | 150Z46 | 8 x 10 | 150Z810 | 12 x 18 | 1911218 |

Custom Sizes and Printing Available.

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

* **RoHS 2011/65/EU Compliant** means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty section.


**Lead-free means that the product has less than 2 ppm of lead when tested by ICP-AES, with reference to EPA method 3051A/3052.



Electronic Solutions Division Static Control Products

926 JR Industrial Drive
Sanford, NC 27332
Toll-Free: 866-722-3736
International: 919-718-0000
Email: 3mstaticinfo@mmm.com
www.3Mstatic.com

Please recycle. Printed in USA.
© 3M 2014. All rights reserved.
98-0799-1154-5 JHA



- Standard sizes stocked for prompt shipment (usually same day).
- Width is measured from inside seam to inside seam.
- Length is measured from the top edge to the bottom fold.
- Opening is in the "width" dimension.
- Custom bag sizes, custom printing, and custom hot stamping are available.
- Most sizes are packed 100 per case.
- Small sizes are packed 500 or 1,000 per case.

Tolerance (inches): Width -0, +0.250
Length +/- 0.125 Offset 0 to 0.250
Seal width +/- 0.125

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.