

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0009931300

Status:

Active

Overview:

kk

Description:

3.96mm (.156") Pitch KK® Crimp Terminal Housing, Friction Ramp, 13 Circuits, Glow Wire Compatible

Documents:

3D Model

Drawing (PDF)


Product Specification PS-99020-0087 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	3069
Overview	kk
Product Name	KK®
Physical	
Circuits (maximum)	13
Circuits Detail	13
Color - Resin	Natural
Gender	Female
Glow-Wire Compliant	Yes
Lock to Mating Part	Yes
Material - Resin	Nylon
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.156 In
Pitch - Mating Interface (mm)	3.96 mm
Temperature Range - Operating	0°C to +75°C

Material Info	
Old Part Number	3069-G13

Reference - Drawing Numbers	
Product Specification	PS-99020-0087
Sales Drawing	SD-3069-GN***



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

3069Series


Mates With

2220 , 3190 , 3192 , 3243, 3246, A4042, 41661 , 41662 , 41671 , 41672 , 41681 , 41682 , 41701 , 41711 , 41721 , 41741 , 41761 , 41771 , 41772 , 41791 , 41792 , 42441 , 42461 , 42471 , 42491 , 42492



Use With

2478 Crimp Terminals for 18-24 AWG, 2578 Crimp Terminals for 22-26 AWG


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




OPTIONAL WINDOW DETAIL



RECOMMENDED P/C BOARD



LOCKING
RAMP OPTIONAL
(2.5)
.10



DIRECTION OF
TERMINAL INSERTION.

ENG. No. DESIGNATION

3069 - G N 2

"G" GWT (750°C) PA66 BALCK

"2" INDICATES HOUSING WITHOUT RAMP
"BLANK" INDICATES HOUSING WITH RAMP

NO. OF CKT'S

NOTES:

1. FOR USE WITH TERMINAL No. 2478 OR 2578
2. ASSEMBLED CONNECTOR MATES WITH (1.14)/0.045 SQUARE OR ROUND PIN.
3. EXTENDED PIN ENTRY WINDOWS ARE POSSIBLE.

No. OF CCTS.	C	D	No. OF CCTS.	C	D
14	(51.51 ± .03) 2.028 ± .01	(55.37 ± .03) 2.180 ± .01	2	(3.96 ± .03) .156 ± .005	(7.82 ± .03) .308 ± .01
15	(55.47 ± .03) 2.184 ± .01	(59.33 ± .03) 2.336 ± .01	3	(7.92 ± .03) .312 ± .005	(11.79 ± .03) .464 ± .01
16	(59.44 ± .03) 2.340 ± .01	(63.30 ± .03) 2.492 ± .01	4	(11.89 ± .03) .620 ± .005	(15.75 ± .03) .620 ± .01
17	(63.40 ± .03) 2.496 ± .01	(67.26 ± .03) 2.648 ± .01	5	(15.85 ± .03) .624 ± .005	(19.71 ± .03) .776 ± .01
18	(67.36 ± .03) 2.652 ± .01	(71.22 ± .03) 2.804 ± .01	6	(19.81 ± .03) .780 ± .005	(23.67 ± .03) .932 ± .01
19	(71.32 ± .03) 2.808 ± .01	(75.18 ± .03) 2.960 ± .01	7	(23.77 ± .03) .936 ± .005	(27.64 ± .03) 1.088 ± .01
20	(75.29 ± .03) 2.964 ± .01	(79.15 ± .03) 3.116 ± .01	8	(27.74 ± .03) 1.092 ± .005	(31.60 ± .03) 1.244 ± .01
			9	(31.70 ± .03) 1.248 ± .005	(35.56 ± .03) 1.400 ± .01
			10	(35.66 ± .03) 1.404 ± .005	(39.52 ± .03) 1.556 ± .01
			11	(39.62 ± .03) 1.560 ± .005	(43.48 ± .03) 1.712 ± .01
			12	(43.59 ± .03) 1.716 ± .005	(47.45 ± .03) 1.868 ± .01
			13	(47.55 ± .03) 1.872 ± .005	(51.41 ± .03) 2.024 ± .01

WORKMANAGER ERROR EC NO: E2008-0403 DRAWN:BRUTTE 2008/01/30 CHKD: 2008/01/30 APPR:BMAGUIRE 2008/01/30	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
					MM/IN		4:1	METRIC	⊙ □	
				mm	INCH	DRAWN BY	DATE	TITLE	HOUSING KK CONNECTOR (3.96)/0.156 CRIMP 750 GLOW WIRE VERSION MOLEX INCORPORATED	SHEET NO. 1 OF 2
			4 PLACES	± ---	± ---	BRIAN RUTLE	10/12/2007			
			3 PLACES	± ---	± .010	CHECKED BY	DATE			
			2 PLACES	± 0.25	± .014	B. MAGUIRE	12/12/2007			
			1 PLACE	± 0.35	± ---	APPROVED BY	DATE			
			ANGULAR ± 2 °		B. MAGUIRE	14/12/2007	DOCUMENT NO.	SD-3069-GN***		
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		SEE CHART			
					SIZE A 2		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

	10	9	8	7	6	5	4	3	2	1	
F	No. OF CCTS.	ENG. No.	PART No.	LOCKING RAMP							F
	2	3069-G02	09-93-0200	YES							
		↑ -G022	↑ -94-0200	NO							
	3	-G03	-93-0300	YES							
		-G032	-94-0300	NO							
	4	-G04	-93-0400	YES							
		-G042	-94-0400	NO							
	5	-G05	-93-0500	YES							
		-G052	-94-0500	NO							
	6	-G06	-93-0600	YES							
		-G062	-94-0600	NO							
	7	-G07	-93-0700	YES							
		-G072	-94-0700	NO							
	8	-G08	-93-0800	YES							
		-G082	-94-0800	NO							
	9	-G09	-93-0900	YES							
		-G092	-94-0900	NO							
	10	-G10	-93-1000	YES							
		-G102	-94-1000	NO							
	11	-G11	-93-1100	YES							
		-G112	-94-1100	NO							
	12	-G12	-93-1200	YES							
		-G122	-94-1200	NO							
	13	-G13	-93-1300	YES							
		-G132	-94-1300	NO							
	14	-G14	-93-1400	YES							
		-G142	-94-1400	NO							
	15	-G15	-93-1500	YES							
		-G152	-94-1500	NO							
	16	-G16	-93-1600	YES							
		-G162	-94-1600	NO							
	17	-G17	-93-1700	YES							
		-G172	-94-1700	NO							
	18	-G18	-93-1800	YES							
		-G182	-94-1800	NO							
	19	-G19	-93-1900	YES							
		-G192	-94-1900	NO							
	20	-G20	-93-2000	YES							
		3069-G202	09-94-2000	NO							
E											E
D											D
C											C
B											B
A											A

SEE SHEET 1

EC NO: E2008-0403

DRWN:BRUTTLE

CHKD:

APPR:BMAGUIRE

REV

2008/01/30

2008/01/30

DESCRIPTION

QUALITY SYMBOLS

▽=0

▽=0

2008/01/30

GENERAL TOLERANCES (UNLESS SPECIFIED)

mm

INCH

4 PLACES

3 PLACES

2 PLACES

1 PLACE

± ---

± ---

± 0.25

± 0.35

± ---

± ---

± .010

± .014

ANGULAR ± 2 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE

MM/IN

DRAWN BY

DATE

BRIAN RUTTLE

10/12/2007

CHECKED BY

DATE

B. MAGUIRE

12/12/2007

APPROVED BY

DATE

B. MAGUIRE

14/12/2007

MATERIAL NO.

SEE CHART

SIZE

A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE

1:1

DESIGN UNITS

METRIC

THIRD ANGLE PROJECTION

TITLE

HOUSING KK CONNECTOR (3.96)/0.156 CRIMP 750 GLOW WIRE VERSION

MOLEX INCORPORATED

DOCUMENT NO.

SD-3069-GN***

SHEET NO.

2 OF 2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.