


FP0404

High frequency, high current power inductors



Product features

- High current carrying capacity
- Low core loss
- DC-DC converter applications up to 2 MHz
- Filtering applications see inductance vs frequency and impedance vs frequency curves on page 5
- Inductance Range from 22 nH to 170 nH
- Current range up to 40 A
- 4.0 mm x 4.0 mm footprint surface mount package in 3.0 mm and 4.0 mm heights
- Moisture sensitivity level (MSL): 1
- Ferrite core material

Applications

- Multi-phase and Vcore regulators
- Voltage Regulator Modules (VRMs)
- Server and desktop VRMs and EVRDs
- Laptop and notebook regulators
- Data networking and storage systems
- Graphics cards and battery power systems
- Point-of-Load modules

Environmental data

- Storage temperature range (component): -40 °C to +125 °C
- Operating temperature range: -40 °C to +125 °C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020 (latest revision) compliant



Product specifications


Part number ⁵	OCL ¹ (nH) ±15%	FLL ² (nH) minimum	I _{max} ³ (A)	I _{max} ¹ ⁴ (A)	I _{max} ² ⁵ (A)	I _{max} ³ ⁶ (A)	DCR (mΩ) @ +20 °C ±25%	K-factor ⁷
FP0404R1-R022-R	22 ±20%	15	40	40	34	32	0.32 ± 15%	2351
FP0404R1-R065-R	65	44	40	24	22	20	0.32	2248
FP0404R1-R080-R	80	54	40	19.5	18	16	0.32	2248
FP0404R1-R100-R	100	68	40	15.6	14	13	0.32	2248
FP0404R1-R110-R	110	74.5	40	14.2	13	11.8	0.32	2248
FP0404R1-R170-R	170	116	40	9.0	7.8	7.6	0.32	2248

1. Open Circuit Inductance (OCL) Test parameters: 100 kHz (1 MHz for R022), 0.1 Vrms, 0.0 Adc, +25 °C
 2. Full Load Inductance (FLL) Test parameters: 100 kHz (1 MHz for R022), 0.1 Vrms, I_{max}¹, +25 °C
 3. I_{max}¹: DC current for an approximate temperature rise of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed +125 °C underworst case operating conditions verified in the end application.

4. I_{max}¹: Peak current for approximately 20% rolloff @ +25 °C
 5. I_{max}²: Peak current for approximately 20% rolloff @ +100 °C
 6. I_{max}³: Peak current for approximately 20% rolloff @ +125 °C
 7. K-factor: Used to determine Bp-p for core loss (see graph). Bp-p = K * L * ΔI * 10⁻³. Bp-p:(Gauss), K: (K-factor from table), L: (Inductance in nH), ΔI (Peak to peak ripple current in Amps).
 8. Part Number Definition: FP0404Rx-Rxxx-R
 FP0404 = Product code and size
 Rx= DCR indicator
 Rxxx=Inductance value in μH, R=decimal point
 -R suffix = RoHS compliant

Dimensions (mm)

Part number	C max
R022-R	3.0
R065-R	4.0
R080-R	4.0
R100-R	4.0
R110-R	4.0
R170-R	4.0




Part marking: Rxxx xxx=inductance value in uH, R=decimal point, wly= date code
 All soldering surfaces to be coplanar within 0.1 millimeters
 DCR is measured from point "a" to point "b"
 Do not route traces or vias underneath the inductor

Packaging information (mm)

FP0404R1-R022-R


Supplied in tape and reel packaging, 1,800 parts per 13" diameter reel



Packaging information (mm)


FP0404R1-R065-R, R080-R, R100-R, R110-R, R-170

Supplied in tape and reel packaging, 1,800 parts per 13" diameter reel




Temperature rise vs. total loss

FP0404R1-R022-R




FP0404R1-R065-R, R080-R, R100-R, R110-R, R170




Core loss vs Bp-p

FP0404R1-R022-R




FP0404R1-R065-R, R080-R, R100-R, R110-R, R-170




Inductance vs frequency


FP0404R1-R022-R




FP0404R1-R065-R




FP0404R1-R080-R




FP0404R1-R100-R









FP0404R1-R110-R



FP0404R1-R0170-R




Impedance vs frequency




Inductance characteristics


FP0404R1-R022-R




FP0404R1-R065-R




FP0404R1-R080-R




FP0404R1-R100-R



FP0404R1-R110-R



FP0404R1-R170-R



Solder reflow profile




Table 1 - Standard SnPb solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference JDEC J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak	<ul style="list-style-type: none"> Temperature min. (T_{smin}) Temperature max. (T_{smax}) Time (T_{smin} to T_{smax}) (t_s) 	<ul style="list-style-type: none"> 100 °C 150 °C 60-120 seconds
Average ramp up rate T _{smax} to T _p	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T _L)	183 °C	217 °C
Time at liquidous (t _L)	60-150 seconds	60-150 seconds
Peak package body temperature (T _p)*	Table 1	Table 2
Time (t _p)** within 5 °C of the specified classification temperature (T _c)	20 seconds**	30 seconds**
Average ramp-down rate (T _p to T _{smax})	6 °C/ second max.	6 °C/ second max.
Time 25 °C to Peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.
** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2019 Eaton
All Rights Reserved
Printed in USA
Publication No. 4373 PCN19008
June 2019

Eaton is a registered trademark.
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.