

Step up to Higher Performance Monochrome Graphic & Character LCDs



These new STN LCDs offer designers a range of passive matrix display solutions. Optrex STEP products deliver remarkable readability in any ambient lighting condition, with exceptional performance over a wide operating temperature range.

A Higher Standard for STN

Step up to higher performance in passive matrix monochrome graphic and character LCDs.

Key Features:

- Wide operating temperature (-20 to +70°C) standard
- High contrast ratio up to 80:1
- High brightness up to 100 nits
- High ambient-light legibility
- Built-in controllers
- Selectable interface

Backward Compatible

The new LCDs are available in industry-standard configurations and compatible with existing Optrex LCDs to provide an easy upward migration path for designers.

RoHS Compliant*

All modules are built in complete compliance with the European Union's RoHS (Reduction of Hazardous Substances) directive that restricts the use of certain substances such as lead, mercury and cadmium in electronic equipment.

Range of Colors

Designers can choose from a wide variety of colors to suit their applications.





Graphic LCDs

Featuring built-in controllers, standard operating temperatures of -20° to 70°C, and a luminance of up to 100 nits, these are the “next step” in STN graphic displays. These displays are mechanically compatible and require only a minor change to the software to make them electrically compatible with existing displays.



Part #	Size	Color Background	Dot Format	Module Dimension (mm)	Interface
F-51852	2.8"		128 x 64	89.7 x 49.8 x 6 (low profile)	Selectable 8-bit Parallel or Serial
F-51852	2.8"		128 x 64	89.7 x 49.8 x 11.8	Selectable 8-bit Parallel or Serial
F-51854	4.7"		160 x 128	129.0 x 102.0 x 13.5	8-bit Parallel
F-51851	5.2"		240 x 64	135.2 x 51.7 x 9.8	8-bit Parallel


Character LCDs

Offering a 5V power supply, standard operating temperatures of -20° to 70°C, and a luminance of up to 70 nits, these LCDs are the new generation in STN character displays. They are mechanically and electrically compatible with existing displays for an easy upward migration path.



Part #	Color	Dot Format	Module Dimension (mm)	Interface
C-51848	W G B	16 character x 2 line	122.0 x 44.0 x 14.6	8-bit Parallel
C-51505	W G B B B	20 character x 2 line	116.0 x 37.0 x 15.7	8-bit Parallel
C-51847	W G B	20 character x 4 line	98.5 x 61.0 x 15.6	8-bit Parallel
C-51850	W G B	40 character x 2 line	182.0 x 34.5 x 15.1	8-bit Parallel
C-51849	W G	40 character x 4 line	190.0 x 54.0 x 14.6	8-bit Parallel

A Higher Standard for STN



Take the Next Step...

[Detailed Product Information](#)

[Request a Product Quote](#)

[Contact a Representative in your area](#)

[Engineering Resources](#)

[Free Optrex Newsletter](#)

Optrex America, Inc.
46723 Five Mile Road
Plymouth, Michigan 48170

Telephone: (734) 416-8500
Fax: (734) 416-8520

Released June 2006 | Copyright © 1998-2006 Optrex America, Inc.

These specifications are subject to change without notice. Please check with OPTREX prior to designing equipment using this information.

* RoHS compliance is based upon Optrex America's understanding of RoHS and Optrex America's knowledge of the materials used by the manufacturer in its products.

All trademarks are the property of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.