

CoreModule® 920

Extreme Rugged™ PCI/104-Express 3rd Generation
Intel® Core™ Processor Single Board Computer



Features

- Dual-core 3rd Generation Intel® Core™ Processor
- Up to 4GB industrial grade solder-down ECC 1600MHz DDR3 memory
- One HDMI, one VGA, and one 18/24-bit LVDS display interfaces
- 8GB industrial grade Solid State Disk
- one PCIe x16 (Gen 3) and 1 x4 or 4 x1 (Gen 2)
- Two SATA 6 Gb/s ports, two Gigabit Ethernet, four USB 2.0 interfaces, and two serial ports
- PCI/104-Express Type 1 and PCI/104 expansion interfaces
- Extended Temperature: -40°C to +85°C
- 50% thicker PCB for high vibration environments



Choose Ampro by ADLINK™ CoreModule® 920 for...

A small form factor high performance single board computer for extreme rugged and mobile environments.

Description

The Ampro by ADLINK™ CoreModule 920 is a PCI/104-Express Type 1 compatible single board computer with dual-core 3rd Generation Intel® Core™ processor. The CoreModule 920 is designed Extreme Rugged to support the extremes of shock, vibration, humidity, and temperature.

Specifications

Core System

CPU	Intel® Core™ i7-3517UE 1.7GHz (up to 2.8GHz Turbo), 4MB L3 cache, 17W, dual core Intel® Celeron® 807UE 1.0GHz, 1MB L3 cache, 10W, single core
Chipset	Mobile Intel® QM67 Express Chipset (PCH)
Memory	2 or 4GB single channel industrial grade solder down ECC 1600 MHz DDR3 memory
BIOS	AMI EFI with CMOS backup in 16 Mb SPI flash
Hardware Monitor	Supply voltages and CPU temperature
Watchdog Timer	Programmable timer range to generate RESET
Expansion Busses	PCI/104 (32-bit 33/66MHz) PCI/104-Express Type 1 with PCI Express x16 (Gen3) bus LPC bus, SMBus (system), I²C (user)
Technologies	PAVP 3.0, Intel® AMT 8.0, Intel® VT, Intel® AES-NI, Intel® HT, Intel® HD Graphics with Dynamic Frequency, Intel® Turbo Boost, Dynamic Turbo, Intel® AVX 1.0, Intel® Quick Sync Video

Video

Integrated in Processor	HD Graphics 4000 at 350-1000 MHz
Integrated Video	DirectX 11.0, OpenGL 3.1, and OCL 1.1
Media Processing	Decode (HW JPEG & MJPEG decode), encode (full HW MPEG2 encode), transcode Intel® Clear Video HD Technology + enhanced media processing
VGA Interface	Analog VGA support with 300 MHz DAC Analog monitor support up to QXGA (2048 x 1536) and VGA hot plug
LVDS Interface	Dual-channel 18/24-bit LVDS
Digital Display Interface	One DVI

Audio

Chipset	Integrated on mobile Intel® QM67 Express Chipset, available on HDMI port
---------	--

LAN

10/100/1000Mbps	Two GbE: one from PCH using Intel® 82579 PHY, one from Intel® 82574 MAC/PHY
-----------------	---

Multi I/O

Chipset	Integrated on mobile Intel® QM67 Express Chipset
USB	Four USB 2.0 ports (plus two to the PCI/104-Express stack)
SATA	Two SATA 6 Gb/s (plus two SATA 3 Gb/s to the PCI/104-Express stack) with support for RAID 0,1,5,10

Serial Ports

Two RS-232 Serial ports implemented in LPC based Super I/O

Power Specifications

Input Power	5V (3.3V and 12 V if required by the PCI/104-Express stack)
Power States	Supports S1, S4, S5
Power Consumption	9W typical

Mechanical and Environmental

Size	106 mm x 96 mm, PCI/104-Express form factor compatible
Board Thickness	0.093" (2.36 mm thick)
Temperature	Standard: -20°C to +70°C Extended: -40°C to +85°C (CPU throttling at 800MHz, no throttling to +75°C) Storage: -55°C to +85°C
Humidity	90% at 60°C non-condensing
Shock	50G peak-to-peak, 11ms duration, MIL-STD-202G Method 213B
Vibration	Operating: 11.96 Grms, 50-20,000 Hz, each axis, MIL-STD-202G Method 214A
Certifications	CE, FCC, HALT

Operating Systems

Standard Support	Windows 7, Linux
Extended Support (BSP)	Windows Embedded Standard 7, Windows Embedded Standard 2009, Windows Embedded Compact 7, VxWorks 6.9, QNX 6.5

Ordering Information

Model Number	Description/Configuration
CM-920-R-10	PCI/104-Express with Intel® Celeron 807UE 1.0GHz, 10W, 2GB solder down DDR3 1066 memory, 8GB SSD, 18/24 bit LVDS, VGA, HDMI, SATA, PCI Express, PCI
CM-920-R-17	PCI/104-Express with Intel® Core™ i7-3517UE 1.7GHz, 17W, 2GB solder down DDR3 1066 memory, 8GB SSD, 18/24 bit LVDS, VGA, HDMI, SATA, PCI Express, PCI
CM-920-L-10	CM-920 Quick Start Kit includes CM-920-R-10, cable kit, CM920-TM-CU. USB stick with BSP/drivers and manuals
CM-920-L-17	CM-920 Quick Start Kit includes CM-920-R-17, cable kit, CM920-TM-CU. USB stick with BSP/drivers and manuals
CM-920-X-01	CM-920 cable kit (RoHS). Additional cables to be defined as required for extreme rugged pin headers
CM-920-TM-AL	CM-920 Aluminum Heatspreader
CM-920-TM-CU	CM-920 Copper Heatsink
CM-920-TM-FAN	CM-920 Aluminum Heatsink with FAN



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.