

## Features

## Unregulated Converters

- Ultra-compact size - only 8.3 x 8.3 x 6.8mm
- 1kVDC/1s or 2kVDC/1s basic isolation
- Optional continuous short circuit protected
- Fully encapsulated
- UL and EN certified, CB report
- Efficiency to 84%

**RECOM**  
DC/DC Converter

## RNM

**1 Watt  
DIP6  
Single Output**



**UL**  
E358085



### Description

The RNM series DC/DC converters are ultra-compact isolated single output converters for applications where board space is at a premium. Despite their small size, the converters are fully featured with a full industrial operating temperature range of -40°C to +85°C without derating (+100°C with derating), 1kVDC or 2kVDC isolation and optional short circuit protection. The converters are also UL-60950-1 and EN-60950-1 certified and have a CB Report.

### Selection Guide


| Part Number                 | nom. Input Voltage [VDC] | Output Voltage [VDC] | Output Current [mA] | Efficiency typ. <sup>(1)</sup> [%] | max. Capacitive Load <sup>(2)</sup> [μF] |
|-----------------------------|--------------------------|----------------------|---------------------|------------------------------------|------------------------------------------|
| RNM-xx3.3S <sup>(3,4)</sup> | 3.3, 5, 12, 15           | 3.3                  | 303                 | 75                                 | 2200                                     |
| RNM-xx05S <sup>(3,4)</sup>  | 3.3, 5, 12, 15           | 5                    | 200                 | 70-82                              | 1000                                     |
| RNM-xx09S <sup>(3,4)</sup>  | 3.3, 5, 12, 15           | 9                    | 111                 | 70-78                              | 1000                                     |
| RNM-xx12S <sup>(3,4)</sup>  | 3.3, 5, 12, 15           | 12                   | 83                  | 76-80                              | 470                                      |
| RNM-xx15S <sup>(3,4)</sup>  | 3.3, 5, 12, 15           | 15                   | 66                  | 78-84                              | 470                                      |

#### Notes:

Note1: Efficiency is tested at nominal input and full load at +25°C ambient

Note2: Max Cap Load is tested at nominal input and full resistive load and is defined as the capacitive load that will allow start up in under 1s without damage to the converter

### Model Numbering



#### Notes:

Note3: standard part is without continuous short circuit protection  
add suffix „/P“ for continuous short circuit protection

Note4: add suffix „/H“ for 2kVDC/1s isolation  
or add suffix „/HP“ for continuous short circuit protection and 2kVDC/1s Isolation

#### Ordering Examples:

RNM-0505S/P: 5V Input Voltage, 5V Output Voltage, Single Output with continuous short circuit protection

RNM-0505S/HP: 5V Input Voltage, 5V Output Voltage, Single Output with 2kVDC/1s Isolation and continuous short circuit protection




UL60950-1 certified\*  
CAN/CSA-C22.2 No. 60950-1-07 certified\*  
IEC/EN60950-1 certified

**Specifications** (measured @ Ta= 25°C, nom. Vin and full load otherwise stated)

### BASIC CHARACTERISTICS

| Parameter                    | Condition | Min.  | Typ.   | Max.     |
|------------------------------|-----------|-------|--------|----------|
| Input Voltage Range          |           |       | ±10%   |          |
| Minimum Load                 |           | 0%    |        |          |
| Internal Operating Frequency |           | 50kHz | 100kHz | 105kHz   |
| Output Ripple and Noise      | 20MHz BW  |       |        | 100mVp-p |

### Efficiency vs. Load



### REGULATIONS


| Parameter                      | Condition             |               | Value                  |
|--------------------------------|-----------------------|---------------|------------------------|
| Output Accuracy                |                       |               | ±5.0% max.             |
| Line Regulation                | low line to high line |               | ±1.2% of 1.0% Vin typ. |
| Load Regulation <sup>(5)</sup> | 10% to 100% load      | 3.3Vout       | 20.0% max.             |
|                                |                       | 5Vout         | 15.0% max.             |
|                                |                       | 9, 12, 15Vout | 10.0% max.             |

continued on next page




**Notes:**

Note5: Operation below 10% load will not harm the converter, but specifications may not be met

**Tolerance Envelope**



**Deviation vs. Load**



**Specifications** (measured @ Ta= 25°C, nom. Vin and full load otherwise stated)

**PROTECTIONS**

| Parameter                        | Type                               |                     | Value                                                                                 |
|----------------------------------|------------------------------------|---------------------|---------------------------------------------------------------------------------------|
| Short Circuit Protection (SCP)   | without suffix<br>with suffix "/P" |                     | 1 second<br>continuous                                                                |
| Isolation Voltage <sup>(6)</sup> | I/P to O/P                         | without suffix      | tested for 1 second<br>rated for 1 minute                                             |
|                                  |                                    | with suffix<br>"/H" | tested for 1 second<br>rated for 1 minute                                             |
| Isolation Resistance             |                                    |                     | 1kVDC<br>500VAC/60Hz                                                                  |
| Isolation Capacitance            |                                    |                     | 2kVDC<br>1kVAC/60Hz                                                                   |
| Insulation Grade                 |                                    |                     | 10GΩ min.<br>20pF min. / 75pF max.<br>basic (IEC/EN60950-1)<br>functional (UL60950-1) |

**Notes:**

Note6: For repeat Hi-Pot testing, reduce the time and/or the test voltage


Note7: Refer to local safety regulations if input over-current protection is also required. Recommended fuse: slow blow type

**ENVIRONMENTAL**

| Parameter                   | Condition                                   |                | Value                                                         |
|-----------------------------|---------------------------------------------|----------------|---------------------------------------------------------------|
| Operating Temperature Range | full load @ free air convection (see graph) |                | -40°C to +85°C                                                |
| Operating Altitude          |                                             |                | 2000m                                                         |
| Operating Humidity          | non-condensing                              |                | 95% RH max.                                                   |
| Pollution Degree            |                                             |                | PD2                                                           |
| MTBF                        | according to MIL-HDBK-217F, G.B.            | +25°C<br>+85°C | 22900 x 10 <sup>3</sup> hours<br>9100 x 10 <sup>3</sup> hours |

**Derating Graph**

(@ free air convection)



### Specifications (measured @ Ta= 25°C, nom. Vin and full load otherwise stated)

#### SAFETY AND CERTIFICATIONS

| Certificate Type (Safety)                                                                     | Report / File Number | Standard                                                                      |
|-----------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------|
| Information Technology Equipment, General Requirements for Safety <sup>®</sup>                | E358085              | UL60950-1, 2nd Edition:2007<br>CAN/CSA C22.2 No. 60950-1-07, 2nd Edition:2007 |
| Information Technology Equipment, General Requirements for Safety                             | 1602031              | IEC60950-1:2005, 2nd Edition + A2:2013<br>EN60950-1:2006 + A2:2013            |
| Information Technology Equipment, General Requirements for Safety <sup>®</sup><br>(CB Scheme) | US-13859-UL          | IEC60950-1:2005, 2nd Edition                                                  |
| EAC                                                                                           | RU-AT.49.09571       | TP TC 004/2011                                                                |
| RoHS 2+                                                                                       |                      | RoHS-2011/65/EU + AM-2015/863                                                 |


#### Notes:

Note8: suffix "P" excluded

#### DIMENSION AND PHYSICAL CHARACTERISTICS

| Parameter         | Type                   | Value                                                                            |
|-------------------|------------------------|----------------------------------------------------------------------------------|
| Material          | case<br>potting<br>PCB | non-conductive black plastic, (UL94 V-0)<br>epoxy, (UL94 V-0)<br>FR4, (UL94 V-0) |
| Dimension (LxWxH) |                        | 8.3 x 8.3 x 6.8mm                                                                |
| Weight            |                        | 1.1g typ.                                                                        |

#### Dimension Drawing (mm)



#### Pinning information

| Pin # | Single |
|-------|--------|
| 1     | -Vin   |
| 3     | +Vin   |
| 4     | +Vout  |
| 5     | -Vout  |

Tolerance: xx.x=  $\pm 0.5$ mm  
xx.xx=  $\pm 0.25$ mm

#### PACKAGING INFORMATION

| Parameter                   | Type           | Value                 |
|-----------------------------|----------------|-----------------------|
| Packaging Dimension (LxWxH) | tube           | 530.0 x 14.0 x 10.0mm |
| Packaging Quantity          |                | 60pcs                 |
| Storage Temperature Range   |                | -55°C to +125°C       |
| Storage Humidity            | non-condensing | 95% RH max.           |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.