

Three Phase Bridge (Power Modules), 25/35 A



D-63

FEATURES

- Universal, 3 way terminals: push-on, wrap around or solder
- High thermal conductivity package, electrically insulated case
- Center hole fixing
- Excellent power/volume ratio
- UL E300359 approved
- Gold plated terminals solderable using lead (Pb)-free solder; solder alloy Sn/Ag/Cu (SAC305); solder temperature 260 to 275 °C
- RoHS compliant
- Designed and qualified for industrial and consumer level


RoHS
COMPLIANT

PRODUCT SUMMARY

| | |
|-------|---------|
| I_o | 25/35 A |
|-------|---------|

DESCRIPTION

A range of extremely compact, encapsulated three phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and instrumentation applications.

MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL | CHARACTERISTICS | 26MT | 36MT | UNITS |
|-----------|-----------------|-------------|------|------------------|
| I_o | | 25 | 35 | A |
| | T_c | 70 | 60 | °C |
| I_{FSM} | 50 Hz | 360 | 475 | A |
| | 60 Hz | 375 | 500 | |
| I^2t | 50 Hz | 635 | 1130 | A ² s |
| | 60 Hz | 580 | 1030 | |
| V_{RRM} | | 100 to 1600 | | V |
| T_J | | - 55 to 150 | | °C |

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

| TYPE NUMBER | VOLTAGE CODE | V_{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V | I_{RRM} MAXIMUM AT T_J MAXIMUM mA |
|---------------|--------------|--|--|--|
| 26MT../36MT.. | 10 | 100 | 150 | 2 |
| | 20 | 200 | 275 | |
| | 40 | 400 | 500 | |
| | 60 | 600 | 725 | |
| | 80 | 800 | 900 | |
| | 100 | 1000 | 1100 | |
| | 120 | 1200 | 1300 | |
| | 140 | 1400 | 1500 | |
| | 160 | 1600 | 1700 | |

| FORWARD CONDUCTION | | | | | | | |
|--|---------------|--|---------------------------|--------------------------------|--------|-------------------|------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | | UNITS | |
| | | | | 26MT | 36MT | | |
| Maximum DC output current at T_C | I_O | 120° rect. conduction angle | | 25 | 35 | A | |
| | | | | 70 | 60 | °C | |
| Maximum peak, one-cycle non-repetitive forward current | I_{FSM} | t = 10 ms | No voltage reapplied | Initial $T_J = T_J$ maximum | 360 | 475 | A |
| | | t = 8.3 ms | | | 375 | 500 | |
| | | t = 10 ms | 100 % V_{RRM} reapplied | | 300 | 400 | |
| | | t = 8.3 ms | | | 314 | 420 | |
| Maximum I^2t for fusing | I^2t | t = 10 ms | No voltage reapplied | | 635 | 1130 | A ² s |
| | | t = 8.3 ms | | | 580 | 1030 | |
| | | t = 10 ms | 100 % V_{RRM} reapplied | | 450 | 800 | |
| | | t = 8.3 ms | | | 410 | 730 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | I^2t for time $t_x = I^2\sqrt{t} \times \sqrt{t_x}$; $0.1 \leq t_x \leq 10$ ms, $V_{RRM} = 0$ V | | 6360 | 11 300 | A ² √s | |
| Low level of threshold voltage | $V_{F(TO)1}$ | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum | | 0.88 | 0.86 | V | |
| High level of threshold voltage | $V_{F(TO)2}$ | $(I > \pi \times I_{F(AV)})$, T_J maximum | | 1.13 | 1.03 | | |
| Low level forward slope resistance | r_{t1} | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum | | 7.9 | 6.3 | mΩ | |
| High level forward slope resistance | r_{t2} | $(I > \pi \times I_{F(AV)})$, T_J maximum | | 5.2 | 5.0 | | |
| Maximum forward voltage drop | V_{FM} | $T_J = 25$ °C, $I_{FM} = 40$ Apk - per single junction | | 1.26 | 1.19 | V | |
| Maximum DC reverse current | I_{RRM} | $T_J = 25$ °C, per junction at rated V_{RRM} | | 100 | | μA | |
| RMS isolation voltage | V_{INS} | $T_J = 25$ °C, all terminal shorted; f = 50 Hz, t = 1 s | | 2700 | | V | |

| THERMAL - MECHANICAL SPECIFICATIONS | | | | | | |
|--|----------------|---|--|-------------|------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | | UNITS |
| | | | | 26MT | 36MT | |
| Maximum junction and storage temperature range | T_J, T_{Stg} | | | - 55 to 150 | | °C |
| Maximum thermal resistance, junction to case | R_{thJC} | DC operation per bridge (based on total power loss of bridge) | | 1.42 | 1.35 | K/W |
| Maximum thermal resistance, case to heatsink | R_{thCS} | Mounting surface, smooth, flat and greased | | 0.2 | 0.2 | |
| Approximate weight | | | | 20 | | g |
| Mounting torque ± 10 % | | Bridge to heatsink with screw M4 | | 2.0 | | Nm |



Three Phase Bridge
(Power Modules), 25/35 A

Vishay High Power Products




Fig. 1 - Current Ratings Characteristics



Fig. 2 - Forward Voltage Drop Characteristics





Fig. 3 - Total Power Loss Characteristics



Fig. 4 - Maximum Non-Repetitive Surge Current



Fig. 5 - Maximum Non-Repetitive Surge Current

26MT../36MT.. Series



Vishay High Power Products Three Phase Bridge
(Power Modules), 25/35 A



Fig. 6 - Current Ratings Characteristics



Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Total Power Loss Characteristics



Fig. 9 - Maximum Non-Repetitive Surge Current



Fig. 10 - Maximum Non-Repetitive Surge Current




Fig. 11 - Thermal Impedance Z_{thJC} Characteristics



Fig. 12 - Thermal Impedance Z_{thJC} Characteristics

D-63

DIMENSIONS in millimeters (inches)



Suggested plugging force:
400 N maximum;
axially applied to fast on terminals

Not to scale



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.