

The 89 Series is a high-performance axial type resistor. These molded-construction metal-housed resistors are available in higher power ratings than standard axial resistors and are better suited to withstanding vibration, shock and harsh environmental conditions.

The 89 Series Metal-Mite® resistors are aluminum housed to maintain high stability during operation and to permit secure mounting to chassis surfaces.

The metal housing also provides heat-sinking capabilities.

## FEATURES

- High Stability:  $\pm 0.5\%$   $\Delta R$ .
- High power to size ratio.
- Metal housing allows chassis mounting and provides heat sink capability.

**As of September 2006, the 89 Series is no longer offered as Mil. Spec.**

## SPECIFICATIONS

### Material

**Housing:** Metal, anodized aluminum.

**Internal Coating:** Silicone.

**Core:** Ceramic.

**Terminals:** Solder-coated axial.

**Derating:** Linearly from 100% @ +25°C to 0% @ +275°C.

### Electrical

**Tolerance:**  $\pm 1\%$  and  $\pm 5\%$  (other tolerances available).

**Power rating:** Rating is based on chassis mounting area and temperature stability. Proper heat sink as follows: 5W and 10W units, 4" x 6" x 2" x .040" Aluminum chassis; 25W units, 5" x 7" x 2" x .040" Aluminum chassis; 50W units, 12" x 12" x .059" Aluminum panel.

### Maximum ohmic values:

See chart.

**Overload:** 5 times rated wattage for 5 seconds.

### Temperature coefficient:

Under 1Ω:  $\pm 90$  ppm/°C  
1 to 9.99Ω:  $\pm 50$  ppm/°C  
10Ω and over:  $\pm 20$  ppm/°C.


### Dielectric withstanding voltage:

5W and 10W rating, 1000 VAC;  
25 and 50W ratings, 2250 VAC.



# 89 Series

## Metal-Mite® Aluminum Housed Axial Term. Wirewound, 1% Tolerance



Series	Wattage	Ohms	Voltage
805	5	0.10-25K	210
810	10	0.10-50K	320
825	25	0.005-75K	520
850	50	0.005-100K	1170

Non-Inductive versions available. Insert "N" before tolerance code. Example: 850NF560

Series (Industrial)	Dimensions			
	5 watt	10 watt	25 watt	50 watt
805	810	825	850	
Dim. A (in. $\pm 0.062$ / mm $\pm 1.57$ )	1.125 / 28.59	1.375 / 34.93	1.938 / 49.23	2.781 / 70.64
Dim. B (in. $\pm 0.010$ / mm $\pm 0.25$ )	0.490 / 12.45	0.625 / 15.88	0.781 / 19.84	0.844 / 21.44
Dim. C (in. $\pm 0.031$ / mm $\pm 0.79$ )	0.078 / 1.98	0.094 / 2.39	0.172 / 4.37	0.188 / 4.78
Dim. D (in. $\pm 0.010$ / mm $\pm 0.25$ )	0.444 / 11.28	0.562 / 14.28	0.719 / 18.26	1.562 / 39.68
Dim. E (in. $\pm 0.062$ / mm $\pm 1.57$ )	0.600 / 15.24	0.750 / 19.05	1.062 / 26.98	1.938 / 49.23
Dim. F (in. $\pm 0.062$ / mm $\pm 1.57$ )	0.266 / 6.76	0.312 / 7.93	0.438 / 11.13	0.438 / 11.13
Dim. G (in. $\pm 0.062$ / mm $\pm 1.57$ )	0.334 / 8.48	0.438 / 11.13	0.531 / 13.49	0.594 / 15.09
Dim. H (in. $\pm 0.031$ / mm $\pm 0.79$ )	0.245 / 6.22	0.312 / 7.93	0.391 / 9.93	0.422 / 10.72
Dim. J (in. $\pm 0.031$ / mm $\pm 0.79$ )	0.646 / 16.41	0.812 / 20.63	1.094 / 27.79	1.156 / 29.36
Dim. K (in. $\pm 0.005$ / mm $\pm 0.13$ )	0.093 / 2.36	0.094 / 2.39	0.125 / 3.18	0.125 / 3.18
Dim. L (in. $\pm 0.031$ / mm $\pm 0.79$ )	0.320 / 8.13	0.406 / 10.31	0.562 / 14.28	0.625 / 15.88
Dim. M (in. $\pm 0.062$ / mm $\pm 1.57$ )	0.133 / 3.38	0.203 / 5.16	0.281 / 7.14	0.312 / 7.92
Dim. N (in. $\pm 0.031$ / mm $\pm 0.79$ )	0.065 / 1.65	0.094 / 2.39	0.094 / 2.39	0.094 / 2.39
Dim. P (in. $\pm 0.005$ / mm $\pm 0.13$ )	0.050 / 1.27	0.085 / 2.16	0.085 / 2.16	0.085 / 2.16
Q min AWG	16	12	12	12
Dim. R (in., min/mm, min)	0.085/ 2.16	0.140/ 3.56	0.140/ 3.56	0.140/ 3.56

## ORDERING INFORMATION

Non-Inductive Winding  
Optional (blank = std. winding)

**805NF5R0E**

<b>Series</b> 805 = 5 Watt 810 = 10 watt 825 = 25 watt 850 = 50 watt	<b>Tolerance</b> F = 1% J = 5%	<b>Ohms</b> R005 = 0.005Ω R10 = 0.1Ω R10 = 1.0Ω 250 = 250Ω 1K0 = 1,000Ω 1K5 = 1,500Ω 25K = 25,000Ω	<b>RoHS Compliant</b>
--	--------------------------------------	---	-----------------------

## STANDARD PART NUMBERS

Ohmic value	Wattage				Ohmic value	Wattage				Ohmic value	Wattage				
	Part No. Prefix Suffix	5	10	25		50	Part No. Prefix Suffix	5	10		25	50	Part No. Prefix Suffix	5	10
0.005	R005				20	20R				1,500	1K5				
0.010	R010				25	25R				2,000	2K0				
0.025	R025				30	30R				2,500	2K5				
0.1	R10				40	40R				3,000	3K0				
0.3	R30				50	50R				3,500	3K5				
0.5	R50				75	75R				4,000	4K0				
0.7	R70				100	100				4,500	4K5				
1.0	R10				150	150				5,000	5K0				
1.5	R15				200	200				6,000	6K0				
2.0	R20				250	250				10,000	10K				
3.0	R30				300	300				15,000	15K				
4.0	R40				400	400				20,000	20K				
5.0	R50				500	500				25,000	25K				
10.0	R10				750	750				50,000	50K				
15.0	R15				1,000	1K0				75,000	75K				
										100,000	100K				

✓ = Standard values  
✦ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Check product availability at [www.ohmite.com](http://www.ohmite.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.