



har-flexicon terminal block horizontal, screwing, SMC



General information

		PCB Terminal Block				
Design	Type	3,50/3,81 TTSH	5,00 TTSH 1,5mm ²	5,00 TTSH 2,5mm ²	10,16 TTSH	15,00 TTSH
Part numbers		1402xx14402xxx 1402xx15402xxx	1402xx16402xxx	1402xx16404xxx	1402xx25402xxx	1402xx27402xxx
Contact pitch		3,5 mm/3,81mm	5mm	5,08mm	10,16mm	15mm
No. of contacts		2 - 12 poles	2 - 12 poles	2 - 8 poles	2 - 4 poles	2 - 4 poles
Rated surge voltage (II/2) ¹⁾		2,5 kV	4 kV	4 kV	8 kV	8 kV
Rated surge voltage (III/2) ¹⁾		2,5 kV	4 kV	4 kV	8 kV	8 kV
Rated surge voltage (III/3) ¹⁾		2,5 kV	4 kV	4 kV	8 kV	8 kV
Rated Voltage		300 V	300 V	300 V	600 V	600 V
Rated voltage (II/2) ¹⁾		300 V	600 V	600 V	1000 V	1000 V
Rated voltage (III/2) ¹⁾		150 V	300 V	300 V	1000 V	1000 V
Rated voltage (III/3) ¹⁾		150 V	220 V	300 V	1000 V	1000 V
Working current		12 A	13,5 A	17,5 A	60 A	135 A
Usegroup B, rated voltage / current		300 V / 12 A	300 V / 13,5 A	300 V / 17,5 A	300 V / 60 A	600 V / 135 A
Usegroup C, rated voltage / current		- / -	- / -	- / -	300 V / 60 A	600 V / 135 A
Usegroup D, rated voltage / current		300 V / 12 A	300 V / 13,5 A	300 V / 17,5 A	600 V / 5 A	- / -
Contact resistance		max. 15 mOhm				
Insulation resistance		min. 10 ⁹ Ohm (500 V DC)				
Temperature range		-40°C ... +110°C				
Termination technology		THR/SMC Reflow				
PCB thickness		-	-	-	max. 2,4mm	max. 2,4mm
Insertion force		n.a				
Withdrawal force		n.a				
Hot plugging		No				
Mechanical Shock IEC 61373 (05/10)		5 g, 30 ms, 5 shocks/axis and each direction no contact disturbance >= 1µs				
Random Vibration IEC 61373 (05/10)		Cat 1 class B 5,72m/s ² no contact disturbance >= 1µs				
RoHS - compliant		Yes				
UL file		E314677				

Isulator material

Material	PA/PPA
Color	black
UL classification	UL 94-V0
Material group acc. to IEC 60664-1	I (CTI > 600)

Contact material

Contact material	Copper alloy
Plating termination zone	Sn
Plating contact zone	Ni

Derating

The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals.
The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60512-5



¹⁾(overvoltage cat. / pollution degree)

Soldering instructions for lead-free tin soldering



preheating	T0	25°C (77°F)
	T1	from 150°C (302°F) to 190°C (374°F)
	time	from 150s to 180s
	gradient	1,5°C/s (34°F/s)
peak	Tpeak	from 260°C (500°F) to 275°C (527°F)
	time	from 10s to 30s

har-flexicon SMC products with pure tin plated pins without lead, can be soldered by a lead-free reflow process, with a peak temperature till 275°C/527°F according to the related profile.

Cable connection

Type	3,50/3,81 TTSH	5,00 TTSH 1,5mm ²	5,08 TTSH 2,5mm ²	10,16 TTSH	15,00 TTSH
Part numbers	1402xx14402xxx 1402xx15402xxx	1402xx16402xxx	1402xx16404xxx	1402xx25402xxx	1402xx27402xxx
Conductor size AWG max	16 AWG	16 AWG	12 AWG	6 AWG	1 AWG
Conductor size AWG min	28 AWG	30 AWG	30 AWG	20 AWG	20 AWG
Conductor size solid max	1,5 mm ²	1,5 mm ²	2,5 mm ²	16 mm ²	35 mm ²
Conductor size solid min	0,05 mm ²	0,05 mm ²	0,05 mm ²	0,5 mm ²	0,5 mm ²
Conductor size stranded max	1 mm ²	1,0 mm ²	2,5 mm ²	10 mm ²	25 mm ²
Conductor size stranded min	0,05 mm ²	0,05 mm ²	0,05 mm ²	0,5 mm ²	0,5 mm ²
Conductor size stranded for end sleeve					
Stripping length max	6 mm	6 mm	6,5 mm	11,5 mm	18 mm
Stripping length min	5 mm	5 mm	5,5 mm	10,5 mm	18 mm
Screw thread	M2	M3	M3	M4	M5
Tightening Torque max	0,25 Nm	0,6 Nm	0,6 Nm	1,5 Nm	2,5 Nm
Tightening Torque min	0,20 Nm	0,5 Nm	0,5 Nm	1,2 Nm	2,1 Nm

Packging unit

types 3.50/3.81/5.00/5.08 TTSH					
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark
tropical bag	2 - 3	100	100	000	
tropical bag	4 - 5	75	75	000	
tropical bag	6 - 12	50	50	000	
box	2 - 12	1	1	333	samples
type 10.16 TTSH					
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark
tropical bag	2 - 3	50	50	000	
tropical bag	4	40	40	000	
box	2 - 4	1	1	333	sample
type 15.00 TTSH					
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark
tropical bag	2	50	50	000	
tropical bag	3	40	40	000	
tropical bag	4	30	30	000	
box	2 - 4	1	1	333	sample



	All rights reserved	Created by	Inspected by	Standardisation	Date	State
	Department EC PD - CN	ZHUANGJ	LUOK	HOFFMANN	2017-12-15	Final Release
Title						Doc-Key / ECM-Nr. 100542555/UGD/001/E 500000129104
har-flexicon terminal block horizontal, screwing, SMC						
HARTING Electronics GmbH		Type	Number	Rev.		
D-32339 Espelkamp		DS	14027301801	E		
						Page
						1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[14020816402000](#) [14021016402000](#) [14020216404000](#) [14020316402000](#) [14020316404000](#) [14020414402000](#)
[14020416404000](#) [14020516404000](#) [14021214402000](#) [14020416402000](#) [14020516402000](#) [14020814402000](#)
[14020216402000](#) [14020616402000](#) [14021014402000](#) [14020214402000](#) [14020314402000](#) [14020614402000](#)
[14021216402000](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.