M85049 Backshells
D38999 & MS27 Protective Caps

SUNBANK

# High Performance Backshells and Caps

**SUNBANK products define the standard for highly reliable, environment resisting, electrically passive components. We offer a full range of backshells and caps in different materials and platings.**

**Highest reliability**
- Qualified according to:
  . AS85049
  . MIL-DTL-38999
  . MS27501/MS27502

**Designed for a wide range of qualified products**
- Available for most of the standard connectors known on the market.

**Many plating options**
- High corrosion resistance and electrical continuity properties.

Esterline
Connection Technologies

# Overview

| Backshell style | Connector type | AS85049 Series |
|---|---|---|
| Cable clamp strain relief | MIL-DTL-38999 Series III & IV<br>EN3645 | AS85049/38 - *see p.03* |
| | MIL-DTL-27599<br>MIL-DTL-38999 Series I & II | AS85049/49-2 - *see p.05* |
| | MIL-DTL-5015 crimp<br>MIL-DTL-26482 Series 2<br>AS81703 Series 3<br>MIL-DTL-83723 Series 1 & 3 | AS85049/43 - *see p.04*<br>AS85049/51 - *see p.06*<br>AS85049/52 - *see p.07* |
| One arm strain relief | MIL-DTL-5015 crimp<br>MIL-DTL-26482 Series 2<br>AS81703 Series 3<br>MIL-DTL-83723 Series 1 & 3 | AS85049/53 - *see p.08*<br>AS85049/54 - *see p.08*<br>AS85049/55 - *see p.08* |
| Shrink boot adapter | MIL-DTL-5015 crimp<br>MIL-DTL-26482 Series 2<br>AS81703 Series 3<br>MIL-DTL-83723 Series 1 & 3 | AS85049/60-1 - *see p.09* |
| | MIL-DTL-27599<br>MIL-DTL-38999 Series I & II | AS85049/62 - *see p.10* |
| | MIL-DTL-38999 Series III & IV<br>EN3645 | AS85049/69 - *see p.11* |
| Banding backshell<br>with self-locking | MIL-DTL-5015 crimp<br>MIL-DTL-26482 Series 2<br>AS81703 Series 3<br>MIL-DTL-83723 Series 1 & 3 | AS85049/82 - *see p.12*<br>AS85049/83 - *see p.12*<br>AS85049/84 - *see p.12* |
| | MIL-DTL-27599<br>MIL-DTL-38999 Series I & II | AS85049/85 - *see p.13*<br>AS85049/86 - *see p.13*<br>AS85049/87 - *see p.13* |
| | MIL-DTL-38999 Series III & IV<br>EN3645 | AS85049/88 - *see p.14*<br>AS85049/89 - *see p.14*<br>AS85049/90 - *see p.14* |
| Shield support ring | All | AS85049/93 - *see p.15* |

| Cap style | Connector type | Series |
|---|---|---|
| Screw mating | MIL-DTL-38999 Series III | D38999 - *see p.16* |
| Bayonet mating | MIL-DTL-38999 Series I | MS27 - *see p.17* |

# AS85049/38 Series - Cable clamp strain relief

## For connectors:

- MIL-DTL-38999 Series III & IV
- EN3645

## Ordering information

| Basic Series | M85049/38 | S | 11 | N |
|---|---|---|---|---|

**Self-locking option**
**S:** Self-locking, detented - utilizes an audible detented anti-decoupling device.
**N:** Self-locking, non detented - utilizes an internal captivated anti-decoupling device (Self-Seating) with no audible clicking mechanism.
**- :** Non self locking

**Shell size**
**9, 11, 13, 15, 16, 17, 19, 21, 23, 25**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**S:** Stainless steel, passivated
**W:** Aluminum, olive drab cadmium over electroless nickel, 500 hours salt spray

## Dimensions




| Shell size | A Thread Class 2B | B Max Self-locking only | | C Max Self-locking only | | D Max | | Cable entry Min | | Cable entry Max | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| 9 | M12X1-6H | 0.858 | 21.79 | 0.91 | 23.11 | 0.85 | 21.60 | 0.098 | 2.49 | 0.234 | 5.94 |
| 11 | M15X1-6H | 0.984 | 24.99 | 0.91 | 23.11 | 0.90 | 22.90 | 0.153 | 3.89 | 0.234 | 5.94 |
| 13 | M18X1-6H | 1.157 | 29.39 | 1.01 | 25.65 | 1.10 | 27.90 | 0.19 | 4.83 | 0.328 | 8.33 |
| 15 | M22X1-6H | 1.279 | 32.49 | 1.06 | 26.92 | 1.15 | 29.20 | 0.26 | 6.60 | 0.457 | 11.61 |
| 17 | M25X1-6H | 1.406 | 35.71 | 1.16 | 29.46 | 1.30 | 33.00 | 0.283 | 7.19 | 0.614 | 15.60 |
| 19 | M28X1-6H | 1.516 | 38.51 | 1.41 | (35.81 | 1.50 | 38.10 | 0.325 | 8.26 | 0.634 | 16.10 |
| 21 | M31X1-6H | 1.642 | 41.71 | 1.51 | 38.35 | 1.60 | 40.60 | 0.343 | 8.71 | 0.698 | 17.73 |
| 23 | M34X1-6H | 1.768 | 44.91 | 1.66 | 42.16 | 1.70 | 43.20 | 0.381 | 9.68 | 0.823 | 20.90 |
| 25 | M37X1-6H | 1.889 | 47.98 | 1.76 | 44.70 | 1.80 | 45.70 | 0.418 | 10.62 | 0.853 | 21.67 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/43 Series - 45° cable clamp strain relief

For connectors:

**MIL-DTL-5015 crimp**
**AS81703 Series 3**
**MIL-DTL-26482 Series 2**
**MIL-DTL-83723 Series 1 & 3**

## Ordering information

| | | | | |
|---|---|---|---|---|
| **Basic Series** | **M85049/43** | **-** | **10** | **N** |

**Self-locking option**
**- :** Non self locking

**Shell size**
**3, 8, 10, 12, 14, 16, 18, 20, 22, 24, 28, 32, 36, 40, 44, 48, 61**

**Material and plating**
**N:** Aluminum, electroless nickel
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max closed | | D Max | | Cable entry Min | | Cable entry Max | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **3** | 0.562 - 24 UNEF | 0.669 | 16.99 | 1.160 | 29.46 | 0.772 | 19.61 | 0.125 | 3.20 | 0.204 | 5.20 |
| **8** | 0.500 - 20 UNF | 0.885 | 22.50 | 1.650 | 41.91 | 0.772 | 19.61 | 0.125 | 3.20 | 0.204 | 5.20 |
| **10** | 0.625 - 24 UNEF | 1.010 | 25.70 | 1.694 | 43.03 | 0.803 | 20.40 | 0.187 | 4.70 | 0.286 | 7.30 |
| **12** | 0.750 - 20 UNEF | 1.135 | 28.80 | 1.768 | 44.91 | 0.866 | 21.00 | 0.291 | 7.40 | 0.416 | 10.60 |
| **14** | 0.875 - 20 UNEF | 1.260 | 32.00 | 1.840 | 46.74 | 0.928 | 23.57 | 0.351 | 8.90 | 0.476 | 12.10 |
| **16** | 1.000 - 20 UNEF | 1.385 | 35.20 | 1.916 | 48.67 | 0.991 | 25.17 | 0.501 | 12.70 | 0.625 | 15.90 |
| **18** | 1.062 - 18 UNEF | 1.570 | 39.88 | 2.034 | 51.66 | 1.110 | 28.19 | 0.518 | 13.20 | 0.706 | 17.90 |
| **20** | 1.188 - 18 UNEF | 1.635 | 41.50 | 2.078 | 52.78 | 1.172 | 29.77 | 0.581 | 14.80 | 0.831 | 21.10 |
| **22** | 1.313 - 18 UNEF | 1.760 | 44.70 | 2.122 | 53.90 | 1.235 | 31.37 | 0.644 | 16.40 | 0.956 | 24.30 |
| **24** | 1.438 - 18 UNEF | 1.885 | 47.90 | 2.166 | 55.02 | 1.297 | 32.94 | 0.706 | 17.90 | 1.081 | 27.50 |
| **28** | 1.750 - 18 UNS | 2.135 | 54.20 | 2.461 | 62.51 | 1.543 | 39.19 | 0.750 | 19.10 | 1.187 | 30.10 |
| **32** | 2.000 - 18 UNS | 2.315 | 58.80 | 2.549 | 64.75 | 1.668 | 42.37 | 0.875 | 22.20 | 1.250 | 31.80 |
| **36** | 2.250 - 16 UN | 2.635 | 66.90 | 2.595 | 65.91 | 1.793 | 45.54 | 0.938 | 23.80 | 1.375 | 34.90 |
| **40** | 2.500 - 16 UN | 2.885 | 73.30 | 2.599 | 66.01 | 1.918 | 48.72 | 0.938 | 23.80 | 1.500 | 38.10 |
| **44** | 2.750 - 16 UN | 3.135 | 79.60 | 2.860 | 72.64 | 2.132 | 54.15 | 1.188 | 30.20 | 1.750 | 44.50 |
| **48** | 3.000 - 16 UN | 3.385 | 86.00 | 2.918 | 74.12 | 2.257 | 57.33 | 1.312 | 33.30 | 1.875 | 47.60 |
| **61** | 1.500 - 18 UNEF | 1.653 | 41.99 | 1.676 | 42.57 | 1.204 | 30.58 | 0.706 | 17.90 | 1.081 | 27.50 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/49-2 Series - Cable clamp strain relief

For connectors:
**MIL-DTL-27599**
**MIL-DTL-38999 Series I & II**

## Ordering information

| Basic Series | M85049/49-2 | S | 10 | N |
|---|---|---|---|---|

**Self-locking option**
**S:** Self-locking, detented - utilizes an audible detented anti-decoupling device.
**N:** Self-locking, non detented - utilizes an internal captivated anti-decoupling device (Self-Seating) with no audible clicking mechanism.
**- :** Non self locking

**Shell size**
**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**S:** Stainless steel, passivated
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

## Dimensions




| Shell size | A Thread Class 2B | B Max Self-locking only | | C Max Self-locking only | | D Max | | Cable entry Min | | Cable entry Max | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| 8 | 0.438-28 UNEF | 0.858 | 21.80 | 0.91 | 23.10 | 0.85 | 21.60 | 0.098 | 2.50 | 0.234 | 5.90 |
| 10 | 0.562-24 UNEF | 0.984 | 25.00 | 0.91 | 23.10 | 0.90 | 22.90 | 0.153 | 3.90 | 0.234 | 5.90 |
| 12 | 0.688-24 UNEF | 1.157 | 29.40 | 1.01 | 25.70 | 1.10 | 27.90 | 0.19 | 4.80 | 0.328 | 8.30 |
| 14 | 0.812-20 UNEF | 1.279 | 32.50 | 1.06 | 26.90 | 1.15 | 29.20 | 0.26 | 6.60 | 0.457 | 11.60 |
| 16 | 0.938-20 UNEF | 1.406 | 35.70 | 1.16 | 29.50 | 1.30 | 33.00 | 0.283 | 7.20 | 0.614 | 15.60 |
| 18 | 1.062-18 UNEF | 1.516 | 38.50 | 1.41 | 35.80 | 1.50 | 38.10 | 0.325 | 8.30 | 0.634 | 16.10 |
| 20 | 1.188-18 UNEF | 1.642 | 41.70 | 1.51 | 38.40 | 1.60 | 40.60 | 0.343 | 8.70 | 0.698 | 17.70 |
| 22 | 1.312-18 UNEF | 1.768 | 44.90 | 1.66 | 42.20 | 1.70 | 43.20 | 0.381 | 9.70 | 0.823 | 20.90 |
| 24 | 1.438-18 UNEF | 1.889 | 48.00 | 1.76 | 44.70 | 1.80 | 45.70 | 0.418 | 10.60 | 0.853 | 21.70 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/51 Series - 90° cable clamp strain relief

For connectors:

**MIL-DTL-5015 crimp**
**AS81703 Series 3**
**MIL-DTL-26482 Series 2**
**MIL-DTL-83723 Series 1 & 3**

## Ordering information

| Basic Series | AS85049/51 | S | 10 | N |
|---|---|---|---|---|

**Self-locking option**
**S:** Self-locking, detented - utilizes an audible detented anti-decoupling device.
**N:** Self-locking, non detented - utilizes an internal captivated anti-decoupling device (Self-Seating) with no audible clicking mechanism.
**-1:** Non self locking

**Shell size**
**3, 8, 10, 12, 14, 16, 18, 20, 22, 24, 28, 32, 36, 40, 44, 48, 61**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

## Dimensions







| Shell size | A Thread Class 2B | B Max Self-locking only | | C Max Self-locking only | | D Max | | E ± 0.062 / 1.6 | | Cable entry Min | | Cable entry Max | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| 3 | 0.562 - 24 UNEF | Not available in self-locking | | | | 0.782 | 19.90 | 0.777 | 19.70 | 0.125 | 3.20 | 0.204 | 5.20 |
| 8 | 0.500 - 20 UNF | 0.885 | 22.50 | 1.257 | 31.90 | 0.782 | 19.90 | 0.746 | 18.90 | 0.125 | 3.20 | 0.204 | 5.20 |
| 10 | 0.625 - 24 UNEF | 1.010 | 25.70 | 1.339 | 34.00 | 0.862 | 21.90 | 0.805 | 20.40 | 0.187 | 4.70 | 0.286 | 7.30 |
| 12 | 0.750 - 20 UNEF | 1.135 | 28.80 | 1.532 | 38.90 | 0.968 | 24.60 | 0.867 | 22.00 | 0.291 | 7.40 | 0.416 | 10.60 |
| 14 | 0.875 - 20 UNEF | 1.26 | 32.00 | 1.592 | 40.40 | 1.003 | 25.50 | 0.930 | 23.60 | 0.351 | 8.90 | 0.476 | 12.10 |
| 16 | 1.000 - 20 UNEF | 1.385 | 35.20 | 1.741 | 44.20 | 1.061 | 26.90 | 0.994 | 25.20 | 0.501 | 12.70 | 0.626 | 15.90 |
| 18 | 1.062 - 18 UNEF | 1.510 | 38.40 | 1.853 | 47.10 | 1.394 | 35.40 | 1.171 | 29.70 | 0.518 | 13.20 | 0.706 | 17.90 |
| 20 | 1.188 - 18 UNEF | 1.635 | 41.50 | 1.978 | 50.20 | 1.466 | 37.20 | 1.234 | 31.20 | 0.581 | 14.80 | 0.831 | 21.10 |
| 22 | 1.313 - 18 UNEF | 1.760 | 44.70 | 2.108 | 53.50 | 1.572 | 39.90 | 1.296 | 32.90 | 0.644 | 16.40 | 0.956 | 24.30 |
| 24 | 1.438 - 18 UNEF | 1.885 | 47.90 | 2.228 | 56.60 | 1.698 | 43.10 | 1.358 | 34.50 | 0.706 | 17.90 | 1.081 | 27.50 |
| 28 | 1.750 - 18 UNS | 2.135 | 54.20 | 2.528 | 64.20 | 1.790 | 45.50 | 1.572 | 39.90 | 0.750 | 19.10 | 1.187 | 30.10 |
| 32 | 2.000 - 18 UNS | 2.395 | 60.80 | 2.591 | 65.80 | 2.035 | 51.70 | 1.797 | 45.60 | 0.875 | 22.20 | 1.250 | 31.80 |
| 36 | 2.250 - 16 UN | 2.635 | 66.90 | 2.716 | 69.00 | 2.386 | 60.60 | 1.922 | 48.80 | 0.938 | 23.80 | 1.375 | 34.90 |
| 40 | 2.500 - 16 UN | 2.885 | 73.30 | 2.841 | 72.20 | 2.566 | 65.20 | 2.047 | 52.00 | 0.938 | 23.80 | 1.500 | 38.10 |
| 44 | 2.750 - 16 UN | 3.135 | 79.60 | 3.091 | 78.50 | 2.86 | 72.60 | 2.296 | 58.30 | 1.188 | 30.20 | 1.750 | 44.50 |
| 48 | 3.000 - 16 UN | 3.385 | 86.00 | 3.216 | 81.70 | 3.344 | 84.90 | 2.421 | 61.50 | 1.312 | 33.30 | 1.875 | 47.60 |
| 61 | 1.500 - 18 UNEF | Not available in self-locking | | | | 1.775 | 45.10 | 1.388 | 35.30 | 0.706 | 17.90 | 1.081 | 27.50 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/52 Series - Straight cable clamp strain relief

For connectors:

**MIL-DTL-5015 crimp** **MIL-DTL-26482 Series 2**
**AS81703 Series 3** **MIL-DTL-83723 Series 1 & 3**

## Ordering information

| **Basic Series** | **AS85049/52** | **S** | **10** | **N** |
|---|---|---|---|---|

**Self-locking option**
**S:** Self-locking, detented - utilizes an audible detented anti-decoupling device.
**N:** Self-locking, non detented - utilizes an internal captivated anti-decoupling device (Self-Seating) with no audible clicking mechanism.
**-1:** Non self locking

**Shell size**
**3, 8, 10, 12, 14, 16, 18, 20, 22, 24, 28, 32, 36, 40, 44, 48, 61**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

## Dimensions







| Shell size | A Thread Class 2B | B Max Self-locking only | | C Max Self-locking only | | D Max | | Cable entry Min | | Cable entry Max | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **3** | 0.562 - 24 UNEF | Not available in self-locking | | | | 0.782 | 19.90 | 0.125 | 3.20 | 0.204 | 5.20 |
| **8** | 0.500 - 20 UNF | 0.885 | 22.50 | 0.73 | 18.50 | 0.782 | 19.90 | 0.125 | 3.20 | 0.204 | 5.20 |
| **10** | 0.625 - 24 UNEF | 1.010 | 25.70 | 0.85 | 21.60 | 0.862 | 21.90 | 0.187 | 4.70 | 0.286 | 7.30 |
| **12** | 0.750 - 20 UNEF | 1.135 | 28.80 | 0.98 | 24.90 | 0.968 | 24.60 | 0.291 | 7.40 | 0.416 | 10.60 |
| **14** | 0.875 - 20 UNEF | 1.26 | 32.00 | 0.98 | 24.90 | 1.003 | 25.50 | 0.351 | 8.90 | 0.476 | 12.10 |
| **16** | 1.000 - 20 UNEF | 1.385 | 35.20 | 1.10 | 27.90 | 1.061 | 26.90 | 0.501 | 12.70 | 0.626 | 15.90 |
| **18** | 1.062 - 18 UNEF | 1.510 | 38.40 | 1.35 | 34.30 | 1.394 | 35.40 | 0.518 | 13.20 | 0.706 | 17.90 |
| **20** | 1.188 - 18 UNEF | 1.635 | 41.50 | 1.48 | 37.60 | 1.466 | 37.20 | 0.581 | 14.80 | 0.831 | 21.10 |
| **22** | 1.313 - 18 UNEF | 1.760 | 44.70 | 1.60 | 40.60 | 1.572 | 39.90 | 0.644 | 16.40 | 0.956 | 24.30 |
| **24** | 1.438 - 18 UNEF | 1.885 | 47.90 | 1.73 | 43.90 | 1.698 | 43.10 | 0.706 | 17.90 | 1.081 | 27.50 |
| **28** | 1.750 - 18 UNS | 2.135 | 54.20 | 1.88 | 47.80 | 1.790 | 45.50 | 0.750 | 19.10 | 1.187 | 30.10 |
| **32** | 2.000 - 18 UNS | 2.395 | 60.80 | 2.13 | 54.10 | 2.035 | 51.70 | 0.875 | 22.20 | 1.250 | 31.80 |
| **36** | 2.250 - 16 UN | 2.635 | 66.90 | 2.44 | 62.00 | 2.386 | 60.60 | 0.938 | 23.80 | 1.375 | 34.90 |
| **40** | 2.500 - 16 UN | 2.885 | 73.30 | 2.63 | 66.80 | 2.566 | 65.20 | 0.938 | 23.80 | 1.500 | 38.10 |
| **44** | 2.750 - 16 UN | 3.135 | 79.60 | 3.00 | 76.20 | 2.86 | 72.60 | 1.188 | 30.20 | 1.750 | 44.50 |
| **48** | 3.000 - 16 UN | 3.385 | 86.00 | 3.40 | 86.40 | 3.344 | 84.90 | 1.312 | 33.30 | 1.875 | 47.60 |
| **61** | 1.500 - 18 UNEF | Not available in self-locking | | | | 1.775 | 45.10 | 0.706 | 17.90 | 1.081 | 27.50 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/53, 54, 55 Series - One arm strain relief

For connectors:

**MIL-DTL-5015 crimp**
**AS81703 Series 3**
**MIL-DTL-26482 Series 2**
**MIL-DTL-83723 Series 1 & 3**

## Ordering information

| | | | | | |
|---|---|---|---|---|---|
| **Basic Series** | **AS85049/** | **53** | **-** | **10** | **N** |
| **Angle**<br>**53:** Straight<br>**54:** 45°<br>**55:** 90° | | | | | |
| **Self-locking option**<br>**- :** Non self locking | | | | | |
| **Shell size**<br>**3, 8, 10, 12, 14, 16, 18, 20, 22, 24, 28** | | | | | |
| **Material and plating**<br>**A:** Aluminum, black anodize<br>**N:** Aluminum, electroless nickel<br>**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray | | | | | |

## Dimensions










**For new design use:**
M85049/43 (45°),
M85049/51 (90°) and
M85049/52 (straight)

| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | E Max | | F Max | | Cable entry | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **3** | 0.562 - 24 UNEF | 0.780 | 19.80 | 0.954 | 24.00 | 1.232 | 31.30 | 0.730 | 18.50 | 1.290 | 32.80 | 0.260 | 6.60 |
| **8** | 0.500 - 20 UNF | 0.660 | 16.80 | | | | | | | | | 0.260 | 6.60 |
| **10** | 0.625 - 24 UNEF | 0.780 | 19.80 | | | | | | | | | 0.365 | 9.30 |
| **12** | 0.750 - 20 UNEF | 0.940 | 23.90 | | | | | | | 1.620 | 41.10 | 0.501 | 12.70 |
| **14** | 0.875 - 20 UNEF | 1.050 | 26.70 | 1.204 | 30.60 | | | | | 1.660 | 42.20 | 0.575 | 14.60 |
| **16** | 1.000 - 20 UNEF | 1.240 | 31.50 | | | | | | | 1.720 | 43.70 | 0.700 | 17.80 |
| **18** | 1.062 - 18 UNEF | 1.380 | 35.10 | | | | | | | | | 0.779 | 19.80 |
| **20** | 1.188 - 18 UNEF | 1.500 | 38.10 | 1.310 | 33.30 | 1.482 | 37.60 | 0.750 | 19.10 | 1.790 | 45.50 | 0.904 | 23.00 |
| **22** | 1.313 - 18 UNEF | 1.630 | 41.40 | 1.430 | 36.30 | | | | | 1.850 | 47.00 | 1.029 | 26.10 |
| **24** | 1.438 - 18 UNEF | 1.750 | 44.50 | 1.560 | 39.60 | | | | | 1.910 | 48.50 | 1.144 | 29.10 |
| **28** | 1.750 - 18 UNS | 1.970 | 50.00 | 1.560 | 39.60 | 1.469 | 37.30 | | | 2.060 | 52.30 | 1.379 | 35.00 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/60-1 Series - Shrink boot adapter

For connectors:

**MIL-DTL-5015 crimp**
**AS81703 Series 3**
**MIL-DTL-26482 Series 2**
**MIL-DTL-83723 Series 1 & 3**

## Ordering information

| Basic Series | M85049/60-1 | N | 10 |
|---|---|---|---|

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Shell size**
**3, 8, 10, 12, 14, 16, 18, 20, 22, 24, 28, 32, 36, 40, 44, 48, 61**

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | Cable entry | |
|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm |
| 3 | 0.562 - 24 UNEF | 0.670 | 17.00 | 0.832 | 21.10 | 0.533 | 13.50 | 0.250 | 6.40 |
| 8 | 0.500 - 20 UNF | 0.620 | 15.70 | | | 0.533 | 13.50 | 0.250 | 6.40 |
| 10 | 0.625 - 24 UNEF | 0.740 | 18.80 | | | 0.605 | 15.40 | 0.355 | 9.00 |
| 12 | 0.750 - 20 UNEF | 0.860 | 21.80 | | | 0.774 | 19.70 | 0.491 | 12.50 |
| 14 | 0.875 - 20 UNEF | 0.980 | 24.90 | | | 0.838 | 21.30 | 0.565 | 14.40 |
| 16 | 1.000 - 20 UNEF | 1.110 | 28.20 | | | 0.963 | 24.50 | 0.690 | 17.50 |
| 18 | 1.062 - 18 UNEF | 1.220 | 31.00 | | | 1.042 | 26.50 | 0.769 | 19.50 |
| 20 | 1.188 - 18 UNEF | 1.350 | 34.30 | | | 1.217 | 30.90 | 0.894 | 22.70 |
| 22 | 1.313 - 18 UNEF | 1.470 | 37.30 | | | 1.355 | 34.40 | 1.019 | 25.90 |
| 24 | 1.438 - 18 UNEF | 1.590 | 40.40 | | | 1.443 | 36.70 | 1.134 | 28.80 |
| 28 | 1.750 - 18 UNS | 1.970 | 50.00 | 0.994 | 25.30 | 1.709 | 43.40 | 1.369 | 34.80 |
| 32 | 2.000 - 18 UNS | 2.220 | 56.40 | | | 1.919 | 48.70 | 1.615 | 41.00 |
| 36 | 2.250 - 16 UN | 2.470 | 62.70 | | | 2.169 | 55.10 | 1.830 | 46.50 |
| 40 | 2.500 - 16 UN | 2.720 | 69.10 | | | 2.402 | 61.00 | 2.045 | 51.90 |
| 44 | 2.750 - 16 UN | 2.970 | 75.40 | | | 2.657 | 67.50 | 2.300 | 58.40 |
| 48 | 3.000 - 16 UN | 3.220 | 81.80 | | | 2.907 | 73.80 | 2.550 | 64.80 |
| 61 | 1.500 - 18 UNEF | 1.650 | 41.90 | 0.832 | 21.10 | 1.529 | 38.80 | 1.174 | 29.80 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/62 Series - Shrink boot adapter

For connectors:
**MIL-DTL-27599**
**MIL-DTL-38999 Series I & II**

## Ordering information

| Basic Series | M85049/62 | 10 | N | D |
|---|---|---|---|---|

**Shell size**
**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**S:** Stainless steel, passivated
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Drain hole**
**D:** with drain hole
**empty:** without drain hole

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | Cable entry | |
|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm |
| 8 | 0.438 - 28 UNEF | 0.750 | 19.10 | 1.000 | 25.40 | 0.533 | 13.50 | 0.250 | 6.40 |
| 10 | 0.562 - 24 UNEF | 0.850 | 21.60 | | | 0.605 | 15.40 | 0.375 | 9.50 |
| 12 | 0.688 - 24 UNEF | 1.000 | 25.40 | | | 0.774 | 19.70 | 0.500 | 12.70 |
| 14 | 0.813 - 20 UNEF | 1.100 | 27.90 | | | 0.838 | 21.30 | 0.625 | 15.90 |
| 16 | 0.938 - 20 UNEF | 1.250 | 31.80 | | | 0.963 | 24.50 | 0.750 | 19.10 |
| 18 | 1.063 - 18 UNEF | 1.400 | 35.60 | | | 1.042 | 26.50 | 0.812 | 20.60 |
| 20 | 1.188 - 18 UNEF | 1.500 | 38.10 | | | 1.217 | 30.90 | 0.937 | 23.80 |
| 22 | 1.313 - 18 UNEF | 1.650 | 41.90 | | | 1.355 | 34.40 | 1.062 | 27.00 |
| 24 | 1.438 - 18 UNEF | 1.750 | 44.50 | | | 1.443 | 36.70 | 1.188 | 30.20 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/69 Series - Shrink boot adapter

For connectors:
**MIL-DTL-38999 Series III & IV**
**EN3645**

## Ordering information

| Basic Series | M85049/69 | 11 | N |
|---|---|---|---|

**Shell size**
**9, 11, 13, 15, 17, 19, 21, 23, 25**

**Material and plating**
**A:** Aluminum, black anodize
**N:** Aluminum, electroless nickel
**S:** Stainless steel, passivated
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Drain hole**
**D:** with drain hole
**empty:** without drain hole

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | Cable entry | |
|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm |
| **9** | M12 X 1 - 6H | 0.750 | 19.10 | | | 0.533 | 13.50 | 0.250 | 6.40 |
| **11** | M15 X 1 - 6H | 0.850 | 21.60 | | | 0.605 | 15.40 | 0.375 | 9.50 |
| **13** | M18 X 1 - 6H | 1.000 | 25.40 | | | 0.774 | 19.70 | 0.500 | 12.70 |
| **15** | M22 X 1 - 6H | 1.150 | 29.20 | | | 0.838 | 21.30 | 0.625 | 15.90 |
| **17** | M25 X 1 - 6H | 1.250 | 31.80 | 0.710 | 18.00 | 0.963 | 24.50 | 0.750 | 19.10 |
| **19** | M28 X 1 - 6H | 1.400 | 35.60 | | | 1.042 | 26.50 | 0.812 | 20.60 |
| **21** | M31 X 1 - 6H | 1.500 | 38.10 | | | 1.217 | 30.90 | 0.938 | 23.80 |
| **23** | M34 X 1 - 6H | 1.650 | 41.90 | | | 1.355 | 34.40 | 1.062 | 27.00 |
| **25** | M37 X 1 - 6H | 1.785 | 47.00 | | | 1.443 | 36.70 | 1.188 | 30.20 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/82, 83, 84 Series - Banding backshell with self-locking

For connectors:

**MIL-DTL-5015 crimp** **MIL-DTL-26482 Series 2**
**AS81703 Series 3** **MIL-DTL-83723 Series 1 & 3**

## Ordering information

| **Basic Series** | **AS85049/** | **82** | **-** | **10** | **N** | **02** |
|---|---|---|---|---|---|---|

**Angle**
**82:** Straight
**83:** 45°
**84:** 90° (size 28 not qualified for AS85049/84)

**Self-locking option**
**- :** Detended
**N:** Non detended

**Shell size: 8, 10, 12, 14, 16, 18, 20, 22, 24, 28** (size 28 not qualified for AS85049/84)

**Material and plating**
**N:** Aluminum, electroless nickel
**P:** Aluminum, olive drab cadmium over electroless nickel with polysulfide sealant strips
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Entry size** (see table below): **02, 03**

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | E Max | | F Max | | Cable entry Size 02 ±0.01/0.30 | | Cable entry Size 03 ±0.01/0.30 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **8** | 0.500 - 20 UNF | 0.886 | 22.40 | 0.870 | 22.10 | 1.160 | 29.50 | 1.188 | 30.20 | 1.417 | 36.00 | N/A | N/A | 0.250 | 6.40 |
| **10** | 0.625 - 24 UNEF | 1.010 | 25.70 | 0.890 | 22.60 | 1.180 | 30.00 | 1.281 | 32.50 | 1.480 | 37.60 | N/A | N/A | 0.312 | 7.90 |
| **12** | 0.750 - 20 UNEF | 1.130 | 28.70 | 0.920 | 23.40 | 1.200 | 30.50 | 1.406 | 35.70 | 1.542 | 39.20 | 0.312 | 7.90 | 0.438 | 11.10 |
| **14** | 0.875 - 20 UNEF | 1.260 | 32.00 | 0.940 | 23.90 | 1.220 | 31.00 | 1.531 | 38.90 | 1.605 | 40.80 | 0.438 | 11.10 | 0.562 | 14.30 |
| **16** | 1.000 - 20 UNEF | 1.386 | 35.10 | 0.960 | 24.40 | 1.250 | 31.80 | 1.656 | 42.10 | 1.667 | 42.30 | 0.500 | 12.70 | 0.625 | 15.90 |
| **18** | 1.062 - 18 UNEF | 1.510 | 38.40 | 0.980 | 24.90 | 1.260 | 32.00 | 1.718 | 43.60 | 1.730 | 43.90 | 0.625 | 15.90 | 0.750 | 19.10 |
| **20** | 1.188 - 18 UNEF | 1.636 | 41.40 | 1.000 | 25.40 | 1.290 | 32.80 | 1.844 | 46.80 | 1.792 | 45.50 | 0.625 | 15.90 | 0.812 | 20.60 |
| **22** | 1.313 - 18 UNEF | 1.760 | 44.70 | 1.030 | 26.20 | 1.310 | 33.30 | 1.938 | 49.20 | 1.850 | 47.00 | 0.688 | 17.50 | 0.938 | 23.80 |
| **24** | 1.438 - 18 UNEF | 1.886 | 47.80 | 1.050 | 26.70 | 1.340 | 34.00 | 2.093 | 53.20 | 1.917 | 48.70 | 0.750 | 19.10 | 1.000 | 25.40 |
| **28** | 1.750 - 18 UNS | 2.136 | 54.10 | 1.100 | 27.90 | 1.380 | 35.10 | 2.531 | 64.30 | 2.042 | 51.90 | 0.875 | 22.20 | 1.125 | 28.60 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/85, 86, 87 Series - Banding backshell with self-locking

For connectors:
**MIL-DTL-27599**
**MIL-DTL-38999 Series I & II**

## Ordering information

| Basic Series | AS85049/ | 85 | - | 10 | N | 02 |
|---|---|---|---|---|---|---|

**Angle**
**85:** Straight
**86:** 45°
**87:** 90°

**Self-locking option**
**- :** Detended
**N:** Non detended

**Shell size: 8, 10, 12, 14, 16, 18, 20, 22, 24**

**Material and plating**
**N:** Aluminum, electroless nickel
**P:** Aluminum, olive drab cadmium over electroless nickel with polysulfide sealant strips
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Entry size** (see table below)**: 02, 03**

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | E Max | | F Max | | Cable entry for AS85049/85, Straight version | | | | Cable entry for AS85049/86 and AS85049/87, 45° & 90° | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | Size 01 | | Size 02 | | Size 02 | | Size 03 | |
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| 8 | 0.438-28 UNEF | 0.860 | 21.80 | 0.870 | 22.10 | 1.160 | 29.50 | 1.375 | 34.90 | 1.417 | 36.00 | N/A | N/A | 0.250 | 6.40 | N/A | N/A | 0.250 | 6.40 |
| 10 | 0.562-24 UNEF | 0.990 | 25.10 | 0.900 | 22.90 | 1.190 | 30.20 | 1.437 | 36.50 | 1.480 | 37.60 | N/A | N/A | 0.312 | 7.90 | N/A | N/A | 0.312 | 7.90 |
| 12 | 0.688-24 UNEF | 1.160 | 29.50 | 0.920 | 23.40 | 1.210 | 30.70 | 1.562 | 39.70 | 1.553 | 39.40 | 0.312 | 7.90 | 0.438 | 11.10 | 0.312 | 7.90 | 0.438 | 11.10 |
| 14 | 0.812-20 UNEF | 1.280 | 32.50 | 0.950 | 24.10 | 1.240 | 31.50 | 1.687 | 42.80 | 1.614 | 41.00 | 0.438 | 11.10 | 0.562 | 14.30 | 0.438 | 11.10 | 0.562 | 14.30 |
| 16 | 0.938-20 UNEF | 1.410 | 35.80 | 0.980 | 24.90 | 1.260 | 32.00 | 1.750 | 44.50 | 1.678 | 42.60 | 0.500 | 12.70 | 0.625 | 15.90 | 0.500 | 12.70 | 0.625 | 15.90 |
| 18 | 1.062-18 UNEF | 1.520 | 38.60 | 0.980 | 24.90 | 1.270 | 32.30 | 1.875 | 47.60 | 1.733 | 44.00 | 0.625 | 15.90 | 0.750 | 19.10 | 0.625 | 15.90 | 0.750 | 19.10 |
| 20 | 1.188-18 UNEF | 1.640 | 41.70 | 1.010 | 25.70 | 1.300 | 33.00 | 1.938 | 49.20 | 1.796 | 45.60 | 0.625 | 15.90 | 0.812 | 20.60 | 0.625 | 15.90 | 0.812 | 20.60 |
| 22 | 1.312-18 UNEF | 1.770 | 45.00 | 1.040 | 26.40 | 1.330 | 33.80 | 2.062 | 52.40 | 1.859 | 47.20 | 0.688 | 17.50 | 0.938 | 23.80 | 0.688 | 17.50 | 0.938 | 23.80 |
| 24 | 1.438-18 UNEF | 1.890 | 48.00 | 1.070 | 27.20 | 1.350 | 34.30 | 2.125 | 54.00 | 1.919 | 48.70 | 0.750 | 19.10 | 1.000 | 25.40 | 0.750 | 19.10 | 1.000 | 25.40 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# AS85049/88, 89, 90 Series - Banding backshell with self-locking

For connectors:
**MIL-DTL-38999 Series III & IV**
**EN3645**

## Ordering information

| | | | | | | |
|---|---|---|---|---|---|---|
| **Basic Series** | **AS85049/** | **88** | **-** | **11** | **N** | **02** |

**Angle**
**88:** Straight
**89:** 45°
**90:** 90°

**Self-locking option**
**- :** Detended
**N:** Non detended

**Shell size: 9, 11, 13, 15, 17, 19, 21, 23, 25**

**Material and plating**
**N:** Aluminum, electroless nickel
**P:** Aluminum, olive drab cadmium over electroless nickel with polysulfide sealant strips
**W:** Aluminum, olive drab cadmium over electroless nickel, 1000 hours salt spray

**Entry size** (see table below)**: 02, 03**

## Dimensions




| Shell size | A Thread Class 2B | B Max | | C Max | | D Max | | E Max | | F Max | | Cable entry Size 02 | | Cable entry Size 03 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **9** | M12X1-6H | 0.860 | 21.80 | 1.010 | 25.70 | 1.160 | 29.50 | 1.375 | 34.90 | 1.417 | 36.00 | N/A | N/A | 0.250 | 6.40 |
| **11** | M15X1-6H | 0.990 | 25.10 | 1.030 | 26.20 | 1.190 | 30.20 | 1.437 | 36.50 | 1.480 | 37.60 | N/A | N/A | 0.312 | 7.90 |
| **13** | M18X1-6H | 1.160 | 29.50 | 1.060 | 26.90 | 1.210 | 30.70 | 1.562 | 39.70 | 1.553 | 39.40 | 0.312 | 7.90 | 0.438 | 11.10 |
| **15** | M22X1-6H | 1.280 | 32.50 | 1.080 | 27.40 | 1.240 | 31.50 | 1.687 | 42.80 | 1.614 | 41.00 | 0.438 | 11.10 | 0.562 | 14.30 |
| **17** | M25X1-6H | 1.410 | 35.80 | 1.110 | 28.20 | 1.260 | 32.00 | 1.750 | 44.50 | 1.678 | 42.60 | 0.500 | 12.70 | 0.625 | 15.90 |
| **19** | M28X1-6H | 1.520 | 38.60 | 1.120 | 28.40 | 1.270 | 32.30 | 1.875 | 47.60 | 1.733 | 44.00 | 0.625 | 15.90 | 0.750 | 19.10 |
| **21** | M31X1-6H | 1.640 | 41.70 | 1.150 | 29.20 | 1.300 | 33.00 | 1.938 | 49.20 | 1.796 | 45.60 | 0.625 | 15.90 | 0.812 | 20.60 |
| **23** | M34X1-6H | 1.770 | 45.00 | 1.170 | 29.70 | 1.330 | 33.80 | 2.062 | 52.40 | 1.859 | 47.20 | 0.688 | 17.50 | 0.938 | 23.80 |
| **25** | M37X1-6H | 1.890 | 48.00 | 1.200 | 30.50 | 1.350 | 34.30 | 2.125 | 54.00 | 1.919 | 48.70 | 0.750 | 19.10 | 1.000 | 25.40 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.
Cable entry is defined as the envelope area of the cable or wire bundle. It is not intended for inspection criteria.

# M85049/93 Series - Shield support ring

For **ALL** connectors.

## Ordering information

| | | |
|---|---|---|
| **Basic Series** | **M85049/93** | **10** |
| **Dash number**<br>**4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28** | | |

## Dimensions




| Dash number | X | | Y | | Z | |
|---|---|---|---|---|---|---|
| | inch | mm | inch | mm | inch | mm |
| **4** | 0.25 | 6.40 | 0.404 | 10.30 | 0.36 | 9.10 |
| **6** | 0.38 | 9.70 | 0.529 | 13.40 | 0.49 | 12.40 |
| **8** | 0.50 | 12.70 | 0.654 | 16.60 | 0.61 | 15.50 |
| **10** | 0.63 | 16.00 | 0.779 | 19.80 | 0.74 | 18.80 |
| **12** | 0.75 | 19.10 | 0.904 | 23.00 | 0.86 | 21.80 |
| **14** | 0.88 | 22.40 | 1.029 | 26.10 | 0.99 | 25.10 |
| **16** | 1.00 | 25.40 | 1.154 | 29.30 | 1.11 | 28.20 |
| **18** | 1.13 | 28.70 | 1.279 | 32.50 | 1.24 | 31.50 |
| **20** | 1.25 | 21.80 | 1.404 | 35.70 | 1.36 | 34.50 |
| **22** | 1.38 | 35.10 | 1.529 | 38.90 | 1.49 | 37.80 |
| **24** | 1.50 | 38.10 | 1.654 | 42.00 | 1.61 | 40.90 |
| **26** | 1.63 | 41.40 | 1.779 | 45.20 | 1.74 | 44.20 |
| **28** | 1.75 | 44.50 | 1.904 | 48.60 | 1.86 | 47.20 |

Note: All dimensions are in inches and millimeters (inch/mm). For complete dimensions, see the applicable Military Specification.

# MS27501/MS27502 Series - Protective caps for plug and receptacle

For connectors:
**MIL-DTL-38999 Series I**

## Ordering information

| | | | | | |
|---|---|---|---|---|---|
| **Basic Series** | **MS27** | **501** | **B** | **11** | **N** |

**Cap type**
**501:** Cap for plug
**502:** Cap for receptacle

**Material and plating**
**B:** Aluminum, olive drab cadmium, 500 hours salt spray
**C:** Aluminum, black anodize
**F:** Aluminum, electroless nickel

**Shell size: 9, 11, 13, 15, 17, 19, 21, 23, 25**

**Style**
**A:** Without chain
**C:** Chain with eyelet
**N:** Chain with ring (MS27502 only)

**Chain length (in inches/mm)**
**empty:** Standard chain length, see table below (C Max)
**L:** 5.0/127.0
**M:** 6.0/152.4 (MS27501 only)
**N:** 7.0/177.8 (MS27501 only)

## Dimensions

**Cap for plug Type 501**




**Cap for receptacle Type 502**




| Size | ØA Max | | ØB Max | | C Max | | ØD Min | |
|---|---|---|---|---|---|---|---|---|
| | inch | mm | inch | mm | inch | mm | inch | mm |
| **9** | 0.82 | 20.80 | 0.82 | 20.80 | 3.00 | 76.20 | 0.70 | 17.80 |
| **11** | 0.94 | 23.90 | 0.94 | 23.90 | | | 0.84 | 21.30 |
| **13** | 1.07 | 27.20 | 1.10 | 27.90 | 3.50 | 88.90 | 1.01 | 25.70 |
| **15** | 1.19 | 30.20 | 1.22 | 31.00 | | | 1.14 | 29.00 |
| **17** | 1.35 | 33.50 | 1.34 | 34.00 | | | 1.26 | 32.00 |
| **19** | 1.44 | 36.60 | 1.46 | 37.10 | | | 1.39 | 35.30 |
| **21** | 1.57 | 39.90 | 1.58 | 40.10 | 4.00 | 101.60 | 1.51 | 38.40 |
| **23** | 1.69 | 42.90 | 1.70 | 43.20 | | | 1.64 | 41.70 |
| **25** | 1.82 | 46.20 | 1.83 | 46.50 | | | 1.76 | 44.70 |

Note: All dimensions are in inches and millimeters (inch/mm).

# D38999 Series - Protective caps for plug and receptacle

For connectors:
**MIL-DTL-38999 Series III**

## Ordering information

| Basic Series | D38999/ | 32 | W | 11 | N |
|---|---|---|---|---|---|
| **Cap type**<br>**32:** Cap for plug<br>**33:** Cap for receptacle | | | | | |
| **Material and plating**<br>**W:** Aluminum, olive drab cadmium<br>**F:** Aluminum, nickel<br>**Z:** Aluminum, black zinc nickel | | | | | |
| **Shell size: 9, 11, 13, 15, 17, 19, 21, 23, 25** | | | | | |
| **Style**<br>**N:** With stainless steel rope and ring<br>**R:** With stainless steel rope and eyelet | | | | | |

## Dimensions

**Cap for plug Type 32**




**Cap for receptacle Type 33**




| Size | ØA Max | | ØB Max | | C Max | | ØD | | ØE | | Thread: Stub ACME 2A/2B modified 60° |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | |
| **9** | 0.889 | 22.60 | 0.898 | 22.80 | 3.31 | 84.00 | 0.591 | 15.00 | 0.724 | 18.40 | 0.6250-0.1P-0.3L-TS |
| **11** | 1.016 | 25.80 | 1.043 | 26.50 | | | 0.724 | 18.40 | 0.913 | 23.20 | 0.7500-0.1P-0.3L-TS |
| **13** | 1.181 | 30.00 | 1.181 | 30.00 | 3.90 | 99.00 | 0.913 | 23.20 | 1.043 | 26.50 | 0.8750-0.1P-0.3L-TS |
| **15** | 1.299 | 33.00 | 1.252 | 31.80 | | | 0.913 | 23.20 | 1.193 | 30.30 | 1.0000-0.1P-0.3L-TS |
| **17** | 1.437 | 36.50 | 1.449 | 36.80 | | | 1.043 | 26.50 | 1.283 | 32.60 | 1.1875-0.1P-0.3L-TS |
| **19** | 1.543 | 39.20 | 1.528 | 38.80 | | | 1.193 | 30.30 | 1.437 | 36.50 | 1.2500-0.1P-0.3L-TS |
| **21** | 1.673 | 42.50 | 1.646 | 41.80 | 4.49 | 114.00 | 1.283 | 32.60 | 1.547 | 39.30 | 1.3750-0.1P-0.3L-TS |
| **23** | 1.803 | 45.80 | 1.764 | 44.80 | | | 1.437 | 36.50 | 1.689 | 42.90 | 1.5000-0.1P-0.3L-TS |
| **25** | 1.925 | 48.90 | 1.921 | 48.80 | | | 1.547 | 39.30 | 1.772 | 45.00 | 1.6250-0.1P-0.3L-TS |

Note: All dimensions are in inches and millimeters (inch/mm).

For further information contact us at sunbank.sales@esterline.com
or visit our web site www.sunbankcorp.com

WPNM85049WUSEN01 © Copyright SOURIAU Sept 2015 - SOURIAU is a registered trademark.
All information in this document presents only general particulars and shall not form part of any contract. All rights reserved to SOURIAU for changes without prior notification or public announcement. Any duplication is prohibited, unless approved in writing.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.