



## Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

### General Description

The MAX5188 is a dual 8-bit, alternate-phase-update, current-output digital-to-analog converter (DAC) designed for superior performance in systems requiring analog signal reconstruction with low distortion and low-power operation. The MAX5191 provides equal specifications, with on-chip output resistors for voltage-output operation. Both devices are designed for 10pVs glitch operation to reduce distortion and minimize unwanted spurious signal components at the output. An on-board +1.2V bandgap circuit provides a well-regulated, low-noise reference that may be disabled for external reference operation.

The MAX5188/MAX5191 are designed to provide a high level of signal integrity for the least amount of power dissipation. Both DACs operate from a +2.7V to +3.3V single supply. Additionally, these DACs have three modes of operation: normal, low-power standby, and full shutdown. A full shutdown provides the lowest possible power dissipation with a maximum shutdown current of 1 $\mu$ A. A fast wake-up time (0.5 $\mu$ s) from standby mode to full DAC operation allows for power conservation by activating the DACs only when required.

The MAX5188/MAX5191 are available in a 28-pin QSOP package and are specified for the extended (-40°C to +85°C) temperature range. For pin-compatible 10-bit versions, refer to the MAX5182/MAX5185 data sheet.

### Applications

- Signal Reconstruction Applications
- Digital Signal Processing
- Arbitrary Waveform Generators
- Imaging Applications

### Features


- ◆ +2.7V to +3.3V Single-Supply Operation
- ◆ Wide Spurious-Free Dynamic Range: 70dB at  $f_{OUT} = 2.2\text{MHz}$
- ◆ Fully Differential Outputs for Each DAC
- ◆  $\pm 0.5\%$  FSR Gain Mismatch Between DAC Outputs
- ◆ Low-Current Standby or Full Shutdown Modes
- ◆ Internal +1.2V Low-Noise Bandgap Reference
- ◆ Small 28-Pin QSOP Package

**MAX5188/MAX5191**

### Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
<b>MAX5188BEEI</b>	-40°C to +85°C	28 QSOP
<b>MAX5191BEEI</b>	-40°C to +85°C	28 QSOP

### Pin Configuration



Maxim Integrated Products 1

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at [www.maxim-ic.com](http://www.maxim-ic.com).

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## ABSOLUTE MAXIMUM RATINGS

AV <sub>DD</sub> , DV <sub>DD</sub> to AGND, DGND .....	-0.3V to +6V
Digital Inputs to DGND .....	-0.3V to +6V
OUT1P, OUT1N, OUT2P, OUT2N, CREF1, CREF2 to AGND .....	-0.3V to +6V
V <sub>REF</sub> to AGND .....	-0.3V to +6V
AV <sub>DD</sub> to DV <sub>DD</sub> .....	±3.3V
AGND to DGND.....	-0.3V to +0.3V
Maximum Current into Any Pin.....	.50mA

Continuous Power Dissipation (T <sub>A</sub> = +70°C) 28-Pin QSOP (derate 9.00mW/°C above +70°C).....	725mW
Operating Temperature Ranges MAX5188/MAX5191BEEI .....	-40°C to +85°C
Storage Temperature Range .....	-65°C to +150°C
Lead Temperature (soldering, 10s) .....	+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ELECTRICAL CHARACTERISTICS

(AV<sub>DD</sub> = DV<sub>DD</sub> = +3V ±10%, AGND = DGND = 0, f<sub>CLK</sub> = 40MHz, I<sub>FS</sub> = 1mA, 400Ω differential output, C<sub>L</sub> = 5pF, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
<b>STATIC PERFORMANCE</b>							
Resolution	N			8			Bits
Integral Nonlinearity	INL			-1	±0.25	+1	LSB
Differential Nonlinearity	DNL	Guaranteed monotonic		-1	±0.25	+1	LSB
Zero-Scale Error		MAX5188		-1		+1	LSB
		MAX5191		-4		+4	LSB
Full-Scale Error		(Note 1)		-20	±4	+20	LSB
<b>DYNAMIC PERFORMANCE</b>							
Output Settling Time		To ±0.5LSB error band		25			ns
Glitch Impulse				10			pVs
Spurious-Free Dynamic Range to Nyquist	SFDR	f <sub>CLK</sub> = 40MHz	f <sub>OUT</sub> = 500kHz f <sub>OUT</sub> = 2.2MHz, T <sub>A</sub> = +25°C	72 57	70		dBc
Total Harmonic Distortion to Nyquist	THD	f <sub>CLK</sub> = 40MHz	f <sub>OUT</sub> = 500kHz f <sub>OUT</sub> = 2.2MHz, T <sub>A</sub> = +25°C	-70 -68	-63		dB
Signal-to-Noise Ratio to Nyquist	SNR	f <sub>CLK</sub> = 40MHz	f <sub>OUT</sub> = 500kHz f <sub>OUT</sub> = 2.2MHz, T <sub>A</sub> = +25°C	52 46	52		dB
DAC-to-DAC Output Isolation		f <sub>OUT</sub> = 2.2MHz		-60			dB
Clock and Data Feedthrough		All 0s to all 1s		50			nVs
Output Noise				10			pA/√Hz
Gain Mismatch Between DAC Outputs		f <sub>OUT</sub> = 2.2MHz, T <sub>A</sub> = +25°C		±0.5	±1		LSB
<b>ANALOG OUTPUT</b>							
Full-Scale Output Voltage	V <sub>FS</sub>			400			mV
Voltage Compliance of Output				-0.3	0.8		V
Output Leakage Current		DACEN = 0, MAX5188 only		-1	1		μA
Full-Scale Output Current	I <sub>FS</sub>	MAX5188 only		0.5	1	1.5	mA
DAC External Output Resistor Load		MAX5188 only		400			Ω

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## ELECTRICAL CHARACTERISTICS (continued)

(AV<sub>DD</sub> = DV<sub>DD</sub> = +3V ±10%, AGND = DGND = 0, f<sub>CLK</sub> = 40MHz, I<sub>FS</sub> = 1mA, 400Ω differential output, C<sub>L</sub> = 5pF, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)










PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>REFERENCE</b>						
Output Voltage Range	V <sub>REF</sub>		1.12	1.2	1.28	V
Output Voltage Temperature Drift	TCV <sub>REF</sub>		50			ppm/°C
Reference Output Drive Capability	I <sub>REFOUT</sub>		10			μA
Reference Supply Rejection			0.5			mV/V
Current Gain (I <sub>FS</sub> / I <sub>REF</sub> )			8			mA/mA
<b>POWER REQUIREMENTS</b>						
Analog Power-Supply Voltage	AV <sub>DD</sub>		2.7	3.3		V
Analog Supply Current	I <sub>AVDD</sub>	PD = 0, DACEN = 1, digital inputs at 0 or DV <sub>DD</sub>	2.7	5		mA
Digital Power-Supply Voltage	DV <sub>DD</sub>		2.7	3.3		V
Digital Supply Current	I <sub>DVDD</sub>	PD = 0, DACEN = 1, digital inputs at 0 or DV <sub>DD</sub>	4.2	5		mA
Standby Current	I <sub>STANDBY</sub>	PD = 0, DACEN = 0, digital inputs at 0 or DV <sub>DD</sub>	1	1.5		mA
Shutdown Current	I <sub>SHDN</sub>	PD = 1, DACEN = X, digital inputs at 0 or DV <sub>DD</sub> (X = don't care)	0.5	1		μA
<b>LOGIC INPUTS AND OUTPUTS</b>						
Digital Input High Voltage	V <sub>IH</sub>		2			V
Digital Input Low Voltage	V <sub>IL</sub>			0.8		V
Digital Input Current	I <sub>IN</sub>	V <sub>IN</sub> = 0 or DV <sub>DD</sub>		±1		μA
Digital Input Capacitance	C <sub>IN</sub>		10			pF
<b>TIMING CHARACTERISTICS</b>						
DAC1 DATA to CLK Rise Setup Time	t <sub>DS1</sub>		10			ns
DAC2 DATA to CLK Fall Setup Time	t <sub>DS2</sub>		10			ns
DAC1 CLK Rise to DATA Hold Time	t <sub>DH1</sub>		0			ns
DAC2 CLK Fall to DATA Hold Time	t <sub>DH2</sub>		0			ns
CS Fall to CLK Rise Time			5			ns
CS Fall to CLK Fall Time			5			ns
DACEN Rise Time to V <sub>OUT</sub>			0.5			μs
PD Fall Time to V <sub>OUT</sub>			50			μs
Clock Period	t <sub>CLK</sub>		25			ns
Clock High Time	t <sub>CH</sub>		10			ns
Clock Low Time	t <sub>CL</sub>		10			ns

**Note 1:** Excludes reference and reference resistor (MAX5191) tolerance.

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## Typical Operating Characteristics

(AV<sub>DD</sub> = DV<sub>DD</sub> = +3V, AGND = DGND = 0, 400Ω differential output, I<sub>FS</sub> = 1mA, C<sub>L</sub> = 5pF, T<sub>A</sub> = +25°C, unless otherwise noted.)










# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## Typical Operating Characteristics (continued)

(AV<sub>DD</sub> = DV<sub>DD</sub> = +3V, AGND = DGND = 0, 400Ω differential output, I<sub>FS</sub> = 1mA, C<sub>L</sub> = 5pF, T<sub>A</sub> = +25°C, unless otherwise noted.)







**MAX5188/MAX5191**



# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## Typical Operating Characteristics (continued)

(AV<sub>DD</sub> = DV<sub>DD</sub> = +3V, AGND = DGND = 0, 400Ω differential output, I<sub>FS</sub> = 1mA, C<sub>L</sub> = 5pF, T<sub>A</sub> = +25°C, unless otherwise noted.)



# **Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs**

## **Pin Description**

PIN	NAME	FUNCTION
1	CREF1	Reference Bias Bypass, DAC1
2	OUT1P	Positive Analog Output, DAC1. Current output for the MAX5188; voltage output for the MAX5191.
3	OUT1N	Negative Analog Output, DAC1. Current output for the MAX5188; voltage output for the MAX5191.
4	AGND	Analog Ground
5	AVDD	Analog Positive Supply, +2.7V to +3.3V
6	DACEN	DAC Enable, Digital Input 0: Enter DAC standby mode with PD = DGND 1: Power-up DAC with PD = DGND X: Enter shutdown mode with PD = DV <sub>DD</sub> (X = don't care)
7	PD	Power-Down Select 0: Enter DAC standby mode (DACEN = DGND) or power-up DAC (DACEN = DV <sub>DD</sub> ) 1: Enter shutdown mode
8	CS	Active-Low Chip Select
9	CLK	Clock Input
10	N.C.	Not Connected. <b>Do not connect to this pin.</b>
11	REN	Active-Low Reference Enable. Connect to DGND to activate on-chip +1.2V reference.
12, 13, 23	DGND	Digital Ground
14	D0	Data Bit D0 (LSB)
15–20	D1–D6	Data Bits D1–D6
21	D7	Data Bit D7 (MSB)
22	DV <sub>DD</sub>	Digital Supply, +2.7V to +3.3V
24	REFR	Reference Input
25	REFO	Reference Output
26	OUT2N	Negative Analog Output, DAC2. Current output for the MAX5188; voltage output for the MAX5191.
27	OUT2P	Positive Analog Output, DAC2. Current output for the MAX5188; voltage output for the MAX5191.
28	CREF2	Reference Bias Bypass, DAC2

## Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs




Figure 1. Functional Diagram

### Detailed Description

The MAX5188/MAX5191 are dual 8-bit digital-to-analog converters (DACs) capable of operating with clock speeds up to 40MHz. Each of these dual converters consists of separate input and DAC registers, followed by a current-source array capable of generating up to 1.5mA full-scale output current (Figure 1). An integrated +1.2V voltage reference and control amplifier determine the data converters' full-scale output currents/voltages. Careful reference design ensures close gain matching and excellent drift characteristics. The MAX5191's voltage output operation features matched 400Ω on-chip resistors that convert the current from the current array into a voltage.

#### Internal Reference and Control Amplifier

The MAX5188/MAX5191 provide an integrated 50ppm/°C, +1.2V, low-noise bandgap reference that can be disabled and overridden by an external reference voltage. REFO serves either as an input for an external reference or as an output for the integrated reference. If REN is connected to DGND, the internal reference is selected and REFO provides a +1.2V output.

Due to its limited 10µA output drive capability, the REFO pin must be buffered with an external amplifier if heavier loading is required.

The MAX5188/MAX5191 also employ a control amplifier, designed to simultaneously regulate the full-scale output current IFS for both MAX5188/MAX5191 outputs. The output current is calculated as follows:

$$IFS = 8 \times IREF$$

where IREF is the reference output current ( $IREF = VREFO / RSET$ ) and IFS is the full-scale output current. RSET is the reference resistor that determines the amplifier's output current (Figure 2) on the MAX5188. This current is mirrored into the current-source array, where it is equally distributed between matched current segments and summed to valid output current readings for the DACs.

Inside the MAX5191, each output current (DAC1 and DAC2) is converted to an output voltage ( $V_{OUT1}$ ,  $V_{OUT2}$ ) with two internal, ground-referenced, 400Ω load resistors. Using the internal +1.2V reference voltage, the integrated reference output current resistor of the MAX5191 ( $RSET = 9.6k\Omega$ ) sets IREF to 125µA and IFS to 1mA.

## Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs




Figure 2. Setting  $I_{FS}$  with the Internal +1.2V Reference and Control Amplifier

### External Reference

To disable the MAX5188/MAX5191's internal reference, connect  $\overline{\text{REN}}$  to DVDD. A temperature-stable external reference may now be applied to drive the REFO pin (Figure 3) to set the full-scale output. Choose a reference that can supply at least 150 $\mu\text{A}$  to drive the bias circuit that generates the cascode current for the current array. For improved accuracy and drift performance, choose a fixed output voltage reference such as the +1.2V, 25ppm/ $^{\circ}\text{C}$  MAX6520 bandgap reference.

### Standby Mode

To enter the lower-power standby mode, connect digital inputs PD and DACEN to DGND. In standby, both the reference and the control amplifier are active with the current array inactive. To exit this condition, DACEN

must be pulled high with PD held at DGND. The MAX5188/MAX5191 typically require 50 $\mu\text{s}$  to wake up and allow both the outputs and the reference to settle.

### Shutdown Mode

For lowest power consumption, the MAX5188/MAX5191 provide a power-down mode in which the reference, control amplifier, and current array are inactive and the DAC's supply current is reduced to 1 $\mu\text{A}$ . To enter this mode, connect PD to DVDD. To return to active mode, connect PD to DGND and DACEN to DVDD. About 50 $\mu\text{s}$  are required for the devices to leave shutdown mode and settle their outputs to the values prior to shutdown. Table 1 lists the power-down mode selection.

Table 1. Power-Down Mode Selection

PD (POWER-DOWN SELECT)	DACEN (DAC ENABLE)	POWER-DOWN MODE	OUTPUT STATE	
0	0	Standby	MAX5188	High-Z
			MAX5191	AGND
0	1	Wake-Up	Last state prior to standby mode	
1	X	Shutdown	MAX5188	High-Z
			MAX5191	AGND

X = Don't care

## Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs




Figure 3. MAX5188/MAX5191 Using an External Reference




Figure 4. Timing Diagram

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## Timing Information

Both internal DAC cells write to their outputs in alternate phase (Figure 4). The input latch of the first DAC (DAC1) is loaded after the clock signal transitions high. When the clock signal transitions low, the input latch of the second DAC (DAC2) is loaded. The contents of the first input latch are shifted into the DAC1 register on the rising edge of the clock; the contents of the second input latch are shifted into the input register of DAC2 on the falling edge of the clock. Both outputs are updated on alternate phases of the clock.

## Outputs

The MAX5188 outputs are designed to supply 1mA full-scale output currents into  $400\Omega$  loads in parallel with a capacitive load of 5pF. The MAX5191 features integrat-

ed  $400\Omega$  resistors that restore the array currents into proportional, differential voltages of 400mV. These differential output voltages can then be used to drive a balun transformer or a low-distortion, high-speed operational amplifier to convert the differential voltage into a single-ended voltage.

## Applications Information

### Static and Dynamic Performance Definitions

#### Integral Nonlinearity

Integral nonlinearity (INL) (Figure 5a) is the deviation of the values on an actual transfer function from either a best-straight-line fit (closest approximation to the actual transfer curve) or a line drawn between the endpoints




Figure 5a. Integral Nonlinearity




Figure 5b. Differential Nonlinearity




Figure 5c. Offset Error




Figure 5d. Gain Error

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

of the transfer function once offset and gain errors have been nullified. For a DAC, the deviations are measured at every single step.

## **Differential Nonlinearity**

Differential nonlinearity (DNL) (Figure 5b) is the difference between an actual step height and the ideal value of 1LSB. A DNL error specification of less than 1LSB guarantees no missing codes and a monotonic transfer function.

## **Offset Error**

Offset error (Figure 5c) is the difference between the ideal and the actual offset point. For a DAC, the offset point is the step value when the digital input is zero. This error affects all codes by the same amount and can usually be compensated by trimming.

## **Gain Error**

Gain error (Figure 5d) is the difference between the ideal and the actual full-scale output voltage on the transfer curve, after nullifying the offset error. This error alters the slope of the transfer function and corresponds to the same percentage error in each step.

## **Settling Time**

The settling time is the amount of time required from the start of a transition until the DAC output settles its new output value to within the converter's specified accuracy.

## **Digital Feedthrough**

Digital feedthrough is the noise generated on a DAC's output when any digital input transitions. Proper board layout and grounding will significantly reduce this noise, but there will always be some feedthrough caused by the DAC itself.

## **Total Harmonic Distortion**

Total harmonic distortion (THD) is the ratio of the RMS sum of the input signal's first four harmonics to the fundamental itself. This is expressed as:

$$\text{THD} = 20 \times \log \left( \frac{\sqrt{(V_2^2 + V_3^2 + V_4^2 + V_5^2)}}{V_1} \right)$$

where  $V_1$  is the fundamental amplitude, and  $V_2$  through  $V_5$  are the amplitudes of the 2nd- through 5th-order harmonics.

## **Spurious-Free Dynamic Range**

Spurious-free dynamic range (SFDR) is the ratio of RMS amplitude of the fundamental (maximum signal component) to the RMS value of the next-largest distortion component.

## **Differential to Single-Ended Conversion**

The MAX4108 low-distortion, high input-bandwidth amplifier may be used to generate a voltage from the MAX5188's current-array output. The differential voltage across OUT1P (or OUT2P) and OUT1N (or OUT2N) is converted into a single-ended voltage by designing an appropriate operational amplifier configuration as shown in Figure 6.

## **Grounding and Power-Supply Decoupling**

Grounding and power-supply decoupling strongly influence the performance of the MAX5188/MAX5191. Unwanted digital crosstalk may couple through the input, reference, power-supply, and ground connections, which may affect dynamic specifications like SNR or SFDR. In addition, electromagnetic interference (EMI) can either couple into or be generated by the MAX5188/MAX5191. Therefore, grounding and power-supply decoupling guidelines for high-speed, high-frequency applications should be closely followed.

First, a multilayer PC board with separate ground and power-supply planes is recommended. High-speed signals should run on controlled impedance lines directly above the ground plane. Since the MAX5188/MAX5191 have separate analog and digital ground buses (AGND and DGND, respectively), the PC board should also have separate analog and digital ground sections with only one point connecting the two. Digital signals should run above the digital ground plane, and analog signals should run above the analog ground plane.

Both devices have two power-supply inputs: analog  $V_{DD}$  ( $AV_{DD}$ ) and digital  $V_{DD}$  ( $DV_{DD}$ ). Each  $AV_{DD}$  input should be decoupled with parallel  $10\mu F$  and  $0.1\mu F$  ceramic-chip capacitors as close to the pin as possible. Their opposite ends should have the shortest possible connection to the ground plane. The  $DV_{DD}$  pins should also have separate  $10\mu F$  and  $0.1\mu F$  capacitors, again adjacent to their respective pins. Try to minimize the analog load capacitance for proper operation. For best performance, bypass CREF1 and CREF2 with low-ESR,  $0.1\mu F$  capacitors to  $AV_{DD}$ .

The power-supply voltages should also be decoupled with large tantalum or electrolytic capacitors at the point they enter the PC board. Ferrite beads with additional decoupling capacitors forming a pi network could also improve performance.

## Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs




Figure 6. Differential to Single-Ended Conversion Using the MAX4108 Low-Distortion Amplifier


### Chip Information

TRANSISTOR COUNT: 9464

SUBSTRATE CONNECTED TO GND

# Dual, 8-Bit, 40MHz, Current/Voltage, Alternate-Phase Output DACs

## Package Information



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

14 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.