ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

VR Miniature Sized series

Anti-Solvent Feature (Through 100V only)

- One rank smaller case sizes than VX series.
- Compliant to the RoHS directive (2002/95/EC).





■Specifications

Item	Performance Characteristics
Category Temperature Range	−40 to +85˚C (6.3V to 400V), −25 to +85˚C (450V)
Rated Voltage Range	6.3 to 450V
Rated Capacitance Range	0.1 to 33000μF
Capacitance Tolerance	±20% at 120Hz, 20˚C
Leakage Current	Rated voltage (V) | 6.3 to 100V: After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4 (μA), whichever is greater. After 2 minutes' application of rated voltage, leakage current is not more than 0.01CV or 3 (μA), whichever is greater. | 160 to 450V: After 1 minute's application of rated voltage, CV ≦ 1000 : I = 0.1CV+40μA or less. After 1 minute's application of rated voltage, CV > 1000 : I = 0.04CV+100 (μA) or less
Tangent of loss angle (tan δ)	For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF. Measurement frequency : 120Hz at 20˚C

Rated voltage (V)	6.3	10	16	25	35	50	63	100	160 to 315	350 to 450
tan δ (MAX.)	0.28	0.24	0.20	0.16	0.14	0.12	0.10	0.08	0.20	0.25

Stability at Low Temperature — Measurement frequency : 120Hz

Rated voltage (V)		6.3	10	16	25	35	50	63	100	160 to 200	250 to 350	400	450
Impedance ratio	Z−25˚C / Z+20˚C	5	4	3	2	2	2	2	2	3	4	6	15
ZT / Z20 (MAX.)	Z−40˚C / Z+20˚C	12	10	8	5	4	3	3	3	4	8	10	—

Endurance — The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 85°C.

Capacitance change	Within ±20% of the initial capacitance value
tan δ	200% or less than the initial specified value
Leakage current	Less than or equal to the initial specified value

Shelf Life — After storing the capacitors under no load at 85˚C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.

Marking — Printed with white color letter on black sleeve.

■Radial Lead Type



(mm)

φD	4	5	6.3	8	10	12.5	16	18	20	22	25
P	1.5	2.0	2.5	3.5	5.0	5.0	7.5	7.5	10.0	10.0	12.5
φd	0.45	0.5	0.5	0.6	0.6	0.6	0.8	0.8	1.0	1.0	1.0
β	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0

α	(L<20) 1.5
	(L≧20) 2.0

• Please refer to page 20 about the end seal configulation.

Type numbering system (Example : 10V 330μF)

1	2	3	4	5	6	7	8	9	10	11	12
U	V	R	1	A	3	3	1	M	E	D	

- 12: Size code
- 10 11: Configuration※
- 9: Capacitance tolerance (±20%)
- 6 7 8: Rated capacitance (330μF)
- 4 5: Rated voltage (10V)
- 1 2 3: Series name
- Type

※ Configuration

φ D	Pb-free leadwire Pb-free PET sleeve
4	DD6
5	DD
6.3	ED
8 · 10	PD
12.5 to 18	HD
20 to 25	RD

Please refer to page 20, 21, 22 about the formed or taped product spec.
Please refer to page 4 for the minimum order quantity.

● Dimension table in next page.

VR series

■Dimensions

Cap.(μF) \ V / Code	6.3 / 0J		10 / 1A		16 / 1C		25 / 1E		35 / 1V		50 / 1H		63 / 1J		100 / 2A	
0.1 / 0R1											• 5×11	1.3			5×11	2.1
0.22 / R22											• 5×11	2.9			5×11	4.7
0.33 / R33											• 5×11	4.3			5×11	7
0.47 / R47											• 5×11	6.2			5×11	10
1 / 010											• 5×11	17			5×11	21
2.2 / 2R2											• 5×11	28			5×11	30
3.3 / 3R3											• 5×11	35			5×11	40
4.7 / 4R7							• 5×11	35	• 5×11	40	• 5×11	40			5×11	45
10 / 100					• 5×11	50	• 5×11	55	• 5×11	60	• 5×11	60	5×11	65	6.3×11	75
22 / 220	• 5×11	65	• 5×11	65	• 5×11	75	• 5×11	80	• 5×11	90	5×11	95	5×11	100	6.3×11	130
33 / 330	• 5×11	80	• 5×11	85	• 5×11	90	• 5×11	95	5×11	105	5×11	125	6.3×11	140	8×11.5	180
47 / 470	• 5×11	95	• 5×11	100	• 5×11	110	• 5×11	115	5×11	130	6.3×11	155	6.3×11	170	10×12.5	230
100 / 101	• 5×11	135	• 5×11	145	5×11	160	6.3×11	190	6.3×11	210	8×11.5	260	10×12.5	300	10×20	370
220 / 221	5×11	200	6.3×11	240	6.3×11	260	8×11.5	330	10×12.5	385	10×12.5	430	10×16	490	12.5×25	620
330 / 331	6.3×11	270	6.3×11	290	8×11.5	370	10×12.5	440	10×12.5	490	10×16	590	10×20	710	12.5×25	760
470 / 471	6.3×11	320	6.3×11	350	8×11.5	440	10×12.5	550	10×16	650	12.5×20	760	12.5×20	900	16×25	1000
1000 / 102	8×11.5	540	10×12.5	650	10×16	790	10×20	960	12.5×20	1150	12.5×25	1350	16×25	1300	18×40	1380
2200 / 222	10×20	1000	10×20	1100	12.5×20	1300	12.5×25	1550	16×25	1800	16×35.5	2100	18×35.5	2300	22×50	2400
															▲25×40	2400
3300 / 332	10×20	1190	12.5×20	1450	12.5×25	1700	16×25	1980	16×35.5	2280	18×35.5	2500	20×40	2700	25×50	2900
											▲22×30	2450	▲25×30	2600		
4700 / 472	12.5×20	1550	12.5×25	1800	16×25	2100	16×31.5	2450	18×35.5	2700	20×40	2900	22×50	3400		
									▲20×31		▲25×30	2900	▲25×40	3200		
6800 / 682	12.5×25	1920	16×25	2250	16×35.5	2650	18×35.5	2900	20×40	3000	22×50	3500	25×50	3900		
							▲20×31	2700	▲25×30	2900	▲25×40	3300				
10000 / 103	16×25	2350	16×35.5	2700	18×35.5	2950	20×40	3000	22×50	3700	25×50	4000				
					▲20×31	3000	▲25×30	2900	▲25×40	3600						
15000 / 153	16×35.5	2850	18×35.5	3100	20×40	3400	22×50	3800	25×50	4300						
					▲25×30	3300	▲25×40	3600								
22000 / 223	18×40	3350	20×40	3700	22×50	4200	25×50	4500								
	▲22×30	3200	▲25×30	3300	▲25×40	4000										
33000 / 333	22×50	3900	22×50	4500	25×50	4800									Case size ϕD×L (mm)	Rated ripple
	▲25×40	3800	▲25×40	4800												

Cap.(μF) \ V / Code	160 / 2C		200 / 2D		250 / 2E		315 / 2F		350 / 2V		400 / 2G		450 / 2W		
0.47 / R47	6.3×11	15	6.3×11	15	6.3×11	15									
1 / 010	6.3×11	22	6.3×11	22	6.3×11	22	6.3×11	22	6.3×11	22	8×11.5	25	8×11.5	23	
2.2 / 2R2	6.3×11	33	6.3×11	33	6.3×11	33	8×11.5	33	8×11.5	38	10×12.5	45	10×12.5	35	
3.3 / 3R3	6.3×11	40	6.3×11	40	8×11.5	46	10×12.5	55	10×12.5	55	10×12.5	55	10×16	45	
4.7 / 4R7	6.3×11	50	8×11.5	55	8×11.5	55	10×12.5	65	10×12.5	65	10×16	70	10×20	55	
10 / 100	8×11.5	80	10×12.5	95	10×16	105	10×20	115	10×20	115	12.5×20	130	12.5×20	90	
22 / 220	10×16	155	10×20	170	12.5×20	190	12.5×20	190	12.5×25	200	16×25	240	16×25	165	
33 / 330	10×20	205	12.5×20	230	12.5×20	230	16×25	275	16×25	275	16×31.5	300	16×35.5	230	
47 / 470	12.5×20	270	12.5×20	270	12.5×25	300	16×25	340	16×35.5	380	16×35.5	370	18×40	300	
													▲22×30	290	
100 / 101	12.5×25	430	16×31.5	530	16×31.5	520	18×35.5	560	18×40	590	20×40	550	22×40	350	
									▲22×30	570	▲25×30	530			
220 / 221	16×35.5	800	18×35.5	810	20×40	740	22×50	850	22×50	850	25×50	750			
					▲22×30	820	▲25×30	770	▲25×40	890					
330 / 331	18×40	940	20×40	1130	22×50	1170	25×50	1250							
	▲22×30	900	▲25×30	1090	▲25×30	970									
470 / 471	22×40	1410	22×50	1490	25×50	1600							Case size ϕD×L (mm)	Rated ripple	
	▲25×30	1290	▲25×40	1550											
1000 / 102	25×50	1900													

Size 4×11 is available for capacitors marked "●"
In this case, 6 will be put at 12th digit of type numbering system "▲"

Rated ripple current (mArms) at 85°C 120Hz

●Frequency coefficient of rated ripple current

V	Cap.(μF) \ Frequency	50Hz	120Hz	300Hz	1 kHz	10kHz or more
6.3 to 100	0.1 to 47	0.75	1.00	1.35	1.57	2.00
	100 to 470	0.80	1.00	1.23	1.34	1.50
	1000 to 33000	0.85	1.00	1.10	1.13	1.15
160 to 450	0.47 to 220	0.80	1.00	1.25	1.40	1.60
	330 to 1000	0.90	1.00	1.10	1.13	1.15

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.