

High Voltage $I_O=500\text{mA}$ Low Dropout Regulator


■ GENERAL DESCRIPTION

The NJW4185 is a high voltage and low current consumption low dropout regulator.

NJW4185 is mounted to TO-252-5 package and corresponded to Low ESR capacitor (MLCC).

The wide input range makes NJW4185 suitable for a Car accessory, Industrial supplies, battery equipment and various applications.

■ PACKAGE OUTLINE




NJW4185DL3

■ FEATURES

- | | |
|--|---------------------------------|
| ● Wide Operating Voltage Range | 4.0V ~ 40V |
| ● Low Current Consumption | 55 μA (typ.) |
| ● Correspond to Low ESR capacitor (MLCC) | |
| ● Output Current | $I_O(\text{min.})=500\text{mA}$ |
| ● Output Voltage Range | 2.0V to 15.0V |
| ● High Precision Output | $V_O \pm 1.0\%$ |
| ● ON/OFF Function | |
| ● Internal Thermal Overload Protection | |
| ● Internal Over Current Protection | |
| ● Package Outline | TO-252-5 |


■ PIN CONFIGURATION



PIN FUNCTION

1. V_{IN}
2. CONTROL
3. GND
4. N.C.
5. V_{OUT}

■ BLOCK DIAGRAM



■ OUTPUT VOLTAGE RANK LIST

Device Name	V _{OUT}
NJW4185DL3-33	3.3V
NJW4185DL3-05	5.0V
NJW4185DL3-08	8.0V
NJW4185DL3-15	15.0V

■ ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Input Voltage	V _{IN}	-0.3 to +45	V
Control Voltage	V _{CONT}	-0.3 to +45	V
Output Voltage	V _{OUT}	-0.3 to V _{IN} ≤ +17	V
Power Dissipation	P _D	1190 (*1) 3125 (*2)	mW
Junction Temperature	T _J	-40 to +150	°C
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +150	°C

(*1): Mounted on glass epoxy board. (76.2×114.3×1.6mm:based on EIA/JDEC standard size, 2Layers, Cu area 100mm²)

(*2): Mounted on glass epoxy board. (76.2×114.3×1.6mm:based on EIA/JDEC standard, 4Layers)

(For 4Layers: Applying 74.2 x 74.2mm inner Cu area and thermal via hole to a board based on JEDEC standard JESD51-5)

■ INPUT VOLTAGE RANGE

V_{IN}=4.0V~40V

■ ELECTRICAL CHARACTERISTICS

Unless otherwise noted, $V_O \geq 3.0V$: $V_{IN} = V_O + 1V$, $C_{IN} = 1.0\mu F$, $C_O = 2.2\mu F$, $T_a = 25^\circ C$

$V_O < 3.0V$: $V_{IN} = 4.0V$, $C_{IN} = 1.0\mu F$, $C_O = 4.7\mu F$, $T_a = 25^\circ C$

PARAMETER	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	I _O =30mA		-1.0%	-	+1.0%	V
Quiescent Current	I _Q	I _O =0mA, except I _{CONT}		-	55	90	μA
Quiescent Current at Control OFF	I _{Q (OFF)}	V _{CONT} =0V		-	-	1	μA
Output Current	I _O	V _O × 0.9		500	-	-	mA
Line Regulation	ΔV _O /ΔV _{IN}	V _{IN} = V _O +1V to 40V, I _O =30mA (V _O ≥3V) V _{IN} = 4V to 40V, I _O =30mA (V _O <3V)		-	-	0.03	%/V
Load Regulation	ΔV _O /ΔI _O	I _O =0mA to 500mA		-	-	0.006	%/mA
Ripple Rejection	RR	V _{IN} = V _O +1V ,e _{in} =200mVrms, f=1kHz, I _O =10mA	V _O =3.3V	-	62	-	dB
			V _O =5.0V	-	60	-	
			V _O =8.0V	-	55	-	
			V _O =15V	-	50	-	
Dropout Voltage(*3)	ΔV _{I_O}	I _O =300mA		-	0.27	0.42	V
Average Temperature Coefficient of Output Voltage	ΔV _O /ΔTa	Ta=0 to 85°C, I _O =30mA		-	±50	-	ppm/°C
Control Current	I _{CONT}	V _{CONT} =1.6V		-	1	3	μA
Control Voltage for ON-state	V _{CONT(ON)}			1.6	-	-	V
Control Voltage for OFF-state	V _{CONT(OFF)}			-	-	0.6	V


(*3): The output voltage excludes under 3.8V

The above specification is a common specification for all output voltages.


Therefore, it may be different from the individual specification for a specific output voltage.

■ POWER DISSIPATION vs. AMBIENT TEMPERATURE

NJW4185DL3 PowerDissipation
($T_{opr} = -40 \sim +85^\circ C$, $T_j = 150^\circ C$)




■ TEST CIRCUIT




■ TYPICAL APPLICATION

① In the case where ON/OFF Control is not required



Connect control pin to V_{IN} pin

② In use of ON/OFF CONTROL



State of control pin:

- "H" → output is enabled.
- "L" or "open" → output is disabled.

*In the case of using a resistance "R" between V_{IN} and control.

If this resistor is inserted, it can reduce the control current when the control voltage is high.

The applied voltage to control pin should set to consider voltage drop through the resistor "R" and the minimum control voltage for ON-state.

The $V_{CONT(ON)}$ and I_{CONT} have temperature dependence as shown in the "Control Current vs. Temperature" and "Control Voltage vs. Temperature" characteristics. Therefore, the resistance "R" should be selected to consider the temperature characteristics.

***Input Capacitor C_{IN}**

Input Capacitor C_{IN} is required to prevent oscillation and reduce power supply ripple for applications when high power supply impedance or a long power supply line.

Therefore, use the recommended C_{IN} value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and V_{IN} as shortest path as possible to avoid the problem.

***Output Capacitor C_O**

Output capacitor (C_O) will be required for a phase compensation of the internal error amplifier.

The capacitance and the equivalent series resistance (ESR) influence to stable operation of the regulator.

Use of a smaller C_O may cause excess output noise or oscillation of the regulator due to lack of the phase compensation.

On the other hand, Use of a larger C_O reduces output noise and ripple output, and also improves output transient response when rapid load change.

Therefore, use the recommended C_O value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and V_{OUT} as shortest path as possible for stable operation

The recommended capacitance depends on the output voltage rank. Especially, low voltage regulator requires larger C_O value.

In addition, you should consider varied characteristics of capacitor (a frequency characteristic, a temperature characteristic, a DC bias characteristic and so on) and unevenness peculiar to a capacitor supplier enough.

When selecting C_O , recommend that have withstand voltage margin against output voltage and superior temperature characteristic.

*The notes of the evaluation when output pin is shorted to GND


When evaluated short circuit test, the IC may break down because of regenerated energy by the parasitic inductance included in wiring pattern.

It phenomenon appears conspicuously when output voltage is high($V_o=8.0V$ or more) or connected to inductive load.


In case of short circuit in actual application, not likely to destruction of IC because of some of Resistance exist between load.

If happened above phenomenon by the short circuit test with the actual application, recommend connecting schottky barrier diode(SBD) between V_o pin and the GND or using output condensers that have ESR more than 2ohm like a tantalum or aluminum electrolytic capacitor.(see below figure)

(a) In case of insert Schottky barrier diode between output pin - GND




(b) In case of using the electrolysis condenser or insert series resistance




■ TYPICAL CHARACTERISTICS


NJW4185_5.0V
Output Voltage vs. Input Voltage




NJW4185_5.0V
Output Voltage vs. Output Current




NJW4185_5.0V
Ground Pin Current vs. Output Current




NJW4185_5.0V
Quiescent Current vs. Input Voltage




NJW4185_5.0V
Output Voltage vs. Control Voltage




NJW4185_5.0V
Control Current vs. Control Voltage




NJW4185_5.0V
Load Regulation vs. Output Current




NJW4185_5.0V
Peak Output Current vs. Input Voltage




NJW4185_5.0V
Dropout Voltage vs. Output Current




NJW4185_5.0V
Ripple Rejection Ratio vs. Frequency













NJW4185_5.0V
Ripple Rejection Ratio vs. Output Current







NJW4185_5.0V
Equivalent Series Resistance vs. Output Current









[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.